

International Standard

ISO/FDIS 28560-3

Third edition: 2022-xx-xx(E)

ISO/TC 46/SC 4

Secretariat: KATS

Information and documentation — RFID in libraries

Part 3:

Fixed length encoding

Partie 3: Encodage de longueur fixe

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 28560-3

<https://standards.iteh.ai/catalog/standards/sist/256389fb-df1e-4935-91e3-504d18504800/iso-fdis-28560-3>

Formatted: Font: Cambria

Style Definition: Heading 1

Style Definition: Heading 2: Indent: Left: 0 cm, Tab stops: Not at 1.63 cm

Style Definition: Heading 3

Style Definition: Heading 4

Style Definition: Heading 5

Style Definition: Heading 6

Style Definition: Default Paragraph Font

Style Definition: ANNEX

Style Definition: List Continue 5: Font: Indent: Hanging: 0.71 cm, Don't add space between paragraphs of the same style

Style Definition: RefNorm

Style Definition: bib_comment: Font: Cambria

Style Definition: bib_deg: Font: Cambria

Style Definition: bib_suffix: Font: Cambria

Style Definition: bib_unpubl: Font: Cambria

Style Definition: cite_box: Font: Cambria

Style Definition: bib_medline: Font: Cambria

Style Definition: Base_Text: Tab stops: 0.7 cm, Left + 1.4 cm, Left + 2.1 cm, Left + 2.8 cm, Left + 3.5 cm, Left + 4.2 cm, Left + 4.9 cm, Left + 5.6 cm, Left + 6.3 cm, Left + 7 cm, Left

Style Definition: Body Text_Center

Style Definition: Code: Tab stops: 0.57 cm, Left + 1.15 cm, Left + 1.72 cm, Left + 2.3 cm, Left + 2.87 cm, Left + 3.45 cm, Left + 4.02 cm, Left + 4.6 cm, Left + 5.17 cm, Left + 5.74 cm, Left

Style Definition: Dimension_100

Style Definition: Figure Graphic

Style Definition: Figure subtitle

Style Definition: List Continue 1

Style Definition: List Continue 2 (-): Indent: Left: 0.69 cm, Hanging: 1.43 cm, Space After: 12 pt

Style Definition: List Number 1: Tab stops: Not at 0.71 cm

Formatted

Formatted: French (Switzerland)

Formatted: French (Switzerland)

Formatted: Font color: Black, French (Switzerland)

Formatted: French (Switzerland)

Formatted: English (United States)

Formatted

Formatted: Font: Cambria

Formatted: Font: Cambria

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

CP 401 • Ch. de Blandonnet 8

CH-1214 Vernier, Geneva

Phone: +41 22 749 01 11

Email: copyright@iso.org

Website: www.iso.org

Published in Switzerland

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 28560-3

<https://standards.iteh.ai/catalog/standards/sist/256389fb-df1c-4935-91ed-a0766e75d4fb/iso-fdis-28560-3>

Formatted: Font: Cambria, 11 pt, English (United Kingdom)

Formatted: Left, Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria, 10 pt

Formatted: Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria

Formatted: Justified

Formatted: Font: Cambria

Formatted: Font: Cambria

Contents

Page

Foreword.....iv

Introduction.....v

1 Scope1

2 Normative references1

3 Terms and definitions.....1

4 Requirements.....3

5 General encoding rules.....3

6 Data elements6

7 Data blocks.....10

8 Miscellaneous.....17

Annex A (informative) -Information about ISO 28560 RFID in libraries.....18

A.1 Informational website18

A.2 Types of support information18

Annex B (informative)- Encoding examples19

B.1 Example 1, encoding of truncated basic block.....19

B.2 Example 2, encoding of basic block and structured extension blocks20

B.3 Example 3, encoding of Primary item identifier21

B.4 Example 4, encoding of Owner institution (ISIL)22

B.5 Example 5, encoding of Alternative owner institution22

Annex C (normative)- Cyclic redundancy check (CRC)24

C.1 Specification24

C.2 Example.....24

C.3 Example code24

Annex D (informative)- Reading optimization25

D.1 General25

D.2 Fast reading25

D.3 Optimized reading.....25

D.4 Structured or unstructured extensions.....25

Annex E (informative) -Guidelines for regional profiling.....26

Bibliography27

STANDARD PREVIEW

ISO FDIS 28560-3

35-91ed-a0766e75d4fb/iso-

File: 28560-3

Formatted: Font: Cambria, 10 pt

Formatted: Left, Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria, 11 pt

Formatted: Font: Cambria, 10 pt, Not Bold

Formatted: Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria

Formatted: Justified

Formatted: Font: Cambria

Formatted: Font: Cambria

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see the following URL: www.iso.org/iso/foreword.html.

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: English (United States)

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Formatted: English (United States)

Formatted: English (United States)

This document was prepared by Technical Committee ISO/TC 46, Information and documentation, Subcommittee SC 4, Technical interoperability.

This third edition cancels and replaces the second edition (ISO 28560-3:2014), of which it constitutes a minor revision. A few updates are made.

A list of all parts in the ISO 28560 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Formatted: English (United States)

Formatted: Font: Cambria, 11 pt, English (United Kingdom)

Formatted: Font: Cambria, 10 pt

Formatted: Left, Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria, 10 pt

Formatted: Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria

Formatted: Justified

Formatted: Font: Cambria

Formatted: Font: Cambria

Introduction

Libraries are implementing radio frequency identification (RFID) as item identification to replace bar codes. RFID streamlines applications like user self-service, security, and materials handling. This standard data model for encoding information on RFID tags increases the cost-effectiveness of the technology within libraries, particularly through greater interoperability of RFID tags and equipment, and enhance support for resource sharing between libraries.

This [part of ISO 28560 document](#) deals with the encoding of a basic set of data elements in a fixed length format and the rest of the data elements in optional extension blocks. ISO 28560-1 defines the set of mandatory and optional data elements.

ISO 28560-2 and this [part of ISO 28560 document](#) are mutually exclusive with respect to an RFID tag being applied to a loan item. In other words, the RFID tag is encoded according to the rules of this [part of ISO 28560 document](#), or to the rules of ISO 28560-2, or to some proprietary rules. Depending on the technologies being used, and other features of tags that are claiming compliance with ISO 28560-2, the reading system might achieve a degree of interoperability.

This [International Standard document](#) provides essential standards-based information about RFID in libraries. Ongoing advice needs to be provided because of the evolving nature of RFID technology, and the opportunities to migrate between different types of legacy system and encoding rules of this [International Standard document](#).

iteh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 28560-3

<https://standards.iteh.ai/catalog/standards/sist/256389fb-df1c-4935-91ed-a0766e75d4fb/iso-fdis-28560-3>

Formatted: Font: Cambria, 10 pt

Formatted: Left, Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria, 11 pt

Formatted: Font: Cambria, 10 pt, Not Bold

Formatted: Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria

Formatted: Justified

Information and documentation — RFID in libraries — Part 3: Fixed length encoding

1 Scope

This ~~part of ISO 28560 document~~ provides a data model and encoding rules for the use of radio frequency identification (RFID) tags for items appropriate for the needs of all types of libraries (including national, academic, public, corporate, special, and school libraries).

This ~~part of ISO 28560 document~~ specifies the rules for encoding

- a subset of data elements taken from the total set of data elements listed in ISO 28560-1 into a basic block, and
- other data elements into extension blocks onto the RFID tag.

A source of additional information about implementation issues is provided in Annex A.

2 Normative references

The following documents, ~~are referred to in whole the text in such a way that some or in part are normatively referenced in all of their content constitutes requirements of this document and are indispensable for its application.~~ For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 28560-1, *Information and documentation — RFID in libraries — Data elements and general guidelines for implementation*

ISO/IEC 10646, *Information technology — Universal Coded Character Set coded character set (UCS)*

ISO/IEC 18000-3, *Information technology — Radio frequency identification for item management — Part 3: Parameters for air interface communications at 13,56 MHz*

ISO/IEC 18046-3, *Information technology — Radio frequency identification device performance test methods — Part 3: Test methods for tag performance*

ISO/IEC 18047-3, *Information technology — Radio frequency identification device conformance test methods — Part 3: Test methods for air interface communications at 13,56 MHz*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 28560-1 and the following apply.

3.1

basic block

data block occupying the first 272 bits of the RFID tag

Formatted: Font: Cambria

Formatted: Section start: New page, Different first page header

Formatted: English (United States)

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.7 cm, Left + 1.4 cm, Left + 2.1 cm, Left + 2.8 cm, Left + 3.5 cm, Left + 4.2 cm, Left + 4.9 cm, Left + 5.6 cm, Left + 6.3 cm, Left + 7 cm, Left

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Formatted: cite_app

Formatted: RefNorm, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.7 cm, Left + 1.4 cm, Left + 2.1 cm, Left + 2.8 cm, Left + 3.5 cm, Left + 4.2 cm, Left + 4.9 cm, Left + 5.6 cm, Left + 6.3 cm, Left + 7 cm, Left

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: std_docTitle, Font: Not Italic

Formatted: Font: Not Italic

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Note 1 to entry: If the RFID tag is limited to 256 bits (i.e. 32 bytes), the basic block is truncated.

3.2 byte
8-bit byte
group of eight consecutive bits

Note 1 to entry: A byte can represent one *character* (3.3) or be part of a representation of a character.

3.3 character
one or more *bytes* (3.2)

3.4 CRC
cyclic redundancy check
value calculated from the data on the tag

3.5 data block
container for encoding data elements, *CRC* (3.4), filler, and end mark

3.6 end block
data block (3.5) containing the end mark terminating the information on the RFID tag

3.7 extension block
optional *data block* (3.5) following the *basic block* (3.1)

3.8 field
entry in a *data block* (3.5)

3.9 filler data block
optional *data block* (3.5) that can be inserted to align other data blocks on *page* (3.11) boundaries

3.10 fixed length field
field (3.8) of prescribed size in a *data block* (3.5)

3.11 page
minimum data unit that can be read from or written to a tag

Note 1 to entry: This is measured in *bytes* (3.2).

3.12 string
sequence of *characters* (3.3)

3.13

ICS 35.040; 35.240.30
Price based on 24 pages

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/FDIS 28560-3

<https://standards.iteh.ai/catalog/standards/sist/256389fb-df1c-4935-91ed-a0766e75d4fb/iso-fdis-28560-3>

Inserted Cells

Formatted Table

Formatted: Right, Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria

Formatted: Right

Formatted: Font: Cambria

unsigned integer

binary value of a number of consecutive bits

3.14**variable length field***field* (3.8) of variable size in a *data block* (3.5)**4 Requirements****4.1 Data elements**

The data elements shall be as defined and compliant with those listed in ISO 28560-1.

NOTE There is a degree of flexibility in using locally defined codes that enable enhancements and variations to be implemented while still complying with the basic set of data elements.

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

4.2 RFID air interface**4.2.1 Air interface conformance**

The air interface for compliant tags shall be in accordance with the specification for Mode 1.

For migration purposes, additional non-compliant air interfaces used in legacy systems can be supported during a transition period, which is permitted to remain in place for years, as necessary.

The air interface conformance shall be tested in accordance with ISO/IEC TR 18047-3.

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

4.2.2 Tag performance

Where there are requirements for test tag performance, these shall be performed in accordance with ISO/IEC 18046-3.

4.3 Data protocol

The fixed length encoding described in this [part of ISO 28560 document](#) does not require a separate data protocol.

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

5 General encoding rules**5.1 Distinguishing from other applications and encodings**

The value of the application family identifier (AFI) is used to distinguish tags for library applications from other applications. The values of AFI for library applications are defined in ISO 28560-1.

ISO 28560-1 describes how the data storage format identifier (DSFID), if present in the system memory as a programmable register, is used to distinguish tags in the library application area, i.e. with the same AFI.

Tags encoded according to this [part of ISO 28560 document](#) shall be programmed with the value 3E_{HEX} in the DSFID register if the tag contains a programmable DSFID register.

This [part of ISO 28560 document](#) is not able to encode the DSFID if the tag does not contain a programmable DSFID register. In this case, ISO 28560-2 encodes the DSFID in the first byte of the working area of the tag. To take this situation into account, the content parameter (see Table 1) shall not take the value 6 on RFID tags encoded according to this [part of ISO 28560 document](#).

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

Formatted: Font: Cambria

Formatted: Font: Cambria

If and only if the tag does not contain a programmable DSFID register, it is permissible to distinguish tags encoded according to this [part of ISO 28560 document](#) from other encodings by verifying the cyclic redundancy check (CRC) encoded in the basic block (see 7.2).

5.2 -Writing/reading direction

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

Data shall be written to and read from the tag as specified in ISO/IEC 18000-3, Mode 1, such that the first bit transmitted to or from the tag is the least significant bit of the first field of the basic block. This field contains the content parameter (see Table 1). From that starting point, bytes are transmitted to or from the tag in order from left to right, with byte 0 to the left of bytes 1, 2, and 3, as shown in the memory map in Annex B.

5.3 -Memory area layout

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

5.3.1 Specifications

The memory area shall be encoded starting with a basic block with fixed length encoding of a basic set of data elements for use in the library.

If the size of the RFID tag is limited to 256 bits (32 bytes), the RFID tag can only contain a truncated basic block.

If the size of the RFID tag is greater than 256 bits, extension blocks (structured or unstructured) can be inserted after the basic block up to the capacity of the chip. If extension blocks are inserted, the order of these is optional. The length of an extension block is determined by the first byte of the block. The type of extension block is defined in the following two bytes.

Filler data blocks may be inserted between blocks to align to page boundaries.

An end block shall terminate the encoding, unless the basic block and possible extension blocks take up the whole space on the RFID tag, in which case an end block is not needed.

5.3.2 Layout for tags greater than 32 bytes

The layout for tags greater than 32 bytes (256 bits) shall be as follows:

<basic block>[<filler data block>]*<extension block>*<filler data block>*<end block>

The end block is mandatory if the tag is not full ([see 5.3.1](#)). Basic block, filler data block, structured extension blocks, unstructured extension blocks, and end block are specified in Clause 7.

An example is given in Annex B.

5.3.3 Layout for 32-byte tags

The layout for 32-byte tags shall be as follows:

<truncated basic block>

The truncated basic block is specified in Clause 7.

An example is given in Annex B.

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Right, Space Before: 18 pt, Line spacing: Exactly 12 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria, 10 pt

Formatted: Font: Cambria

Formatted: Right

Formatted: Font: Cambria

5.4 Strings and integers

5.4.1 String encoding

All strings shall be encoded in UTF-8 in accordance with ISO/IEC 10646, with the first character of the string stored in the lowest memory location. Note that UTF-8 encoding implies that a character can occupy more than one byte.

The end of a string can be defined in the following different ways:

- with one byte 00_{HEX};
- with the length of a fixed length field;
- with the end of a structured extension block.

For fixed length fields, all unused bytes shall be 00_{HEX}.

For variable length fields, one byte 00_{HEX} shall be used between each field.

5.4.2 Integer encoding

Integer-encoded fields shall use 4, 8, or 16 bits unsigned integers.

5.5 Writing the tag

5.5.1 Cyclic redundancy check (CRC)

For RFID tags with only 32 bytes (256 bits) user data space of the basic block is truncated two bytes, but the CRC shall be calculated for a full-length basic block with the two missing bytes assumed to be 00_{HEX}.

See 7.2 and Annex C for a description of CRC.

5.5.2 Unused space

Any unused space in blocks shall be filled with 00_{HEX}, i.e. a 6-byte primary item identifier encoded in the basic block (see 7.2) shall be written as the 6-byte primary item identifier followed by 10 bytes 00_{HEX}. It is very important for reading optimization that this rule be followed.

5.5.3 End of tag

If a data block ends on the last user byte of a tag, no “end block” is required. The length specified in the last data block shall not indicate a size larger than the tag.

5.6 Reading optimization

Guidelines for reading optimization are given in Annex D.

5.7 Profiling

Guidelines for regional profiling are given in Annex E.

5.8 Locking

It is technically possible to lock parts of the tag, but this [part of ISO 28560 document](#) does not prescribe any strategy for locking. Such a strategy is left for regional profiling.

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers, Tab stops: 0.71 cm, Left

Formatted: Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Formatted: Font: Cambria