



FINAL DRAFT International Standard

ISO/FDIS 22932-9

Mining — Vocabulary —

Part 9: Drainage

*Exploitation minière — Vocabulaire —
Partie 9: Drainage*

ISO/TC 82

Secretariat: **DIN**

Voting begins on:
2025-04-18

Voting terminates on:
2025-06-13

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/FDIS 22932-9

<https://standards.iteh.ai/catalog/standards/iso/2734bd33-9d88-4928-832c-800978a1576c/iso-fdis-22932-9>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/FDIS 22932-9

<https://standards.iteh.ai/catalog/standards/iso/2734bd33-9d88-4928-832c-800978a1576c/iso-fdis-22932-9>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 Ground water	1
3.2 Drainage planning	5
3.2.1 Pumps planning	5
3.2.2 Patterns	8
3.2.3 Drainage	8
3.2.4 Water reactions	10
3.2.5 Areas	11
3.3 Pumps	12
3.3.1 Centrifugal pumps	12
3.3.2 Air displacement pumps	15
3.3.3 Reciprocating pumps	17
3.3.4 Other pumps	18
3.3.5 Operation and performance	20
3.3.6 Components	21
3.4 Drainage installation	23
3.4.1 Sump	23
3.4.2 Main pump	23
3.4.3 Pipelines	24
3.4.4 Drills	24
3.4.5 Prevention of water entering to mine	27
3.4.6 Prevention of mine water contamination	28
Bibliography	30
Index	31

<https://standards.itech.ai/catalog/standards/iso/2734bd33-9d88-4928-832c-800978a1576c/iso-fdis-22932-9>

<https://standards.itech.ai/catalog/standards/iso/2734bd33-9d88-4928-832c-800978a1576c/iso-fdis-22932-9>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 82, *Mining*.

A list of all parts in the ISO 22932 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

ISO/FDIS 22932-9

<https://standards.iteh.ai/catalog/standards/iso/2734bd33-9d88-4928-832c-800978a1576c/iso-fdis-22932-9>

Introduction

The ISO 22932 series has been prepared in order to standardize and to co-ordinate the global use of technical terms and definitions in mining, for the benefit of the experts working on different types of mining activities.

The need for the ISO 22932 series arose from the widely varying interpretation of terms used within the industry and the prevalent use of more than one synonym.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 22932-9](https://standards.iteh.ai/catalog/standards/iso/2734bd33-9d88-4928-832c-800978a1576c/iso-fdis-22932-9)

<https://standards.iteh.ai/catalog/standards/iso/2734bd33-9d88-4928-832c-800978a1576c/iso-fdis-22932-9>

Mining — Vocabulary —

Part 9: Drainage

1 Scope

This document specifies the commonly used terms in mine drainage.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1 Ground water

3.1.1

aquifer

porous water bearing stratum

3.1.2

aquifer test

in situ procedure, such as single-well (bail test or slug test) and multiple-well *pumping* (3.3.5.9) tests, used to determine hydraulic properties of an aquifer

Note 1 to entry: See Reference [1].

3.1.3

aquifuge

rock that contains no interconnected openings or interstices and therefore neither absorbs nor transmits water

Note 1 to entry: That can be as the opposite of aquifer.

Note 2 to entry: Compare with confining bed.

Note 3 to entry: See Reference [1].

3.1.4

attached ground water

that portion of the subsurface water adhering to the pore walls

Note 1 to entry: It is assumed to be equal in quantity to the pellicular water, and it is measured by specific retention.

Note 2 to entry: See Reference [1].

3.1.5

capillary

action by which the surface of a liquid is elevated at the point at which it is in contact with a solid

Note 1 to entry: Such as in a lamp wick.

Note 2 to entry: See Reference [1].

3.1.5.1

capillarity

capillary action

action by which a fluid, such as water, is drawn up (or depressed) in small interstices or tubes as a result of surface tension

Note 1 to entry: See Reference [1].

3.1.5.2

zone of capillarity

subsurface zone that overlies the *zone of saturation* (3.1.20) in which *capillary* (3.1.5) voids hold water above the *zone of saturation* (3.1.20) by molecular attraction acting against gravity

Note 1 to entry: Compare with zone of aeration.

Note 2 to entry: See Reference [1].

3.1.6

confining bed

aquiclude

impervious stratum above and/or below an aquifer

Note 1 to entry: Compare with aquifuge.

3.1.7

connate water

inherent water contemporary with the rocks containing it, as opposed to water subsequently permeating the rocks

Note 1 to entry: Compare with interstitial water and formation water.

3.1.8

depressed water level

pumping water level

lowest level of *ground water* (3.1.10) during *drainage* (3.2.3.2) or pumping

3.1.9

formation water

native water

water present in a water-bearing formation under natural conditions, as opposed to introduced fluids, such as drilling mud

Note 1 to entry: Compare with connate water.

Note 2 to entry: See Reference [1].

3.1.10

ground water

meteoric water

subterranean water

water penetrating from the surface and filling naturally the pores and fissures of the strata below the water table

3.1.11

ground water hydrology

aspect of *hydrology* (3.1.13) which is concerned with the physical and chemical characteristics of water and similar liquids found in the ground

3.1.12

ground water province

area or region in which geology and climate combine to produce ground-water conditions consistent enough to permit useful generalizations

Note 1 to entry: See Reference [1].

3.1.13

hydrology

study of the movement of water above, on and within the earth's crust

3.1.14

interstitial water

pore water

subsurface water in the voids of a rock

Note 1 to entry: Compare with connate water.

Note 2 to entry: See Reference [1].

3.1.15

piestic level

level at which water in a confined *aquifer* (3.1.1) will rise under its full hydrostatic head

3.1.16

piezometric surface

potentiometric surface

imaginary surface that coincides with the hydrostatic pressure level of the water in a confined *aquifer* (3.1.1)

3.1.16.1

cone of depression

space enclosed between the water table, at which water would stand naturally in the ground, and the position at which it in fact stands owing to *drainage* (3.2.3.2) or pumping at some point in the vicinity

Note 1 to entry: In the case of confined water under pressure, the cone of depression is the space between the undisturbed piezometric surface and the piezometric surface after pumping.

3.1.16.2

piezometer

instrument for measuring pressure head

Note 1 to entry: Usually consisting of a small pipe tapped into the side of a closed or open conduit and flush with the inside; connected with a pressure gage, mercury, water column, or other device for indicating head.

Note 2 to entry: See Reference [1].

3.1.17

secondary water

water entering the mine from other workings, as opposed to water inherent in the area worked by the mine

3.1.18

water table

free water elevation

free water surface

ground water level

ground water surface

ground water table

level of saturation

phreatic surface

plane of saturation

saturated surface

plane or surface below which fissures and pores in the strata are naturally saturated with water

3.1.18.1

perched water table

water table (3.1.18) of a body of perched ground water

Note 1 to entry: See Reference [1].

3.1.18.1.1

perched ground water

perched water

unconfined *ground water* (3.1.10) separated from an underlying main body of *ground water* (3.1.10) by an unsaturated zone

Note 1 to entry: See Reference [1].

3.1.18.2

water table contour

line drawn on a map to represent an imaginary line in the *water table* (3.1.18) of a definite level.

Note 1 to entry: These contours are constructed from the data provided by the water-table levels, corrected for differences in surface level at the respective boreholes. A site investigation or opencast plan sometimes show water-table contours.

Note 2 to entry: See Reference [1].

3.1.18.3

water table level

level showing the depth of the *water table* (3.1.18) below the surface

Note 1 to entry: Also is the depth at which water is encountered in trial pits or boreholes.

Note 2 to entry: See Reference [1].

3.1.18.4

water table map

contour map of the upper surface of the saturated zone

Note 1 to entry: See Reference [1].

3.1.18.5

water table stream

concentrated *ground water* (3.1.10) flow at the *water table* (3.1.18) in a formation or structure of high permeability

Note 1 to entry: See Reference [1].

3.1.19

zone of aeration

subsurface zone containing water under pressure less than that of the atmosphere, including water held by capillarity, and containing air or gases generally under atmospheric pressure

Note 1 to entry: This zone is limited above by the land surface and below by the water table. It contains vadose water.

Note 2 to entry: Compare with zone of capillarity.

Note 3 to entry: See Reference [1].

3.1.19.1

vadose water

suspended water

water of the zone of aeration

Note 1 to entry: See Reference [1].

3.1.20

zone of saturation

phreatic zone

saturated zone

subsurface zone in which all the interstices are filled with water under pressure greater than that of the atmosphere

Note 1 to entry: This zone is separated from the zone of aeration by the water table.

Note 2 to entry: See Reference [1].

3.2 Drainage planning

3.2.1 Pumps planning

3.2.1.1

booster pump

pump that operates in the discharge line of another pump, either to increase pressure or to restore pressure lost by friction in the line or by lift

Note 1 to entry: See Reference [1].

3.2.1.2

booster station

in long-distance *pumping* (3.3.5.9) of liquids or mineral slurries, an intermediate pump station

Note 1 to entry: See Reference [1].

3.2.1.3

hogger pump

topmost pump in a shaft

Note 1 to entry: See Reference [1].

3.2.1.4

pump chamber

underground *pumping* (3.3.5.9) station

Note 1 to entry: See Reference [1].

3.2.1.5
pitwright
plugman

person who operates one or a battery of pumps to force excess water from a lower level to the surface or to a *drainage* ([3.2.3.2](#)) tunnel

Note 1 to entry: See Reference [\[1\]](#).

3.2.1.6
pumping head

<airlift> distance from the surface to the level of the water during *pumping* ([3.3.5.9](#))

Note 1 to entry: It equals static head plus drop.

Note 1 to entry: See Reference [\[1\]](#).

3.2.1.7
pumping shaft

shaft containing the *pumping* ([3.3.5.9](#)) machinery of a mine

Note 1 to entry: See Reference [\[1\]](#).

3.2.1.8
pump lift

vertical distance that a pump can suck up water or the vertical distance a pump can force water to flow

Note 1 to entry: Theoretically, the vertical distance that a pump can suck up water should be about 10,4 m at sea level but practically, the limit is about 7,9 m.

Note 2 to entry: See Reference [\[1\]](#).

3.2.1.9
pump load

back pressure and/or resistance to flow of fluids that a pump must overcome to force a fluid to flow through a pipeline, drill string, etc.

Note 1 to entry: See Reference [\[1\]](#).

3.2.1.10
pump pressure

force per unit area or pressure against which a pump acts to force a fluid to flow through a pipeline, drill string, etc.

Note 1 to entry: Also, it's the pressure imposed on the fluid ejected from a pump.

Note 2 to entry: See Reference [\[1\]](#).

3.2.1.11
pump slip

leakage past the valves and the plunger in a *reciprocating pump* ([3.3.3.7](#)), which should not be greater than 2 % or 3 % for a pump in good condition

Note 1 to entry: See Reference [\[1\]](#).

3.2.1.12
pump slope

slope in which pumps are operated

Note 1 to entry: See Reference [\[1\]](#).