



SLOVENSKI STANDARD

SIST EN 300 324-1 V2.1.1:2005

01-januar-2005

Vmesniki V pri digitalnih krajevnih centralah (LE) – Vmesnik V5.1 za podporo dostopnega omrežja (AN) – 1. del: Specifikacija vmesnika V5.1

V interfaces at the digital Local Exchange (LE); V5.1 interface for the support of Access Network (AN); Part 1: V5.1 interface specification

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 324-1 Version 2.1.1**

SIST EN 300 324-1 V2.1.1:2005
<https://standards.iteh.ai/catalog/standards/sist/5c2880b8-2943-4b15-a59c-c047f602d853/sist-en-300-324-1-v2-1-1-2005>

ICS:

33.040.30	Komutacijski in signalizacijski sistem	Switching and signalling systems
-----------	--	----------------------------------

SIST EN 300 324-1 V2.1.1:2005

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 324-1 V2.1.1:2005

<https://standards.iteh.ai/catalog/standards/sist/5e2880b8-2943-4bf3-a39e-c047f602d853/sist-en-300-324-1-v2-1-1-2005>

ETSI EN 300 324-1 V2.1.1 (2000-04)

European Standard (Telecommunications series)

V interfaces at the digital Local Exchange (LE); V5.1 interface for the support of Access Network (AN); Part 1: V5.1 interface specification

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 324-1 V2.1.1:2005](https://standards.iteh.ai/catalog/standards/sist/5e2880b8-2943-4bf3-a39e-c047f602d853/sist-en-300-324-1-v2-1-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/5e2880b8-2943-4bf3-a39e-c047f602d853/sist-en-300-324-1-v2-1-1-2005>



Reference

REN/SPAN-09106-1

Keywords

V interface, V5 interface, LE, AN

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from<http://www.etsi.org>If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).

In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	13
Foreword	13
Introduction	14
1 Scope	15
2 References	16
3 Definitions and abbreviations	17
3.1 Definitions	17
3.2 Abbreviations	20
4 Electrical and physical interface requirements	21
5 Procedural interface requirements	26
6 Services and architecture aspects and requirements	29
6.1 On-demand services	29
6.1.1 PSTN	29
6.1.2 ISDN Basic Access (ISDN-BA)	29
6.2 Permanent Line (PL) capability	30
6.3 Semi-permanent leased line	30
6.4 Permanent leased line services	31
7 Control and provisioning	31
7.1 Control principles	31
7.1.1 General requirements and assumptions	31
7.1.2 Control of ISDN user port for the PL capability	33
7.1.2.1 Statements and assumptions	33
7.1.2.2 ISDN and PL capability	33
7.1.2.3 Decoupling of AN and LE FSM	33
7.2 Provisioning strategy and requirements	33
7.2.1 General	33
7.2.2 Provisioning requirements	33
8 Protocol architecture and multiplexing structure	35
8.1 Functional description	35
8.2 Protocol requirements for PSTN and ISDN	36
8.3 Time slots	37
8.4 Time slot allocation for C-channels	37
8.5 L2 sublayering and multiplexing on C-channels	38
8.6 L3 multiplexing	38
8.7 Congestion control	38
8.7.1 Flow control end to end	38
8.7.2 Congestion control on the V5.1 interface	38
8.7.3 Blocking of ISDN user ports at L2	38
8.7.4 Flow control using LAPV5-DL mechanisms	39
9 Envelope Function sublayer of LAPV5 (LAPV5-EF)	39
9.1 Frame structure for peer-to-peer communication	39
9.1.1 General	39
9.1.2 Flag sequence	39
9.1.3 Interframe time fill	39
9.1.4 Envelope function address field	39
9.1.5 Envelope information field	40
9.1.6 Transparency	40
9.1.7 FCS	40
9.1.8 Format convention	40
9.1.9 Invalid frames	40

9.1.10	Frame aborts	41
9.2	Format of fields for data link envelope peer-to-peer communication	41
9.2.1	Envelope function address field format	41
9.2.2	Address field variables.....	41
9.2.2.1	Address field extension bit.....	41
9.2.2.2	EFaddr.....	41
10	Data link sublayer of LAPV5 (LAPV5-DL).....	41
10.1	Frame structure for peer-to-peer communication	41
10.1.1	General.....	41
10.1.2	Link address field.....	42
10.1.3	Control field.....	42
10.1.4	Information field.....	42
10.1.5	Format convention	42
10.2	Invalid frames.....	42
10.3	Elements of procedures and formats of fields for data link sublayer peer-to-peer communication	42
10.3.1	Link address field format	42
10.3.2	Link address field variables	43
10.3.2.1	Address field extension (EA) bit.....	43
10.3.2.2	Command/response field bit.....	43
10.3.2.3	V5DLaddr	43
10.3.3	Control field formats.....	43
10.3.4	Control field parameters and associated state variables.....	43
10.3.5	Frame types.....	43
10.4	Definition of the peer-to-peer procedures of the data link sublayer	43
10.4.1	General.....	43
10.4.2	Procedure for the use of the Poll/Final (P/F) bit.....	45
10.4.3	Terminal Endpoint Identifier (TEI) management procedures	45
10.4.4	Automatic negotiation of data link layer parameters	45
10.4.5	Procedures for establishment and release of multiple frame operation.....	45
10.4.5.1	Establishment of multiple frame operation.....	45
10.4.5.1.1	General	45
10.4.5.1.2	Establishment procedures.....	46
10.4.5.1.3	Procedure on expiry of timer T200.....	46
10.4.5.2	Information transfer.....	47
10.4.5.3	Termination of multiple frame operation	47
10.4.5.4	Link-not-established state.....	47
10.4.5.5	Collision of unnumbered commands and responses.....	47
10.4.5.5.1	Identical transmitted and received commands	47
10.4.5.5.2	Different transmitted and received commands.....	47
10.4.5.6	Unsolicited DM response and SABME command	47
10.4.6	Procedures for information transfer in multiple frame operation.....	48
10.4.7	Re-establishment of multiple frame operation	48
10.4.7.1	Criteria for re-establishment.....	48
10.4.7.2	Procedures.....	48
10.4.8	Exception condition reporting and recovery	48
10.4.9	List of system parameters.....	49
10.4.10	Data link monitor function.....	49
10.4.10.1	General	49
10.4.10.2	Data link layer supervision in the multiple-frame-established state	49
10.4.10.3	Connection verification procedures.....	49
10.4.11	PSTN and control data link FSM and requirements	49
10.4.11.1	General.....	50
10.4.11.2	Data link FSM.....	51
11	AN frame relay sublayer	52
11.1	General	52
11.2	Invalid frames.....	52
11.3	Detailed description of the AN frame relay function.....	53
11.3.1	Frame received from LE	53
11.3.2	Frame received from ISDN user port.....	53

12	Sublayer-to-sublayer communication and MF	54
12.1	LAPV5-EF to LAPV5-DL communication	54
12.2	LAPV5-DL to LAPV5-EF communication	54
12.3	AN-FR to LAPV5-EF communication	54
12.4	LAPV5-EF to AN-FR communication	54
13	PSTN signalling protocol specification and L3 multiplexing	54
13.1	General	54
13.1.1	Introduction	54
13.1.2	Separation of responsibilities	55
13.1.3	National specific PSTN signal information elements	55
13.2	PSTN protocol entity definition	56
13.2.1	Definition of PSTN path states and explanation	56
13.2.1.1	Path states in the AN (AN(PSTN))	56
13.2.1.2	Path states in the LE (LE(PSTN))	56
13.2.2	Definition of PSTN protocol primitives, messages and timers	57
13.3	PSTN protocol message definition and content	58
13.3.1	Establish	59
13.3.2	Establish ACK	59
13.3.3	Signal	60
13.3.4	Signal ACK	60
13.3.5	Status	61
13.3.6	Status enquiry	61
13.3.7	Disconnect	61
13.3.8	Disconnect complete	61
13.3.9	Protocol parameter	62
13.4	General message format and information element coding	62
13.4.1	Overview	62
13.4.2	Protocol discriminator	63
13.4.3	L3addr	63
13.4.4	Message type	63
13.4.5	Coding of other information elements	64
13.4.6	Single octet information elements	65
13.4.6.1	Pulse notification	65
13.4.6.2	Line-information	65
13.4.6.3	State	65
13.4.6.4	Autonomous-signalling-sequence	66
13.4.6.5	Sequence-response	66
13.4.7	Information elements with variable length format	66
13.4.7.1	Sequence-number	66
13.4.7.2	Cadenced-ringing	67
13.4.7.3	Pulsed-signal	68
13.4.7.4	Steady-signal	69
13.4.7.5	Digit-signal	70
13.4.7.6	Recognition-time	71
13.4.7.7	Enable-autonomous-acknowledge	71
13.4.7.8	Disable-autonomous-acknowledge	72
13.4.7.9	Cause	73
13.4.7.10	Resource-unavailable	74
13.4.7.11	Enable-metering	74
13.4.7.12	Metering-report	75
13.4.7.13	Attenuation	76
13.5	PSTN call control procedures	76
13.5.1	General	77
13.5.2	Handling of error conditions	77
13.5.2.1	Protocol discriminator error	78
13.5.2.2	L3addr error	78
13.5.2.3	Message type error	78
13.5.2.4	Information element out of sequence	79
13.5.2.5	Repeated information elements	79
13.5.2.6	Mandatory information element missing	79

13.5.2.7	Unrecognized information element	80
13.5.2.8	Content error of mandatory information element	80
13.5.2.9	Content error of optional information element	80
13.5.2.10	Unexpected message	81
13.5.2.11	Optional information element not allowed	81
13.5.2.12	Optional information element missing	81
13.5.2.13	Status enquiry procedure	81
13.5.2.14	Status procedure	82
13.5.3	Path related procedures	83
13.5.3.1	Path initiation by AN	84
13.5.3.1.1	Subscriber seizure request	84
13.5.3.1.2	Subscriber seizure confirmation	84
13.5.3.2	Path initiation by LE	85
13.5.3.2.1	Establish request	85
13.5.3.2.2	Establish acknowledge	86
13.5.3.3	Path collision	86
13.5.3.3.1	Originating call prevail	87
13.5.3.3.2	Destination call prevail	87
13.5.3.4	Path active	87
13.5.3.4.1	Normal operation	87
13.5.3.4.2	Exceptional procedures	88
13.5.3.5	Disconnecting path	88
13.5.3.5.1	Disconnect request	89
13.5.3.5.2	Disconnect acknowledge	90
13.5.3.6	Line information procedure	90
13.5.3.6.1	Normal operation	90
13.5.3.6.2	Exceptional procedures	91
13.5.4	Non-path related procedures	91
13.5.4.1	Protocol parameter procedures	91
13.5.4.1.1	Normal operation	91
13.5.4.1.2	Exceptional procedures	91
13.5.4.2	Port blocking procedures	92
13.5.4.3	Restart procedure	92
13.5.5	L3 error detection procedure	93
13.5.5.1	Multiple SIGNAL message operation - variables, sequence numbers and timers	93
13.5.5.1.1	Modulus	93
13.5.5.1.2	Send sequence variable S(S)	93
13.5.5.1.3	Acknowledge sequence variable S(A)	93
13.5.5.1.4	Send sequence number M(S)	93
13.5.5.1.5	Receive sequence variable S(R)	93
13.5.5.1.6	Receive sequence number M(R)	94
13.5.5.1.7	Timer Tt	94
13.5.5.1.8	Timer Tr	94
13.5.5.2	Multiple SIGNAL message operation - procedures	94
13.5.5.2.1	Initialization	94
13.5.5.2.2	Sending a SIGNAL message	94
13.5.5.2.3	Sending a SIGNAL ACK message	94
13.5.5.2.4	Receiving a SIGNAL message	94
13.5.5.2.5	Receiving a SIGNAL ACK message	94
13.5.5.2.6	Start of timer Tr	95
13.5.5.2.7	Stop of timer Tr	95
13.5.5.2.8	Timeout of timer Tr	95
13.5.5.2.9	Start of timer Tt	95
13.5.5.2.10	Stop of timer Tt	95
13.5.5.2.11	Timeout of timer Tt	95
13.5.5.2.12	Receiving a DISCONNECT message	95
13.5.5.3	Multiple SIGNAL message operation - values	95
13.5.5.3.1	Number of outstanding SIGNAL messages	95
13.5.5.3.2	Timer Tt	95
13.5.5.3.3	Timer Tr	95

13.6	List of system parameters	96
13.7	AN and LE side state tables.....	97
14	Control requirements and protocol	103
14.1	ISDN user port status indication and control protocol	104
14.1.1	General aspects	104
14.1.2	Events and function elements relevant for the control of the state machines	105
14.1.3	ISDN user port FSMs, AN (ISDN port) and LE (ISDN port).....	107
14.1.3.1	Description of the states	107
14.1.3.2	Definition of port control states.....	108
14.1.3.2.1	ISDN user port FSM - AN (ISDN port)	108
14.1.3.2.2	ISDN User port FSM - LE (ISDN port)	109
14.1.3.3	Principles and procedures	110
14.1.3.3.1	General	110
14.1.3.3.2	Blocking	110
14.1.3.3.3	Blocking request	110
14.1.3.3.4	Co-ordinated unblocking	110
14.1.3.3.5	Activation	111
14.1.3.4	ISDN port FSM at the AN.....	112
14.1.3.5	ISDN port FSM at the LE	114
14.1.4	Performance monitoring aspects	115
14.2	PSTN user port status indication and control protocol.....	115
14.2.1	General aspects	115
14.2.2	Events and function elements relevant for the control of the state machines	116
14.2.3	PSTN user port FSM, AN (PSTN port) and LE (PSTN port)	117
14.2.3.1	Description of the states	117
14.2.3.2	Definition of port control states.....	117
14.2.3.2.1	PSTN user port FSM - AN (PSTN port)	117
14.2.3.2.2	PSTN user port FSM - LE (PSTN port).....	118
14.2.3.3	Principles and procedures	118
14.2.3.3.1	General	118
14.2.3.3.2	Blocking	118
14.2.3.3.3	Blocking request	118
14.2.3.3.4	Co-ordinated unblocking	119
14.2.3.4	PSTN port FSM at the AN	119
14.2.3.5	PSTN port FSM at the LE.....	119
14.3	Interface L1 maintenance requirements and protocol	120
14.3.1	Events and failure reports	120
14.3.2	Detection algorithm for events and signals	121
14.3.3	V5.1 interface L1 FSM	121
14.3.4	Requirements and procedures for the additional functions	122
14.4	Control protocol	122
14.4.1	Control protocol message definition and content.....	122
14.4.1.1	PORT CONTROL message	123
14.4.1.2	PORT CONTROL ACK message	123
14.4.1.3	COMMON CONTROL message	124
14.4.1.4	COMMON CONTROL ACK message.....	124
14.4.2	General message format and information element coding	124
14.4.2.1	Overview	124
14.4.2.2	Protocol discriminator information element.....	125
14.4.2.3	L3addr information element	125
14.4.2.4	Message type information element.....	125
14.4.2.5	Other information elements	126
14.4.2.5.1	Coding rules.....	126
14.4.2.5.2	Performance grading information element.....	126
14.4.2.5.3	Rejection cause information element.....	127
14.4.2.5.4	Control function element information element	127
14.4.2.5.5	Control function ID information element	127
14.4.2.5.6	Variant information element	128
14.4.2.5.7	Interface ID information element.....	128
14.4.3	State definitions of the control protocol.....	129

14.4.3.1	Port control protocol	129
14.4.3.2	Common control protocol	129
14.4.4	Control protocol procedures	130
14.4.4.1	General	130
14.4.4.2	Handling of error conditions	130
14.4.4.2.1	Protocol discriminator error	131
14.4.4.2.2	L3addr error.....	131
14.4.4.2.3	Message type error	131
14.4.4.2.4	Repeated information elements.....	131
14.4.4.2.5	Mandatory information element missing	131
14.4.4.2.6	Unrecognized information element.....	131
14.4.4.2.7	Content error of mandatory information elements	132
14.4.4.2.8	Content error of conditional information element	132
14.4.4.2.9	Conditional information element not allowed.....	132
14.4.4.3	Start traffic indication.....	132
14.4.4.4	Stop traffic indication.....	133
14.4.4.5	Port control protocol procedure	133
14.4.4.6	Common control protocol procedure	134
14.4.4.7	Timers for the control protocol	134
14.4.4.8	AN and LE side state tables	135
14.5	V5.1 re-provisioning procedures	136
14.5.1	General aspects	136
14.5.2	Events and states.....	137
14.5.2.1	Events.....	137
14.5.2.2	Definition of the AN and LE states for the re-provisioning procedures	137
14.5.3	Re-provisioning FSMs	137
14.5.3.1	AN (variant&ID) and LE (variant&ID) state tables for the verification procedure.....	138
14.5.3.2	AN (re-pro) and LE (re-pro) state tables for the re-provisioning synchronization procedure	138
14.5.4	Procedures	139
14.5.4.1	Request variant and ID.....	139
14.5.4.2	Verify re-provisioning.....	140
14.5.4.3	Re-provisioning synchronization.....	140
14.5.4.4	Restart procedure	141
Annex A (normative):	Requirements for the support of the PL capability through an ISDN-BA.....	142
Annex B (normative):	Assumptions and requirements for the support of semi-permanent leased lines	143
B.1	General	143
B.2	Signalling associated with semi-permanent leased lines	143
B.3	User ports	143
B.4	Requirements for non-ISDN user ports for semi-permanent leased lines.....	144
Annex C (normative):	Basic requirements of the system management functions in AN and LE	145
Annex D (normative):	Use of the protocol information elements for national PSTN protocols	157
D.1	Introduction	157
D.2	The placement of information elements.....	158
D.2.1	Information elements within the ESTABLISH message.....	158
D.2.2	Information elements within the ESTABLISH-ACK message	158
D.2.3	Information elements within the SIGNAL message	159
D.2.4	Information elements within the DISCONNECT message	159
D.2.5	Information elements within the DISCONNECT-COMplete message.....	159
D.2.6	Information elements within the PROTOCOL-PARAMETER message.....	160

D.3	The information elements	160
D.3.1	Line-information information elements	160
D.3.1.1	Impedance marker reset	160
D.3.1.2	Impedance marker set	160
D.3.1.3	Low loop impedance	160
D.3.1.4	Anomalous loop impedance	161
D.3.1.5	Anomalous line condition received	161
D.3.2	Pulse-notification information element	161
D.3.3	Autonomous-signalling-sequence information element	161
D.3.4	Sequence-response information element	161
D.3.5	Cadenced-ringing information element	161
D.3.6	Pulsed-signal information element	162
D.3.6.1	The pulse type	162
D.3.6.2	The suppression indicator	162
D.3.6.2.1	Suppression indicator value 00	162
D.3.6.2.2	Suppression indicator value 01	162
D.3.6.2.3	Suppression indicator value 10	162
D.3.6.2.4	Suppression indicator value 11	163
D.3.6.3	The pulse duration type	163
D.3.6.4	The acknowledgement request indicator	163
D.3.6.5	The number of pulses	163
D.3.7	Use of pulsed signals	163
D.3.7.1	Pulsed normal polarity	163
D.3.7.2	Pulsed reverse polarity	163
D.3.7.3	Pulsed battery on C-wire	164
D.3.7.4	Pulsed on-hook	164
D.3.7.5	Pulsed reduced battery	164
D.3.7.6	Pulsed no battery	164
D.3.7.7	Meter pulse	164
D.3.7.8	Initial ring	164
D.3.7.9	Pulsed off-hook	164
D.3.7.10	Pulsed b-wire connected to earth	164
D.3.7.11	Register recall (timed open loop)	164
D.3.7.12	Earth loop pulse	164
D.3.7.13	50 Hz pulse	164
D.3.7.14	Pulsed b-wire connected to battery	164
D.3.7.15	Pulsed a-wire connected to earth	164
D.3.7.16	Pulsed a-wire connected to battery	165
D.3.7.17	Pulsed c-wire connected to earth	165
D.3.7.18	Pulsed c-wire disconnected	165
D.3.7.19	Pulsed normal battery	165
D.3.7.20	Pulsed a-wire disconnected	165
D.3.7.21	Pulsed b-wire disconnected	165
D.3.8	Use of steady signals	165
D.3.8.1	Normal-polarity	165
D.3.8.2	Reversed-polarity	165
D.3.8.3	Battery on c-wire	165
D.3.8.4	No battery on c-wire	165
D.3.8.5	Off hook (loop closed)	165
D.3.8.6	On hook (loop open)	166
D.3.8.7	Battery on a-wire	166
D.3.8.8	No battery on b-wire	166
D.3.8.9	Reduced battery	166
D.3.8.10	No battery	166
D.3.8.11	Alternate reduced power/no power	166
D.3.8.12	No battery on a-wire	166
D.3.8.13	Normal battery	166
D.3.8.14	Stop ringing	166
D.3.8.15	Start pilot frequency	166
D.3.8.16	Stop pilot frequency	166

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 324-1 V2.1.1:2005](#)

[/catalog/standards/sist/5e2880b8-2943-4bf3-a39e-1853/sist-en-300-324-1-v2-1-1-2005](#)

D.3.8.17	A-wire on earth	166
D.3.8.18	Low impedance on b-wire.....	167
D.3.8.19	B-wire connected to earth	167
D.3.8.20	B-wire disconnected from earth	167
D.3.8.21	Battery on b-wire	167
D.3.8.22	Low loop impedance.....	167
D.3.8.23	High loop impedance	167
D.3.8.24	Anomalous loop impedance.....	167
D.3.8.25	A-wire disconnected from earth.....	167
D.3.8.26	C-wire on earth	167
D.3.8.27	C-wire disconnected from earth.....	167
D.3.8.28	Ramp to reversed polarity.....	167
D.3.8.29	Ramp to normal polarity	167
D.3.9	Digit-signal information element	168
D.3.10	Recognition-time information element.....	168
D.3.11	Enable-autonomous-acknowledge information element.....	168
D.3.11.1	Suppression indicator value 00	168
D.3.11.2	Suppression indicator value 01	168
D.3.11.3	Suppression indicator value 10	168
D.3.11.4	Suppression indicator value 11	169
D.3.12	Default values for the Enable-autonomous-acknowledge information element.....	169
D.3.13	Use of the Autonomous-signalling-sequence.....	169
D.3.14	Disable-autonomous-acknowledge information element.....	169
D.3.15	Enable-metering information element	169
D.3.15.1	The pulse type.....	169
D.3.15.2	The rate type	170
D.3.15.3	The reporting pulse count	170
D.3.15.4	The repetition indicator.....	170
D.3.15.5	The suppression indicator.....	170
D.3.15.6	The pulse duration type.....	170
D.3.16	Metering-report information element.....	170
D.3.16.1	The pulse count.....	170
D.3.16.2	The Report type	170
D.3.16.2.1	Report type value 00	171
D.3.16.2.2	Report type value 01	171
D.3.16.2.3	Report type value 10	171
D.3.16.2.4	Report type value 11	171
D.3.16.3	The failure reason	171
D.3.17	Attenuation information element	171
D.4	Signalling sequences in the event of failure of a V5.1 interface to return a user port to the idle condition before releasing the signalling path	171
D.4.1	Protocol implications of going directly to the NULL state.....	172
D.4.2	Protocol implications of going to the BLOCKED state.....	172

D.5	Leaving the BLOCKED state.....	172
D.6	Pre-defined PSTN port states.....	172
D.7	The line parked condition	173
D.8	Information element meaning	173
D.9	Coding of pulse duration types	173
D.10	Ring signals and their placement in V5 messages	173
D.11	Resource unavailable	174
Annex E (informative):	Service scenarios, architecture and functional definition of access arrangements with AN at the LE.....	175
E.1	Conclusions on multiple V5 interface applications	175
E.2	Conclusions on architecture aspects	175
E.3	Implementation of QAN.....	176
Annex F (informative):	The concept and requirements for the upgrade of a V5.1 interface to a V5.2 interface	177
Annex G (informative):	Use of function element primitives in the V5 PSTN protocol	178
G.1	Introduction	178
G.2	FE primitives used in the PSTN protocol entity in the AN	178
G.2.1	FE-subscriber_seizure	178
G.2.2	FE-subscriber_release	178
G.2.3	FE-line_information	179
G.2.4	FE-line_signal	179
G.3	FE primitives used in the PSTN protocol entity in the LE	179
G.3.1	FE-establish_request.....	179
G.3.2	FE-establish_acknowledge_indication	179
G.3.3	FE-establish_indication	180
G.3.4	FE-establish_acknowledge	180
G.3.5	FE-disconnect_request	180
G.3.6	FE-disconnect_complete_request.....	180
G.3.7	FE-line_signal_request.....	180
G.3.8	FE-line_signal_indication.....	181
G.3.9	FE-protocol_parameter_request	181
G.3.10	FE-disconnect_complete_indication.....	181

Annex H (informative):	PSTN protocol; explanatory notes and information flow.....	182
H.1	Explanatory notes.....	182
H.2	Information flow diagrams.....	184
Annex J (informative):	AN requirement for pulse dialling	187
Annex K (informative):	L3 error detection procedure	188
K.1	Variables and sequence numbers	188
K.2	Values of counters and timers.....	189
K.3	Procedures.....	189
K.4	Examples of the error detection mechanism.....	189
Annex L (informative):	SDL diagrams	191
Annex M (informative):	Structures used in the V5.1 interface.....	192
Annex N (informative):	Protocol architecture for PSTN and ISDN user port control	194
N.1	Scope.....	194
N.2	ISDN user port status control.....	194
N.2.1	Functional split between LE and AN.....	194
N.2.2	Information transfer between LE and AN.....	194
N.2.3	Activation/deactivation procedure.....	195
N.3	PSTN user port control - information transfer between LE and AN.....	196
Annex P (informative):	Items identified to be pre-defined or provisioned	197
Bibliography	198
Index	199
History	201

ITeh STANDARD PREVIEW
 (standards.iteh.ai)

SIST EN 300 324-1 V2.1.1:2005

<https://standards.iteh.ai/catalog/standards/sist/5e2880b8-2943-4bf3-a39e->

[c047f602d853/sist-en-300-324-1-v2-1-1-2005](https://standards.iteh.ai/catalog/standards/sist/5e2880b8-2943-4bf3-a39e-c047f602d853/sist-en-300-324-1-v2-1-1-2005)

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

The present document is part 1 of a multi-part EN covering the V interfaces at the digital Local Exchange (LE); V5.1 interface for the support of Access Network (AN), as identified below:

- Part 1: "V5.1 Interface Specification";**
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network layer (AN side)";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network layer (AN side)";
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network layer (LE side)";
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network layer (LE side)";
- Part 7: "Test Suite Structure and Test Purposes (TSS&TP) specification for the data link layer";
- Part 8: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the data link layer";
- Part 9: "Test specification for the physical layer".

National transposition dates

Date of adoption of this EN:	7 April 2000
Date of latest announcement of this EN (doa):	31 July 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2001
Date of withdrawal of any conflicting National Standard (dow):	31 January 2001