



SLOVENSKI STANDARD

SIST EN 300 957 V7.0.1:2003

01-december-2003

8 [[]HJb]`WV] b]`hY`Y_ca i b]_UW`g_]`g]ghYa `fZuU&ŽL`E`BYgfi _hi f]fUb]`dcXUh_] Xcdc`b]`bY`gbcf]hj Yfi GG8L`E`Grcdb`U' `fi GA `\$("- \$žfUn`]]WJ+"\$"%ž]nXU`U% - , Ł

Digital cellular telecommunications system (Phase 2+) (GSM); Unstructured Supplementary Service Data (USSD); Stage 3 (GSM 04.90 version 7.0.1 Release 1998)

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten z: ^{SIST EN 300 957 V7.0.1:2003} EN 300 957 Version 7.0.1

<https://standards.iteh.ai/catalog/standards/sist/1074aa85-c5e5-4b2c-97aa-448a38552391/sist-en-300-957-v7-0-1-2003>

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST EN 300 957 V7.0.1:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 957 V7.0.1:2003](https://standards.iteh.ai/catalog/standards/sist/1074aa85-c5e5-4b2c-97aa-448a38552391/sist-en-300-957-v7-0-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/1074aa85-c5e5-4b2c-97aa-448a38552391/sist-en-300-957-v7-0-1-2003>

ETSI EN 300 957 V7.0.1 (2000-01)

European Standard (Telecommunications series)

**Digital cellular telecommunications system (Phase 2+);
Unstructured Supplementary Service Data (USSD);
Stage 3
(GSM 04.90 version 7.0.1 Release 1998)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

GSM®
GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

[SIST EN 300 957 V7.0.1:2003](https://standards.iteh.ai/catalog/standards/sist/1074aa85-c5e5-4b2c-97aa-448a38552391/sist-en-300-957-v7-0-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/1074aa85-c5e5-4b2c-97aa-448a38552391/sist-en-300-957-v7-0-1-2003>



Reference

REN/SMG-030490Q7

Keywords

Digital cellular telecommunications system,
Global System for Mobile communications (GSM)

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88<https://standards.etsi.org/standards-search/3e5-4b2c-97aa-448a38552391/sist-en-300-957-v7-0-1-2003>

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from

<http://www.etsi.org>

If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).

In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
3 Abbreviations	5
4 Cross phase compatibility	5
5 Network initiated unstructured supplementary service data operations	6
5.1 Unstructured supplementary service data request.....	6
5.1.1 Normal operation	6
5.2 Unstructured supplementary service data notification	8
5.2.1 Normal operation	8
6 Mobile initiated unstructured supplementary service data operations.....	10
6.1 Normal operation.....	10
6.2 Cross phase compatibility.....	12
6.2.1 Network only supports protocol version 1 of unstructured supplementary service data operations.....	12
6.2.2 Mobile station only supports protocol version 1 of unstructured supplementary service data operations.....	12
Annex A (informative): Change Request History	13
History	14

[SIST EN 300 957 V7.0.1:2003](https://standards.iteh.ai/catalog/standards/sist/1074aa85-c5e5-4b2c-97aa-448a38552391/sist-en-300-957-v7-0-1-2003)
<https://standards.iteh.ai/catalog/standards/sist/1074aa85-c5e5-4b2c-97aa-448a38552391/sist-en-300-957-v7-0-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by the Special Mobile Group (SMG).

The present document specifies the stage 3 description of the Unstructured Supplementary Service Data (USSD) operations within the digital cellular telecommunications system.

The specification from which the present document has been derived was originally based on CEPT documentation, hence the presentation of the present document may not be entirely in accordance with the ETSI/PNE rules.

The contents of the present document is subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document it will be re-released with an identifying change of release date and an increase in version number as follows:

Version 7.x.y

where:

- 7 indicates Release 1998 of GSM Phase 2+.
- x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

National transposition dates

Date of adoption of this EN:	31 December 1999
Date of latest announcement of this EN (doa):	31 March 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 September 2000
Date of withdrawal of any conflicting National Standard (dow):	30 September 2000

1 Scope

The present document gives the stage 3 description of the Unstructured Supplementary Service Data (USSD) operations.

The group of unstructured supplementary service data operations is divided into two different classes:

- Network initiated unstructured supplementary service data operations (clause 5);
- Mobile initiated unstructured supplementary service data operations (clause 6).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1998 document, references to GSM documents are for Release 1998 versions (version 7.x.y).

- [1] GSM 01.04: "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 04.08: "Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification".
- [3] GSM 04.80: "Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 supplementary services specification; Formats and coding".

3 Abbreviations

Abbreviations used in the present document are listed in GSM 01.04.

4 Cross phase compatibility

For the mobile initiated USSD operations, a number of changes exist between the present document and the protocol version 1 specification. For these operations the main body of the present document assumes that all network entities comply with this version of the service. In this case an additional subclause defines the additional requirements for when one or more network entities or the Mobile Station (MS) complies with the protocol version 1 specifications for the USSD operations.

5 Network initiated unstructured supplementary service data operations

5.1 Unstructured supplementary service data request

5.1.1 Normal operation

The network invokes an USSD request by sending a REGISTER message containing a UnstructuredSS-Request invoke component to the MS.


The MS shall respond to the request by sending a FACILITY message containing the user's mobile subscriber's response in a return result component. The network shall pass the data received in the response to the application handling USSD operations and shall wait for the response of the application. The application may either continue or terminate the dialogue.

When the application continues the dialogue, it may initiate another USSD operation by sending a FACILITY message (see figure 5.2). The operation may either be an USSD request or notification (see subclause 5.1.2).

When the application terminates the dialogue, the network shall clear the transaction by sending a RELEASE COMPLETE message. The MS may also clear the transaction at any time by sending a RELEASE COMPLETE message upon the request of the user.


If the MS is unable to process the request received from the network, it shall return an error indication by sending a FACILITY message containing a return error component. Error values are specified in GSM 04.80.

When the MS receives an USSD operation in parallel to any call independent supplementary service transaction, it shall respond with a return error component in a RELEASE COMPLETE message, containing the "USSD-Busy" error as specified in GSM 04.80, to indicate the failure in handling a parallel USSD operation. However, the network is allowed to initiate USSD operations in parallel to call related transactions.



NOTE: The MS may clear the transaction at any time by sending a RELEASE COMPLETE upon request of the user.

Figure 5.1: Single network initiated USSD request



NOTE 1: The MS may clear the transaction at any time by sending a RELEASE COMPLETE upon request of the user.

NOTE 2: The second USSD operation may also be an USSD notification. The network may use the on-going transaction for sending further USSD operations. Only one additional USSD request is shown.

Figure 5.2: Multiple network initiated USSD request