

International **Standard**

ISO/IEC 15444-4

Information technology — JPEG 2000 image coding system —

Part 4:

Conformance testing iTeh Standards

Technologies de l'information — Système de codage d'images JPEG 2000 — **Document Preview**

Partie 4: Tests de conformité

Fourth edition 2024-05

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/IEC 15444-4:2024

https://standards.iteh.ai/catalog/standards/iso/223c7739-442f-4b7f-b650-bd9200e144cd/iso-iec-15444-4-2024



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted.

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and https://patents.iec.ch. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by ITU-T (as ITU-T Rec T.803) and drafted in accordance with its editorial rules, in collaboration with Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

This fourth edition cancels and replaces the third edition (ISO/IEC 15444-4:2021), which has been technically revised.

The main changes are as follows:

- the maximum allowable errors associated with compliance Class 1, for both Rec. ITU-T T.800 | ISO/IEC 15444-1 and Rec. ITU-T T.814 | ISO/IEC 15444-15 codestreams, have been relaxed in a few cases to ensure that well designed 16-bit fixed-point implementations of the inverse discrete wavelet transform should be able to pass all compliance tests for Class 1;
- two additional test codestreams have been added along with conformance bounds, to facilitate testing of inverse wavelet and component decorrelating transform accuracy;
- a number of codestreams and files conforming to Rec. ITU-T T.801 | ISO/IEC 15444-2 have been included for informative purposes only, to facilitate the development of decoders and file format readers that are able to support features beyond the core capabilities found in Rec. ITU-T T.800 | ISO/IEC 15444-1 and Rec. ITU-T T.814 | ISO/IEC 15444-15.

A list of all parts in the ISO/IEC 15444 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/IEC 15444-4:2024

CONTENTS

L	Scope				
2	Refer	rences			
3	Defin	nitions			
1	Abbre	eviations	and symbols		
	4.1		iations		
	4.2		S		
5		•			
_					
)	General description.				
	6.1		, derived sets and compliance classes		
	6.2		rs		
	6.3		rs and codestreams		
			entation compliance statement		
	6.5		t test suites		
	6.6		r compliance testing procedure		
	6.7		r compliance testing procedure		
	6.8		ares for testing file format readers		
	6.9		nal test codestreams and files		
7	Copy	right			
3	Comr	oliance fil	es availability and updates		
	_		mpliance classes		
AIIIIC.	A.1		ance class parameter definitions		
	A.1	A.1.1	Profile: codestream guarantees.		
		A.1.2	H, W, C: Image size guarantees		
		A.1.3	$N_{\rm cb}$: Code-block parsing guarantee		
		A.1.4	N_{comp} : Component parsing guarantee		
		A.1.5	L _{body} : Coded data buffering guarantee		
		A.1.6	M: Decoded bit-plane guarantee		
		A.1.7	P: 9-7I precision guarantee		
		A.1.8	B: 5-3R precision guarantee		
		A.1.9	T _L : Transform level guarantee		
		A.1.10	L: Layer guarantee		
		A.1.11 A.1.12	Progressions Tile-parts		
			Precincts Precincts		
			M _{MAGB} : Magnitude bound guarantee		
	A.2		ance class definitions		
	A.3		s encoding and decoding		
A					
Anne			mpliance testing procedures		
	B.1				
	B.2		r test procedure		
		B.2.1	Files for testing.		
		B.2.2 B.2.3	Decoder settings Output file format conversion		
		B.2.3 B.2.4	Compare decoded and formatted components with reference components		
		B.2.4 B.2.5	Compare error metrics with specification		
		B.2.6	Reference components file format		
1 nna	, C C		tests		
-xiine		-			
	C.1		t test suite (informative)		
		C.1.1 C.1.2	Syntax and compressed data order Arithmetic entropy encoding		
		C.1.2 C.1.3	Coefficient bit modelling		
		C.1.3	Quantization		
		C.1.5	Discrete wavelet transform.		
		C.1.6	DC level shift and multiple component transform		

	C.1.7 Region of interest							
	C.1.8 JP2 file format							
	C.1.9 High throughput cleanup pass coding							
	C.1.10 HT refinement pass coding							
	C.1.11 Placeholder passes							
	C.1.12 Whiting of 111 and 32K code-blocks within 11132K codesucanis							
C.2								
C.2	C.2.1 Class 0 Profile-0							
	C.2.2 Class 0 Profile-1							
	C.2.3 Class 1 Profile-0	28						
	C.2.4 Class 1 Profile-1	30						
	C.2.5 Class 1HF Profile 1	30						
Annex D I	Encoder compliance test procedure	32						
D.1	l General	32						
D.2	2 Reference decoder	32						
D.3	3 Compliance requirement and acceptance	32						
D.4	4 Encoding compliance test procedure	32						
Annex E I	Decoder implementation compliance statement	34						
E.1	•							
E.2								
E.3	<u>.</u>							
Annex F F	Encoder implementation compliance statement							
F.1								
F.2								
	JP2 and JPH file format reader compliance testing procedures							
G.1								
G.1 G.2								
G.2 G.3								
G.3 G.4								
0.4	G.4.1 Test files							
	G.4.2 Reference decoded images							
	G.4.3 Tolerances G.4.3							
	G.4.4 Additional information regarding the JP2 test files	41						
G.5	5 JPH file format test codestreams and images							
	G.5.1 Test files							
	G.5.2 Relationship between the JP2 and JPH test files							
	nex H Test codestreams and files conforming to Rec. ITU-T T.801 ISO/IEC 15444-2							
H.1								
H.2	2 Extended test codestreams	43						
H.3	3 JPX test files	44						
Bibliograp	phy	45						
Electronic	attachment: Codestreams used in the application of the procedures described in this Specific	cation.						
	List of Tables							
		Page						
Table 1 – H	HTJ2K derived sets employed in this Recommendation International Standard	8						
	- Definitions of compliance classes (Cclass) for J2K decoders							
	•							
	- Definitions of HiFi compliance classes							
Table C.1 -	- Class 0 Profile-0 reference images and allowable errors	23						
Table C.1b	bis – Additional allowable errors for HTJ2K TCSs belonging to derived set 0	24						
Table C.2 -	- Items tested by Profile-0 codestreams	24						
	bis – Items tested by derived set 0 HTJ2K codestreams							
1 aoic C.20	and the state of defined set of 111321x codestication	23						

Table C.3 – Profile-0 codestream 0 contents	. 26
Table C.4 – Class 0 Profile-1 reference images and allowable errors	. 27
Table C.4bis – Additional allowable errors for HTJ2K TCSs belonging to derived set 1	. 27
Table C.5 – Items tested by Profile-1 codestreams	. 28
Table C.5bis – Items tested by derived set 1 HTJ2K codestreams	. 28
Table C.6 – Class 1 Profile-0 reference files and maximum error	. 29
Table C.7 – Class 1 Profile-1 reference images and allowable error	. 30
Table C.8 – Class 1HF Profile 1 reference images and allowable error	. 31
Table E.1 – ICS for defined Cclasses, profiles and derived sets	. 34
Table E.2 – Extended capabilities for Cclass 0	. 35
Table E.3 – Extended capabilities for Cclass 1	. 35
Table E.4 – Extended capabilities for Cclass 2	. 35
Table E.5 – Extended capabilities for derived Cclass 0h	. 36
Table E.6 – Extended capabilities for derived Cclass 1h	. 36
Table E.7 – Extended capabilities for derived Cclass 2h	. 36
Table F.1 – Encoder implementation marker usage	. 37
Table G.1 – JP2 reference images and allowable error	. 41
Table H.1 – Properties of each extended codestream	. 43
Table H.2 – Properties of each JPX test file	. 44
iTeh Standards List of Figures	
Figure B.1 – Decoder compliance test flow chart	. 15
Figure D.1 – Encoder compliance test block diagram	
Figure C.1. IP2 file format reader compliance test block diagram	40

ISO/IEC 15444-4:2024

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/IEC 15444-4:2024

INTERNATIONAL STANDARD ITU-T RECOMMENDATION

Information technology – JPEG 2000 image coding system: Conformance testing

1 Scope

This Recommendation | International Standard specifies the framework, concepts, methodology for testing, and criteria to be achieved to claim compliance to Rec. ITU-T T.800 | ISO/IEC 15444-1 or Rec. ITU-T T.814 | ISO/IEC 15444-15. It provides a framework for specifying abstract test suites (ATSs) and for defining the procedures to be followed during compliance testing.

This Recommendation | International Standard:

- specifies compliance testing procedures for encoding and decoding using Rec. ITU-T T.800 |
 ISO/IEC 15444-1 and Rec. ITU-T T.814 | ISO/IEC 15444-15;
- specifies codestreams, decoded images, and error metrics to be used with the testing procedures;
- specifies ATSs;
- provides guidance for creating an encoder compliance test

This Recommendation | International Standard does not include the following tests:

Acceptance testing: the process of determining whether an implementation satisfies acceptance criteria and enables the user to determine whether or not to accept the implementation. This includes the planning and execution of several kinds of tests (e.g., functionality, quality, and speed performance testing) that demonstrate that the implementation satisfies the user requirements.

Performance testing: measures the performance characteristics of an implementation under test (IUT) such as its throughput and responsiveness, under various conditions.

Robustness testing: the process of determining how well an implementation processes data which contains errors.

2 References

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

- Recommendation ITU-T T.800 | ISO/IEC 15444-1, Information technology JPEG 2000 image coding system: Core coding system.
- Recommendation ITU-T T.814 | ISO/IEC 15444-15, Information technology JPEG 2000 image coding system: High-throughput JPEG 2000.

3 Definitions

For the purposes of this Recommendation | International Standard, the terms and definitions given in Rec. ITU-T T.800 | ISO/IEC 15444-1, Rec. ITU-T T.814 | ISO/IEC 15444-15 and the following apply.

- **3.1 abstract test suite (ATS)**: Generic compliance testing concepts and procedures for a given requirement.
- **3.2 arithmetic coder**: Entropy coder that converts variable length strings to variable length codes (encoding) and vice versa (decoding).

¹ This Recommendation | International Standard includes an electronic attachment with the codestreams used in the application of the procedures described the Specification.

- **3.3 big endian**: Order of bytes in which the most significant byte comes first.
- **3.4 bit**: Contraction of the term "binary digit"; a unit of information represented by a 0 or a 1.
- **3.5 bit-depth**: Number of bits required to represent an original component of an image:
- **3.6 bit-**plane: Two-dimensional array of bits, referring to all the bits of the same magnitude in all coefficients or samples, within a component, a tile- component, a code-block, a region of interest, or other.
- **3.7 bitstream**: Sequence of bits resulting from the coding of a sequence of symbols, not including any markers or marker segments from the main and tile-part headers, not including packet headers, and not including in stream markers or marker segments or the end of codestream marker.
- **3.8 box**: Portion of the file format defined by a length and unique box type.

Note on entry: Boxes of some types may contain other boxes.

- **3.9 byte**: Eight bits.
- **3.10** Cclass: Defines a level of performance for a decoder, also providing guidance for encoders to produce codestreams that are easily decodable by compliant decoders.
- **3.11** code-block: A rectangular grouping of coefficients from the same sub-band of a tile-component.
- **3.12 coder**: Embodiment of either an encoding or decoding process.
- **3.13 codestream**: Collection of one or more bitstreams and the main header, tile-part headers, and the end of codestream marker required for their decoding and expansion into image data.

Note on entry: This is the image data in a compressed form with all of the signalling needed to decode, but not including the file format.

3.14 coding pass: Procedure accessing coefficients in a code-block where the context and bit are determined.

Note on entry: Typically, there are three different coding passes for each bit-plane, each coefficient will be represented in exactly one of the three passes; for an encoder a coding pass examines coefficients and augments a bitstream; for a decoder a coding pass reads a bitstream and updates coefficients.

- 3.15 coefficient: Value that result from a transformation.
- **3.16 component**: Two-dimensional array of samples.

Note on entry: An image typically consists of several components (e.g., red, green, and blue).

- **3.17 compressed image data**: Part or all of a codestream, or a collection of bitstreams in part or all of a codestream.
- **3.18 compliance**: Fulfilment of the specified requirements, as defined in this Recommendation | International Standard, for a given Profile and Cclass.
- **3.19 compliance test procedure**: The process of assessing compliance.
- **3.20 context**: Function of coefficients previously decoded and used to condition the decoding of the present coefficient.
- **3.21 decoder**: Embodiment of a decoding process, and optionally a colour transformation process.
- **3.22 decoding process**: Process that takes as its input all or part of a codestream and outputs all or part of a reconstructed image.
- **3.23 decomposition level**: Collection of wavelet sub-bands where each coefficient has the same spatial impact or span with respect to the source component samples, including all sub-bands of the same two-dimensional sub-band decomposition, where the last decomposition level also includes the LL sub-band.
- **3.24 discrete wavelet transformation (DWT)**: Transformation that iteratively transforms one signal into two or more filtered and decimated signals corresponding to different frequency bands.

Note on entry: This transformation operates on spatially discrete samples.

- **3.25 encoder**: Embodiment of an encoding process, optionally including a colour transformation process.
- **3.26 encoding process**: Process that takes as its input all or part of a source image data and outputs a codestream.
- **3.27 executable test suite (ETS)**: Set of executable test cases that support the abstract test cases.
- **3.28 file format**: Codestream and additional support data and information not explicitly required for the decoding of the codestream.

2

Note on entry: Examples of such support data include text fields providing titling, security and historical information, data to support placement of multiple codestreams within a given data file, and data to support exchange between platforms or conversion to other file formats.

- **3.29 fully decode**: Applying Rec. ITU-T T.800 | ISO/IEC 15444-1 to produce an image from a codestream where all coded data in the codestream has been used to produce the image.
- **3.30 guard bits**: Additional most significant bitplanes, beyond the nominal dynamic range of a wavelet sub-band, that have been included in coding of the sample data.
- **3.31 header**: Either a part of the codestream that contains only markers and marker segments (main header and tile part header) or the signalling part of a packet (packet header).
- **3.32 image**: Set of all components.
- **3.33 image data**: Component samples making up an image.

Note on entry: Image data can refer to either the source image data or the reconstructed image data.

- **3.34 implementation**: Realization of a specification.
- **3.35 implementation compliance statement (ICS)**: Statement of specification options and the extent to which they have been implemented by an implementation under test.
- **3.36 implementation under test (IUT)**: Implementation that is being evaluated for compliance.
- **3.37 irreversible**: Transformation, progression, system, quantization, or other process that, due to systemic or quantization error, prevents lossless recovery.
- **3.38 JPEG** (**Joint Photographic Experts Group**): The joint ISO/ITU committee responsible for developing standards for continuous-tone still picture coding, also referring to the standards produced by this committee: Rec. ITU-T T.81 | ISO/IEC 10918-1, Rec. ITU-T T.83 | ISO/IEC 10918-2, Rec. ITU-T T.84 | ISO/IEC 10918-3 and Rec. ITU-T T.87 | ISO/IEC 14495-1.
- **3.39 LL sub-band**: Sub-band obtained by forward horizontal low-pass filtering and vertical low-pass filtering. Note on entry: This sub-band contributes to reconstruction with inverse vertical low-pass filtering and horizontal low-pass filtering.
- **3.40 layer**: Collection of compressed image data from coding passes of one, or more, code-blocks of a tile-component, where layers have an order for encoding and decoding that has to be preserved.
- **3.41 lossless**: Descriptive term for the effect of the overall encoding and decoding processes in which the output of the decoding process is identical to the input to the encoding process, such that distortion-free restoration can be assured and all of the coding processes or steps used for encoding and decoding are reversible.
- **3.42 lossy**: Descriptive term for the effect of the overall encoding and decoding processes in which the output of the decoding process is not identical to the input to the encoding process, because at least one of the coding processes or steps used for encoding and decoding is irreversible.
- **3.43 main header**: Group of markers and marker segments at the beginning of the codestream that describe the image parameters and coding parameters that can apply to every tile and tile-component.
- **3.44** marker: Two-byte code in which the first byte is hexadecimal FF (0xFF) and the second byte is a value between 1 (0x01) and hexadecimal FE (0xFE).
- **3.45 marker segment**: Marker and associated (not empty) set of parameters.
- **3.46 packet**: Part of the codestream comprising a packet header and the compressed image data from one layer of one precinct of one resolution level of one tile-component.
- **3.47** packet header: Portion of the packet that contains signalling necessary for decoding that packet.
- **3.48** parser: Reads and identifies components of the codestream down to the code-block level.
- **3.49** partial decoding: Producing an image from a subset of an entire codestream.
- **3.50 precinct**: Rectangular region of a transformed tile-component, within each resolution level, used for limiting the size of packets.
- **3.51 precision**: Number of bits allocated to a particular sample, coefficient, or other binary numerical representation.
- **3.52 progression**: Order of a codestream where the decoding of each successive bit contributes to a "better" reconstruction of the image.

Note on entry: What metrics make the reconstruction "better" is a function of the application; some examples of progression are increasing resolution or improved sample fidelity.

3.53 profile: Subset of technology, from Rec. ITU-T T.800 | ISO/IEC 15444-1, that meets the needs of a given application with limits on parameters within a selected technology.

Note on entry: Profiles are codestream limitations.

3.54 quantization: Method of reducing the precision of the individual coefficients to reduce the number of bits used to represent them.

Note on entry: Quantization can be achieved by an explicit operation with a given quantization value (scalar quantization) or by dropping (truncating) coding passes from the codestream.

- **3.55 reconstructed image**: Image that is the output of a decoder.
- **3.56** reference grid: Regular rectangular array of points used to define other rectangular arrays of data.

Note on entry: The reference grid is used to determine the number of samples in tile-components for example.

- **3.57 region of interest (ROI)**: Collection of coefficients that are considered of particular relevance by some user-defined measure.
- **3.58 reversible**: Transformation, progression, system, or other process that does not suffer systemic or quantization error and therefore allows for lossless signal recovery.
- **3.59** reversible filter: Particular filter pair used in the wavelet transformation which allows lossless compression.
- **3.60 sample**: One element in the two-dimensional array that comprises a component.
- **3.61 selective arithmetic coding bypass**: Coding style where some of the code-block passes are not coded by the arithmetic coder, where the bits to be coded are instead appended directly to the bitstream without coding.
- **3.62 shift**: Multiplication or division of a number by powers of two, where ivision of an integer via shift implies truncation toward minus infinity of the non-integer portion.
- **3.63** sign bit: Bit that indicates whether a number is positive (value 0) or negative (value 1).
- **3.64 sign-magnitude notation**: Binary representation of an integer where the distance from the origin is expressed with a positive number and the direction from the origin (positive or negative) is expressed with a separate single sign bit.
- **3.65 source image**: Image used as input to an encoder.
- **3.66 sub-band**: Group of transform coefficients resulting from the same sequence of low-pass and high-pass filtering operations, both vertically and horizontally.
- **3.67 testing**: Process of evaluating compliance. EC 15444-4:2024
- **3.68 tile**: Rectangular array of points on the reference grid, registered with an offset from the reference grid origin and defined by a width and height.
- **3.69 tile-component**: All the samples of a given component in a tile.
- **3.70 tile-part**: Portion of the codestream with compressed image data for some, or all, of a tile, including one or more packets that make up the coded tile.
- **3.71 tile-part header** Group of markers and marker segments at the beginning of each tile-part in the codestream that describe the tile-part coding parameters.
- **3.72 transformation**: Mathematical mapping from one signal space to another.
- **3.73 transform coefficient**: Value that is the result of a transformation.

4 Abbreviations and symbols

4.1 Abbreviations

For the purposes of this Recommendation | International Standard, the abbreviations given in Rec. ITU-T T.800 | ISO/IEC 15444-1 and the following apply.

ATS Abstract Test Suite

BSET subset of the ETS consisting of HTJ2K test codestreams that differ only by B_{MAGB} value

ETS Executable Test Suite
HT High Throughput

4 Rec. ITU-T T.803 (V3) (02/2024)

HTJ2K High Throughput JPEG 2000 ICC International Colour Consortium

ICS Implementation Compliance Statement
ICT Irreversible Component Transform

IDWT Inverse Discrete Wavelet TransformationIEC International Electrotechnical CommissionISO International Organization for Standardization

ITU International Telecommunication Union

ITU-T International Telecommunication Union – Telecommunication Standardization Sector

IUT Implementation Under Test

J2K JPEG 2000²

JPEG Joint Photographic Experts Group

MAGB Magnitude Bound MSE Mean Squared Error

RCT Reversible Component Transform

ROI Region Of Interest

sRGB standard Red-Green-Blue

TCS Test Codestream

4.2 Symbols

For the purposes of this Recommendation | International Standard, the following symbols apply.

0x---- Denotes a hexadecimal number

Bit-depth precision for reversible 5-3

 B_{MAGB} Magnitude bound parameter for an HTJ2K codestream

C Component guaranteed to be decoded

CAP Capabilities

COC Coding style Component / IEC 15444-4:2024

COD Coding style Default

COM Comment

CPF Corresponding Profile
CRG Component Registration
EPH End of Packet Header
EOC End of Codestream
H image Height guarantee

L Layer guarantee

L_{body} code data buffering guarantee M decoded bit-plane guarantee

 $M_{\rm MAGB}$ Magnitude bound decoding guarantee

 $N_{\rm cb}$ code-block parsing guarantee $N_{\rm comp}$ component parsing guarantee P irreversible 9-7 Precision guarantee PLM Packet Length, Main header marker PLT Packet Length, Tile-part header marker

² As defined in Rec. ITU-T T.800 | ISO/IEC 15444-1.

POC Progression Order Change marker **PPM** Packed Packet headers, Main header marker PPT Packed Packet headers, Tile-part header marker **PRF** Profile marker QCC Quantization Component marker QCD Quantization Default marker **RGN** Region of interest marker SIZ image and tile Size marker SOC Start Of Codestream marker SOD Start Of Data marker SOP Start Of Packet marker SOT Start Of Tile-part marker T_L Transform level guarantee **TLM** Tile-part Lengths marker

image Width guarantee

5 Conventions

The compliance files including test codestreams, JP2 files, JPH files, reference decoded images, and descriptive files are supplied in the form of a compressed file. File locations given in this Recommendation | International Standard are expressed relative to the top level of the directory tree. A Unix style file structure and delimiters are assumed.

This Recommendation | International Standard contains instructions for the use of these files. No support can be provided by ISO | ITU-T beyond that offered in this Recommendation | International Standard.

6 General description

Perhaps the most distinctive feature of JPEG 2000 is its emphasis on and support for scalability. An existing codestream may be accessed at a reduced resolution, at a reduced quality (higher compression), at a reduced number of components, and even over a reduced spatial region. Moreover, this Recommendation | International Standard supports a rich family of information progression sequences whereby the information may be reordered without introducing additional distortion. This enables a single compressed codestream to serve the needs of a diverse range of applications.

This Recommendation | International Standard also covers compliance for implementations of Rec. ITU-T T.814 | ISO/IEC 15444-15. To avoid confusion, the terms JPEG 2000 (J2K) and high throughput JPEG 2000 (HTJ2K) are used in this Recommendation | International Standard, where necessary, to differentiate between JPEG 2000 codestreams that conform to Rec. ITU-T T.800 | ISO/IEC 15444-1 and those that conform to Rec. ITU-T T.814 | ISO/IEC 15444-15, respectively. J2K codestreams can be reversibly transcoded to HTJ2K and vice-versa, without any loss in information. This property allows compliance for HTJ2K and J2K implementations to be treated in a very similar manner. In fact, all of the HTJ2K test codestreams and JPH files provided in the electronic attachment have been obtained by reversibly transcoding corresponding J2K test codestreams and JP2 files available at the same location. The decoded output from an HTJ2K decoder is expected to conform to the same guidelines as the decoded output from a J2K decoder, processing the corresponding J2K codestream or JP2 file.

From the perspective of compliance, the main distinction between HTJ2K and J2K is that an HTJ2K codestream does not generally possess the same quality scalability attributes as the corresponding J2K codestream. An HTJ2K decoder cannot choose to stop the decoding of a code-block bit-stream at an arbitrary bit-plane, providing a fine grain trade-off between implementation complexity and reconstructed image quality. Considering this difference between HTJ2K and J2K, this Recommendation | International Standard provides multiple transcodings of J2K test codestreams, allowing implementations to be tested at multiple quality operating points.

JPEG 2000 encoders may employ only a fraction of the features supported by Rec. ITU-T T.800 | ISO/IEC 15444-1. Likewise, some decoders will not support all the features supported by this Recommendation | International Standard. It is impossible to provide test cases for all possible combinations of tools that an encoder or decoder may choose to implement. This Recommendation | International Standard provides abstract test procedures for JPEG 2000 encoders and decoders. A developer may designate the features that have been implemented and determine a set of test cases that applies to those features. For the greatest level of interoperability, there are explicit decoder test procedures. These tests are run