

INTERNATIONAL STANDARD

IEC
61993-1

First edition
1999-04

Maritime navigation and radiocommunication equipment and systems –

Part 1:

Shipborne automatic transponder system installation using VHF digital selective calling (DSC) techniques –

Operational and performance requirements, methods of testing and required test results

*Matériels et systèmes de navigation et
de radiocommunication maritimes –*

Partie 1:

*Installation de systèmes de répondeur automatique
de bord de navires utilisant des techniques d'appel sélectif
numérique en ondes métriques – Exigences d'exploitation
et de fonctionnement, méthodes d'essai et résultats
d'essai exigés*



Reference number
IEC 61993-1:1999(E)

Numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series.

Consolidated publications

Consolidated versions of some IEC publications including amendments are available. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Validity of this publication

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology.

Information relating to the date of the reconfirmation of the publication is available in the IEC catalogue.

Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is to be found at the following IEC sources:

- **IEC web site***
- **Catalogue of IEC publications**
Published yearly with regular updates
(On-line catalogue)*
- **IEC Bulletin**
Available both at the IEC web site* and as a printed periodical

Terminology, graphical and letter symbols

For general terminology, readers are referred to IEC 60050: *International Electrotechnical Vocabulary* (IEV).

For graphical symbols, and letter symbols and signs approved by the IEC for general use, readers are referred to publications IEC 60027: *Letter symbols to be used in electrical technology*, IEC 60417: *Graphical symbols for use on equipment. Index, survey and compilation of the single sheets* and IEC 60617: *Graphical symbols for diagrams*.

* See web site address on title page.

INTERNATIONAL STANDARD

IEC
61993-1

First edition
1999-04

Maritime navigation and radiocommunication equipment and systems –

Part 1: Shipborne automatic transponder system installation using VHF digital selective calling (DSC) techniques – Operational and performance requirements, methods of testing and required test results

Matériels et systèmes de navigation et de radiocommunication maritimes –

Partie 1: Installation de systèmes de répondeur automatique de bord de navires utilisant des techniques d'appel sélectif numérique en ondes métriques – Exigences d'exploitation et de fonctionnement, méthodes d'essai et résultats d'essai exigés

© IEC 1999 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission
Telefax: +41 22 919 0300

3, rue de Varembe Geneva, Switzerland
e-mail: inmail@iec.ch IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

W

For price, see current catalogue

CONTENTS

	Page
FOREWORD	4
INTRODUCTION	5
Clause	
1 Scope	6
2 Normative references	7
3 Definitions and abbreviations.....	8
3.1 Definitions.....	8
3.2 Abbreviations	8
4 General requirements.....	9
4.1 General.....	9
4.2 Composition.....	9
4.3 Design and construction.....	9
4.4 Controls and indicators.....	9
4.5 Interfacing.....	10
4.6 Permissible warming-up period.....	10
5 Performance requirements	10
5.1 General.....	10
5.2 Compatibility	11
5.3 Identification	11
6 Operational requirements.....	11
6.1 Ship-shore identification	11
6.2 Ship-ship identification	12
7 Technical requirements	12
7.1 Channel sensing.....	12
7.2 Class of emission and modulation characteristics	13
7.3 Frequency bands and channels	13
7.4 Switching time.....	13
7.5 Safety precautions	13
7.6 Transmitter.....	13
7.7 Receiver	14
7.8 Antenna system	14
7.9 Power supply	14
7.10 System DSC facility.....	14
8 Test conditions.....	15
8.1 General.....	15
8.2 Unspecified tests	15
8.3 Test power source.....	15
8.4 Normal test conditions.....	15
8.5 Extreme test conditions	16
8.6 Procedures for tests at extreme temperatures	16
8.7 Test signals	17
8.8 Measurement of bit error rate (BER).....	17
8.9 Measurement uncertainty and interpretation of the measurement results	18

9	Environmental tests.....	18
9.1	Introduction.....	18
9.2	Temperature tests.....	18
9.3	Vibration	19
9.4	Corrosion.....	19
9.5	Rain.....	19
10	Performance tests.....	19
10.1	General.....	19
10.2	Compatibility	20
10.3	Identification	20
11	Operational tests.....	20
11.1	Ship-shore identification.....	20
11.2	Ship-ship identification	20
12	Technical tests.....	21
12.1	Sensing capability	21
12.2	Switching time.....	21
13	Transmitter tests	22
13.1	Frequency error	22
13.2	Carrier power	22
13.3	Frequency deviation	23
13.4	Sensitivity of the modulator	23
13.5	Modulation index.....	24
13.6	Adjacent channel power	24
13.7	Conducted spurious emissions conveyed to the antenna.....	25
13.8	Transient frequency behaviour of the transmitter	25
14	Receiver tests	27
14.1	Calling sensitivity.....	27
14.2	Dynamic range.....	27
14.3	Co-channel rejection	27
14.4	Adjacent channel selectivity.....	28
14.5	Blocking immunity.....	28
14.6	Intermodulation response.....	29
14.7	Conducted spurious emissions into the antenna	29
15	Other tests	29
15.1	Antenna system.....	29
15.2	Power supply	29
15.3	Compass safe distance	30
16	Safety precautions	30
17	EMC emissions	30
18	EMC immunity.....	30

Annex A (informative)	Relationship between bit error rate (BER) input and symbol error rate (SER) output	32
-----------------------	--	----

Annex B (normative)	Power measuring receiver specification	36
---------------------	--	----

Annex C (informative)	Description of the operation of the system	38
-----------------------	--	----

Figures

1	Test set-up for measuring transient frequency behaviour.....	30
2	Storage oscilloscope view t_1 , t_2 and t_3	31

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Part 1: Shipborne automatic transponder system installation using VHF digital selective calling (DSC) techniques – Operational and performance requirements, methods of testing and required test results

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61993-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/212/FDIS	80/222/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

Annex B is an integral part of the standard.

Annexes A and C are for information only.

A bilingual version of this standard may be issued at a later date.

INTRODUCTION

In 1995 the IMO instigated work on the development of performance standards for a shipborne automatic identification system (AIS) using VHF digital selective calling (DSC) techniques.

These performance standards were developed into a draft resolution which was expected to be adopted by the IMO Maritime Safety Committee. However, there were objections to this on the grounds that some requirements for AIS were not met by the draft resolution.

The outcome has been that IMO has now developed further performance standards for a "Universal AIS" as a resolution which was adopted by the IMO Maritime Safety Committee in May 1998 as MSC. 74(69) annex 3.

During this period, some countries have gone ahead and implemented operational systems based upon the original IMO draft performance standards for AIS. There is therefore a need for a technical testing standard for such equipment.

At their plenary meeting in September 1997, technical committee 80 came to the following decisions:

- a draft technical standard which had been prepared on the basis of the original IMO performance standards would go ahead with the reference 61993-1, but would not directly refer to any IMO resolution for AIS;
- work would commence at the earliest opportunity on preparing a technical standard for a "Universal AIS" based rigorously upon the IMO resolution MSC.74(69) and a new recommendation ITU-R M.1371. This standard would have the reference 61993-2.

IEC 61993-1:1999

<https://standards.iteh.ai/en/standards/iec/a327/a3d3-1d1e-4f90-9331-c7b0ccd6a0b0/iec-61993-1-1999>

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS –

Part 1: Shipborne automatic transponder system installation using VHF digital selective calling (DSC) techniques – Operational and performance requirements, methods of testing and required test results

1 Scope

This part of IEC 61993 specifies the performance requirements, technical characteristics, operational requirements, methods of testing and required test results for shipborne automatic transponder system installations using VHF digital selective calling (DSC) techniques and is associated with IEC 60945. When a requirement in this standard is different from IEC 60945, the requirement in this standard shall take precedence.

The shipborne transponder installation is intended to assist in the efficient operation of ship-reporting systems and vessel traffic services (VTS) by enabling operators to identify, poll and automatically locate and track ships when they are approaching, entering and sailing within the limits of a ship-reporting system.

The system may also be used for the identification of ships by a ship and ships by aircraft. A description of the system is given in annex C.

This standard

- incorporates the technical characteristics included in ITU-R Recommendation M.825 for transponder systems using DSC and the technical characteristics included in ITU-R Recommendation M.489 for VHF radiotelephone equipment;
- incorporates the technical characteristics of DSC equipment and the operational procedures for its use contained in Recommendations ITU-R M.493 and ITU-R M.541;
- incorporates applicable parts of the performance standards of IMO Resolution A.803 for shipborne VHF radio installations;
- takes account of IMO Resolution A.694 for general requirements; and
- conforms with the International Telecommunication Union (ITU) Radio Regulations where applicable.

This standard for a transponder system is not intended to meet the requirements for a universal automatic identification system (AIS), as detailed in IMO Resolution MSC.74(69) annex 3.

NOTE – All text in this standard whose meaning complies with that in the normative references, namely IMO Resolution A.803(19) and ITU-R Recommendations M.825, M.489, M.493 and M.541 is followed by a reference to the source (number of IMO Resolution or ITU-R Recommendation and paragraph number) in brackets.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 61993. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However parties to agreements based on this part of IEC 61993 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative documents referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60945:1996, *Maritime navigation and radiocommunication equipment and systems – General requirements, methods of testing and required test results*

IEC 61097-3:1994, *Global maritime distress and safety system (GMDSS) – Part 3: Digital selective calling (DSC) equipment – Operational and performance requirements, methods of testing and required testing results*

IEC 61097-7:1996, *Global maritime distress and safety system (GMDSS) – Part 7: Shipborne VHF radiotelephone transmitter and receiver – Operational and performance requirements, methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radiocommunication equipment and systems – Digital interfaces*

IMO International Convention for Safety of Life at Sea (SOLAS) 1974, as amended

IMO Resolution A.694:1991, *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A.803:1995, *Performance standards for shipborne VHF radio installations capable of voice communication and digital selective calling*

IMO MSC.74(69):1998, *annex 3 – Performance standards for an Universal shipborne automatic identification system (AIS)*

ITU Radio Regulations:1997

ITU-R Recommendation M.489-2:1995, *Technical characteristics of VHF radiotelephone equipment operating in the maritime mobile service in channels spaced by 25 kHz*

ITU-R Recommendation M.493-9:1997, *Digital selective-calling system for use in the maritime mobile service*

ITU-R Recommendation M.541-8:1997, *Operational procedures for the use of digital selective calling (DSC) equipment in the maritime mobile service*

ITU-R Recommendation M.825-2:1997, *Characteristics of a transponder system using digital selective-calling techniques for use with vessel traffic services and ship-to-ship identification*

ITU-R Recommendation M.1371:1998, *Technical characteristics for a universal shipborne automatic identification system using time division multiple access in the VHF maritime mobile band*

ITU-T Recommendation V.11:1996, *Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s*

ITU-T Recommendation V.24:1996, *List of definitions for interchange circuits between data terminal equipment (DTE) and data circuit-terminating equipment (DCE)*

ITU-T Recommendation V.28:1993, *Electrical characteristics for unbalanced double-current interchange circuits*

3 Definitions and abbreviations

3.1 Definitions

For the purpose of this standard, the following definitions apply.

3.1.1

status

navigational status of the ship as expressed by the second digit 1-7 of the two-digit symbols to indicate other ships (table 3 of Recommendation ITU-R M.825)

3.1.2

performance check

quick test under normal test conditions of the transmitter frequency error to 13.1, the transmitter output power to 13.2 (high power only) and the receiver calling sensitivity to 14.1, with standard test signal number 2 applied at a level of +12 dB μ V. For results required, see 9.1.2

3.1.3

sensor

device which provides information to the system such as position, course and speed

3.2 Abbreviations

BER	Bit error rate
DCE	Data circuit-terminating equipment
DSC	Digital selective calling
DTE	Data terminal equipment
ECDIS	Electronic chart display and information system
EMC	Electromagnetic compatibility
e.m.f.	Electromotive force
EUT	Equipment under test
GMDSS	Global maritime distress and safety system
GPS	Global positioning system
IEC	International Electrotechnical Commission
IMO	International Maritime Organization
ITU	International Telecommunication Union
ITU-R	ITU Radiocommunication sector (formerly CCIR)
ITU-T	ITU Standardization sector (formerly CCITT)
MMSI	Maritime mobile service identity
p.t.t.	press-to-transmit
r.m.s.	root-mean-square
SOLAS	Safety of Life at Sea (International convention for the)
UTC	Universal time co-ordinated
VHF	Very high frequency
VTs	Vessel traffic services

4 General requirements

4.1 General

4.1.1 Requirements contained in clause 4 cannot be verified by repeatable measurements. The manufacturer shall declare that compliance to these requirements is achieved and shall provide relevant documentation. The declaration(s), documentation and, when necessary, the equipment shall be checked.

4.1.2 The system shall have a high level of availability, shall enable operators to obtain information from the ship automatically, whenever practicable, and require a minimum of involvement of ship's personnel, thus reducing the burden of communication on board ships.

4.1.3 The system installation, in addition to meeting the requirements of the Radio Regulations, the relevant ITU-R recommendations ¹⁾ and the general requirements set out in IMO A.694, as detailed in IEC 60945, shall comply with the following requirements and the requirements contained in clauses 5 and 6 of this standard.

4.2 Composition

4.2.1 The installation shall comprise of at least

- a transmitter/receiver including antenna;
- a digital selective calling facility;
- a dedicated DSC watchkeeping facility to maintain watch on the designated calling frequency except during periods when the installation is required to operate on working channels in accordance with instructions from shore-based stations;
- an electronic position-fixing system capable of providing horizontal accuracy of 100 m (95 %);
- means to input and receive information;
- means for the automatic change to a working channel on request of the shore-based interrogating station.

4.2.2 The manufacturer shall declare the composition of the equipment and also the relevant category to IEC 60945 for each unit.

4.3 Design and construction

4.3.1 The installation shall operate continuously while underway or at anchor. The equipment shall be designed for continuous operation.

4.3.2 The system functions may be performed by separate units appropriately interconnected or be integrated with a radio transmitter and/or receiver.

NOTE – "Integrated" means that the system function is physically integrated into a radio transmitter and/or receiver so that the system functions can only be tested by RF measurements.

4.4 Controls and indicators

4.4.1 The installation shall be provided with visual indication to show

- the equipment is switched on;
- the transponder function is disabled;
- the equipment is being interrogated; and
- the equipment is transmitting;
- loss of external data.

¹⁾ Recommendations ITU-R M.825, M.493, M.541

4.5 Interfacing

4.5.1 To enable a user display of information for example at a radar or ECDIS, the system shall be provided with a serial interface conforming to IEC 61162.

4.5.2 Interfaces for external sensors providing data for the system shall conform to IEC 61162.

4.5.3 As a minimum, the system shall be capable of operating with the sentences GGA, GLL, VBW, VTG, DSI, and DSR of IEC 61162.

4.5.4 When the installation comprises an external watch receiver, input terminals for AF, or alternatively DSC signals at logic level, the interfaces shall be as follows.

4.5.4.1 AF terminals for DSC signals shall have input and output impedance of 600 Ω , symmetrical and free of earth, with a closed-circuit level adjustable to 0,775 V (r.m.s.) \pm 10 dB for connection to AF terminals of external radio equipment.

4.5.4.2 Alternatively, terminals for DSC signals at logic levels shall have the electrical characteristics compatible with Recommendation ITU-T V.11. The B-state shall be the logic "0", and the Y-state shall be the logic "1".

4.5.4.3 Additionally, terminals for DSC signals may be provided with characteristics as defined in ITU-T Recommendations V.24 and V.28.

4.6 Permissible warming-up period

The installation shall be operational within 1 min of switching on.

NOTE – Sensors used with the system shall meet the requirements of their individual product standards (for example, IEC 61108-1 for GPS which permits 30 min to operation when there is no valid almanac data available).

5 Performance requirements

5.1 General

5.1.1 The system shall provide for calls of the category safety using DSC. (825/6.1)

5.1.2 Means shall be provided to automatically record all periods when the installation is non-functioning. It shall not be possible for the user to alter any information recorded by this device.

5.1.3 The last 10 times when the equipment is non-functioning for more than 15 min shall be recorded in UTC time and duration in a non-volatile memory. Means shall be provided to recover this data.

5.1.4 The installation shall be capable of receiving and processing all calls transmitted by an interrogating station.

5.1.5 The installation may not be required to process DSC type calls which are not AIS calls; however, such calls shall not affect correct system operation.

5.1.6 The installation shall be capable of operating on single-frequency channels or on single- or two-frequency channels.