ISO/FDIS 9221:2024(E)

ISO/TC 136/ WG 6

Secretariat: UNI

Date: 2024-07-0208-23

Furniture — Children's high chairs — Safety requirements and test methods

Ameublement — Chaises hautes pour enfants — Exigences de sécurité et méthodes d'essai

iTeh Standards

FDIS stage

SO/FDIS 9221

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: + 41 22 749 01 11 E-mail: copyright@iso.org Website: <u>www.iso.org</u>

Published in Switzerland

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 9221

Contents

Forew	ord	iv	
Introd	uction	v	
1	Scope	1	
2	Normative references	1	
3	Terms and definitions	1	
4 4.1 4.2 4.3 4.4 4.5	General Test conditions Application of forces Tolerances Test sequence Determination of the junction line Test equipment	3 3 3 3 3 3	
6 6.1 6.2 6.3	Chemical hazards (see Clause A.2) General Requirements Migration of certain elements	13 13 13 13 14	
6.4 6.5 6.6	Phthalates Azo colorants Flame retardants	14 15 16	
7	Thermal hazards (see Clause A.3)	17	
8 8.1 8.2 8.3 8.4 8.5 8.6 8.7 8.8 8.9 8.10 8.11 8.12 9	Mechanical hazards (see Clause A.4) Hazards caused by foldable products Hazards caused by height adjustment Entrapment hazards (see A.4.1) Hazards caused by moving parts (see A.4.2) Entanglement hazards (see A.4.3) Choking and ingestion hazards (see A.4.4) Hazards caused by edges, corners and protruding parts (see A.4.6) Strength and durability hazards, and structural integrity (see A.4.7) Hazards from falls out of the high chair (see A.4.8) Suffocation hazards (see A.4.9) Stability (see A.4.10) Marking and product information	17 18 19 20 21 23 23 27 35 35 37 40	
9 9.1 9.2 9.3 9.4	Marking and product information General Marking Instructions for use Purchase information	40 40 41 41 41 42	
Annex	Annex A (informative) Rationale		
Bibliog	graphy	47	

ISO/FDIS 9221:2024(en)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <u>www.iso.org/patents</u>. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 136, *Furniture*.

<u>This first</u> edition cancels and replaces the second edition (ISO 9221-1:2015 and ISO 9221-2:2015), which have been merged into one single document and has been technically revised.

The main changes are as follows:

ISO 9221-1:2015 and ISO 9221-2:2015 have been merged into one single document;

- complete review of the document in a hazard base format;
- addition of chemical and thermal hazardsⁱ
- addition of a dynamic strength test in $\underline{8.8.5}$;
- inclusion of specific requirements for high chairchairs with more than two castors/wheels in <u>8.11.1;</u>
- improvement of restraint system requirements to require a passive crotch restraint for products with a horizontal component in front of the baby in <u>8.9.1.1</u>.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

This document has been prepared in order to specify requirements and test methods intended to minimize accidents to children resulting from normal use and reasonably foreseeable misuse of children's high chairs.

The test methods are designed to evaluate properties without regard to materials, design/construction, or manufacturing processes.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 9221

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 922

<u>Furniture — Children's high chairs — — Safety requirements</u> and test methods

1 Scope

This document specifies safety requirements for free_standing children's high chairs that elevate children to dining table height, usually for the purposes of feeding or eating. Children's high chairs are for children up to <u>3three</u> years of age who are capable of sitting unaided.

With the exception of special high chairs for medical purposes, this This document applies is applicable to children's children's high chairs for domestic and non-domestic use. It does not apply to special high chairs for medical purposes.

NOTE If a children's high chair is or can be converted into other functions, additional standards can apply.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 48-4:2018, Rubber, vulcanized or thermoplastic — Determination of hardness — Part 4: Indentation hardness by durometer method (Shore hardness)

ISO 8124-2:2023, Safety of toys — Part 2: Flammability

ISO 8124-3, Safety of toys — Part 3: Migration of certain elements VI every

ISO 8124-6, Safety of toys — Part 6: Certain phthalate esters

<u>ISO/FDIS 922</u>

ISO 14362-1, Textiles — Methods for determination of certain aromatic amines derived from azo colorants — Part 1: Detection of the use of certain azo colorants accessible with and without extracting the fibres

ISO 14362-3, Textiles — Methods for determination of certain aromatic amines derived from azo colorants — Part 3: Detection of the use of certain azo colorants, which may release 4-aminoazobenzene

ISO 17234-1, Leather — Chemical tests for the determination of certain azo colourants in dyed leathers — Part 1: Determination of certain aromatic amines derived from azo colourants

ISO 17234-2, Leather — Chemical tests for the determination of certain azo colorants in dyed leathers — Part 2: Determination of 4-aminoazobenzene

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>
- IEC Electropedia: available at <u>https://www.electropedia.org/</u>

3.1

active restraint system

system where thea carer performs an action to ensure that thea child is secured in the restraint system

3.2

passive restraint system

system where thea carer does not perform an action to ensure that thea child is secured in the restraint system

3.3

crotch restraint

device passing between the legs of the<u>a</u> child and preventing the child from slipping forwards out of the high chair

3.4

waist restraint

rigid or flexible device(s), which, when fastened, goes from one side of the high chair to the other, passing in front of the child's waist or surrounding the child's waist

3.5

shoulder restraint

device passing over the shoulders and connecting either to the crotch restraint (3.3) or to the waist restraint (3.4)

iTeh Standards

3.6 locking device

component that maintains part(s) of the<u>a</u> product in the position of use

EXAMPLE Latch, a hook, an over centre lock.

er centre lock. Preview

3.7

operating device

part of the *locking mechanism(s)* (3.9) or *parking device(s)* (3.8) designed to be activated by thea carer by one or several action(s)

3.8

parking device

device intended to prevent rolling of castors/wheels

3.9

locking mechanism

assembly consisting of one or more *locking device(s)* (<u>3.6</u>) and one or more *operating device(s)* (<u>3.7</u>)

3.10

junction line

intersection of thea seat and the back resta backrest

3.11

paint andor similar surface-coating

fluid, semi-fluid or other material, with or without colouring matter, which changes to a solid film when a thin layer is applied to a metal, wood, leather, cloth, plastic or another surface

4 General

4.1 Test conditions

The high chair shall be tested as delivered. If the high chair is a knock-down type, it shall be assembled according to the instructions supplied with it. If the instructions allow for different adjustments or configurations of components (e.g. inclination of the backrest, height of the seat, position of the tray, position of castors/wheels, etc.), the most onerous combination shall be used for each test, unless otherwise specified in the test method.

Knock-down fittings shall be tightened before testing. Further re-tightening shall not take place.

4.2 Application of forces

The forces in the static load tests shall be applied sufficiently slowly to ensure that negligible dynamic force is applied.

The tests are described in terms of the application of forces; however, masses can be used. The relationship 10 N = 1 kg shall be used for this purpose.

4.3 Tolerances

Unless otherwise stated, the following tolerances apply:

- forces: ±5 % of the nominal force;
- masses: ±0,5 % of the nominal mass; / Standards.iteh.ai)
- dimensions: ±1,0 mm of the nominal dimension; 1 Preview
- angles: $\pm 2^{\circ}$ of the nominal angle;

ISO/FDIS 9221

- positioning of loading pads: ±5 mm.lards/iso/4ff67697-6b34-4adc-b764-d6005477ec54/iso-fdis-9221

NOTE For the purposes of uncertainty in measurements, test results are not considered to be adversely affected when the above tolerances are met.

4.4 Test sequence

The tests in <u>Clause 8</u> shall be carried out on the same high chair and in the order of the clauses of this document.

4.5 Determination of the junction line

The junction line (3.10) is shown in <u>Figure 1</u> below.

Where the backrest and the seat do not meet, the junction line is the projection of the backrest onto the seat (see <u>Figure 1</u>).



Kev

- 1 backrest
- 2 seat
- LL junction line

Figure 1 — Junction line

When the seat unit is in the form of a hammock, a theoretical junction line, "LL", shall be determined as shown in Figure 2. The junction line may vary when the backrest is adjusted in different positions.



Key

- top edge of the backrest AA front edge of the seat hai/catalog/standards/iso/4ff67697-6b34-4adc-b764-d6005477ec54/iso-fdis-9221 BB
- junction line LL
- vertical projection of C on the hammock CL
- С mid-point between A and B

Figure 2 — Junction line for seat units in the form of a hammock

Test equipment 5

A.1.1 General

Unless otherwise specified, test forces may be applied by any suitable device as results are dependent only upon correctly applied forces and not upon the apparatus.

Test mass A: A rigid cylinder 200 mm in diameter and 300 mm in height, having a mass of 15 kg with 5.1 its centre of gravity 150 mm above its base. The edges shall have a radius of 5 mm. Two anchorage points

shall be provided. These shall be positioned 150 mm from the base and at an angle of 180° to each other around the circumference (see Figure 3).

Dimensions in millimetres



5.2 Impact hammer: A striker in the form of a cylindrical object having a total mass of 6,5 kg supported from a pivot by a steel tube of 38 mm in diameter and with a wall thickness of 2 mm (see Figure 4). The

distance between the pivot and the centre of gravity of the striker shall be 1 000 mm. The pendulum arm shall be pivoted by a low friction bearing.

Dimensions in millimetres



Key

- 1 pendulum head, steel mass 6,4 kg
- 2 hardwood
- 3 rubber (50 ± 10-shore) Shore A (see ISO 48-4:2018)
- 4 pendulum arm, length 950 mm; high tensile steel tube Ø 38 mm × 2 mm; mass (2 ± 0,2) kg
- 5 pivot point

Mass of assembly (Keykey numbers 1, 2 and 3): (6,5 ± 0,07) kg.

Figure 4 — Impact hammer

ISO/FDIS 9221:2024(en)

5.3 Large loading pad: A rigid cylindrical object 100 mm in diameter having a smooth hard surface and edges rounded with radius of 12 mm.

5.4 Small loading pad: A rigid cylindrical object 30 mm in diameter having a smooth hard surface and edges rounded with radius of (0.8 ± 0.3) mm.

5.5 Stops

5.65.5 Stops to, which prevent the high chair from sliding but not tilting, no higher than 12 mm-except. Except in cases where the design of the item necessitates the use of higher stops, in which case the lowest stops that will prevent the item from sliding shall be used.

5.75.6 Floor surface: A horizontal, flat and rigid plane with a smooth surface.

A horizontal, flat and rigid plane with a smooth surface.

For the tests according to 8.8.6.4, a 2 mm thick rubber mat, with hardness (75 ± 10) Shore A in accordance with ISO 48-4, shall be used on a concrete floor.

5.8 Beams

5.9<u>5.7</u>**Beam** for stability testing and for measuring the length of the lateral protection.

5.9.2 Beam for measuring the height for lateral protection test

5.9.35.7.2 A beam, 86 mm wide and with a mass of (0,5 ± 0,01) kg.

5.105.8 **Probes** for finger entrapment.

5.10.1-Finger probe, with hemispherical end. SO/FDIS 9221

5.10.25.8.1 Probes made of plastic or **other**<u>another</u> hard, smooth material, with diameters $7^{0}_{-0,1}$ mm and $12^{+0,1}_{0}$ mm, with a hemispherical end (see Figure 5) and which can be mounted on a force-measuring device.

Dimensions in millimetres



Key

- 1 line around the probe showing the depth of penetration
- A diameter

Figure 5 — Test probes with hemispherical ends

ISO/FDIS 9221:2024(en)

5.10.3 5.8.2 Shape assessment probe, made of rigid and smooth material, with the dimensions shown in **Figure 6**.

Probe made of rigid and smooth material with the dimensions shown in Figure 6.



ISO/FDIS 922