



Designation: D2944 – 13

## Standard Practice of Sampling Processed Peat Materials <sup>1</sup>

This standard is issued under the fixed designation D2944; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reappraisal.

### 1. Scope\*

1.1 This practice covers procedures for obtaining samples for use in the determination of moisture, ash, and organic matter; volume; pH; volume weights, water-holding capacity, and air capacity of water-saturated peat materials; total nitrogen; particle size range; and sand content of processed peat materials. This procedure is valid for sampling peat materials for horticultural purposes and produces a sample that is representative of a material.

1.2 The values stated in SI units are to be regarded as the standard. The inch-pound units in parentheses are for information only.

1.3 *This practice offers a set of instructions for performing one or more specific operations. This document cannot replace education or experience and should be used in conjunction with professional judgment. Not all aspects of this practice may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care by which the adequacy of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process.*

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

[D653 Terminology Relating to Soil, Rock, and Contained Fluids](#)

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.22 on Soil as a Medium for Plant Growth.

Current edition approved June 1, 2013. Published July 2013. Originally approved in 1971. Last previous edition approved in 2008 as D2944 – 71 (2008). DOI: 10.1520/D2944-13.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

[D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction](#)

### 3. Terminology

3.1 *Definitions:*

3.1.1 For definitions of terms used in this practice, refer to Terminology [D653](#).

### 4. Significance and Use

4.1 This practice provides a uniform procedure for obtaining representative samples when obtained from multiple sources. It provides a sample that is more representative of a product that may be heterogeneous in nature. Producing a representative sample of a material is central to the validity of results any testing/analytical procedure.

NOTE 1—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice [D3740](#) are generally considered capable of competent and objective testing/sampling/inspection/etc. Users of this standard are cautioned that compliance with Practice [D3740](#) does not in itself assure reliable results. Reliable results depend on many factors; Practice [D3740](#) provides a means of evaluating some of those factors.

### 5. Apparatus

5.1 *Slotted Tube Corer*, a single or double tube, with holes (slots) along the length, pointed end and a minimum 25-mm (1-in.) inside diameter.

5.2 *Sample Splitter*.

5.3 *Oil Cloth*.

5.4 *Sample Containers* which can hold the type and size of sample obtained and be hermetically sealed.

5.5 *Indelible Markers* for marking containers or other suitable record system.

### 6. Procedure

6.1 Take a representative sample from the lot or shipment with a slotted tube corer as follows:

6.1.1 *Packaged or Baled Peats*—Lay the bag or bale horizontally and remove the core diagonally from end to end. Determine the number of cores as follows: from 1 – 4 bags, sample all bags, take at least 1 core from each bag for a total

\*A Summary of Changes section appears at the end of this standard

of at least 5 cores; from lots of 5 to 10 bags, sample all bags, take 1 core from each bag; from lots of 11 or more, sample 10 bags, take 1 core from each bag sampled.

6.1.2 *Bulk Samples*—Draw at least 10 cores from different regions.

6.1.3 *Small Containers* (4.5 kg (10 lb) or less)—Using all of the contents of a small container and, working rapidly to prevent moisture losses, reduce the composite sample to not less than 500 g by mass or 2 L by volume by mixing on a clean oilcloth or paper and quartering with a sample splitter. Place the sample in an airtight container.

6.2 Sampling by random “grab” procedure is necessary if the particle size range is to be determined or if representative

sample cannot be taken with a core sampler. Individual samples should not be less than 500 g by mass or 2 L by volume.

6.3 Mark each sample with site identification, analyses required, sampling personnel, time, and date.

6.4 Preserve the as-received moisture content of the sample using the airtight sample containers.

## 7. Keywords

7.1 ash; organic matter; peat; samples; sampling

## SUMMARY OF CHANGES

Committee D18 has identified the location of selected changes to this standard since the last issue (D2944 – 71 (2008)) that may impact the use of this standard. (Approved June 1, 2013.)

(1) Changed directive of standard from a test method to a practice

(2) Added units statement and judgment caveat to Section 1.

(3) Added Sections 2 and 3.

(4) Removed former Section 6, Precision and Bias.

*ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT).*