



FINAL DRAFT International Standard

ISO/FDIS 20766-22

Road vehicles — Liquefied petroleum gas (LPG) fuel system components —

Part 22: Power supply bushing (fuel pump/ actuators/fuel level sensor)

*Véhicules routiers — Équipements pour véhicules utilisant le gaz
de pétrole liquéfié (GPL) comme combustible —*

*Partie 22: Douille d'alimentation (pompe à carburant/
actionneurs/capteur de niveau de carburant)*

ISO/TC 22/SC 41

Secretariat: **UNI**

Voting begins on:
2024-12-11

Voting terminates on:
2025-02-05

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 20766-22](https://standards.iteh.ai/catalog/standards/iso/eda844a0-f2a2-4b68-836b-c7f3b6e95409/iso-fdis-20766-22)

<https://standards.iteh.ai/catalog/standards/iso/eda844a0-f2a2-4b68-836b-c7f3b6e95409/iso-fdis-20766-22>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Markings	2
5 Construction and assembly	2
6 Tests	3
6.1 Applicability.....	3
6.2 Hydrostatic strength.....	3
Bibliography	4

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 20766-22](https://standards.iteh.ai/catalog/standards/iso/eda844a0-f2a2-4b68-836b-c7f3b6e95409/iso-fdis-20766-22)

<https://standards.iteh.ai/catalog/standards/iso/eda844a0-f2a2-4b68-836b-c7f3b6e95409/iso-fdis-20766-22>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 41, *Specific aspects for gaseous fuels*.

A list of all parts in the ISO 20766 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

<https://standards.iteh.ai/catalog/standards/iso/eda844a0-f2a2-4b68-836b-c7f3b6c95409/iso-fdis-20766-22>

Road vehicles — Liquefied petroleum gas (LPG) fuel system components —

Part 22:

Power supply bushing (fuel pump/actuators/fuel level sensor)

1 Scope

This document specifies general requirements and definitions for power supply bushing (fuel pump/actuators/fuel level sensor), a liquefied petroleum gas (LPG) fuel component, intended for use on the types of motor vehicles defined in ISO 3833. It also provides general design principles and specifies requirements for instructions and marking.

This document is applicable to vehicles (mono-fuel, bi-fuel or dual-fuel applications) that use gaseous fuels in accordance with ISO 9162. It is not applicable to:

- fuel containers;
- stationary gas engines;
- container mounting hardware;
- electronic fuel management;
- refuelling receptacles.

Miscellaneous components not specifically addressed in this document can be examined for conformity with the criteria of any applicable part of the ISO 20766 series, including testing to the appropriate functional tests.

All references to pressure in this document are considered gauge pressures unless otherwise specified.

This document applies to devices that have a service pressure in the range of 110 kPa (butane rich at 20 °C) and 840 kPa (propane rich at 20 °C). Other service pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 20766-1, *Road vehicles — Liquefied petroleum gas (LPG) fuel systems components — Part 1: General requirements and definitions*

ISO 20766-2, *Road vehicles — Liquefied petroleum gas (LPG) fuel systems components — Part 2: Performance and general test methods*

IEC 60529, *Degrees of protection provided by enclosures (IP Code)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 20766-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Markings

The power supply bushing (fuel pump/actuators/fuel level sensor) shall bear the following identification markings, which shall be clearly legible and indelible and consist of characters, figures or symbols:

- a) the manufacturer or agent's name, trademark or symbol;
- b) the model designation (part number);
- c) the working pressure and temperature range;
- d) the year and month of fabrication;
- e) electrical ratings (if applicable).

The following additional markings are recommended:

- the type of fuel;
- the symbol of the certification agency;
- the type approval number;
- the serial number or date code;
- a reference to this document.

5 Construction and assembly

5.1 The power supply bushing (i.e. fuel pump/actuators/fuel level sensor) shall withstand the maximum designed operating pressure.

5.2 The power supply bushing (i.e. fuel pump/actuators/fuel level sensor) shall withstand a temperature between the minimum designed operating temperature and the maximum operating temperature.

5.3 To prevent electric sparks on the surface, in case of fracture of the component, the electrically operated power supply bushing (i. e. fuel pump/actuators/fuel level sensor) shall:

- a) be insulated in a manner that no current is conducted through parts that contain LPG;
- b) have the electrical system of the device isolated from the body.

Isolation resistance shall be $>10\text{ M}\Omega$.

5.4 If a power supply bushing (i.e fuel pump/actuators/fuel level sensor) is activated by an electric or external power, the power supply bushing shall not be connected to a live wire when its power is switched off.

5.5 If the power supply bushing is located in the boot or and the passenger compartment, the electrical connections shall comply with protection degree class IP 40 and IP 54 in accordance with IEC 60529.

5.6 The power supply bushing (i.e. fuel pump/actuators/fuel level sensor) shall be of a hermetic sealed type in order to establish an isolated and tight electrical connection.