



International
Standard

ISO 3864-3

**Graphical symbols — Safety colours
and safety signs —**

Part 3:

**Design principles for graphical
symbols for use in safety signs**

*Symboles graphiques — Couleurs de sécurité et signaux de
sécurité —*

*Partie 3: Principes de conception pour les symboles graphiques
utilisés dans les signaux de sécurité*

[ISO/PRF 3864-3](https://standards.iteh.ai/catalog/standards/iso/bad4df49-d7f8-476f-9841-a58fc234c55b/iso-prf-3864-3)

<https://standards.iteh.ai/catalog/standards/iso/bad4df49-d7f8-476f-9841-a58fc234c55b/iso-prf-3864-3>

Third edition

PROOF/ÉPREUVE

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/PRF 3864-3](https://standards.iteh.ai/catalog/standards/iso/bad4df49-d7f8-476f-9841-a58fc234c55b/iso-prf-3864-3)

<https://standards.iteh.ai/catalog/standards/iso/bad4df49-d7f8-476f-9841-a58fc234c55b/iso-prf-3864-3>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

PROOF/ÉPREUVE

© ISO 2024 – All rights reserved

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Designing graphical symbols for use in safety signs	2
5 Review of existing International Standards	2
6 Assignment of meaning, function, image content and hazard to the safety sign	2
7 Design criteria	3
7.1 Geometric shapes and colours of safety signs.....	3
7.2 Size and position of the graphical symbol.....	3
7.3 Layout of templates.....	6
7.4 Exclusion zone.....	7
7.4.1 General.....	7
7.4.2 Prohibition signs.....	7
7.4.3 Mandatory action signs.....	8
7.4.4 Warning signs.....	8
7.4.5 Safe condition signs and fire equipment signs.....	9
7.5 Line width.....	9
7.6 Consistency within a family of graphical symbols.....	11
7.7 Determinants.....	12
7.8 Combination of graphical symbols or graphical symbol elements.....	13
7.9 Use of arrows in graphical symbols.....	14
7.10 Characters.....	14
Annex A (informative) Additional design guidelines	15
Bibliography	26

[ISO/PRF 3864-3](https://standards.iteh.ai/catalog/standards/iso/bad4df49-d7f8-476f-9841-a58fc234c55b/iso-prf-3864-3)

<https://standards.iteh.ai/catalog/standards/iso/bad4df49-d7f8-476f-9841-a58fc234c55b/iso-prf-3864-3>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 145, *Graphical symbols*, Subcommittee SC 2, *Safety identification, signs, shapes, symbols and colours*.

This third edition cancels and replaces the second edition (ISO 3864-3:2012), which has been technically revised.

The main changes are as follows:

- references have been added in the Introduction providing a listing of graphical symbols and further information on related procedural points;
- normative references have been updated;
- clarification has been added concerning the exclusion zone for warning signs in [7.4.4](#).

A list of all parts in the ISO 3864 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Graphical symbols in safety signs are used for a wide range of purposes. There is a need to standardize the principles for creating these graphical symbols to ensure visual clarity, to maintain consistency and thereby to improve recognition and comprehension. The principles set out in this document specify the design criteria by which graphical symbols are judged for standardization and publication in ISO 7010.

Graphical symbols used in safety signs are not always intuitively understood. Often training can be necessary to inform people about the meaning of a graphical symbol. Such training can take place by including the meaning of a graphical symbol in operation manuals, company bulletins and training programme materials, as well as by using supplementary text with the safety sign.

NOTE 1 Information on procedures, criteria of acceptability, safety sign templates and application of safety signs, as well as translations of the referents, can be found at: <https://www.iso.org/tc145/sc2>.

NOTE 2 All safety signs are available on the ISO Online Browsing Platform at <https://www.iso.org/obp>.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/PRF 3864-3](https://standards.iteh.ai/catalog/standards/iso/bad4df49-d7f8-476f-9841-a58fc234c55b/iso-prf-3864-3)

<https://standards.iteh.ai/catalog/standards/iso/bad4df49-d7f8-476f-9841-a58fc234c55b/iso-prf-3864-3>

Graphical symbols — Safety colours and safety signs —

Part 3:

Design principles for graphical symbols for use in safety signs

IMPORTANT — The colours represented in the electronic file of this document can be neither viewed on screen nor printed as true representations. For the purposes of colour matching see ISO 3864-4, which provides colorimetric and photometric properties together with, as a guideline, references from colour order systems.

1 Scope

This document provides principles, criteria and guidance for the design of graphical symbols for use in safety signs as defined in ISO 3864-1, and for the safety sign element of product safety labels as defined in ISO 3864-2.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3864-1:2011, *Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings*

ISO 3864-4, *Graphical symbols — Safety colours and safety signs — Part 4: Colorimetric and photometric properties of safety sign materials*

ISO 7010, *Graphical symbols — Safety colours and safety signs — Registered safety signs*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

determinant

graphical symbol used as a common element within a series of graphical symbols

EXAMPLE The fire determinant, when used with the graphical symbol for a hose reel, conveys the meaning “fire hose reel”; see [Figure 17](#).

4 Designing graphical symbols for use in safety signs

Before designing a graphical symbol the designer shall:

- develop a clear and unambiguous description of the hazard that the graphical symbol is intended to address;
- confirm that a new graphical symbol for use in a safety sign is required (i.e. confirm that a suitable graphical symbol does not already exist; see [Clause 5](#));
- identify the safety message that the safety sign is intended to convey;
- define the characteristics of the target group, including their general skill and ability to understand the information that the particular safety sign is intended to convey, and design the graphical symbol for that group;
- assign a meaning and function to the safety sign in accordance with [Clause 6](#);
- identify the type of the safety sign required in accordance with [7.1](#).

Consideration should be given as to the types of safety sign for which the graphical symbol can be appropriate and to the design implications such multiple applicability can have. For example, a graphical symbol for use in a mandatory action sign can be adversely affected by the diagonal bar of a prohibition sign. Also, the restricted space within the triangle of a warning sign can adversely affect the graphical symbol originally designed for a prohibition sign.

During the creation process, the designer shall follow the criteria given in [Clause 7](#).

Designers are strongly recommended to use the guidelines set out in [Annex A](#).

5 Review of existing International Standards

The designer shall determine:

- whether a safety sign incorporating a graphical symbol conveying the required meaning is specified in ISO 7010;
- in cases where a safety sign incorporating a graphical symbol conveying the required meaning is not specified in ISO 7010, whether there is a registered graphical symbol conveying the required meaning;
- whether registered graphical symbols with similar meanings can be adapted or combined to form the graphical symbol for the new safety sign;
- whether there are standardized determinants appropriate for use with the graphical symbol for the new safety sign (see [7.8](#)).

If specific graphical elements are borrowed from existing graphical symbols, they should convey the same meaning as that described in the existing graphical symbol.

6 Assignment of meaning, function, image content and hazard to the safety sign

Each safety sign shall be used to convey only one safety message in accordance with ISO 3864-1.

The new safety sign shall be assigned a meaning and a function. The hazard shall be described. Once the safety sign original is complete, the image content shall be identified. An example is shown in [Figure 1](#).



Meaning: No smoking

Function: To prohibit smoking

Image content: Cigarette (profile, outlined) with two wavy lines

Hazard: Fire or explosion caused by lit cigarettes or other smoking materials or harm from the smoke

Figure 1 — Example of assignment of meaning, function, image content and hazard to a safety sign (ISO 7010-P002)

7 Design criteria

7.1 Geometric shapes and colours of safety signs

The graphical symbol shall be designed within the appropriate safety sign template. The safety sign templates used by the designer shall conform to the geometrical shapes and colours given in ISO 3864-1:

- for prohibition: see ISO 3864-1:2011, Figure 1;
- for mandatory action: see ISO 3864-1:2011, Figure 2;
- for warning: see ISO 3864-1:2011, Figure 3;
- for safe condition: see ISO 3864-1:2011, Figure 4;
- for fire equipment: see ISO 3864-1:2011, Figure 5.

For safety signs, the colorimetric and photometric properties of the colours shall be in accordance with ISO 3864-4.

7.2 Size and position of the graphical symbol

The graphical symbol shall make full use of the central area up to the boundary of the exclusion zone of the applicable safety sign template (see 7.4) and shall be centred as closely as practicable within the applicable geometric shape of the safety sign template. For examples see Figures 2 to 6.



Figure 2 — No thoroughfare (ISO 7010-P004)



A supplementary text sign is required with the general mandatory action sign.

Figure 3 — General mandatory action sign (ISO 7010-M001)



Figure 4 — Warning; Floor-level obstacle (ISO 7010-W007)



Figure 5 — Emergency telephone (ISO 7010-E004)