

INTERNATIONAL
STANDARD

ISO/IEC
20237

First edition
2023-10

**Information technology —
Sparkplug® version 3.0**

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/IEC 20237:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/de0a21c9-8fb4-40ba-a739-339f77098c69/iso-iec-20237-2023>



Reference number
ISO/IEC 20237:2023(E)

© ISO/IEC 2023

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ISO/IEC 20237:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/de0a21c9-8fb4-40ba-a739-339f77098c69/iso-iec-20237-2023>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by OASIS (as Sparkplug 3.0.0, Sparkplug Specification) and drafted in accordance with its editorial rules. It was adopted, under the JTC 1 PAS procedure, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Table of Contents

1. Introduction.....	2
1.1. Rationale and Use Case	2
1.1.1. Define an MQTT Topic Namespace.....	2
1.1.2. Define MQTT State Management.....	2
1.1.3. Define the MQTT Payload.....	2
1.1.4. Background	3
1.2. Intellectual Property Rights.....	4
1.2.1. Disclaimers	4
1.3. Organization of the Sparkplug Specification.....	4
1.4. Terminology.....	5
1.4.1. Infrastructure Components	5
1.5. Normative References	8
1.6. Consolidated List of Normative Statements	9
1.7. Security.....	9
1.7.1. Authentication.....	9
1.7.2. Authorization.....	9
1.7.3. Encryption	9
1.8. Normative Keywords	10
1.9. Leveraging Standards and Open Source	10
2. Principles Principles.....	10
2.1. Pub/Sub.....	10
2.2. Report by Exception	10
2.3. Continuous Session Awareness	11
2.4. Birth and Death Certificates.....	11
2.5. Persistent vs Non-Persistent Connections for Edge Nodes.....	12
3. Sparkplug Architecture and Infrastructure Components.....	12
3.1. MQTT Server(s).....	13
3.2. MQTT Edge Node.....	13
3.3. Device/Sensor.....	14
3.4. MQTT Enabled Device (Sparkplug).....	14
3.5. Primary Host Application.....	14
3.6. Sparkplug Host Application.....	14
4. Topics and Messages.....	14
4.1. Topic Namespace Elements.....	15
4.1.1. namespace Element	15
4.1.2. group_id Element	15

4.1.3.	message_type Element.....	15
4.1.4.	edge_node_id Element.....	16
4.1.5.	device_id Element	16
4.2.	Message Types and Contents.....	17
4.2.1.	Edge Node	17
4.2.2.	Device/Sensor	21
4.2.3.	Birth Certificate Message (STATE)	24
4.2.4.	Death Certificate Message (STATE).....	25
5.	Operational Behavior.....	26
5.1.	Timestamps in Sparkplug.....	26
5.2.	Case Sensitivity in Sparkplug.....	26
5.3.	Host Application Session Establishment.....	27
5.4.	Edge Node Session Establishment.....	30
5.5.	Edge Node Session Termination.....	34
5.6.	Device Session Establishment.....	36
5.7.	Device Session Termination.....	39
5.8.	Sparkplug Host Applications.....	40
5.9.	Sparkplug Host Application Message Ordering	40
5.10.	Primary Host Application STATE in Multiple MQTT Server Topologies	41
5.11.	Edge Node NDATA and NCMD Messages	43
5.12.	MQTT Enabled Device Session Establishment.....	46
5.13.	Sparkplug Host Application Session Establishment.....	46
5.14.	Sparkplug Host Application Session Termination	47
5.15.	Sparkplug Host Application Receive Data	48
5.16.	Data Publish	49
5.17.	Commands	50
6.	Payloads	52
6.1.	Overview	52
6.2.	Google Protocol Buffers	53
6.3.	Sparkplug A MQTT Payload Definition	53
6.4.	Sparkplug B MQTT Payload Definition	53
6.4.1.	Google Protocol Buffer Schema.....	54
6.4.2.	Payload Metric Naming Convention.....	59
6.4.3.	Sparkplug B v1.0 Payload Components	60
6.4.4.	Payload Component Definitions	60
6.4.5.	Payload	60
6.4.6.	Metric	61

6.4.7.	MetaData.....	64
6.4.8.	PropertySet.....	64
6.4.9.	PropertyValue	65
6.4.10.	PropertySetList.....	66
6.4.11.	DataSet.....	66
6.4.12.	DataSet.Row.....	67
6.4.13.	DataSet.DataSetValue	67
6.4.14.	Template.....	68
6.4.15.	Template.Parameter	70
6.4.16.	Data Types	71
6.4.17.	Datatype Details	72
6.4.18.	Payload Representation on Host Applications	77
6.4.19.	NBIRTH	78
6.4.20.	DBIRTH.....	80
6.4.21.	NDATA.....	83
6.4.22.	DDATA.....	84
6.4.23.	NCMD	85
6.4.24.	DCMD	86
6.4.25.	NDEATH	87
6.4.26.	DDEATH	89
6.4.27.	STATE.....	89
7.	Security.....	90
7.1.	TLS	90
7.2.	Authentication	91
7.3.	Authorization	91
7.4.	Implementation Notes.....	91
7.4.1.	Underlying MQTT Security.....	91
7.4.2.	Encrypted Sockets	91
7.4.3.	Access Control Lists	91
8.	High Availability	92
8.1.	High Availability for MQTT Servers	92
8.1.1.	MQTT Server HA Clustering (non-normative).....	93
8.1.2.	High Availability Cluster	93
8.1.3.	High Availability Cluster with Load Balancer	94
8.2.	Multiple Isolated MQTT Servers (non-normative)	94
9.	Acknowledgements	96
10.	Conformance	97

10.1.	Conformance Profiles.....	97
10.1.1.	Sparkplug Edge Node	97
10.1.2.	Sparkplug Host Application	97
10.1.3.	Sparkplug Compliant MQTT Server.....	98
10.1.4.	Sparkplug Aware MQTT Server.....	98
11.	Appendix A: Open Source Software (non-normative).....	99
11.1.	OASIS MQTT Specifications	99
11.2.	Eclipse Foundation IoT Resources.....	100
11.3.	Eclipse Paho	100
11.4.	Google Protocol Buffers.....	100
11.5.	Eclipse Kura Google Protocol Buffer Schema.....	100
11.6.	Raspberry Pi Hardware.....	100
12.	Appendix B: List of Normative Statements (non-normative)	100
12.1.	Host Applications.....	100
12.2.	Sparkplug Identifiers.....	101
12.3.	Report by Exception.....	101
12.4.	Birth and Death Certificates	101
12.5.	Persistent vs Non-Persistent Connections for Edge Nodes	101
12.6.	Sparkplug Host Application.....	101
12.7.	Topic Namespace Elements.....	101
12.8.	namespace Element	ISO/IEC 20237-2023
12.9.	group_id Element	102
12.10.	edge_node_id Element	102
12.11.	device_id Element.....	102
12.12.	Topic (NBIRTH)	102
12.13.	Payload (NBIRTH)	102
12.14.	Topic (NDATA).....	103
12.15.	Payload (NDATA).....	103
12.16.	Topic (NDEATH).....	103
12.17.	Payload (NDEATH).....	104
12.18.	Topic (NCMD).....	104
12.19.	Payload (NCMD).....	104
12.20.	Topic (DBIRTH)	104
12.21.	Payload (DBIRTH)	104
12.22.	Topic (DDATA).....	105
12.23.	Payload (DDATA).....	105
12.24.	Topic (DDEATH).....	105

12.25.	Payload (DDEATH).....	105
12.26.	Topic DCMD).....	105
12.27.	Payload (DCMD).....	105
12.28.	Birth Certificate Message (STATE)	106
12.29.	Birth Certificate Topic (STATE)	106
12.30.	Birth Certificate Payload (STATE)	106
12.31.	Death Certificate Message (STATE)	106
12.32.	Death Certificate Topic (STATE)	106
12.33.	Death Certificate Payload (STATE).....	106
12.34.	Case Sensitivity in Sparkplug.....	107
12.35.	Host Application Session Establishment.....	107
12.36.	Edge Node Session Establishment.....	108
12.37.	Edge Node Session Termination.....	109
12.38.	Device Session Establishment	110
12.39.	Device Session Termination	111
12.40.	Sparkplug Host Application Message Ordering.....	111
12.41.	Primary Host Application STATE in Multiple MQTT Server Topologies	112
12.42.	Sparkplug Host Application Session Establishment.....	112
12.43.	Sparkplug Host Application Session Termination	113
12.44.	Data Publish	113
12.45.	Commands	114
12.46.	Payload.....	115
12.47.	Metric.....	115
12.48.	PropertySet	116
12.49.	PropertyValue	116
12.50.	Quality Codes.....	116
12.51.	DataSet	116
12.52.	DataSet.DataSetValue	117
12.53.	Template.....	117
12.54.	Template.Parameter.....	118
12.55.	NBIRTH	118
12.56.	DBIRTH	119
12.57.	NDATA.....	119
12.58.	DDATA.....	120
12.59.	NCMD.....	120
12.60.	DCMD	120
12.61.	NDEATH.....	120

12.62.	DDEATH	121
12.63.	STATE	121
12.64.	Sparkplug Host Application.....	122
12.65.	Sparkplug Compliant MQTT Server	122
12.66.	Sparkplug Aware MQTT Server	122

**iTeh Standards
(<https://standards.iteh.ai>)
Document Preview**

[ISO/IEC 20237:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/de0a21c9-8fb4-40ba-a739-339f77098c69/iso-iec-20237-2023>



ECLIPSE

FOUNDATION

(<https://standards.iteh.ai>)

Document Preview

[ISO/IEC 20237:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/de0a21c9-8fb4-40ba-a739-339f77098c69/iso-iec-20237-2023>

Revision Number	Date	Author	Description
1.0	5/26/16	Cirrus Link	Initial Release
2.1	12/10/16	Cirrus Link	Payload B Addition
2.2	10/11/19	Cirrus Link	Re-branding for Eclipse foundation added TM to Sparkplug
3.0.0	11/16/22	Eclipse Sparkplug Specification Project Team	Reorganized to be in AsciiDoc format and to include normative and non-normative statements

Sparkplug®, Sparkplug Compatible, and the Sparkplug Logo are trademarks of the Eclipse Foundation.

1. Introduction

1.1. Rationale and Use Case

Eclipse Sparkplug provides an open and freely available specification for how Edge of Network Gateways (Sparkplug Edge Nodes) or native MQTT enabled end devices and Sparkplug Host Applications communicate bi-directionally within an MQTT Infrastructure. This document details the structure and implementation requirements for Sparkplug compliant MQTT Client implementations on both Edge Nodes and Host Applications.

It is recognized that MQTT is used across a wide spectrum of application solution use-cases, and an almost indefinable variation of network topologies. To that end the Sparkplug Specification strives to accomplish the three following goals.

1.1.1. Define an MQTT Topic Namespace

As noted many times in this document one of the many attractive features of MQTT is that it does not specify any required MQTT Topic Namespace within its implementation. This fact has meant that MQTT has taken a dominant position across a wide spectrum of IoT solutions. The intent of the Sparkplug Specification is to identify and document a Topic Namespace that is well thought out and optimized for the SCADA/IoT solution sector. In addition, Sparkplug defines a Topic Namespace in such a way that it provides semantics which allow for automatic discovery and bi-directional communication between MQTT clients in a system.

1.1.2. Define MQTT State Management

One of the unique aspects of MQTT is that it was originally designed for real time SCADA systems to help reduce data latency over bandwidth limited and outage prone network infrastructures. These can include cellular, satellite, and other radio based networks. In many implementations the full benefit of this "Continuous Session Awareness" is not well understood, or not even implemented. The intent of the Sparkplug Specification is to take full advantage of MQTT's native Continuous Session Awareness capability as it applies to real time SCADA/IoT solutions.

It is important to note that reducing bandwidth usage and being resilient to network drops is advantageous on more reliable and high bandwidth networks as well. By reducing the bandwidth usage, Sparkplug is able to move more data through the network because of its efficiency. This in turn can reduce network costs.

1.1.3. Define the MQTT Payload

Just as the MQTT Specification does not dictate any particular Topic Namespace, it also does not dictate any particular payload data encoding. The intent of the Sparkplug Specification is to define payload encoding mechanisms that remain true to the original, lightweight, bandwidth efficient, low latency features of MQTT while adding modern encoding schemes targeting the SCADA/IoT solution space.

Sparkplug has defined an approach where the Topic Namespace can aid in the determination of the encoding scheme of any particular payload. Historically there have been two Sparkplug defined encoding schemes. The first one was the 'Sparkplug A' and the second is 'Sparkplug B'. Each of these uses a 'first topic token identifier' so Sparkplug Edge Nodes can declare the payload encoding scheme they are using. These first topic tokens are:

spAv1.0
spBv1.0

Each token is divided up into three distinct components. These are:

- Sparkplug Identifier
 - Always 'sp'
- Payload Encoding Scheme
 - Currently 'A' or 'B' but there could be future versions
- Payload Encoding Scheme Version
 - Currently v1.0 but denoted in the event that future versions are released

The original 'Sparkplug A' encoding scheme was based on the Eclipse Kura™ open source Google Protocol Buffer definition. 'Sparkplug B' was released shortly after the release of Sparkplug A and addressed a number of issues that were present in the A version of the payload encoding scheme. Due to lack of adoption and the fact that 'Sparkplug B' was made available shortly after the release of 'A', the Sparkplug A definition has been omitted from this document and is no longer supported.

The 'Sparkplug B' encoding scheme was created with a richer data model developed with the feedback of many system integrators and end user customers using MQTT. These additions included metric timestamp support, complex datatype support, metadata, and other improvements.

1.1.4. Background

MQTT was originally designed as a message transport for real-time SCADA systems. The MQTT Specification does not specify the Topic Namespace nor does it define the Payload representation of the data being published and/or subscribed to. In addition to this, since the original use-case for MQTT was targeting real-time SCADA, there are mechanisms defined to provide the state of an MQTT session such that SCADA/Control Human-Machine Interface (HMI) application can monitor the current state of any MQTT enabled device in the infrastructure. As with the Topic Namespace and Payload the way state information is implemented and managed within the MQTT infrastructure is not defined. All of this was intentional within the original MQTT Specification to provide maximum flexibility across any solution sector that might choose to use MQTT infrastructures.

But at some point, for MQTT based solutions to be interoperable within a given market sector, the Topic Namespace, Payload representation, and session state must be defined. The intent and purpose of the Sparkplug Specification is to define an MQTT Topic Namespace, payload, and session state management that can be applied generically to the overall IIoT market sector, but specifically meets the requirements of real-time SCADA/Control HMI solutions. Meeting the operational requirements for these systems will enable MQTT based infrastructures to provide more valuable real-time information to Line of Business and MES solution requirements as well.

The purpose of the Sparkplug Specification is to remain true to the original notion of keeping the Topic Namespace and message sizes to a minimum while still making the overall message

transactions and session state management between MQTT enabled devices and MQTT SCADA/IoT applications simple, efficient, easy to understand, and implement.

1.2. Intellectual Property Rights

1.2.1. Disclaimers

THIS DOCUMENT IS PROVIDED "AS IS," AND THE COPYRIGHT HOLDERS AND THE ECLIPSE FOUNDATION MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DOCUMENT ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

THE COPYRIGHT HOLDERS AND THE ECLIPSE FOUNDATION WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE DOCUMENT OR THE PERFORMANCE OR IMPLEMENTATION OF THE CONTENTS THEREOF.

The name and trademarks of the copyright holders or the Eclipse Foundation may NOT be used in advertising or publicity pertaining to this document or its contents without specific, written prior permission. Title to copyright in this document will at all times remain with copyright holders.

1.3. Organization of the Sparkplug Specification

This specification is split into the following chapters and appendices:

- Chapter 1 - Introduction [ISO/IEC 20237:2023](#)
<https://standards.iteh.ai/catalog/standards/sist/de0a21c9-8fb4-40ba-a739-339f77098c69/iso-iec-20237-2023>
- Chapter 2 - Principles
- Chapter 3 - Sparkplug Architecture and Infrastructure Components
- Chapter 4 - Topics and Messages
- Chapter 5 - Operational Behavior
- Chapter 6 - Payloads
- Chapter 7 - Security
- Chapter 8 - High Availability
- Chapter 9 - Acknowledgements
- Chapter 10 - Conformance
- Appendix A - Open Source Software
- Appendix B - List of Normative Statements