



**International  
Standard**

**ISO 16484-2**

**Building automation and control  
systems (BACS) —**

**Part 2:  
Hardware**

*Systèmes d'automatisation et de contrôle des bâtiments  
(BACS) —*

*Partie 2: Matériel*

**Second edition  
2025-01**

iTeh Standards  
(<http://standards.itih.ai>)  
Document Preview

[ISO 16484-2:2025](https://standards.itih.ai/catalog/standards/iso/7f72f0b1-5c23-44ec-837b-4e25bd45b71c/iso-16484-2-2025)

<https://standards.itih.ai/catalog/standards/iso/7f72f0b1-5c23-44ec-837b-4e25bd45b71c/iso-16484-2-2025>

iTeh Standards  
(<https://standards.itih.ai>)  
Document Preview

[ISO 16484-2:2025](https://standards.itih.ai/catalog/standards/iso/7f72f0b1-5c23-44ec-837b-4e25bd45b71c/iso-16484-2-2025)

<https://standards.itih.ai/catalog/standards/iso/7f72f0b1-5c23-44ec-837b-4e25bd45b71c/iso-16484-2-2025>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

|   |           |
|---|-----------|
| <b>Foreword</b> .....   | <b>iv</b> |
| <b>1 Scope</b> .....  | <b>1</b>  |
| <b>2 Normative references</b> .....                           | <b>1</b>  |
| <b>3 Terms and definitions</b> .....                          | <b>1</b>  |
| <b>4 Abbreviated terms</b> .....                              | <b>6</b>  |
| <b>5 BACS features catalogue</b> .....                        | <b>7</b>  |
| 5.1 BACS components.....                                      | 7         |
| 5.1.1 Hardware components.....                                | 7         |
| 5.1.2 System configuration.....                               | 7         |
| 5.1.3 Basic hardware performance criteria.....                | 7         |
| 5.2 Building management.....                                  | 8         |
| 5.2.1 General.....  | 8         |
| 5.2.2 Devices for data processing, storage and archiving..... | 8         |
| 5.2.3 Management stations and operating units.....            | 9         |
| 5.2.4 Data interface unit (DIU).....                          | 9         |
| 5.3 Control devices.....                                      | 9         |
| 5.3.1 General.....  | 9         |
| 5.3.2 Edge device — Tasks.....                                | 9         |
| 5.3.3 Automation station.....                                 | 10        |
| 5.4 Sensors and actuators.....                                | 11        |
| 5.5 Local override/indication device — Task and use.....      | 12        |
| 5.6 Room control device.....                                  | 12        |
| <b>6 Topology</b> .....                                       | <b>12</b> |
| 6.1 Topology.....   | 12        |
| 6.2 System communication.....                                 | 12        |
| 6.2.1 General.....  | 12        |
| 6.2.2 Cyber security.....                                     | 13        |
| 6.2.3 Data security.....                                      | 13        |
| 6.2.4 Human interaction.....                                  | 13        |
| 6.2.5 Storage and analysis of data.....                       | 13        |
| 6.2.6 Cloud to cloud communication.....                       | 14        |
| 6.2.7 Wireless networks.....                                  | 14        |
| <b>Bibliography</b> .....                                     | <b>15</b> |

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 205, *Building environment design*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 247, *Building Automation, Controls and Building Management*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 16484-2:2004), which has been technically revised.

<https://standards.iteh.ai/catalog/standards/iso/71f72f0b1-5c23-44ec-837b-4e25bd45b71c/iso-16484-2-2025>  
The main changes are as follows:

- overall structure of document has been updated;
- Clause 1, Clause 2 and Clause 3 have been revised;
- technical content throughout the document has been modified and updated.

A list of all parts in the ISO 16484 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

# Building automation and control systems (BACS) —

## Part 2: Hardware

### 1 Scope

This document specifies the hardware requirements needed to carry out building automation tasks.

This document is applicable to physical devices, i.e.:

- devices that require human interaction, such as management stations or operator panels;
- devices for data storage and analysis, such as edge or cloud servers;
- devices for control applications, such as automation stations;
- devices for physical quantities acquisition, such as sensors and actuators.

This document provides a generic system topology based on a building network infrastructure, which includes both the devices inside the building envelope and those outside the building envelope.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60529, *Degrees of protection provided by enclosures (IP code)*

IEC/TR 62443-3-1, *Industrial communication networks — Network and system security — Part 3-1: Security technologies for industrial automation and control systems*

IEC 62443-3-3, *Industrial communication networks — Network and system security — Part 3-3: System security requirements and security levels*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

#### 3.1 access control system

dedicated security system, that includes the automatic checking of access rights under organizational measures, barrier and door control for buildings and rooms, and registration of events

#### 3.2 alarm

warning given by the system either:

- a) indicating the presence of a hazard to property, the environment, or to life
- b) a condition detected by a device or controller regarded as abnormal, that implements a rule or logic specifically designed to look for that condition, e.g. "frost alarm"

Note 1 to entry: An alarm can be an annunciation that is either audible, visual or both that alerts an operator to an abnormal condition, which can require corrective action.

### 3.3 analogue input

part of the hardware pertaining to a control device for measuring

### 3.4 analogue output

part of the hardware pertaining to a control device for positioning

### 3.5 application

set of user information processing requirements or functions that together form a logical unit supporting a process

Note 1 to entry: A building automation and control system can support many different applications.

### 3.6 binary input

hardware pertaining to control devices for state processing

Note 1 to entry: The function is also referred to as binary input state.

### 3.7 binary output

hardware pertaining to control devices for switching

Note 1 to entry: The function is also referred to as output switching.

### 3.8 building

large volume separate fixed structures, i.e. commercial or residential premises, however excluding industrial structures

Note 1 to entry: Building automation and control system can also be employed for other structures, such as houses, tunnels, railways, and ships.

### 3.9 building automation and control system

system, comprising all products, software and engineering services for automatic controls (including interlocks), monitoring, optimization, operation, human intervention, and management to achieve energy-efficient, economical, and safe operation of building services

Note 1 to entry: The trade designation and the industry branch are also referred to as either building automation or building control, or both.

[SOURCE: ISO 52120-1:2021, 3.2, modified — Note 1 has been added.]

Note 2 to entry: Building automation and control system (BACS) is also referred to as building management system (BMS), of which building energy management is part.

Note 3 to entry: The use of the word "control" does not imply that either the system or the device or both are restricted to control functions. Processing of data and information is also possible.

Note 4 to entry: If a building automation and control system, or building energy management system, conforms to the requirements of the ISO 16484 series, it may be designated as a BACS.

Note 5 to entry: Building services are divided into technical, infrastructural and financial building services and energy management is part of technical building management.

**3.10  
building management**

totality of services involved in the management, operation and monitoring of buildings (including plants and installations)

Note 1 to entry: Building management is divided into technical building management, infrastructural building management and commercial building management and has interfaces to area and facility management.

[SOURCE: ISO 52120-1:2021, 3.4, modified — Note 1 has been added.]

**3.11  
building network infrastructure**

communication infrastructure next to the traditional electrical and sanitary installations in modern buildings

Note 1 to entry: The network is optimally set up for the needs of the building and its use and ensures that cyber security needs are met, taking IEC 62443 series into consideration.

**3.12  
building services**

utilities and installations supplied and distributed within a building, such as electricity, gas, heating, water, waste, and communications

**3.13  
cabling**

system of cables and connecting hardware that supports the wired connection of the building automation and control system and other equipment

**3.14  
cloud**

servers located in data centres all over the world that are accessed over the internet, as well as the software and databases that run on those servers

Note 1 to entry: By using cloud computing, users and companies do not need to manage physical servers themselves or run software applications on their own machines.

**3.15  
communication**

act of conveying meaning from one entity or group to another through the use of mutually understood signs, symbols, and semiotic rules

**3.16  
communication interface**

physical and electrical requirements for the connection of components of communicating products

**3.17  
configuration**

site-specific information related to physical and functional units, entered during system engineering resulting in the system configuration

Note 1 to entry: Generally, the configuration does not change once the system is functioning.

**3.18  
controller  
automation station**

device for either regulation or logic control, or both, as well as the monitoring and processing of information such as temperature, humidity and pressure

Note 1 to entry: The use of the words "automation" and "control" does not imply that the device or system is restricted to control functions only. Monitoring and processing of other information is possible.

Note 2 to entry: In IT, a device that controls the transfer of data between a computer and a peripheral device is also referred to as a controller.

**3.19  
counter input**

hardware pertaining to a control device for pulse counting

**3.20  
data**

representation of information in a formalized manner suitable for human or automatic processing

Note 1 to entry: Processing includes communication and interpretation.

**3.21  
data interface unit**

functional or physical unit for communication between the devices of a BACS, as well as devices and systems in other networks

Note 1 to entry: Different types of DIUs can exist, such as routers or gateways.

Note 2 to entry: A DIU may be used to conform to the relevant national standards if connected via public data networks.

**3.22  
data-point**

input and output function consisting of all assigned information describing the point's meaning entirely

Note 1 to entry: There are physical and virtual data-points. A physical data-point is related to a direct or remotely connected input/output device. A virtual data-point can be derived from the result of a processing function, or is related to another device as a shared data-point.

Note 2 to entry: Historically, the term "data-point" described only a physical value or state.

Note 3 to entry: A collection of virtual data-points is usually identified as the digital twin of the controller owning the physical data-point counterparts.

**3.23  
data security**

framework conditions to protect data from direct or indirect manipulation or unauthorized use

Note 1 to entry: Data manipulation includes loss of data, destruction or falsification of data.

Note 2 to entry: Data security means are the measures and equipment to secure and maintain the safety of data.

**3.24  
device**

physical product designed and implemented to perform specified or programmable functions, in operational, electrotechnology equipment

Note 1 to entry: For the purposes of this document, a device forms a self-contained physical unit.

**3.25  
digital twin**

virtual representation of real-world entities and processes, synchronized at a specified frequency and fidelity

**3.26  
electromagnetic compatibility**

ability of equipment or a system to function satisfactorily in its electromagnetic environment without introducing intolerable electromagnetic disturbances to anything in that environment

[SOURCE: IEC 60050-161:2018]



### 3.27

#### **edge device**

piece of hardware that controls data flow at the boundary between two networks, fulfilling a variety of roles depending on what type of device they are, but essentially serving as network entries or exit points

Note 1 to entry: Some common functions of edge devices include the transmission, routing, processing, monitoring, filtering, translation and storage of the data passing between networks.

Note 2 to entry: There can be multiple edge devices in a building automation network devoted to different purposes, such as for different portions of the network or for different application requirements.

### 3.28

#### **engineering**

project and system-specific services for the system planning process, configuration, and commissioning of the various parts of a building automation and control system

Note 1 to entry: The services that can be performed as part of engineering include configuration of the physical and logical connections and relationships between all items of a system to achieve the required application.

### 3.29

#### **facility management**

services performed before, during, and after the use of real estate and infrastructure that are based on a holistic (integral) strategy

### 3.30

#### **historical data**

data that is recorded on a storage medium for an undefined time

Note 1 to entry: The data logging performed by storing historical data is referred to as a "historical database function".

### 3.31

#### **input/output**

function that includes either the processing of a signal from a sensor or a signal for an actuator of the system to be controlled

Note 1 to entry: The I/O also provides system users with the specific status and value information for a data-point.

### 3.32

#### **information**

knowledge concerning objects, facts, events, things, processes, or ideas (including concepts), which, within a certain context, has a particular meaning

### 3.33

#### **interface**

functional or physical unit as a defined interconnection between a device or system to another device or system, or to a person

### 3.34

#### **logbook**

record book or its electronic equivalent, where all relevant details of an operation, a system, its performance, and its maintenance can be entered in a secure manner for subsequent retrieval

Note 1 to entry: A logbook can consist of one or more record books.

Note 2 to entry: A logbook can be kept in a centralized or distributed manner.

### 3.35

#### **maintenance**

combination of all technical, administrative and managerial actions during the life cycle of an item intended to retain it in or restore it to a state in which it can perform the required function

**3.36**

**monitoring**

activity of the system, intended to observe the actual state of an item, identify a defined deviation from the normal state, and transmit a message about the observed state

**3.37**

**operating system**

software to control program operation and to provide services for resource allocation, task scheduling, input/output control, and data management

**3.38**

**room control unit**

interface enabling users to interact with the building automation system in order to influence room conditions

Note 1 to entry: Room control units can either be permanently installed on the wall of a room or they can be available as an application on a room user's mobile device.

**3.39**

**cyber security  
security**

protection of networks, devices, programs and data from attacks, damage and unauthorized access

**3.40**

**sensor**

device designed to detect or measure a variable

**3.41**

**topology**

way in which the links and nodes of a network are arranged so that they relate to each other

Note 1 to entry: Topologies are categorized as either a physical network topology, which is the physical medium of signalling, or a logical network topology, which refers to the way in which data is transferred between devices regardless of the physical connection of the devices through the network.

**4 Abbreviated terms**

ISO 16484-2:2025

<https://standards.iteh.org/catalog/standards/iso/7f72f0b1-5c23-44ec-837b-4e25bd45b71c/iso-16484-2-2025>

| Abbreviated term | Description                        |
|------------------|------------------------------------|
| AI               | analogue input                     |
| AO               | analogue output                    |
| BACS             | building automaton control systems |
| BI               | binary input                       |
| BO               | binary output                      |
| CI               | counter input                      |
| DIU              | data interface unit                |
| EMC              | electromagnetic compatibility      |
| GUI              | graphical user interface           |
| I/O              | input/output                       |
| HMI              | human-machine interface            |