



# FINAL DRAFT International Standard

## ISO/FDIS 11237

### Rubber hoses and hose assemblies — Compact wire-braid-reinforced hydraulic types for oil-based or water-based fluids — Specification

*Tuyaux et flexibles en caoutchouc — Types hydrauliques compacts avec armature de fils métalliques tressés pour fluides à base d'huile ou à base d'eau — Spécifications*

[ISO/FDIS 11237](https://standards.iteh.ai/catalog/standards/iso/4314fb58-6ede-423f-aa54-b5f83fcadeec/iso-fdis-11237)

<https://standards.iteh.ai/catalog/standards/iso/4314fb58-6ede-423f-aa54-b5f83fcadeec/iso-fdis-11237>

ISO/TC 45/SC 1

Secretariat: DIN

Voting begins on:  
**2024-07-30**

Voting terminates on:  
**2024-09-24**

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards  
(<https://standards.iteh.ai>)  
Document Preview

[ISO/FDIS 11237](https://standards.iteh.ai/catalog/standards/iso/4314fb58-6ede-423f-aa54-b5f83fcadeec/iso-fdis-11237)

<https://standards.iteh.ai/catalog/standards/iso/4314fb58-6ede-423f-aa54-b5f83fcadeec/iso-fdis-11237>



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Classification</b> .....	<b>2</b>
<b>5 Materials and construction</b> .....	<b>2</b>
5.1 Hoses.....	2
5.2 Hose assemblies.....	2
<b>6 Dimensions</b> .....	<b>2</b>
6.1 Hose diameters and cover thickness.....	2
6.2 Concentricity.....	4
6.3 Hose cover thickness.....	4
<b>7 Performance requirements</b> .....	<b>4</b>
7.1 General.....	4
7.2 Change in length requirements.....	4
7.3 Hydrostatic requirements.....	5
7.4 Minimum bend radius.....	6
7.5 Resistance to impulse.....	7
7.6 Leakage of hose assemblies.....	7
7.7 Low temperature flexibility.....	7
7.8 Adhesion between components.....	7
7.9 Vacuum resistance.....	7
7.10 Fluid resistance.....	8
7.10.1 General.....	8
7.10.2 Oil resistance.....	8
7.10.3 Water-based fluid resistance.....	8
7.10.4 Water resistance.....	8
7.11 Ozone resistance.....	8
7.12 Visual examination.....	9
<b>8 Frequency of testing</b> .....	<b>9</b>
<b>9 Marking</b> .....	<b>9</b>
9.1 Hoses.....	9
9.2 Hose assemblies.....	9
<b>10 Recommendations for length of supplied hoses and tolerances on lengths of hose assemblies</b> .....	<b>10</b>
<b>Annex A (normative) Test frequency for type tests and routine tests</b> .....	<b>11</b>
<b>Annex B (informative) Recommendations for lengths of supplied hoses and length tolerances for hose assemblies</b> .....	<b>12</b>
<b>Bibliography</b> .....	<b>13</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at [www.iso.org/patents](http://www.iso.org/patents). ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 1, *Rubber and plastics hoses and hose assemblies*.

This third edition cancels and replaces the second edition (ISO 11237:2017), which has been technically revised.

The main changes are as follows:

- the scope has been revised to align the water based and water temperatures with ISO 1436, ISO 3862 and ISO 18752;
- subclauses 7.5.2 and 7.5.3 on water based and optional impulse tests have been deleted;
- a new [subclause 7.10.3](#), on water based fluid resistance, has been added;
- new hose sizes have been added to type 2SC in [Tables 1, 3, 4, 5, 6](#) and [7](#);
- [Clause 8](#) has been revised to cite [Annex A](#);
- [Clause 9](#) has been revised;
- [Annex A](#) has been revised to align the document with ISO 1436 and [Annex B](#) has been deleted.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

# Rubber hoses and hose assemblies — Compact wire-braid-reinforced hydraulic types for oil-based or water-based fluids — Specification

## 1 Scope

This document specifies requirements for five types of compact, wire-braid-reinforced hoses and hose assemblies of nominal size from 5 to 76.

They are suitable for use with:

- oil-based hydraulic fluids HH, HL, HM, HR and HV as defined in ISO 6743-4 at temperatures ranging from  $-40\text{ °C}$  to  $+100\text{ °C}$ ;
- water-based fluids HFC, HFAE, HFAS and HFB as defined in ISO 6743-4 at temperatures ranging from  $0\text{ °C}$  to  $+70\text{ °C}$ ;
- water at temperatures ranging from  $0\text{ °C}$  to  $+70\text{ °C}$ .

This document does not include requirements for end fittings. It is limited to requirements for hoses and hose assemblies. The hose assembly maximum working pressure is governed by the lowest maximum working pressure of the components.

NOTE It is the responsibility of the user, in consultation with the hose manufacturer, to establish the compatibility of the hose with the fluid to be used.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1307, *Rubber and plastics hoses — Hose sizes, minimum and maximum inside diameters, and tolerances on cut-to-length hoses*

ISO 1402, *Rubber and plastics hoses and hose assemblies — Hydrostatic testing*

ISO 1817, *Rubber, vulcanized or thermoplastic — Determination of the effect of liquids*

ISO 4671, *Rubber and plastics hoses and hose assemblies — Methods of measurement of the dimensions of hoses and the lengths of hose assemblies*

ISO 6605, *Hydraulic fluid power — Test methods for hoses and hose assemblies*

ISO 6803, *Rubber or plastics hoses and hose assemblies — Hydraulic-pressure impulse test without flexing*

ISO 7233, *Rubber and plastics hoses and hose assemblies — Determination of resistance to vacuum*

ISO 7326, *Rubber and plastics hoses — Assessment of ozone resistance under static conditions*

ISO 8033:2016, *Rubber and plastics hoses — Determination of adhesion between components*

ISO 8330, *Rubber and plastics hoses and hose assemblies — Vocabulary*

ISO 10619-1:2017, *Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 1: Bending tests at ambient temperature*

ISO 10619-2, *Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 2: Bending tests at sub-ambient temperatures*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8330 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 4 Classification

Five types of hose are specified, distinguished by their construction, working pressure and minimum bend radius. These hoses have thin covers designed to permit fitting assembly without the removal of the cover or a portion of the cover.

- a) Type 1SC: Hoses with a single braid of wire reinforcement.
- b) Type 2SC: Hoses with two braids of wire reinforcement.
- c) Type R16S: Hoses with one or two braids of wire reinforcement.
- d) Type R17: 21 MPa (210 bar) constant pressure hoses with one or two braids of wire reinforcement.
- e) Type R19: 28 MPa (280 bar) constant pressure hoses with one or two braids of wire reinforcement.

NOTE Types R16S, R17 and R19 are not subjected to the vacuum resistance tests.

### 5 Materials and construction

[ISO/FDIS 11237](https://standards.iteh.ai/catalog/standards/iso/4314fb58-6ede-423f-aa54-b5f83fcadeec/iso-fdis-11237)

<https://standards.iteh.ai/catalog/standards/iso/4314fb58-6ede-423f-aa54-b5f83fcadeec/iso-fdis-11237>

#### 5.1 Hoses

Hoses shall consist of a rubber lining resistant to oil- or water-based hydraulic fluids, one or two layers of high-tensile steel wire and a weather- and oil-resistant rubber cover.

#### 5.2 Hose assemblies

Hose assemblies shall be manufactured using hoses conforming to the requirements of this document.

Hose assemblies shall be manufactured only with those hose fittings whose correct functioning has been verified in accordance with [7.2](#), [7.3](#), [7.5](#), [7.6](#) and [7.7](#). The manufacturer's instructions shall be followed for the preparation and fabrication of hose assemblies.

### 6 Dimensions

#### 6.1 Hose diameters and cover thickness

The test shall be carried out in accordance with ISO 4671. The hose diameters shall conform to the values given in [Table 1](#) and the cover thickness to [6.3](#).