ISO TC 206/SC

Date: 2023-0405-22

ISO/FDIS 26443:2023(E)

ISO TC 206/SC/WG 10

Secretariat: JISC

Fine ceramics (advanced ceramics, advanced technical ceramics) — Rockwell indentation test for evaluation of adhesion of ceramic coatings

Céramiques techniques — Évaluation de l'adhérence des revétements céramiques par l'essai de pénétration de Rockwell

iTeh STANDARD PREV (standards.iteh.ai)

ISO/FDIS 26443

https://standards.iteh.ai/catalog/standards/sist/6adbfbe0-4cb6-469a

Style Definition	
Style Definition	
Style Definition	<u></u>
Style Definition	
Style Definition	<u></u>
Style Definition	<u></u>
Style Definition	
Style Definition 70 22/150	
Style Definition	

Style Definition
Style Definition
Style Definition
Style Definition
Style Definition
Style Definition

<u>...</u>

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

Case postale 56 • CH-1211 Geneva 20

Tel. + 41 22 749 01 11

Fax + 41 22 749 09 47

E-mail copyright@iso.org

Web www.iso.org

Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

ISO/EDIS 26442

https://standards.iteh.ai/catalog/standards/sist/6adbfbe0-4cb6-469a-a271-edaf658972f3/iso-fdis-26443

Formatted: Font: 10 pt

Formatted: Space Before: 12 pt, Line spacing: Exactly 12 pt

	ISO/FDIS 26443:2023(E) Formatted: Right, Indent: First line: 0 ch	
Contents	Page	

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 26443

https://standards.iteh.ai/catalog/standards/sist/6adbfbe0-4cb6-469a-a271-edaf658972f3/iso-fdis-26443

© ISO 2023 - All rights reserved

Contents Page

Forev	vordiv
4	Scope
2	Normative references1
3	Principle1
4	-Apparatus2
5	Sampling and preparation of test specimens
6	Procedure 2
7	Limits 3
8	Test report3
Anne	x A (informative) Pictorial representations and sample photographs of the classes defined in Table 1
Biblic	graphy6
<u>Forev</u>	vordv
1	Scope1
2	Normative references1
3	Terms and definitions
4	Principle1
5	Apparatus2
6	Sampling and preparation of test specimens
7	Procedure
8	<u>Limits</u> <u>£4is. 264443</u> 3
9	<u>Test report</u> 3
	x A (informative) Pictorial representations and sample photographs of the classes defined in Table 1
<u>Biblio</u>	graphy11

Formatted: Font: Not Bold

Formatted: Font: 10 pt

Formatted: Space Before: 12 pt, Line spacing: Exactly 12 pt

Formatted: Right, Indent: First line: 0 ch

Formatted: Adjust space between Latin and Asian text,

Adjust space between Asjan text and numbers

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part-1. In particular, the different approval criteria needed for the different types of ISO documents document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part—___ 2 directives www.iso.org/directives).

Attention is drawnISO draws attention to the possibility that some of the elementsimplementation of this document may be involve the subjectuse of (a) patent(s). ISO takes no position concerning the evidence validity or applicability of any claimed patent rights, in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement thi document. However, implementers are cautioned that this may not represent the latest information which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declaration received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.htmlwww.iso.org/iso/foreword.html

This document was prepared by Technical Committee ISO/TC 206, Fine ceramics, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 184, Advance technical ceramics, in accordance with the Agreement on technical cooperation between ISO and CE (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 26443:2008), of which it constitutes minor revision. The changes are as follows This document was prepared by Technical Committee ISO/T 206. Fine ceramics.

This second edition cancels and replaces the first edition (ISO 19810:2017), of which it constitute minor revision. The changes are as follows:

- —-_Table of contents was added;
- <u>The title of</u> Normative <u>references</u> reference titles were updated;

Formatted: List Continue 1. Tab stops: 0.7 cm. Left + 1.4 cm, Left + 2.1 cm, Left + 2.8 cm, Left + 3.5 cm, Left + 4.2 cm, Left + 4.9 cm, Left + 5.6 cm, Left + 6.3 cm,

Formatted: English (United States)

Left + 7 cm, Left

© ISO 2023 - All rights reserved

electrotechnical standardization.

— Unit_Units for loads in kgf waswere deleted.

Any feedback or questions on this document should be directed to the user's national standards body. As complete listing of these bodies can be found at www.iso.org/members.html www.iso.org/members.html

Formatted: English (United States)

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: English (United States)

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 26443

https://standards.iteh.ai/catalog/standards/sist/6adbfbe0-4cb6-469a-a271-edaf658972f3/iso-fdis-26443

Formatted: Font: 10 pt

Formatted: Space Before: 12 pt, Line spacing: Exactly 12 pt

Fine ceramics (advanced ceramics, advanced technical ceramics)—Rockwell indentation test for evaluation of adhesion of ceramic coatings

•1_Scope

This International Standarddocument specifies a method for the qualitative evaluation of the adhesion of ceramic coatings up to 20 mm um thick by indentation with a Rockwell diamond indenter. The formation of cracks after indentation maycan also reveal cohesive failure. The indentations are made with a Rockwell hardness test instrument.

The method described in this International Standard maydocument can also be suitable for evaluating the adhesion of metallic coatings.

The test is not suitable for elastic coatings on hard substrates.

•2_Normative references

The following referenced documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO-6508-1, Metallic materials — Rockwell hardness test — Part 1: Test method

ISO-6508–2, Metallic materials — Rockwell hardness test — Part 2: Verification and calibration of testing machines and indenters

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

•4_Principle

An indentation is made into the coated surface of the specimen to be tested, whereby the coating near the indent can be damaged. The indentation and surrounding area are examined for cracks and/or flaking with the aid of an optical microscope.

Formatted	<u></u>
	(
Formatted	<u></u>
Formatted	<u></u>
Formatted	
Formatted	
Formatted	<u></u>
Formatted	<u></u>
Formatted	
Formatted	<u></u>
Formatted	(
Formatted	
Formatted	<u></u>
Formatted	(
Formatted	<u></u>
Formatted	<u></u>
Formatted 89 / Z13/180-	(
Formatted	
Formatted	
Formatted	<u></u>
Formatted	
Formatted	[
Formatted	<u></u>
Formatted	(
Formatted	
Formatted	<u></u>
Formatted	
Formatted	<u></u>

Formatted Table

•<u>5</u> Apparatus

The indentations shall be made in accordance with ISO 6508-1, following the procedure for a Rockwell* hardness indentation.

The Rockwell hardness testing machine shall conform with the requirements of ISO 6508-2.

The contour of the diamond indenter shall be checked regularly by optical means (magnifying glass, optical microscope, stereomicroscope or projection screen). This check shall be made for at least four different axial sections. The indenter shall be replaced if this examination reveals any damage to the indenter (e.g. chipping). A magnification of at least **\(\times\)200 is recommended to detect ring cracks or microwear.

Although a research project to evaluate the effect of indentation parameters showed no major influence of load rate or holding time on the results (see Reference [1]), they should preferably be kept constant for reasons of repeatability. To conform with $150_06508_01_0$ it is necessary to keep the loading time between 1_0 and 1_0 and 1_0 and the hold time at 1_0 and 1_0 Neither loading time nor holding time need to be recorded.

•6 Sampling and preparation of test specimens

Select a representative test specimen from the coating to be tested. Clean the specimen so that it is free from dust and other particles, and also from oil or other surface films.

•7 Procedure

The indentation shall be made in a direction perpendicular to the specimen surface. Therefore, specimens shall be prepared plane parallel and/or levelled before indentation.

Depending on the coating/substrate combination, a suitable load range shall be selected.

The following rules shall apply: ls.iteh.ai/catalog/standards/sist/6adbfbe0-4cb6-469a

- ___for metallic substrates harder than 54_HRC, a load of 14711 471,5-N shall be used (Rockwell C scale);
- —_for metallic substrates softer than 54_HRC and for medium case-hardened steel substrates, a load of 981-N shall be used (Rockwell D scale);
- —_for all other substrates, e.g. shallow case-hardened steel, thin substrates, cemented carbides, solid ceramics and cermets, a load of 588,6-N shall be used (Rockwell A scale).

Using an optical microscope (magnification ×100), relate the indentation to the classification given in Table-1, A pictorial representation and sample photographs of these classes can be found in Annex-A.

Table-1 — Classification of test results

Class	Observation
Class 0	No cracking and no adhesive delamination (see Figure A.1)
Class 1	Cracking without adhesive delamination of the coating (see Figure A.2)

Formatted: English (United Kingdom)

Formatted: Indent: Left: 0 cm, First line: 0 cm, Tab stops: Not at 0.76 cm

Formatted

Formatted: Body Text, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Formatted

Formatted: English (United Kingdom)

Formatted

Formatted: Indent: Left: 0 cm, First line: 0 cm, Tab stops: Not at 0.76 cm

Formatted: English (United Kingdom)

Formatted: Body Text

Formatted: Indent: Left: 0 cm, First line: 0 cm, Tab stops: Not at 0.76 cm

Formatted

Formatted: Body Text, Don't adjust space between Latin and Asian text, Don't adjust space between Asian text and numbers

Formatted: English (United Kingdom)

Formatted

Formatted

Formatted

Formatted Formatted

Formatted

Formatted: Font: 11 pt

Formatted

Formatted

Formatted: Font: 10 pt

Formatted

Formatted Table

Formatted: English (United Kingdom)

Formatted: Font: 10 pt, Font color: Auto, Pattern: Clear

Formatted

Formatted: Font: 10 pt, Font color: Auto, Pattern: Clear

Formatted: English (United Kingdom)

Formatted

2

Class 2	Partial adhesive delamination, with or without cracking <u>(see</u>	
Class Z	Figure A.3)	ŀ
Class 3	Complete adhesive delamination (see Figure A.4)	

Class 0 reveals acceptable adhesion. However, the absence of any visual failure can be due to the test not being suitable for the substrate/coating system under investigation. Class 1 shows no adhesive delamination; adhesion is acceptable. In the cases of class 2 and class 3, adhesion is unacceptable.

The test may also reveal cohesive failure of the coating, e.g. cracking. The observation of cracks can $\mathbf{b}_{\mathbf{a}}^{\mathbf{j}}$ facilitated by using optical contrasting techniques, e.g. Nomarski interference contrast microscopy.

Delamination can be due to adhesive as well as cohesive failure of the coating:

- —_Adhesive delamination is defined as a removal of the coating, whereby the underlying substrate can be clearly seen, or a removal of one or more sublayers in a multilayer coating, whereby the substrate or an underlying sublayer can be clearly distinguished.
- ___Cohesive delamination is defined as a partial removal of the coating, whereby the underlying substrate stays covered by the coating, or a removal of one or more sublayers in a multilayer coating, whereby the substrate and none of the underlying sublayers can be clearly distinguished.

Complete delamination is defined as an uninterrupted removal of the coating along the circumference of the indents.

- —_When a class 2 failure is observed, an estimate of the percentage of delamination in relation to the surface area of the indent shall be given. This estimate shall be based on the sum of the calculated areas of each individual delamination, determined from its dimensions. A micrograph of a typical class 2 failure can be found in Annex-A.
- —_When a class 3 failure is observed, the size of the adhesive delamination shall be described by the ratio(r/a) of the radius of adhesive delamination r to the radius of the indent a.

For a class 3 failure—the radius of adhesive delamination is defined as the maximum radius of the delamination related to the centre of the indent, excluding any needle-like delaminations away from the indent.

It is recommended that at least three measurements be made at representative locations.

•8 Limits

Results shall only be compared when a similar substrate/coating combination and coating thickness are

When comparing results, class designations shall be linked to the load used. Only indents made at the same load shall be compared.

•9 Test report

The test report shall include the following information:

a) the name and address of the testing establishment;

Formatted	L
Formatted	<u></u>
Formatted	
Formatted	<u></u>
Formatted	<u></u>
Formatted	<u></u>
Formatted	
Formatted	
Formatted	
Formatted	
Formatted	<u></u>
Formatted	
Formatted	
Formatted	
Formatted	(
Formatted	<u></u>
Formatted	
Formatted	<u></u>
Formatted	<u></u>
Formatted	(
Formatted (1970 mg/)	
Formatted	
Formatted	
Formatted	
Formatted	(
Formatted	(
Formatted	(
Formatted	
Formatted	<u></u>
Formatted	
Formatted	<u></u>
Formatted	
Formatted	<u></u>
Formatted	<u></u>
Formatted	
Formatted	$\overline{}$

- b) -h)_the date of the test, a unique identification of the test report and of each page, the name and address of the customer and the signature of the responsible individual(s);
- c) a reference to this International Standard document, i.e. ISO 26443;
- d) the type of test equipment used, the manufacturer and the date of the last calibration;
- e) a description of the test material: type of substrate, type of coating and date of receipt;
- f f the method of test (i.e. the load) used, and details of sampling and specimen preparation;
- g)_the results of at least three tests for the load used, including descriptions for any class 2 and class 3 failures:
- h) any comments about the test or the test results (e.g. the observation of cohesive failure).

Formatted: English (United Kingdom)

Formatted: std_publisher

Formatted: std_docNumber

Formatted: English (United Kingdom)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO/FDIS 26443</u>

https://standards.iteh.ai/catalog/standards/sist/6adbfbe0-4cb6-469a-a271-edaf658972f3/iso-fdis-26443

© ISO 2023 - All rights reserved