



**International
Standard**

ISO/IEC 17760-105

**Information technology — AT
Attachment —**

**Part 105:
ATA Command Set - 5 (ACS-5) Standards**

**(<https://standards.iteh.ai>)
Document Preview**

[ISO/IEC PRF 17760-105](#)

<https://standards.iteh.ai/catalog/standards/iso/e32fa7b0-557c-4121-9092-bfe1894fa3ef/iso-iec-prf-17760-105>

**First edition
2024-03**

PROOF/ÉPREUVE

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/IEC PRF 17760-105](#)

<https://standards.iteh.ai/catalog/standards/iso/e32fa7b0-557c-4121-9092-bfe1894fa3ef/iso-iec-prf-17760-105>



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

ISO and IEC draw attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO and IEC take no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO and IEC had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents and <https://patents.iec.ch>. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

iTeh Standards
Definitions
Information at Preview

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by INCITS (as INCITS 558-2021, ATA Command Set – 5) and drafted in accordance with its editorial rules. It was assigned to Joint Technical Committee ISO/IEC JTC 1, *Information technology*, and adopted under the “fast-track procedure”.
c-4121-9092-bfe1894fa3ef/iso-iec-prf-17760-105

A list of all parts in the ISO/IEC 17760 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Contents

	Page
Contents.....	i
Tables	xii
Figures	xx
Foreword	xxi
Introduction	xxiv
1 Scope	1
2 Normative references	2
3 Definitions, abbreviations, and conventions	3
3.1 Definitions	3
3.2 Symbols and abbreviations	9
3.2.1 Abbreviations	9
3.2.2 Units	11
3.2.3 Symbols	11
3.2.4 Mathematical operators	11
3.3 Keywords	11
3.4 Conventions	12
3.4.1 Overview	12
3.4.2 Precedence	13
3.4.3 Lists	13
3.4.4 Numbering	14
3.4.5 Bit conventions	14
3.4.6 Number range convention	14
3.4.7 State diagram conventions	15
3.4.8 Byte, word, DWord, QWord, and DQWord Relationships	17
3.4.9 ATA string convention	18
3.4.10 Offset Convention	19
4 Feature set definitions	20
4.1 Overview	20
4.1.1 Feature set summary	20
4.1.2 Capacity reporting	21
4.2 General feature set	22
4.2.1 Overview	22
4.2.2 Unexpected power removal	22
4.2.3 Interactions with volatile caches	23
4.3 48-bit Address feature set	24
4.4 Accessible Max Address Configuration feature set	25
4.4.1 Overview	25
4.4.2 SET ACCESSIBLE MAX ADDRESS EXT description	25
4.4.3 Interactions with device statistics data	25
4.5 Advanced Background Operation feature set (ABO)	26
4.5.1 Overview	26
4.5.2 Host-initiated advanced background operations	26
4.5.3 Device-initiated advanced background operations	27
4.6 Advanced Power Management (APM) feature set	28
4.7 Command Duration Limits feature set	29
4.7.1 Overview	29

4.7.2 COMMAND DURATION LIMITS INDEX field	30
4.7.3 Command duration limits operation	30
4.7.4 High Priority Enhancement feature	31
4.8 Device Statistics Notification (DSN) feature set	33
4.8.1 Overview	33
4.8.2 DSN notifications	33
4.8.3 DSN notifications setup	34
4.9 Extended Power Conditions (EPC) feature set	35
4.9.1 Overview	35
4.9.2 Power conditions	35
4.9.3 Power condition timers	35
4.9.4 Interaction with resets, commands, and other features if the EPC feature set is enabled	36
4.10 Free-fall Control feature set	38
4.11 General Purpose Logging (GPL) feature set	39
4.12 Hybrid Information feature set	40
4.12.1 Hybrid Information feature overview	40
4.12.2 Syncing	42
4.12.3 Interactions with ATA power management	42
4.12.4 Other Hybrid conditions	43
4.13 Long Logical Sector (LLS) feature set	45
4.14 Long Physical Sector (LPS) feature set	47
4.15 Native Command Queuing (NCQ) feature set	49
4.15.1 Overview	49
4.15.2 Priority	49
4.15.3 Unload with NCQ commands outstanding	50
4.15.4 Command Phases	50
4.15.5 NCQ command processing order requirements	51
4.15.6 ATA device commands encapsulated in NCQ feature set commands	51
4.15.7 Returning sense data for successful NCQ feature set commands	51
4.16 Out Of Band Management Interface	53
4.17 Power Management feature set	55
4.17.1 Overview	55
4.17.2 Power management commands	55
4.17.3 Standby timer	55
4.17.4 Power Management states and transitions	56
4.18 Power-Up In Standby (PUIS) feature set	60
4.18.1 Overview	60
4.18.2 Interactions with the IDENTIFY DEVICE command	60
4.18.3 PUIS feature set device spin-up subcommand	60
4.19 Rebuild Assist feature set	61
4.19.1 Overview	61
4.19.2 Enabling the Rebuild Assist feature set	61
4.19.3 Using the Rebuild Assist feature set	61
4.19.4 Disabling the Rebuild Assist feature set	63
4.19.5 Testing the Rebuild Assist feature set	63
4.20 Sanitize Device feature set	64
4.20.1 Overview	64
4.20.2 Sanitize operation scope	64
4.20.3 Sanitize commands	64
4.20.4 Sanitize operations	64
4.20.5 Interactions of the Sanitize Device feature set and Security feature set	65
4.20.6 Command processing during sanitize operations	65
4.20.7 Sanitize Operation Completed Without Error value	66
4.20.8 Failure Mode Policy value	66
4.20.9 Sanitize Antifreeze value	67
4.20.10 Sanitize Device state machine	67
4.21 SATA Hardware Feature Control feature set	70

4.22 Security feature set	71
4.22.1 Overview	71
4.22.2 Disabling and enabling the Security feature set	71
4.22.3 Passwords	71
4.22.4 Master password capability	71
4.22.5 Frozen mode	72
4.22.6 Commands	72
4.22.7 Security initial setting	72
4.22.8 Password Rules	72
4.22.9 Password attempt counter and SECURITY COUNT EXPIRED bit	72
4.22.10 Master Password Identifier feature	73
4.22.11 Security states	73
4.23 Self-Monitoring, Analysis, and Reporting Technology (SMART) feature set	85
4.23.1 Overview	85
4.23.2 Background data collection	85
4.23.3 Off-line/Captive mode data collection	85
4.23.4 Threshold exceeded condition	85
4.23.5 SMART feature set commands	85
4.23.6 SMART operation with power management modes	85
4.23.7 SMART device error log reporting	85
4.24 Sense Data Reporting feature set	87
4.24.1 General	87
4.24.2 Current information sense data and deferred error sense data	88
4.25 Software Settings Preservation (SSP) feature set	89
4.26 Storage Element Depopulation feature set	90
4.26.1 Overview	90
4.26.2 Status change notification	90
4.26.3 Repurposing Depopulation	91
4.26.4 Repurposing Depopulation Restoration	92
4.26.5 Effects of storage depopulation commands on other commands	93
4.26.6 Interactions with logs	94
4.26.7 Interactions with caches	94
4.27 Streaming feature set	95
4.27.1 Streaming feature set overview	95
4.27.2 Streaming commands	95
4.28 Trusted Computing feature set	97
4.29 User Data Initialization feature set	98
4.29.1 Overview	98
4.29.2 User data initialization operation	98
4.29.3 MUTATE EXT command	100
4.30 Write-Read-Verify feature set	101
5 ATA protocols	102
6 Normal and Error Output field descriptions	103
6.1 Overview	103
6.2 STATUS field	103
6.2.1 Overview	103
6.2.2 ALIGNMENT ERROR bit	103
6.2.3 BUSY bit	103
6.2.4 DATA REQUEST bit	104
6.2.5 DEFERRED WRITE ERROR bit	104
6.2.6 DEVICE FAULT bit	104
6.2.7 DEVICE READY bit	104
6.2.8 ERROR bit	104
6.2.9 SENSE DATA AVAILABLE bit	104
6.2.10 STREAM ERROR bit	105

6.2.11 Transport Dependent bits and fields	105
6.3 ERROR field	105
6.3.1 Overview	105
6.3.2 ABORT bit	105
6.3.3 COMMAND COMPLETION TIME OUT bit	106
6.3.4 ID NOT FOUND bit	106
6.3.5 INTERFACE CRC bit	106
6.3.6 UNCORRECTABLE ERROR bit	106
6.4 COUNT field	106
6.4.1 Overview	106
6.4.2 Contiguous stream logical sectors that contain potentially bad data	106
6.4.3 NCQ Tag	106
6.5 SACTIVE field	106
6.6 SATA STATUS field	107
6.7 LBA field	107
6.7.1 Overview	107
6.7.2 LBA of First Unrecoverable Error	107
6.8 Sense code definitions	107
6.8.1 Overview	107
6.8.2 ACCESS DENIED - NO ACCESS RIGHTS	108
6.8.3 COMMAND SEQUENCE ERROR	109
6.8.4 COMMAND TIMEOUT BEFORE PROCESSING	109
6.8.5 COMMAND TIMEOUT DURING PROCESSING	109
6.8.6 DATA CURRENTLY UNAVAILABLE	109
6.8.7 DEPOPULATION FAILED	109
6.8.8 DEPOPULATION IN PROGRESS	109
6.8.9 DEPOPULATION RESTORATION FAILED	109
6.8.10 DEPOPULATION RESTORATION IN PROGRESS	109
6.8.11 FAILURE PREDICTION THRESHOLD EXCEEDED	109
6.8.12 INFORMATION UNIT iuCRC ERROR DETECTED	109
6.8.13 INITIATOR RESPONSE TIMEOUT	109
6.8.14 INSUFFICIENT RESOURCES	109
6.8.15 INTERNAL TARGET FAILURE	110
6.8.16 INVALID COMMAND OPERATION CODE	110
6.8.17 INVALID FIELD IN CDB	110
6.8.18 INVALID FIELD IN PARAMETER LIST	110
6.8.19 LOGICAL BLOCK ADDRESS OUT OF RANGE	110
6.8.20 LOGICAL UNIT FAILED SELF-TEST	110
6.8.21 LOGICAL UNIT NOT READY, FORMAT IN PROGRESS	110
6.8.22 LOGICAL UNIT NOT READY, INITIALIZING COMMAND REQUIRED	110
6.8.23 LOGICAL UNIT NOT READY, MICROCODE ACTIVATION REQUIRED	110
6.8.24 LOGICAL UNIT NOT READY, POWER CYCLE REQUIRED	110
6.8.25 LOGICAL UNIT NOT READY, SANITIZE IN PROGRESS	110
6.8.26 MEDIUM FORMAT CORRUPTED	110
6.8.27 MULTIPLE READ ERRORS	111
6.8.28 MULTIPLE WRITE ERRORS	111
6.8.29 NO ADDITIONAL SENSE INFORMATION	111
6.8.30 NO DEFECT SPARE LOCATION AVAILABLE	111
6.8.31 OVERLAPPED COMMANDS ATTEMPTED	111
6.8.32 READ ERROR - LBA MARKED BAD BY APPLICATION CLIENT	111
6.8.33 UNRECOVERED READ ERROR	111
6.8.34 WARNING – DEVICE STATISTICS NOTIFICATION ACTIVE	111
6.8.35 WRITE ERROR	111
7 Command descriptions	112
7.1 Command description introduction	112
7.2 Accessible Max Address Configuration	119

7.2.1 Accessible Max Address Configuration overview	119
7.2.2 GET NATIVE MAX ADDRESS EXT – 78h/0000h, Non-Data	120
7.2.3 SET ACCESSIBLE MAX ADDRESS EXT – 78h/0001h, Non-Data	121
7.2.4 FREEZE ACCESSIBLE MAX ADDRESS EXT – 78h/0002h, Non-Data	123
7.3 CHECK POWER MODE – E5h, Non-Data	124
7.4 CONFIGURE STREAM – 51h, Non-Data	125
7.5 DATA SET MANAGEMENT – 06h, DMA	127
7.6 DATA SET MANAGEMENT XL – 07h, DMA	131
7.7 DOWNLOAD MICROCODE – 92h, PIO Data-Out/Non-Data	133
7.8 DOWNLOAD MICROCODE DMA – 93h, DMA/Non-Data	147
7.9 EXECUTE DEVICE DIAGNOSTIC – 90h, Execute Device Diagnostic	148
7.10 FLUSH CACHE – E7h, Non-Data	150
7.11 FLUSH CACHE EXT – EAh, Non-Data	151
7.12 GET PHYSICAL ELEMENT STATUS – 12h, DMA	152
7.13 IDENTIFY DEVICE – ECh, PIO Data-In	157
7.14 IDLE – E3h, Non-Data	191
7.15 IDLE IMMEDIATE – E1h, Non-Data	193
7.16 MUTATE EXT - 96h, Non-Data	195
7.17 NCQ NON-DATA – 63h, Non-Data	197
7.18 NOP – 00h, Non-Data	221
7.19 READ BUFFER – E4h, PIO Data-In	222
7.20 READ BUFFER DMA – E9h, DMA	223
7.21 READ DMA – C8h, DMA	224
7.22 READ DMA EXT – 25h, DMA	225
7.23 READ FPDMA QUEUED – 60h, DMA Queued	227
7.24 READ LOG EXT – 2Fh, PIO Data-In	229
7.25 READ LOG DMA EXT – 47h, DMA	231
7.26 READ SECTOR(S) – 20h, PIO Data-In	233
7.27 READ SECTOR(S) EXT – 24h, PIO Data-In	234
7.28 READ STREAM DMA EXT – 2Ah, DMA	235
7.29 READ STREAM EXT – 2Bh, PIO Data-In	238
7.30 READ VERIFY SECTOR(S) – 40h, Non-Data	239
7.31 READ VERIFY SECTOR(S) EXT – 42h, Non-Data	240
7.32 RECEIVE FPDMA QUEUED – 65h, DMA Queued	241
7.33 REMOVE ELEMENT AND TRUNCATE – 7Ch, Non-Data	243
7.34 REQUEST SENSE DATA EXT – 0Bh, Non-Data	245
7.35 RESTORE ELEMENTS AND REBUILD – 7Dh, Non-Data	246
7.36 Sanitize Device	248
7.36.1 Sanitize Device Overview	248
7.36.2 BLOCK ERASE EXT – B4h/0012h, Non-Data	249
7.36.3 CRYPTO SCRAMBLE EXT – B4h/0011h, Non-Data	252
7.36.4 OVERWRITE EXT – B4h/0014h, Non-Data	255
7.36.5 SANITIZE ANTIFREEZE LOCK EXT – B4h/0040h, Non-Data	258
7.36.6 SANITIZE FREEZE LOCK EXT – B4h/0020h, Non-Data	261
7.36.7 SANITIZE STATUS EXT – B4h/0000h, Non-Data	263
7.37 SECURITY DISABLE PASSWORD – F6h, PIO Data-Out	265
7.38 SECURITY ERASE PREPARE – F3h, Non-Data	267
7.39 SECURITY ERASE UNIT – F4h, PIO Data-Out	268
7.40 SECURITY FREEZE LOCK – F5h, Non-Data	271
7.41 SECURITY SET PASSWORD – F1h, PIO Data-Out	272
7.42 SECURITY UNLOCK – F2h, PIO Data-Out	275
7.43 SEND FPDMA QUEUED – 64h, DMA Queued	278
7.43.8 HYBRID EVICT – 64h/1h, DMA Queued	280
7.44 SET DATE & TIME EXT – 77h, Non-Data	284
7.45 SET FEATURES – EFh, Non-Data	285
7.45.1 Introduction	285
7.45.2 SET FEATURES subcommands	286

7.45.3 Enable/disable volatile write cache	288
7.45.4 Set transfer mode	289
7.45.5 Enable/disable the APM feature set	290
7.45.6 Enable/disable the PUIS feature set	290
7.45.7 PUIS feature set device spin-up	290
7.45.8 Enable/Disable Write-Read-Verify feature set	291
7.45.9 Enable/disable device life control	292
7.45.10 Enable/Disable Command Duration Limits feature set	292
7.45.11 Set Maximum Host Interface Sector Times	294
7.45.12 Set rate basis	294
7.45.13 Enable/disable read look-ahead	294
7.45.14 Enable/disable reverting to defaults	295
7.45.15 Enable/Disable the Free-fall Control feature set	295
7.45.16 Enable/Disable SATA feature	295
7.45.17 Enable/Disable the Sense Data Reporting feature set	299
7.45.18 Enable/Disable sense data return for successful NCQ commands	299
7.45.19 Long Physical Sector Alignment Error Reporting Control	300
7.45.20 Extended Power Conditions subcommand	301
7.45.21 Enable/Disable the DSN feature set	312
7.45.22 Advanced Background Operation Control	312
7.46 SET SECTOR CONFIGURATION EXT – B2h, Non-Data	315
7.47 SLEEP – E6h, Non-Data	318
7.48 SMART	319
7.48.1 Overview	319
7.48.2 SMART READ LOG – B0h/D5h, PIO Data-In	320
7.48.3 SMART RETURN STATUS – B0h/DAh, Non-Data	321
7.48.4 SMART WRITE LOG – B0h/D6h, PIO Data-Out	322
7.49 STANDBY – E2h, Non-Data	324
7.50 STANDBY IMMEDIATE – E0h, Non-Data	325
7.51 TRUSTED NON-DATA – 5Bh, Non-Data	326
7.52 TRUSTED RECEIVE – 5Ch, PIO Data-In	328
7.53 TRUSTED RECEIVE DMA – 5Dh, DMA	335
7.54 TRUSTED SEND – 5Eh, PIO Data-Out	336
7.55 TRUSTED SEND DMA – 5Fh, DMA	338
7.56 WRITE BUFFER – E8h, PIO Data-Out	339
7.57 WRITE BUFFER DMA – EBh, DMA	340
7.58 WRITE DMA – CAh, DMA	341
7.59 WRITE DMA EXT – 35h, DMA	342
7.60 WRITE DMA FUA EXT – 3Dh, DMA	343
7.61 WRITE FPDMA QUEUED – 61h, DMA Queued	345
7.62 WRITE LOG EXT – 3Fh, PIO Data-Out	347
7.63 WRITE LOG DMA EXT – 57h, DMA	349
7.64 WRITE SECTOR(S) – 30h, PIO Data-Out	351
7.65 WRITE SECTOR(S) EXT – 34h, PIO Data-Out	352
7.66 WRITE STREAM DMA EXT – 3Ah, DMA	353
7.67 WRITE STREAM EXT – 3Bh, PIO Data-Out	356
7.68 WRITE UNCORRECTABLE EXT – 45h, Non-Data	357
7.69 ZERO EXT – 44h, Non-Data	360
8 SCT Command Transport	362
8.1 Introduction	362
8.1.1 Overview	362
8.1.2 SCT command interactions with ATA commands	363
8.1.3 NCQ accesses to the SCT logs	363
8.1.4 Resets	363
8.2 Processing SCT commands	364
8.2.1 Processing SCT commands overview	364

8.2.2 SCT capability identification	364
8.2.3 SCT Command transfer	364
8.2.4 SCT data transfer	369
8.2.5 SCT status	375
8.3 SCT Command Set	382
8.3.1 Overview	382
8.3.2 SCT Write Same command	383
8.3.3 SCT Error Recovery Control command	388
8.3.4 SCT Feature Control command	393
8.3.5 SCT Data Table command.....	397
9 Log Definitions	401
9.1 Overview	401
9.2 General Purpose Log Directory (GPL Log Address 00h)	404
9.3 SMART Log Directory (SMART Logging Log Address 00h)	405
9.4 Comprehensive SMART Error log (Log Address 02h)	406
9.4.1 Overview	406
9.4.2 SMART error log version	406
9.4.3 Error log index	406
9.4.4 Error log data structure	406
9.4.5 Device error count	407
9.4.6 Data structure checksum	407
9.5 Device Statistics log (Log Address 04h)	408
9.5.1 Overview	408
9.5.2 FEATURE field for GPL commands	410
9.5.3 List of Supported Device Statistics log pages (log page 00h)	411
9.5.4 Command Duration Limits Statistics (log page 09h)	411
9.5.5 Free Fall Statistics (log page 02h)	419
9.5.6 General Statistics (log page 01h)	421
9.5.7 General Errors Statistics (log page 04h)	428
9.5.8 Rotating Media Statistics (log page 03h)	431
9.5.9 Solid State Device Statistics (log page 07h)	436
9.5.10 Temperature Statistics (log page 05h)	436
9.5.11 Transport Statistics (log page 06h)	444
9.5.12 Vendor Specific Statistics (log page FFh)	445
9.6 Device Vendor Specific logs (Log Addresses A0h-DFh)	447
9.7 Extended Comprehensive SMART Error log (Log Address 03h)	448
9.7.1 Overview	448
9.7.2 SMART error log version	448
9.7.3 Error log index	448
9.7.4 Extended Error log data structure	448
9.7.5 Device error count	452
9.7.6 Data structure checksum	452
9.8 Power Conditions log (Log Address 08h)	453
9.8.1 Overview	453
9.8.2 Idle power conditions (log page 00h)	453
9.8.3 Standby power conditions (log page 01h)	453
9.8.4 Power Conditions log descriptor	454
9.9 Host Specific logs (Log Addresses 80h-9Fh)	458
9.10 IDENTIFY DEVICE data log (Log Address 30h)	459
9.10.1 Overview	459
9.10.2 List of Supported IDENTIFY DEVICE data log pages (Page 00h)	460
9.10.3 Copy of IDENTIFY DEVICE data (page 01h)	460
9.10.4 Capacity (page 02)	461
9.10.5 Supported Capabilities (page 03h)	464
9.10.6 Current Settings (page 04h)	490
9.10.7 Strings (page 05h)	498

9.10.8 Security (page 06h)	499
9.10.9 Parallel ATA (page 07h)	504
9.10.10 Serial ATA (page 08h)	515
9.11 Command Duration Limits log (Log Address 18h)	525
9.11.1 Command Duration Limits log overview	525
9.11.2 Command Duration Limits Descriptor	527
9.12 LBA Status log (Log Address 19h)	532
9.12.1 Overview	532
9.12.2 Number of LBA Valid Ranges log page (Page 0000h)	532
9.12.3 LBA Status log pages	532
9.12.4 LBA Status Descriptor	533
9.13 LPS Mis-alignment log (Log Address 0Dh)	535
9.14 NCQ Command Error log (Log Address 10h)	537
9.14.1 Overview	537
9.14.2 NCQ TAG field	538
9.14.3 NQ bit	538
9.14.4 UNL bit	538
9.14.5 Return Fields	539
9.14.6 NCQ Autosense	539
9.14.7 FINAL LBA IN ERROR field	539
9.14.8 Checksum	539
9.14.9 WRITE POINTER VALID field	539
9.14.10 WRITE POINTER[0..31] fields	540
9.14.11 WRITE POINTER CHECKSUM field	540
9.15 Read Stream Error log (Log Address 22h)	541
9.16 SATA Phy Event Counters log (Log Address 11h)	543
9.16.1 Overview	543
9.16.2 Counter x Identifier	543
9.16.3 Counter x Value	543
9.16.4 Counter x Length	543
9.16.5 Checksum	543
9.17 SATA NCQ Non-Data log (Log Address 12h)	544
9.17.1 Overview	544
9.17.2 SUPPORTS ABORT NCQ QUEUE bit	546
9.17.3 SUPPORTS ABORT ALL AT bit	546
9.17.4 SUPPORTS ABORT STREAMING AT bit	546
9.17.5 SUPPORTS ABORT NON-STREAMING AT bit	546
9.17.6 SUPPORTS ABORT SELECTED TTAG AT bit	546
9.17.7 SUPPORTS DEADLINE HANDLING bit	546
9.17.8 SUPPORTS WDNC bit	546
9.17.9 SUPPORTS RDNC bit	546
9.17.10 SUPPORTS HYBRID DEMOTE BY SIZE bit	547
9.17.11 SUPPORTS HYBRID CHANGE BY LBA RANGE bit	547
9.17.12 SUPPORTS HYBRID CONTROL bit	547
9.17.13 QUEUED SET FEATURES SUPPORTED bit	547
9.17.14 QUEUED ZERO EXT SUPPORTED bit	547
9.17.15 SUPPORTS ZAC MANAGEMENT OUT bit	547
9.17.16 SUPPORTS DURABLE/ORDERED WRITE NOTIFICATION bit	547
9.17.17 SUPPORTS D/O/W bit	547
9.18 SATA NCQ Send and Receive log (Log Address 13h)	548
9.18.1 Overview	548
9.18.2 QUEUED DATA SET MANAGEMENT XL SUPPORTED bit	548
9.18.3 SUPPORTS HYBRID EVICT bit	549
9.18.4 QUEUED DATA SET MANAGEMENT SUPPORTED bit	549
9.18.5 QUEUED DATA SET MANAGEMENT SUPPORTS TRIM bit	549
9.18.6 QUEUED READ LOG DMA EXT FEATURE FIELD SUPPORTED bit	549
9.18.7 SEQUENTIAL QUEUED READ LOG DMA EXT SUPPORTED bit	549

9.18.8 QUEUED READ LOG DMA EXT SUPPORTED bit	549
9.18.9 SEQUENTIAL QUEUED WRITE LOG DMA EXT SUPPORTED bit	549
9.18.10 QUEUED WRITE LOG DMA EXT SUPPORTED bit	549
9.18.11 SUPPORTS ZAC MANAGEMENT IN bit	550
9.18.12 SUPPORTS ZAC MANAGEMENT OUT bit	550
9.19 Hybrid Information log (Log Address 14h)	551
9.19.1 Hybrid Information log overview	551
9.19.2 Hybrid Information Header	552
9.19.3 Hybrid Information Descriptor	555
9.20 Rebuild Assist log (Log Address 15h)	557
9.20.1 Overview	557
9.20.2 MANAGE REBUILD ASSIST ENABLED bit	558
9.20.3 PHYSICAL ELEMENT LENGTH field	558
9.20.4 DISABLED PHYSICAL ELEMENT MASK field	558
9.20.5 DISABLED PHYSICAL ELEMENTS field	558
9.21 Selective Self-Test log (Log Address 09h)	559
9.21.1 Overview	559
9.21.2 REVISION NUMBER field	559
9.21.3 Test span starting LBA and ending LBA	559
9.21.4 CURRENT LBA UNDER TEST field	559
9.21.5 CURRENT SPAN UNDER TEST field	560
9.21.6 FEATURE FLAGS field	560
9.21.7 SELECTIVE SELF-TEST PENDING TIME field	560
9.21.8 CHECKSUM field	560
9.22 Summary SMART Error log (Log Address 01h)	561
9.22.1 Overview	561
9.22.2 SMART error log version	561
9.22.3 Error log index	561
9.22.4 Error log data structure	561
9.22.5 Device error count	564
9.22.6 Data structure checksum	564
9.23 Write Stream Error log (Log Address 21h)	565
9.24 Current Device Internal Status Data log (Log Address 24h)	566
9.24.1 Overview	566
9.24.2 Current Device Internal Status Data header page	567
9.24.3 Current Device Internal Status data pages	568
9.24.4 Examples of data area usage	569
9.25 Saved Device Internal Status Data log (Log Address 25h)	571
9.25.1 Overview	571
9.25.2 Saved Device Internal Status Data header page	571
9.25.3 Current Device Internal Status data pages	572
9.26 Device Statistics Notifications log (Log Address 0Ah)	573
9.27 Pending Defects log (Log Address 0Ch)	577
9.27.1 Overview	577
9.27.2 Detection of an uncorrectable media error	577
9.27.3 Adding descriptors to the Pending Defects log	577
9.27.4 Removing descriptors from the Pending Defects log	577
9.27.5 Contents of the Pending Defects log	577
9.27.6 NUMBER OF LOG DESCRIPTORS field	578
9.27.7 Pending Defects descriptor format	578
9.28 Sense Data for Successful NCQ Commands log (Log address 0Fh)	579
9.28.1 Overview	579
9.28.2 SENSE DATA VALID field	580
9.28.3 Successful Sense Data descriptor	581
9.29 Sector Configuration log (Log Address 2Fh)	582
9.29.1 Overview	582
9.29.2 Sector Configuration descriptors (log page 00h)	582

9.30 Mutate Configurations log (Log Address 42h)	584
9.30.1 Overview	584
9.30.2 Zero padding	584
9.30.3 Mutate Configurations header	584
9.30.4 Mutate Configuration descriptor	585
9.31 Concurrent Positioning Ranges log (Log Address 47h)	591
9.31.1 Concurrent Positioning Ranges log overview	591
9.31.2 Concurrent Positioning Ranges header	591
9.31.3 LBA range descriptor	591
9.31.4 Padding	592
9.31.5 Example Concurrent Positioning Ranges log	592
9.32 Sense Data log (Log Address 53h)	594
9.32.1 Overview	594
9.32.2 DEFERRED ERROR bit	595
9.32.3 Return Fields	595
9.32.4 SENSE KEY field, ADDITIONAL SENSE CODE field, and ADDITIONAL SENSE CODE QUALIFIER field	595
9.32.5 FINAL LBA IN ERROR field	595
9.32.6 Checksum	595
9.33 Out Of Band Management Control log (Log Address 16h)	596
9.33.1 Out Of Band Management Control log overview	596
9.33.2 NUMBER OF VALID DESCRIPTORS field	596
9.33.3 REPORTING ENABLED bit	596
9.33.4 VOLATILE bit	597
9.33.5 PROTOCOL REVISION CODE field	597
9.33.6 Attribute Control Descriptor	597
9.33.7 Temperature attribute control descriptor format	599
10 Normal and Error Outputs	602
10.1 Overview	602
10.2 Normal Outputs	602
10.3 Error Outputs	617
Annex A (informative) Command Set Summary	645
Annex B (informative) How to Use SCT Commands	672
B.1 How to Use SCT Commands Overview	672
B.2 Examples of Log Page Command Sequences	674
B.3 Issuing an SCT Command to a Device	679
B.3.1 Step 1 – Build a Key Page	679
B.3.2 Step 2 – Issue the SCT command	680
B.3.3 Step 3 – Transfer Data if Required	681
B.3.4 Step 4 – Final Status/SCT Command Completion	682
Annex C (informative) Implementation Guidelines for 1 024- and 4 096-Byte Sector Sizes	683
C.1 Scope	683
C.2 Overview	683
C.3 Implementation	685
C.3.1 4 096-Byte Physical Sector Size Implementation	685
C.3.2 Reporting Alignment (512-Byte LBA Only)	685
C.3.3 RMW operations (512-Byte LBA Only)	686
C.4 Implementation Issues (512-Byte LBA Only)	686
C.4.1 Overview	686
C.4.2 Drive Partitioning	687
C.4.3 File System Formatting	688
C.4.4 Virtual Memory accessing	688
C.4.5 Booting	688