

# FINAL DRAFT International Standard

# ISO general purpose metric screw threads — Tolerances —

Part 6:

Limits of sizes for internal and external threads (fine and medium tolerance qualities, first and second choices)

Filetages métriques ISO pour usages généraux — Tolérances — Partie 6: Limites de tailles pour les filetages intérieurs et extérieurs (qualités de tolérance fines et moyennes, premier et

second choix)

### ISO/FDIS 965-6

ISO/TC 1

Secretariat: **SAC** 

Voting begins on: **2025-04-22** 

Voting terminates on: 2025-06-17

12-9/0/-101/400411/0/180-1018-905-0

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

## iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/FDIS 965-6

https://standards.iteh.ai/catalog/standards/iso/bb79de15-246d-43f7-97b7-fc1740e4f17b/iso-fdis-965-6



#### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org

Website: <a href="https://www.iso.org">www.iso.org</a>
Published in Switzerland

| Con    | tents | 5                 | Page |
|--------|-------|-------------------|------|
| Forew  | ord   |                   | iv   |
| 1      | Scope | 3                 | 1    |
| 2      | Norm  | ative references  | 1    |
| 3      | Term  | s and definitions | 1    |
| 4      | Limit | s of sizes        | 1    |
|        | 4.1   | General           |      |
|        | 4.2   | Internal threads  | 3    |
|        | 4.3   | External threads  | 39   |
| Biblio | graph | V                 | 72   |

# iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ISO/FDIS 965-6</u>

https://standards.iteh.ai/catalog/standards/iso/bb79de15-246d-43f2-97b7-fc1740e4f17b/iso-fdis-965-6

#### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="https://www.iso.org/directives">www.iso.org/directives</a>).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <a href="https://www.iso.org/patents">www.iso.org/patents</a>. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

This document was prepared by Technical Committee ISO/TC 1, Screw threads.

A list of all parts in the ISO 965 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <a href="https://www.iso.org/members.html">www.iso.org/members.html</a>.

ISO/FDIS 965-6

https://standards.iteh.ai/catalog/standards/iso/bb79de15-246d-43f2-97b7-fc1740e4f17b/iso-fdis-965-6

### ISO general purpose metric screw threads — Tolerances —

#### Part 6:

# Limits of sizes for internal and external threads (fine and medium tolerance qualities, first and second choices)

#### 1 Scope

This document specifies the limits of sizes for major, pitch and minor diameters of ISO general purpose metric screw threads (M) conforming to ISO 261 and having basic and design profiles in accordance with ISO 68-1.

This document is applicable to the metric fastening screw threads with the ten tolerance classes (4H, 5H, 6H, 7H, 6G, 4h, 6h, 6g, 6f and 6e) recommended in ISO 965-1.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 965-1, ISO general purpose metric screw threads — Part 1: Principles and basic data

ISO 5408, Screw threads — Vocabulary

#### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5408 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <a href="https://www.iso.org/obp">https://www.iso.org/obp</a>
- IEC Electropedia: available at <a href="https://www.electropedia.org/">https://www.electropedia.org/</a>

#### 4 Limits of sizes

#### 4.1 General

The limits of sizes specified shall be derived from the fundamental deviations and tolerances specified in ISO 965-1.

The limits of sizes for major, pitch and minor diameters of screw threads (M) have been calculated by the following formulae, derived from the formulae provided in ISO 68-1 and ISO 965-1, and rounded to the third decimal place.

#### Internal thread:

Major diameter 
$$D_{\min} = D + EI$$

Pitch diameter 
$$D_{2,\text{min}} = D_2 + EI = D - 0,649 519 P + EI$$

$$D_{2,\text{max}} = D_{2,\text{min}} + T_{D2}$$

Minor diameter 
$$D_{1,\text{min}} = D_1 + EI = D - 1,082 532 P + EI$$

$$D_{1,\text{max}} = D_{1,\text{min}} + T_{D1}$$

#### External thread:

Major diameter 
$$d_{\text{max}} = d + es$$

$$d_{\min} = d_{\max} - T_{\rm d}$$

Pitch diameter 
$$d_{2,\text{max}} = d_2 + es = d - 0,649 519 P + es$$

$$d_{2,\min} = d_{2,\max} - T_{d2}$$

Minor diameter 
$$d_{1,\text{max}} = d_1 + es = d - 1,082 532 P + es$$

$$d_{3,\text{max}} = d_{1,\text{max}} - 0.866\ 025\ 404\ P/2 + 2\ C_{\text{max}}$$

$$d_{3,\text{min}} = d_{1,\text{max}} - T_{d2} - 0,866\ 025\ 404\ P/2 + 0,250\ P$$

Where es is a negative value.

For the symbols and their definitions see ISO 965-1.

The maximum major diameter of internal thread  $D_{\rm max}$  is not specified.

Usually, the minimum major diameter of internal thread  $D_{\min}$  and the maximum minor diameter of external thread  $d_{1,\max}$  are gauged by the crest diameter of GO thread gauges in accordance with ISO 1502.

For external threads, controlling the maximum minor diameter  $d_{1,\max}$  and the minimum root radius  $R_{1,\min}$  ensures the conformity of the maximum minor diameter  $d_{3,\max}$ .

Whether to measure the maximum and minimum minor diameters of external thread,  $d_{3,\max}$  and  $d_{3,\min}$ , shall be decided according to the relevant threaded product documents. Unless specifically defined otherwise, it is not necessary to carry out a measurement of the minor diameter  $d_3$ .

For the ten tolerance classes and nominal diameter ranges see <u>Table 1</u>.

Table 1 — M screw threads with the ten recommended tolerance classes

| Screw thread    | Tolerance class | Nominal diameter<br>mm | Table number   |  |
|-----------------|-----------------|------------------------|----------------|--|
|                 | 4H              | From 1 to 100          | Table 2        |  |
|                 | 5H              | From 1 to 300          | <u>Table 3</u> |  |
| Internal thread | 6Н              | From 1,4 to 300        | <u>Table 4</u> |  |
|                 | 7H              | From 3 to 200          | <u>Table 5</u> |  |
|                 | 6G              | From 1,4 to 200        | <u>Table 6</u> |  |

Table 1 (continued)

| Screw thread    | Tolerance class | Nominal diameter<br>mm | Table number   |
|-----------------|-----------------|------------------------|----------------|
|                 | 4h              | From 1 to 100          | <u>Table 7</u> |
|                 | 6h              | From 1 to 100          | <u>Table 8</u> |
| External thread | 6g              | From 1 to 300          | <u>Table 9</u> |
|                 | 6f              | From 1,6 to 200        | Table 10       |
|                 | 6e              | From 3 to 200          | Table 11       |

#### 4.2 Internal threads

Limits of sizes for the internal threads with tolerance class 4H shall be as specified in <u>Table 2</u>.

Table 2 — Limits of sizes for the internal threads with tolerance class 4H

Dimensions in millimetres

| Nominal diam-<br>eter | Pitch               | Major diam-<br>eter | Pitch diameter            |                      | Minor diameter        |              |
|-----------------------|---------------------|---------------------|---------------------------|----------------------|-----------------------|--------------|
| D                     | P                   | $D_{\min}^{a}$      | $D_{2,\max}$              | $D_{2,\min}$         | $D_{1,\max}$          | $D_{1,\min}$ |
| 1                     | 0,2                 | 1,000               | 0,910                     | 0,870                | 0,821                 | 0,783        |
| 1                     | 0,25                | 1,000               | 0,883                     | 0,838                | 0,774                 | 0,729        |
| 1,1                   | 0,2                 | 1,100               | 1,010                     | 0,970                | 0,921                 | 0,883        |
| 1,1                   | 0,25                | 1,100               | 0,983                     | 0,938                | 0,874                 | 0,829        |
| 1,2                   | 0,2                 | 1,200               | 1,110                     | 1,070                | 1,021                 | 0,983        |
| 1,2                   | 0,25                | 1,200               | 1,083                     | 1,038                | 0,974                 | 0,929        |
| 1,4                   | 0,2                 | 1,400               | 1,310                     | 1,270                | 1,221                 | 1,183        |
| 1,4                   | 0,3                 | 1,400               | 1,253                     | 1,205                | 1,128                 | 1,075        |
| 1,6                   | 0,2                 | 1,600               | 1,512                     | 1,470                | 1,421                 | 1,383        |
| 1,6                   | 0,35                | 1,600 IS            | )/F[1,426 <sub>65</sub> - | 1,373                | 1,284                 | 1,221        |
| /stanc1,8ds.iteh      | ai/c <b>0,2</b> 10g | stan 1,800/iso/     | b7 <b>1,712</b> -24       | 6d- <b>1,67</b> 097b | 7-fc <b>1,621</b> e4f | 7b/1,583dis  |
| 1,8                   | 0,35                | 1,800               | 1,626                     | 1,573                | 1,484                 | 1,421        |
| 2                     | 0,25                | 2,000               | 1,886                     | 1,838                | 1,774                 | 1,729        |
| 2                     | 0,4                 | 2,000               | 1,796                     | 1,740                | 1,638                 | 1,567        |
| 2,2                   | 0,25                | 2,200               | 2,086                     | 2,038                | 1,974                 | 1,929        |
| 2,2                   | 0,45                | 2,200               | 1,968                     | 1,908                | 1,793                 | 1,713        |
| 2,5                   | 0,35                | 2,500               | 2,326                     | 2,273                | 2,184                 | 2,121        |
| 2,5                   | 0,45                | 2,500               | 2,268                     | 2,208                | 2,093                 | 2,013        |
| 3                     | 0,35                | 3,000               | 2,829                     | 2,773                | 2,684                 | 2,621        |
| 3                     | 0,5                 | 3,000               | 2,738                     | 2,675                | 2,549                 | 2,459        |
| 3,5                   | 0,35                | 3,500               | 3,329                     | 3,273                | 3,184                 | 3,121        |
| 3,5                   | 0,6                 | 3,500               | 3,181                     | 3,110                | 2,950                 | 2,850        |
| 4                     | 0,5                 | 4,000               | 3,738                     | 3,675                | 3,549                 | 3,459        |
| 4                     | 0,7                 | 4,000               | 3,620                     | 3,545                | 3,354                 | 3,242        |
| 4,5                   | 0,5                 | 4,500               | 4,238                     | 4,175                | 4,049                 | 3,959        |
| 4,5                   | 0,75                | 4,500               | 4,088                     | 4,013                | 3,806                 | 3,688        |
| 5                     | 0,5                 | 5,000               | 4,738                     | 4,675                | 4,549                 | 4,459        |
| 5                     | 0,8                 | 5,000               | 4,560                     | 4,480                | 4,259                 | 4,134        |

nttp