ISO/FDIS 1018:2023(E)

ISO/TC 27/SC 5/WG 1

Secretariat: SA

Date: 2023-07-0308-08

Coal — Determination of moisture-holding capacity

Charbon — Détermination de la capacité de rétention d'humidité

FDIS stage

Warning for WDs and CDs 405a-b6a7-29ef301d8c92/iso-

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

© ISO 20XX

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 1018

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: + 41 22 749 01 11 <u>EmailE-mail</u>: copyright@iso.org Website: <u>www.iso.org</u>www.iso.org

Published in Switzerland

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 1018

ISO/FDIS 1018:2023(E)

Contents

Forewordv		
Introductionv		vi
1	1	.1
2	Normative references	.1
3	Terms and definitions	.1
4	Sampling	.1
5	Principle	.1
Bibliog	graphy	.2

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 1018

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

fdis-1018

This document was prepared by Technical Committee ISO/TC 27, *Solid mineral fuelsCoal and coke*, Subcommittee SC 5, *Methods of analysis*.

This third edition cancels and replaces the second edition (ISO 1018:2019), of which it constitutes a minor revision. In this edition scope and title were widened to coal as in the referenced ASTM D1412, Standard Test Method for Equilibrium Moisture of Coal at 96 to 97 Percent Relative Humidity and 30°C. The changes are as follows:

<u>— the scope and title were widened to coal as in the referenced ASTM D1412.</u>

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

Introduction

The moisture-holding capacity indicates the rank of coals and is used in coal classification for correcting the calorific value of the sample to the moist mineral matter-free basis. The full moisture-holding capacity is that of the coal in equilibrium with an atmosphere saturated with water vapour. Since there are impossible to overcome experimental difficulties in working with such an atmosphere, the determination is carried out at 96 % to 97 % relative humidity.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/FDIS 1018

Coal — Determination of moisture-holding capacity

1 Scope

This document <u>givesmakes</u> reference to ASTM D1412 as a method of determining the moisture-holding capacity of coal.

2 Normative references

The following referenced documents are indispensable for referred to in the application text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ASTM D1412, Standard Test Method for Equilibrium Moisture of Coal at 96 to 97 Percent Relative Humidity and 30 $^\circ \! C$

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological terminology databases for use in standardization at the following addresses:

— — ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>

— — IEC Electropedia: available at <u>https://www.electropedia.org/</u>

4 Sampling

<u>ISO/FDIS 1018</u>

Samples should be collected following the specifications given in ISO 13909, ISO 14180 or ISO 18283, as applicable.

5 Principle

The method is specified for wetted and unwetted coal. Coal is wetted by <u>immersingimmersion</u> in water and the subsequent removal of excess water.

The coal is brought to equilibrium over a saturated solution of potassium sulfate at 30 °C. The conditioning of the coal is carried out under reduced pressure. Afterwards, the sample is dried to constant mass at 105 °C.

The moisture-holding capacity is reported as per centpercent mass fraction of the conditioned moist coal.

All the related equipment requirements, sample preparation, test procedure and reporting shall be in accordance with ASTM D 1412.