



FINAL DRAFT International Standard

ISO/FDIS 13909-2

Coal and coke — Mechanical sampling —

Part 2: Sampling of coal from moving streams

ISO/TC 27/SC 4

Secretariat: **SABS**

Voting begins on:
2025-04-09

Voting terminates on:
2025-06-04

Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/FDIS 13909-2

<https://standards.iteh.ai/catalog/standards/iso/e60ab92c-233e-45e0-bfb9-5ce8311a56d0/iso-fdis-13909-2>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/FDIS 13909-2

<https://standards.iteh.ai/catalog/standards/iso/e60ab92c-233e-45e0-bfb9-5ce8311a56d0/iso-fdis-13909-2>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Establishing a sampling scheme	1
4.1 General	1
4.2 Design of the sampling scheme	2
4.2.1 Material to be sampled	2
4.2.2 Division of lots	2
4.2.3 Basis of sampling	2
4.2.4 Precision of sampling	2
4.2.5 Bias of sampling	3
4.3 Precision of results	3
4.3.1 Precision and total variance	3
4.3.2 Primary increment variance	4
4.3.3 Preparation and testing variance	4
4.3.4 Number of sub-lots and number of increments per sub-lot	4
4.4 Minimum mass of sample	7
4.5 Mass of primary increment	8
4.6 Size analysis	9
5 Methods of sampling	10
5.1 General	10
5.2 Time-basis sampling	11
5.2.1 Method of taking primary increments	11
5.2.2 Sampling interval	11
5.2.3 Mass of increment	11
5.3 Mass-basis sampling	11
5.3.1 Method of taking primary increments	11
5.3.2 Sampling interval	12
5.3.3 Mass of increment	12
5.4 Stratified random sampling	12
5.4.1 General	12
5.4.2 Time-basis stratified random sampling	13
5.4.3 Mass-basis stratified random sampling	13
5.5 Reference sampling	13
6 Design of mechanical samplers	13
6.1 Safety	13
6.2 Information	13
6.3 Basic requirements	13
6.4 Location of sampling equipment	13
6.5 Provision for checking precision	14
6.6 Provision for testing for bias	14
6.7 General requirements for designing mechanical samplers	14
6.8 Design of falling-stream-type samplers	14
6.8.1 General	14
6.8.2 Cutter velocity	15
6.9 Cross-belt-type primary samplers	17
6.9.1 Operation	17
6.9.2 Design of cross-belt samplers	19
6.10 Maintenance and checking of sampling equipment	21
7 Handling and storage of samples	22
8 Sample preparation	22

9	Bias	23
9.1	Minimization of bias	23
9.2	Checking for precision and bias	24
10	Verification	24
Annex A (normative) Evaluation of sampling equipment for mass-basis sampling		25
Bibliography		30

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/FDIS 13909-2](https://standards.iteh.ai/catalog/standards/iso/e60ab92c-233e-45e0-bfb9-5ce8311a56d0/iso-fdis-13909-2)

<https://standards.iteh.ai/catalog/standards/iso/e60ab92c-233e-45e0-bfb9-5ce8311a56d0/iso-fdis-13909-2>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 27, *Coal and coke*, Subcommittee SC 4, *Sampling*.

This third edition cancels and replaces the second edition (ISO 13909-2:2016), which has been technically revised.

The main changes are as follows:

- the title has been modified by replacing “Hard Coal and Coke” with “Coal and coke” and aligned with the rest of the ISO 13909 series;
- the scope has been revised to specifically refer to coal;
- the calculation of number of sub-lots and increments has been updated;
- the references have been updated.

A list of all parts in the ISO 13909 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Coal and coke — Mechanical sampling —

Part 2: Sampling of coal from moving streams

1 Scope

This document specifies procedures and requirements for the design and establishment of mechanical samplers for the sampling of coal from moving streams and describes the methods of sampling used.

It does not cover mechanical sampling from stationary lots, which is dealt with in ISO 13909-3.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 13909-1, *Coal and coke — Mechanical sampling — Part 1: General introduction*

ISO 13909-4, *Coal and coke — Mechanical sampling — Part 4: Preparation of test samples of coal*

ISO 13909-7, *Coal and coke — Mechanical sampling — Part 7: Methods for determining the precision of sampling, sample preparation and testing*

ISO 13909-8, *Coal and coke — Mechanical sampling — Part 8: Methods of testing for bias*

ISO 21398, *Hard coal and coke — Guidance to the inspection of mechanical sampling systems*

<https://standards.iteh.ai/catalog/standards/iso/c60ab92c-233e-45e0-bfb9-5ce8311a56d0/iso-fdis-13909-2>

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13909-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Establishing a sampling scheme

4.1 General

The general procedure for establishing a sampling scheme is as follows.

- a) Define the quality parameters to be determined and the types of samples required.
- b) Define the lot.
- c) Define or assume the precision required (see 4.3.1).
- d) Determine the method of combining the increments into samples and the method of sample preparation (see ISO 13909-4).

- e) Determine or assume the variability of the coal (see [4.3.2](#)) and the variance of preparation and testing (see [4.3.3](#)). Methods for determining variability and the variance of preparation and testing are given in ISO 13909-7.
- f) Establish the number of sub-lots and the number of increments per sub-lot required to attain the desired precision (see [4.3.4](#)).
- g) Decide whether to use time-basis or mass-basis sampling (see [Clause 5](#)) and define the sampling intervals in minutes for time-basis sampling or in tonnes for mass-basis sampling.
- h) Ascertain the nominal top size of coal for the purpose of determining the minimum mass of sample (see [4.4](#) and [Table 1](#)).

NOTE The nominal top size can initially be ascertained by consulting the consignment details, or by visual estimation, and can be verified, if necessary, by preliminary test work.

- i) Determine the minimum average increment mass (see [4.5](#)).

4.2 Design of the sampling scheme

4.2.1 Material to be sampled

The first stage in the design of the scheme is to identify the coal to be sampled. Samples can be required for technical evaluation, process control, quality control and for commercial reasons by both the producer and the customer. It is essential to ascertain exactly at what stage in the coal-handling process the sample is required and, as far as practicable, to design the scheme accordingly. In some instances, however, it can prove impracticable to obtain samples at the preferred points and, in such cases, a more practicable alternative is required.

4.2.2 Division of lots

A lot may be sampled as a whole or as a series of sub-lots, e.g. coal dispatched or delivered over a period of time, a ship load, a train load, a wagon load or coal produced in a certain period, e.g. a shift.

It can be necessary to divide a lot into a number of sub-lots in order to improve the precision of the results. For lots sampled over long periods, it can be expedient to divide the lot into a series of sub-lots, obtaining a sample for each.

4.2.3 Basis of sampling

Sampling may be carried out on either a time-basis or a mass-basis. In time-basis sampling, the sampling interval is defined in minutes and seconds and the increment mass is proportional to the flow rate at the time of taking the increment. In mass-basis sampling, the sampling interval is defined in tonnes and the mass of increments constituting the sample is uniform. Of these two alternatives, time-basis sampling is easier to implement and verify, because only a fixed speed cutter and a timing device are required. On the other hand, for mass-basis sampling, a conveyor belt weightometer is required as well as a device that is controlled sufficiently to adjust the primary cutter speed increment by increment to achieve uniform increment mass.

4.2.4 Precision of sampling

After the desired sampling precision has been selected, the number of sub-lots and the minimum number of increments per sub-lot collected shall be determined as described in [4.3.4](#), and the average mass of the primary increments shall be determined as described in [4.5](#).

For single lots, the quality variation shall be assumed as the worst case (see [4.3.2](#)). The precision of sampling achieved may be measured using the procedure of replicate sampling (see ISO 13909-7).

At the start of regular sampling of unknown coals, the worst-case quality variation shall be assumed, in accordance with [4.3.2](#). When sampling is in operation, a check may be carried out to confirm that the desired precision has been achieved, using the procedures described in ISO 13909-7.

If any subsequent change in precision is required, the number of sub-lots and of increments shall be changed as determined in 4.3.4 and the precision attained shall be rechecked. The precision shall also be checked if there is any reason to suppose that the variability of the coal being sampled has increased. The number of increments determined in 4.3.4 applies to the precision of the result when the sampling errors are large relative to the testing errors, e.g. for moisture content.

4.2.5 Bias of sampling

It is of particular importance in sampling to ensure, as far as possible, that the parameter to be measured is not altered by the sampling and sample preparation process or by subsequent storage prior to testing. This may require, in some circumstances, a limit on the minimum mass of primary increment (see 4.5).

When collecting samples for moisture determination from lots over an extended period, it may be necessary to limit the standing time of samples by dividing the lot into a number of sub-lots (see 4.3.4).

Sampling systems shall be tested for bias in accordance with the methods given in ISO 13909-8.

4.3 Precision of results

4.3.1 Precision and total variance

In all methods of sampling, sample preparation and analysis, errors are incurred and the experimental results obtained from such methods for any given parameter can deviate from the true value of that parameter. While the absolute deviation of a single result from the "true" value cannot be determined, it is possible to make an estimate of the precision of the experimental results. The precision is the closeness with which the results of a series of measurements made on the same coal agree among themselves, and the deviation of the mean of the results from an accepted reference value, i.e. the bias of the results (see ISO 13909-8).

It is possible to design a sampling scheme by which, in principle, an arbitrary level of precision can be achieved.

The desired overall precision for a lot is normally agreed between the parties concerned. In the absence of such agreement, a value of one tenth of the ash shall be assumed up to 10 % ash, subject to a maximum of 1 % absolute for ash above 10 %.

The theory of the estimation of precision is discussed in ISO 13909-7. The following formula is derived:

$$P_L = 2\sqrt{\frac{V_I + V_{PT}}{n}} \quad m \quad (1)$$

where

P_L is the estimated index of overall precision of sampling, sample preparation and testing for the lot at a 95 % confidence level, expressed as a percentage absolute;

V_I is the primary increment variance;

n is the number of increments taken per sub-lot;

m is the number of sub-lots in the lot;

V_{PT} is the preparation and testing variance.

If the quality of a coal of a type not previously sampled is required, then in order to devise a sampling scheme, assumptions shall be made about the variability (see 4.3.2). The precision actually achieved for a particular lot by the scheme devised can be measured by the procedures given in ISO 13909-7.

4.3.2 Primary increment variance

The primary increment variance, V_I , depends upon the type and nominal top size of coal, the degree of pre-treatment and mixing, the absolute value of the parameter to be determined and the mass of increment taken.

The number of increments required for the general-analysis sample and the moisture sample shall be calculated separately using the relevant values of increment variance and the desired precision. If a common sample is required, the number of increments required for that sample shall be the greater of the numbers calculated for the general-analysis sample and the moisture sample, respectively.

NOTE For many coals, the increment variance for ash is higher than that for moisture and hence, for the same precision, the number of increments required for the general-analysis sample is adequate for the moisture sample and for the common sample.

The value of the primary increment variance, V_I , required for the calculation of the precision using [Formula \(1\)](#) can be obtained by either:

- a) direct determination on the coal to be sampled using one of the methods described in ISO 13909-7, or;
- b) assuming a value determined for a similar coal from a similar coal handling and sampling system.

If neither of these values is available, a value of $V_I = 5$ for the ash of unwashed and blended coals and $V_I = 3$ for the ash of washed coals can be assumed initially and checked, after the sampling has been carried out, using one of the methods described in ISO 13909-7.

4.3.3 Preparation and testing variance

The value of the preparation and testing variance, V_{PT} , required for the calculation of the precision using [Formula \(1\)](#) can be obtained by either:

- a) direct determination on the coal to be sampled using one of the methods described in ISO 13909-7, or;
- b) assuming a value determined for a similar coal from a similar sample preparation scheme.

If neither of these values is available, a value of $V_{PT} = 0,20$ with regard to ash can be assumed initially and checked, after the preparation and testing has been carried out, using one of the methods described in ISO 13909-7.

4.3.4 Number of sub-lots and number of increments per sub-lot

4.3.4.1 General

The number of increments taken from a lot in order to achieve a particular precision is a function of the variability of the quality of the coal in the lot, irrespective of the mass of the lot. The lot may be sampled as a whole, resulting in one sample, or divided into a number of sub-lots resulting in a sample from each. Such division may be necessary in order to achieve the required precision, and the necessary number of sub-lots shall be calculated using the procedure given in [4.3.4.2](#).

Another important reason for dividing the lot is to maintain the integrity of the sample, i.e. to avoid bias after taking the increment, particularly, in order to minimize loss of moisture due to standing. The need to do this division is dependent on factors such as the time taken to collect samples, ambient temperature and humidity conditions, the ease of keeping the sample in sealed containers during collection and the particle size of the coal. It is recommended that, if moisture loss is suspected, a bias test be carried out to compare the quality of a reference sample immediately after extraction with the sample after standing for the normal time. If bias is found, the sample standing time shall be reduced by collecting samples more frequently, i.e. increasing the number of sub-lots.

There may be other practical reasons for dividing the lot such as the following:

- a) for convenience when sampling over a long period;
- b) to keep sample masses manageable.

The designer of a sampling scheme shall cater for the worst case anticipated and will then tend to use a higher value for V_1 than may occur when the system is in operation. On implementing a new sampling scheme, a check on the actual precision being achieved should be carried out using the methods described in ISO 13909-7. This can indicate that some changes are required to achieve the required precision, in which case, the number of sub-lots and increments shall be recalculated using the procedures given in [4.3.4.2](#).

4.3.4.2 Calculation of number of sub-lots and increments

The number of sub-lots and number of increments required per sub-lot are established using the following procedure.

Determine the minimum number of sub-lots required for practical reasons (see [4.3.4.1](#)).

Estimate the number of increments, n , in each sub-lot for a desired precision using [Formula \(2\)](#) [obtained by transposing [Formula \(1\)](#)]:

$$n = \frac{4V_1}{mP_L^2 - 4V_{PT}} \quad (2)$$

A value of infinity or a negative number indicates that the errors of preparation and testing are such that the required precision cannot be achieved with this number of sub-lots. In such cases, or if n is impracticably large, increase the number of sub-lots by one of the following means.

- Choose a number for m corresponding to a convenient sub-lot mass, recalculate n from [Formula \(2\)](#) and repeat this process until n is a practicable number.
- Decide on the maximum practicable number of increments per sub-lot, n_1 , and calculate m from [Formula \(3\)](#).

$$m = \frac{4V_1 + 4n_1V_{PT}}{n_1P_L^2} \quad (3)$$

Adjust m upwards, if necessary, to a convenient number and recalculate n .

Take n as 10 if the final calculated value is less than 10.

NOTE This method of calculating the number of increments required per sub-lot for a certain precision from the primary increment variance and the preparation and testing variance generally give a higher value for the required number than needed. The higher number occurs because the method is based on the assumption that the quality of coal varies in a random manner and has no serial correlation; however, serial correlation is always present to some degree. In addition, because a certain amount of preparation and testing is required when measuring the increment variance, the preparation and testing errors are included more than once.

Example 1

The lot is 20 000 t delivered in 5 000 t train loads and the required precision, P_L , is 0,25 % with regard to ash. The quality variation is known and the following values have been determined:

primary increment variance, $V_1 = 0,5$;

preparation and testing variance, $V_{PT} = 0,05$.

- Initial number of sub-lots

It has been decided that the minimum number of sub-lots shall be four. Therefore, take sub-lots of 5 000 t each (i.e. one sub-lot per train load in this case).

- Number of increments per sub-lot

$$n = \frac{4 \times 0,5}{(4 \times 0,25^2) - (4 \times 0,05)} = 40 \text{ using } \text{Formula (2)}$$