

ISO/PRF 16904-2:~~2023~~(E)

ISO/TC 67/~~SC9~~SC 9

~~Date: 2023-10-20~~

Secretariat: AFNOR

Date: 2023-11-28

Installation and equipment for liquefied natural gas — Design and testing of marine transfer systems ~~—~~ —

Part 2: Design and testing of transfer hoses

~~Anlagen und Ausrüstung für Flüssigerdgas - Auslegung und Prüfung von Schiffsübergabesystemen - Teil 2: Auslegung und Prüfung von Übergabeschläuchen~~

~~Installations et équipements de gaz naturel liquéfié - Conception et essais des systèmes de transfert marins -~~ —

Partie 2: Conception et essais des flexibles de transfert

ISO/PRF 16904-2

<https://standards.iteh.ai/catalog/standards/sist/115a82b2-a1a8-46a7-9772-21e0614df87a/iso-prf-16904-2>

PROOF

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

~~CP 401~~ • Ch. de Blandonnet 8 • ~~CP 401~~

CH-1214 Vernier, Geneva, ~~Switzerland~~

~~Tel. Phone:~~ + 41 22 749 01 11

~~Fax + 41 22 749 09 47~~

~~E-mail:~~ copyright@iso.org

~~Website:~~ www.iso.org

~~Published in Switzerland~~

iTeh Standards (<https://standards.iteh.ai>) Document Preview

[ISO/PRF 16904-2](#)

<https://standards.iteh.ai/catalog/standards/sist/115a82b2-a1a8-46a7-9772-21e0614df87a/iso-prf-16904-2>

Contents

Foreword	vi
1 Scope	1
2 Normative references.....	1
3 Terms, definitions and abbreviations.....	1
3.1 Terms and definitions	1
3.2 Abbreviations	6
4 Applications and qualification categories.....	6
4.1 Applications.....	6
4.2 Qualification categories.....	6
5 Description of typical LNG transfer hose assembly designs and accessories.....	7
5.1 General	7
5.2 Mandatory components	7
5.3 Optional components	8
5.4 Typical construction of LNG transfer hose assemblies	8
5.4.1 Main hose categories	8
5.4.2 Corrugated metal hose assemblies	9
5.4.3 Thermoplastic multi-layer (non-vulcanized) hose assemblies (Composite hose assemblies)..	11
5.4.4 Hose-in-hose with annular space	13
6 Design features of the LNG transfer hoses assemblies.....	13
6.1 General	13
6.2 Transfer hose assembly technology design parameters	14
6.3 Project specific design parameters.....	14
6.3.1 Selection of hose assembly length.....	14
6.3.2 Service life	15
6.3.3 Selection of buoyancy and submersion.....	15
6.3.4 Selection of insulation	15
6.3.5 Selection of external protection	15
6.3.6 Selection of leak detection.....	15
6.4 Component details – End fitting	15
6.4.1 General.....	15
6.4.2 Termination.....	17
6.4.3 Connector	17
6.4.4 Bending stiffener/restrictor (optional)	17
6.5 Hose assembly handling / lifting device.....	17

6.6	Safety systems	17
6.6.1	Leak detection (optional)	17
6.6.2	Fire safety requirements	18
6.6.3	Electrical safety requirements	18
6.7	Connection to the ship	18
6.8	Hydraulic and electric control systems	18
7	Qualification requirements	18
7.1	Foreword	18
7.2	Qualification process	19
7.2.1	General principle	19
7.2.2	Qualification levels specific requirements	19
7.2.3	Certification range definition from a tested hose assembly	20
7.2.4	Certification extension and update	21
7.3	Hose assembly tests	22
7.3.1	General	22
7.3.2	Hose assembly property characterization tests	23
7.3.3	Qualification tests with acceptance criteria	34
8	Quality assurance and control	44
8.1	General	44
8.2	Material selection	44
8.3	Manufacturing	44
8.3.1	Manufacturing basics	44
8.3.2	Traceability	45
8.3.3	Marking	45
8.3.4	Packing and preservation	45
8.4	Factory acceptance tests	46
8.4.1	General	46
8.4.2	Tests to be performed on every hose assembly	46
9	Documentation	46
9.1	Purchasing guidelines	46
9.2	Design, qualification and manufacturing documentation	46
9.3	As-built documentation/manufacturing Data Book	46
9.4	Operation manual	47
	Annex A (informative) Purchasing guidelines table	49
	Annex B (informative) Guidelines for additional testing program	51

Annex C (informative) Guidelines for Hose Qualification Categories (HQCs) selection 1
Annex D (informative) Surge pressure considerations for LNG hose assemblies..... 4
Annex E (informative) Pressure leak tests - justification about maximum allowed permeability rate and
leak detection value.....5
Bibliography 7

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO/PRF 16904-2](https://standards.iteh.ai/catalog/standards/sist/115a82b2-a1a8-46a7-9772-21e0614df87a/iso-prf-16904-2)

<https://standards.iteh.ai/catalog/standards/sist/115a82b2-a1a8-46a7-9772-21e0614df87a/iso-prf-16904-2>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by the European Committee for Standardization (CEN) (as EN 1474-2:2020+AC:2023) and drafted in accordance with its editorial rules. It was assigned to Technical Committee ISO/TC 67, *Oil and gas industries including lower carbon energy*, Subcommittee SC 9, *Production, transport and storage facilities for cryogenic liquefied gases* and adopted without modification.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Installation and equipment for liquefied natural gas — Design and testing of marine transfer systems — ~~—~~ ==

Part 2: Design and testing of transfer hoses

1 Scope

This document gives general guidelines for the design, material selection, qualification, certification, and testing details of hose assemblies for Liquefied Natural Gas (LNG) marine transfer applications.

The transfer hose assemblies are part of transfer systems (it means that they may be fitted with ERS, QCDC, handling systems, hydraulic and electric components etc.) To avoid unnecessary repetition, cross-references to EN ISO 16904 and EN 1474-3 are made for all compatible items, and for references, definitions and abbreviations. Where additional references, definitions and abbreviations are required specifically for LNG hose assemblies, they are listed in this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1474-1:2008, *Installation and equipment for liquefied natural gas — Design and testing of marine transfer systems — Part 1: Design and testing of transfer arms*

EN 1474-3:2008, *Installation and equipment for liquefied natural gas - Design and testing of marine transfer systems - Part 3: Offshore transfer systems*

EN ISO 7369:2004, *Pipework - Metal hoses and hose assemblies - Vocabulary (ISO 7369:2004)*

EN ISO 8330:2014, *Rubber and plastics hoses and hose assemblies - Vocabulary (ISO 8330:2014)*

EN ISO 10012:2003, *Measurement management systems - Requirements for measurement processes and measuring equipment (ISO 10012:2003)*

EN ISO 10619-1:2018, *Rubber and plastics hoses and tubing - Measurement of flexibility and stiffness - Part 1: Bending tests at ambient temperature (ISO 10619-1:2017)*

EN ISO 16904:2016, *Petroleum and natural gas industries - Design and testing of LNG marine transfer arms for conventional onshore terminals (ISO 16904:2016)*

3 Terms, definitions and abbreviations

3.1 Terms and ~~Definitions~~definitions

For the purposes of this document, the terms and definitions given in EN ISO 7369:2004 and EN ISO 8330:2014 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- — IEC Electropedia: available at <https://www.electropedia.org/>
- — ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1.1

annular space

space between the inner fluid carrying layer and a second layer which can be used for insulation and/or safety purposes

3.1.2

armour layer

either a braid made of wires (see braid) or strips of metal or plastic used to provide pressure strength and/or external protection

3.1.3

axial stiffness

extent to which a hose assembly resists tensile deformation in response to an applied axial force

3.1.4

bend stiffness

ability of a flexible pipe to resist deflection when subjected to bending loads at constant tension, pressure and temperature

3.1.5

bend restrictor

device for limiting the bend radius by mechanical means

NOTE Note 1 to entry: A bend restrictor typically comprises a series of interlocking metallic or moulded rings, applied over the outer surface.

3.1.6

bending stiffener

ancillary conical shaped component, which locally supports the pipe to limit bending stresses and curvature of the pipe to acceptance levels

Note 1 to entry: Bend stiffeners may be either attached to an end fitting or a support structure where the flexible pipe passes through the bend stiffener.

3.1.7

boil-off gas

BOG

natural evaporation from liquefied natural gas due to vaporization

3.1.8

burst test

test conducted on a hose sample until it failed by internal pressurization

3.1.9

buoyancy

degree, to which the hose assembly has buoyancy capabilities calculated according to [7.3.2.6](#)

3.1.10**connector**

part of the end fitting used to provide a leak-tight structural connection between the end fitting and adjacent piping

3.1.11**crush test**

application of a vertical load through a beam placed laterally across the hose assembly

3.1.12**double-envelope**

layer or set of layers effecting the enclosure, and thus the isolation from the environment, of those structures, systems and components whose failure can lead to an unacceptable release of LNG

3.1.13**dynamic load**

loads to flexible hose assembly or hose assembly configuration which vary in time, or whose deflections or boundary conditions vary in time, while hose is connected

3.1.14**emergency release system****ERS**

system that provides a positive means of quick release of transfer system and safe isolation of LNG carrier and transfer system

Note 1 to entry: The ERS consists of an emergency release coupling (ERC) and interlocked isolating valves which automatically close on both sides, thereby containing the LNG or vapour in the lines (dry disconnect), and, if applicable, associated control system.

3.1.15**end termination**

mechanical device which forms the transition between the flexible pipe body and the connector whose different pipe layers are terminated in the end fitting in such a way as to transfer the load between the flexible hose assembly and the connector

3.1.16**end fitting**

assembly of connector and end termination

3.1.17**emergency release coupler****ERC**

device to provide a means of quick release of the transfer system when such actions is required only as an emergency measure

3.1.18**fatigue life**

number of cycles of a specified character that a given specimen sustains before failure of a specified nature occurs

3.1.19

hose assembly

hose and its fittings

3.1.20

impact test

test for determining the impact strength of a material

3.1.21

leak detection system

system able to detect a failure / leak from the fluid carrying part of the hose assembly

3.1.22

liquefied natural gas

LNG

natural gas that has been cooled and condensed into liquid form

3.1.23

maximum allowable impact energy

MAIE

maximum impact energy which can be applied to the hose assembly without bringing permanent damage to the hose assembly structure and performances

3.1.24

maximum allowable crush load

MACL

maximum allowable crush load which can be applied to the hose assembly without bringing permanent damage to the hose assembly structure and performances

3.1.25

maximum allowable working pressure

MAWP

maximum pressure (gauge) across the entire specified temperature range to which the hose may be exposed and operated

Note 1 to entry: It is commonly used by terminals to define their cargo system pressure capabilities (i.e. pump shut-in plus any static head or cargo system safety valve relief setting).

Note 2 to entry: This pressure rating is not expected to account for dynamic surge pressures, but does include nominal pressure variations during cargo transfer operations).

3.1.26

maximum working load

MWL

maximum allowable tensile force of the hose assembly in axial direction, applied to the end-fittings

3.1.27

minimum Bend Radius

MBR

minimum radius at which the hose assembly is designed to operate

3.1.28
non-destructive test

ND

test that is not expected to cause permanent damage to the hose assembly, so that the hose assembly can be used in subsequent tests and for operation as well

3.1.29
owner

business entity who has the legal or rightful title to the asset intended for LNG transfer

3.1.30
proof pressure

pressure to which the hose assembly is tested (i.e. during a Factory Acceptance Test) to demonstrate its structural integrity when subject to internal pressure

Note 1 to entry: According to the IMO IGC Code this pressure test at ambient temperature shall be not less than 1,5 x MAWP and not more than two-fifths of its burst pressure.

3.1.31
pumping port

connection to attach a vacuum pump for vacuum insulated hose assemblies

3.1.32
quick connect disconnect coupler
QCDC

manual or hydraulic mechanical device used to connect a transfer arm or hose to the cargo manifold without employing bolts

3.1.33
service life

period of time during which the hose assembly fulfils all performance requirements for the specified or less severe condition in the same Hose Qualification Category

3.1.34
static load

flexible hose assemblies not exposed to significant cyclically varying loads or deflections during normal operations

3.1.35
storage bend radius

minimum radius at which the hose assembly is designed to be stored or handled. SBR may be lower than MBR

3.1.36
super-insulation

several high reflecting foils to reduce heat transfer via radiation as part of a vacuum insulation system

3.1.37
type approval certificate

certificate issued by an IVA confirming the suitability and appropriate limits on the manufacturer's design methodologies, manufacturing processes and materials

Note 1 to entry: The name of this certificate can differ according to the IVA.

3.1.38

visual inspection

examination of parts and equipment for visible defects in material and workmanship

3.2 Abbreviations

D	internal bore diameter of the hose assembly
FAT	factory acceptance test
FSRU	floating Storage Regasification Unit
HQC	hose qualification category
IVA	Independent verification agency
L	Length of flexible part of the hose assembly
LNGC	liquefied natural gas carrier
MAAT	Maximum allowable applied twist

4 Applications and qualification categories

4.1 Applications

This subclause describes the main application using LNG transfer hose assemblies.

As industry and technology is developing, other type of application may consider using LNG transfer hose assemblies and shall be covered in this standard.

List of applications (not exhaustive):

- Offshore tandem FLNG offloading / loading aerial or floating;
- Ship-To-Ship transfer such as LNGC to FSRU, LNG Bunkering;
- Shore-To-Ship such as LNG bunkering;
- Ship-To-Shore such as offloading / loading.

Based on the application and use of the hose assembly, there are different categories of hose assembly qualification required. Main difference are the dynamic loads on the hose assembly. The following subclause introduces Hose assembly Qualification Categories (HQC).

NOTE Guidelines for the owners regarding applications and relevant HQC are available in [Annex C](#). Selection of HQC remains the owner's responsibility.

4.2 Qualification categories

This subclause establishes criteria for definition of Hose Qualification Categories for the hose assemblies covered by this standard. The Hose Qualification Categories specified below define different design verification requirements as per [subclause 7.2.2](#).

The test scope within all Qualification Categories define the basis for the hose assemblies qualification but are independent of each project specific data (metocean data, waves & current data,). During the design for a project the required HQC should be checked by the owner and / or IVA.

The owner / IVA can require executing additional tests in order to determine if the proposed hose assembly is “Fit for Purpose” (For fatigue test for example, specific attention should be paid on bending loads adjacent to end terminations)

— ~~—~~ Hose Qualification Category A

This HQC is intended to be used for quasi-static applications (i.e. application only driven by handling and/or thermal and pressure fatigue).

This category is including the performance requirements applicable to all aerial transfer hose assembly, typically transfer hose assemblies used in protected environment for intermittent usage without contact with water and with negligible dynamic motions.

— ~~—~~ Hose Qualification Category B

This HQC is intended to be used for dynamic applications driven by aerial transfer fatigue including significant tensile and bending fatigue loads (e.g. by vessel motions or wind loads).

This Category is including the performance requirements applicable to all aerial transfer hose assemblies and typically applicable for the hose assemblies used in combination of weather exposed environment and/or permanent usage and used in configurations with contact with floating structures.

— ~~—~~ Hose Qualification Category C

This HQC is intended to be used for dynamic applications for submerged or floating hose assemblies.

Qualification tests for this category includes representative tests of contact with water such as insulation, water tightness properties and permanent connection potential issues.

The hose assemblies manufacturer shall propose a fatigue assessment methodology, to be applied at project phase, verifying that the hose assembly is fit for purpose for the intended application.

The methodology shall be validated by an IVA.

5 Description of typical LNG transfer hose assembly designs and accessories

5.1 General

This standard is addressing hose assemblies as a flange-to-flange component.

It means that all statements and requirements based on the hose assemblies shall be considered between conveyed fluid tightening surfaces at both ends.

5.2 Mandatory components

An LNG Transfer Hose assembly shall consist of the following:

- ~~—~~ flexible part of the hose assembly
- ~~—~~ associated end fittings

Hose extremity end fittings can permit the mounting of a QCDC or a spool piece or permit direct connection to LNGC or LNG terminal or another hose assembly.

NOTE A description of QCDC is given in EN ISO 16904:2016, for transfer system reference is made to EN 1474-3:2008.

Hose extremity end fittings can permit the mounting of an emergency release system with valves and ERC (Emergency Release Coupler).

(A description of emergency release system is given in EN ISO 16904:2016 and EN 1474-3:2008).

- permanent identification marks
- hose handling device(s) (pad eye or lifting lugs, lifting collar, ...).

Hose assembly shall include necessary fittings for safe handling, coupling and uncoupling either from the LNGC or the onshore or offshore LNG terminal system as required by the system design according to EN 1474-3:2008.

5.3 Optional components

An LNG Transfer Hose assembly can consist of the following:

- leak detection system

If required by the owner, the hose assembly shall incorporate leak detection system e.

- insulation system (to minimize build-up of external ice)
- intermediate leak barrier(s)
- bending stiffeners or restrictors
- buoyancy
- weight elements
- specific supporting equipment

Hose assembly can support (e.g. piggy back mounted) hydraulic or pneumatic hoses, electric cables for the powering of the ERS and QCDC systems according to EN ISO 16904:2016, Clause 6.

5.4 Typical construction of LNG transfer hose assemblies

5.4.1 Main hose categories

At present LNG transfer hose assemblies are categorized in three types according to their method of construction:

- those based on a reinforced corrugated metal hose construction, hereafter called corrugated metal hose;
- those based on a construction in which polymeric films and fabrics are entrapped between a pair of close wound helical wires, hereafter called composite hose;
- those based on a hose-in-hose construction with annular space and which can derive from one of the above technologies.