

# INTERNATIONAL STANDARD

**ISO**  
**3408-2**

First edition  
1991-06-01

---

---

## Ball screws —

### Part 2:

Nominal diameters and nominal leads — Metric series

**iTeh STANDARD PREVIEW**

*(Vis à billes —*  
**standards.iteh.ai)**

*Partie 2: Diamètres et pas hélicoïdaux, nominaux — Série métrique*

ISO 3408-2:1991

<https://standards.iteh.ai/catalog/standards/sist/1a4f2684-59ea-46cf-8aa0-411262cc666b/iso-3408-2-1991>



Reference number  
ISO 3408-2 : 1991 (E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 3408-2 was prepared by Technical Committee ISO/TC 39, *Machine tools*.

This first edition of ISO 3408-2 cancels and replaces ISO 3408 : 1975 to which the nominal leads 1 mm, 25 mm, 32 mm and 40 mm have been added and from which the inch series of nominal diameters and basic leads has been deleted.

ISO 3408 will consist of the following parts, under the general title *Ball screws*:

- *Part 1: Vocabulary and designation*
- *Part 2: Nominal diameters and nominal leads — Metric series*
- *Part 3: Acceptance conditions and acceptance tests*
- *Part 4: Ball screw axial rigidity*
- *Part 5: Distribution of static and dynamic loads and operational life*

© ISO 1991

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

# Ball screws —

## Part 2 : Nominal diameters and nominal leads — Metric series

### iTeh STANDARD PREVIEW (standards.iteh.ai)

#### 1 Scope

This part of ISO 3408 specifies the nominal diameters and nominal leads, metric series, for ball screws. It also gives preferred combinations of nominal diameter and nominal lead and a general plan which includes additional combinations to be used when it becomes necessary to deviate from the preferred combinations.

#### 2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this part of ISO 3408. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this part of ISO 3408 are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 3408-1 : 1991, *Ball screws — Part 1: Vocabulary and designation*.

#### 3 Definitions

For the purposes of this part of ISO 3408, the definitions given in ISO 3408-1 apply.

#### 4 Nominal diameters

The following series of nominal diameters, in millimetres, shall be used :

6 — 8 — 10 — 12 — 16 — 20 — 25 — 32 — 40 — 50 —  
63 — 80 — 100 — 125 — 160 and 200.

#### 5 Nominal leads

The following series of nominal leads, in millimetres, shall be used :

1 — 2 — 2,5 — 3 — 4 — 5 — 6 — 8 — 10 — 12 — 16 —  
20 — 25 — 32 and 40.

Where possible, preference shall be given to the following nominal leads, in millimetres :

2,5 — 5 — 10 — 20 and 40.

#### 6 Combinations of nominal diameters and nominal leads

##### 6.1 Preferred combinations

See table 1.

##### 6.2 General plan

See table 2.

For preferred combinations, use the nominal lead values which are underlined. When it becomes necessary to deviate from the preferred combinations, use the nominal lead values which are not underlined.

Table 1

Dimensions in millimetres

Nominal diameter	Nominal lead				
	6	2,5			
8	2,5				
10	2,5	5			
12	2,5	5	10		
16	2,5	5	10		
20		5	10	20	
25		5	10	20	
32		5	10	20	
40		5	10	20	40
50		5	10	20	40
63		5	10	20	40
80			10	20	40
100			10	20	40
125			10	20	40
160				20	40
200				20	40

iTeh STANDARD PREVIEW

Table 2

Dimensions in millimetres

Nominal diameter	Nominal lead														
	6	1	2	2,5											
8	1	2	2,5	3											
10	1	2	2,5	3	4	5	6	8	10	12					
12		2	2,5	3	4	5	6	8	10	12	16				
16		2	2,5	3	4	5	6	8	10	12	16	20			
20				3	4	5	6	8	10	12	16	20			
25					4	5	6	8	10	12	16	20	25		
32					4	5	6	8	10	12	16	20	25	32	
40						5	6	8	10	12	16	20	25	32	40
50						5	6	8	10	12	16	20	25	32	40
63						5	6	8	10	12	16	20	25	32	40
80							6	8	10	12	16	20	25	32	40
100									10	12	16	20	25	32	40
125									10	12	16	20	25	32	40
160										12	16	20	25	32	40
200										12	16	20	25	32	40

UDC 62-234

Descriptors: fasteners, screws, ball screws, dimensions.

Price based on 2 pages