

INTERNATIONAL STANDARD



3413

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Information processing — Recorded magnetic tapes for interchange instrumentation applications — Standard tape speeds and track configurations

Traitement de l'information — Bandes magnétiques enregistrées pour l'enregistrement de mesures — Normalisation des vitesses de bande et des dispositions des pistes

First edition — 1975-11-01

(standards.iteh.ai)

[ISO 3413:1975](https://standards.iteh.ai/catalog/standards/sist/ed663bb8-2092-4ed4-9627-f50e7a1396da/iso-3413-1975)

<https://standards.iteh.ai/catalog/standards/sist/ed663bb8-2092-4ed4-9627-f50e7a1396da/iso-3413-1975>

UDC 681.327.64

Ref. No. ISO 3413-1975 (E)

Descriptors : data processing, magnetic tapes, instrumentation recording, specifications, tape speed, recording tracks, layout.

Price based on 10 pages

FOREWORD

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO Member Bodies). The work of developing International Standards is carried out through ISO Technical Committees. Every Member Body interested in a subject for which a Technical Committee has been set up has the right to be represented on that Committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the Technical Committees are circulated to the Member Bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 3413 was drawn up by Technical Committee ISO/TC 97, *Computers and information processing*, and circulated to the Member Bodies in August 1974.

(standards.iteh.ai)

It has been approved by the Member Bodies of the following countries :

ISO 3413:1975

Australia	Germany	Spain
Belgium	Hungary	Switzerland
Bulgaria	Japan	Turkey
Canada	New Zealand	United Kingdom
Czechoslovakia	Portugal	U.S.A.
France	Romania	U.S.S.R.

No Member Body expressed disapproval of the document.

© International Organization for Standardization, 1975 ●

Printed in Switzerland

ISO/TC 97/SC 12 is concerned with the preparation of International Standards in the field of magnetic tape for instrumentation applications. The programme of work envisages an inter-related series of International Standards concerning I) Reels, II) Unrecorded magnetic tape, III) Recorded magnetic tape and IV) Recording methods. This International Standard forms part of that series and should be read accordingly.

STANDARDS PUBLISHED AND IN PREPARATION

ISO/R 1858, *General purpose hubs and reels with 76 mm (3 in) centrehole, for magnetic tape used in interchange instrumentation applications.*

ISO 1859, *Information processing – Unrecorded magnetic tapes for interchange instrumentation applications – General dimensional requirements.*

ISO 1860, *Information processing – Precision reels for magnetic tape for interchange instrumentation applications.*

ISO 2690, *Unrecorded magnetic tapes for instrumentation applications – Physical properties and test methods.*

ISO 3105, *Magnetic tape for instrumentation applications – Standardization of analogue modes of recording.¹⁾*

ISO . . . , *Interchange practices and test methods for unrecorded instrumentation magnetic tape.*

ISO . . . , *Interchange practices and test methods for recorded magnetic tape.*

3615

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 3413:1975
<https://standards.iteh.ai>

1) At present at the stage of draft.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 3413:1975

<https://standards.iteh.ai/catalog/standards/sist/ed663bb8-2092-4ed4-9627-f50e7a1396da/iso-3413-1975>

Information processing – Recorded magnetic tapes for interchange instrumentation applications – Standard tape speeds and track configurations

iTeh STANDARD PREVIEW (standards.iteh.ai)

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies standard tape speeds and track configurations to allow maximum interchange of instrumentation magnetic tape records.

NOTE – See annex for definition of terms and symbols.

2 TAPE SPEEDS

The standard tape speeds for instrumentation magnetic tape recorders shall be 2,38 cm/s (15/16 in/s); 4,76 cm/s (1 7/8 in/s); 9,52 cm/s (3 3/4 in/s); 19,05 cm/s (7 1/2 in/s); 38,1 cm/s (15 in/s); 76,2 cm/s (30 in/s); 152,4 cm/s (60 in/s); and 304,8 cm/s (120 in/s).

3 TAPE WIDTHS

Standard tape widths are specified in the table below, which is an excerpt from ISO 1859.

Standard widths	
mm	in
6,3 ⁰ – 0,06	0,248 ⁰ – 0,0025
12,70 ⁰ – 0,10	0,500 ⁰ – 0,004
25,40 ⁰ – 0,10	1,000 ⁰ – 0,004
50,80 ⁰ – 0,10	2,000 ⁰ – 0,004

4 TRACK GEOMETRY : DIMENSIONS – RECORDED TAPE FORMAT (see figure 1)

4.1 4 Tracks in line on 6,3 mm (1/4 in) wide tape

Track width (W)

0,64 ± 0,05 mm (0.025 ± 0.002 in)

Track spacing (D)

1,78 mm (0.070 in)

Track location (reference edge to track 1 centreline) (G)

0,43 ± 0,05 mm (0.017 ± 0.002 in)

Track spacing tolerance (ΔH_n)

± 0,05 mm (± 0.002 in)

Track number (H_n)

	mm	in
H_1	0	0
H_2	1,78	0.070
H_3	3,56	0.140
H_4	5,34	0.210

NOTE – The simultaneous applications of the tolerances quoted shall not result in the centreline of track 4 being closer to the edge of the tape than 0,35 mm (0.014 in).

ISO 3413-1975 (E)

4.2 7 Tracks interlaced on 6,3 mm (1/4 in) wide tape

Track width (W)

0,64 ± 0,03 mm (0.025 ± 0.001 in)

Track spacing (D)

0,89 mm (0.035 in)

Data spacing (S)

38,10 ± 0,03 mm (1.5 ± 0.001 in) for fixed heads

38,10 ± 0,05 mm (1.5 ± 0.002 in) for adjustable heads

Edge margin, minimum (M_m)

0,025 mm (0.001 in)

Track location (reference edge to track 1 centreline) (G)

0,43 ± 0,04 mm (0.017 ± 0.001 5 in)

Track spacing tolerance (ΔH_n)

± 0,04 mm (± 0.001 5 in)

Track number (H_n)

	mm	in
H_1	0	0
H_2	0,89	0.035
H_3	1,78	0.070
H_4	2,67	0.105
H_5	3,56	0.140
H_6	4,45	0.175
H_7	5,34	0.210

4.3 7 Tracks interlaced on 12,7 mm (1/2 in) wide tape

Track width (W)

1,27 ± 0,13 mm (0.050 ± 0.005 in)

Track spacing (D)

1,78 mm (0.070 in)

Data spacing (S)

38,10 ± 0,03 mm (1.500 ± 0.001 in) for fixed heads

38,10 ± 0,05 mm (1.500 ± 0.002 in) for adjustable heads

Edge margin, minimum (M_m)

0,14 mm (0.006 in)

Track location (reference edge to track 1 centreline) (G)

1,02 ± 0,05 mm (0.040 ± 0.002 in)

Track spacing tolerance (ΔH_n)

± 0,05 mm (± 0.002 in)

Track number (H_n)

	mm	in
H_1	0	0
H_2	1,78	0.070
H_3	3,56	0.140
H_4	5,34	0.210
H_5	7,12	0.280
H_6	8,90	0.350
H_7	10,68	0.420

NOTE — Track numbers 1, 3, 5 and 7 occupy the same nominal positions as the four tracks defined in 4.1.

4.4 14 Tracks interlaced on 12,7 mm (1/2 in) wide tape

- Track width (*W*)
0,64 ± 0,03 mm (0.025 ± 0.001 in)
- Track spacing (*D*)
0,89 mm (0.035 in)
- Data spacing (*S*)
38,10 ± 0,03 mm (1.500 ± 0.001 in) for fixed heads
38,10 ± 0,05 mm (1.500 ± 0.002 in) for adjustable heads
- Edge margin, minimum (*M_m*)
0,13 mm (0.005 in)
- Track location (reference edge to track 1 centreline) (*G*)
0,50 ± 0,04 mm (0.020 ± 0.001 5 in)
- Track spacing tolerance (ΔH_n)
± 0,04 mm (± 0,001 5 in)
- Track number (*H_n*)

4.5 21 Tracks interlaced on 12,7 mm (1/2 in) wide tape

- Track width (*W*)
0,46 ± 0,03 mm (0.018 ± 0.001 in)
- Track spacing (*D*)
0,585 mm (0.023 in)
- Data spacing (*S*)
38,10 ± 0,03 mm (1.500 ± 0.001 in) for fixed heads
38,10 ± 0,05 mm (1.500 ± 0.002 in) for adjustable heads
- Edge margin, minimum (*M_m*)
0,17 mm (0.007 in)
- Track location (reference edge to track 1 centre line) (*G*)
0,44 ± 0,04 mm (0.017 ± 0.001 5 in)
- Track spacing tolerance (ΔH_n)
± 0,03 mm (± 0.001 in)
- Track number (*H_n*)

	mm	in		mm	in
<i>H</i> ₁	0	0	<i>H</i> ₁	0	0
<i>H</i> ₂	0,89	0.035	<i>H</i> ₂	0,585	0.023
<i>H</i> ₃	1,78	0.070	<i>H</i> ₃	1,170	0.046
<i>H</i> ₄	2,67	0.105	<i>H</i> ₄	1,755	0.069
<i>H</i> ₅	3,56	0.140	<i>H</i> ₅	2,340	0.092
<i>H</i> ₆	4,45	0.175	<i>H</i> ₆	2,925	0.115
<i>H</i> ₇	5,34	0.210	<i>H</i> ₇	3,510	0.138
<i>H</i> ₈	6,23	0.245	<i>H</i> ₈	4,095	0.161
<i>H</i> ₉	7,12	0.280	<i>H</i> ₉	4,680	0.184
<i>H</i> ₁₀	8,01	0.315	<i>H</i> ₁₀	5,265	0.207
<i>H</i> ₁₁	8,90	0.350	<i>H</i> ₁₁	5,850	0.230
<i>H</i> ₁₂	9,79	0.385	<i>H</i> ₁₂	6,435	0.253
<i>H</i> ₁₃	10,68	0.420	<i>H</i> ₁₃	7,020	0.276
<i>H</i> ₁₄	11,57	0.455	<i>H</i> ₁₄	7,605	0.299
			<i>H</i> ₁₅	8,190	0.322
			<i>H</i> ₁₆	8,775	0.346
			<i>H</i> ₁₇	9,360	0.368
			<i>H</i> ₁₈	9,945	0.391
			<i>H</i> ₁₉	10,530	0.414
			<i>H</i> ₂₀	11,115	0.437
			<i>H</i> ₂₁	11,700	0.460

STANDARD PREVIEW
(standards.iteh.ai)

ISO 3413:1975
<https://standards.iteh.ai/catalog/standards/sist/ed663bb8-2092-4ed4-9627-f01401396da/iso-3413-1975>

ISO 3413-1975 (E)

4.6 14 Tracks interlaced on 25,4 mm (1 in) wide tape

Track width (W)

$1,27 \pm 0,13$ mm (0.050 ± 0.005 in)

Track spacing (D)

1,78 mm (0.070 in)

Data spacing (S)

$38,10 \pm 0,03$ mm (1.500 ± 0.001 in) for fixed heads

$38,10 \pm 0,05$ mm (1.500 ± 0.002 in) for adjustable heads

Edge margin, minimum (M_m)

0,28 mm (0.011 in)

Track location (reference edge to track 1 centreline) (G)

$1,12 \pm 0,05$ mm (0.044 ± 0.002 in)

Track spacing tolerance (ΔH_n)

$\pm 0,05$ mm (± 0.002 in)

Track number (H_n)

4.7 28 Tracks interlaced on 25,4 mm (1 in) wide tape

Track width (W)

$0,64 \pm 0,03$ mm (0.025 ± 0.001 in)

Track spacing (D)

0,89 mm (0.035 in)

Data spacing (S)

$38,10 \pm 0,03$ mm (1.500 ± 0.001 in) for fixed heads

$38,10 \pm 0,05$ mm (1.500 ± 0.002 in) for adjustable heads

Edge margin, minimum (M_m)

0,22 mm (0.009 in)

Track location (reference edge to track 1 centreline) (G)

$0,66 \pm 0,04$ mm (0.026 ± 0.0015 in)

Track spacing tolerance (ΔH_n)

$\pm 0,04$ mm (± 0.0015 in)

Track number (H_n)

	mm	in		mm	in
H_1	0	0	H_1	0	0
H_2	1,78	0.070	H_2	0,89	0.035
H_3	3,56	0.140	H_3	1,78	0.070
H_4	5,34	0.210	H_4	2,67	0.105
H_5	7,12	0.280	H_5	3,56	0.140
H_6	8,90	0.350	H_6	4,45	0.175
H_7	10,68	0.420	H_7	5,34	0.210
H_8	12,46	0.490	H_8	6,23	0.245
H_9	14,24	0.560	H_9	7,12	0.280
H_{10}	16,02	0.630	H_{10}	8,01	0.315
H_{11}	17,80	0.700	H_{11}	8,90	0.350
H_{12}	19,58	0.770	H_{12}	9,79	0.385
H_{13}	21,36	0.840	H_{13}	10,68	0.420
H_{14}	23,14	0.910	H_{14}	11,57	0.455
			H_{15}	12,46	0.490
			H_{16}	13,35	0.525
			H_{17}	14,24	0.560
			H_{18}	15,13	0.595
			H_{19}	16,02	0.630
			H_{20}	16,91	0.665
			H_{21}	17,80	0.700
			H_{22}	18,69	0.735
			H_{23}	19,58	0.770
			H_{24}	20,47	0.805
			H_{25}	21,36	0.840
			H_{26}	22,25	0.875
			H_{27}	23,14	0.910
			H_{28}	24,03	0.945

4.8 42 Tracks interlaced on 25,4 mm (1 in) wide tape

Track number (H_n)

Track width (W)		mm	in
0,46 ± 0,03 mm (0.018 ± 0.001 in)	H_1	0	0
Track spacing (D)	H_2	0,585	0.023
0,585 mm (0.023 in)	H_3	1,170	0.046
Data spacing (S)	H_4	1,755	0.069
38,10 ± 0,03 mm (1.500 ± 0.001 in) for fixed heads	H_5	2,340	0.092
38,10 ± 0,05 mm (1.500 ± 0.002 in) for adjustable heads	H_6	2,925	0.115
Edge margin, minimum (M_m)	H_7	3,510	0.138
0,32 mm (0.012 in)	H_8	4,095	0.161
Track location (reference edge to track 1 centreline) (G)	H_9	4,680	0.184
0,70 ± 0,04 mm (0.027 5 ± 0.001 5 in)	H_{10}	5,265	0.207
Track spacing tolerance (ΔH_n)	H_{11}	5,850	0.230
± 0,03 mm (0.001 in)	H_{12}	6,435	0.253
	H_{13}	7,020	0.276
	H_{14}	7,605	0.299
	H_{15}	8,190	0.322
	H_{16}	8,775	0.345
	H_{17}	9,360	0.368
	H_{18}	9,945	0.391
	H_{19}	10,530	0.414
	H_{20}	11,115	0.437
	H_{21}	11,700	0.460
	H_{22}	12,285	0.483
	H_{23}	12,870	0.506
	H_{24}	13,455	0.529
	H_{25}	14,040	0.552
	H_{26}	14,625	0.575
	H_{27}	15,210	0.598
	H_{28}	15,795	0.621
	H_{29}	16,380	0.644
	H_{30}	16,965	0.667
	H_{31}	17,550	0.690
	H_{32}	18,135	0.713
	H_{33}	18,720	0.736
	H_{34}	19,305	0.759
	H_{35}	19,890	0.782
	H_{36}	20,475	0.805
	H_{37}	21,060	0.828
	H_{38}	21,645	0.851
	H_{39}	22,230	0.874
	H_{40}	22,815	0.897
	H_{41}	23,400	0.920
	H_{42}	23,985	0.943

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 3413:1975

<https://standards.iteh.ai/catalog/standards/sist/ed663bb8-2212-4cd4-9627-f50e7a1396da/iso-3413-1975>