



Designation: **D3748 – 09 D3748 – 14**

Standard Practice for Evaluating High-Density Rigid Cellular Plastics¹

This standard is issued under the fixed designation D3748; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This practice covers the basic test procedures for determination of the physical properties and reporting of data for high-density rigid cellular plastics.

1.2 The values stated in SI units are to be regarded as standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

NOTE 1—This standard and ISO 9054 address the same subject matter, but differ in technical content.

2. Referenced Documents

2.1 *ASTM Standards:*²

[C177 Test Method for Steady-State Heat Flux Measurements and Thermal Transmission Properties by Means of the Guarded-Hot-Plate Apparatus](#)

[C518 Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus](#)

[D149 Test Method for Dielectric Breakdown Voltage and Dielectric Strength of Solid Electrical Insulating Materials at Commercial Power Frequencies](#)

[D570 Test Method for Water Absorption of Plastics](#)

[D618 Practice for Conditioning Plastics for Testing](#)

[D638 Test Method for Tensile Properties of Plastics](#)

[D648 Test Method for Deflection Temperature of Plastics Under Flexural Load in the Edgewise Position](#)

[D695 Test Method for Compressive Properties of Rigid Plastics](#)

[D696 Test Method for Coefficient of Linear Thermal Expansion of Plastics Between \$-30^{\circ}\text{C}\$ and \$30^{\circ}\text{C}\$ with a Vitreous Silica Dilatometer](#)

[D790 Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials](#)

[D883 Terminology Relating to Plastics](#)

[D1622 Test Method for Apparent Density of Rigid Cellular Plastics](#)

3. Terminology

3.1 *Definitions:*

3.1.1 *cellular plastics*—plastics containing numerous small cavities (cells), interconnecting or not, distributed throughout the mass. These cells cannot be mechanically assembled, but are produced through the “in situ” plastics processing methods.

3.1.1.1 *high density*—greater than 320 kg/m^3 (0.32 g/cm^3) or 20 lb/ft^3 apparent density.

3.1.1.3 *skin*—a relatively dense layer at the surface of a cellular polymeric material.

3.1.2 For definitions of other terms used in this practice, refer to Terminology [D883](#).

4. Significance and Use

4.1 This practice provides appropriate testing methods, and a specific data reporting procedure for high-density rigid cellular plastics.

¹ This practice is under the jurisdiction of ASTM Committee [D20](#) on Plastics and is the direct responsibility of Subcommittee [D20.22](#) on Cellular Materials - Plastics and Elastomers.

Current edition approved ~~Feb. 1, 2009~~ March 1, 2014. Published ~~February 2009~~ March 2014. Originally approved in 1978. Last previous edition approved in ~~2003~~ 2009 as ~~D3748 – 03~~ D3748 – 09. DOI: ~~10.1520/D3748-09~~ 10.1520/D3748-14.

² For referenced ASTM standards, visit the ASTM Web Site, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard’s Document Summary page on the ASTM web site.

*A Summary of Changes section appears at the end of this standard