



Designation: B411/B411M – 14

## Standard Specification for Copper-Nickel-Silicon Alloy Rod and Bar<sup>1</sup>

This standard is issued under the fixed designation B411/B411M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the U.S. Department of Defense.*

### 1. Scope\*

1.1 This specification establishes the requirements for copper-nickel-silicon alloy rod and bar produced from Copper Alloy UNS No. C64700 in straight lengths.

1.2 *Units*—The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

### 2. Referenced Documents

2.1 *ASTM Standards*:<sup>2</sup>

**B193** Test Method for Resistivity of Electrical Conductor Materials

**B249/B249M** Specification for General Requirements for Wrought Copper and Copper-Alloy Rod, Bar, Shapes and Forgings

**B601** Classification for Temper Designations for Copper and Copper Alloys—Wrought and Cast

**B846** Terminology for Copper and Copper Alloys

**B950** Guide for Editorial Procedures and Form of Product Specifications for Copper and Copper Alloys

**E8/E8M** Test Methods for Tension Testing of Metallic Materials

**E54** Test Methods for Chemical Analysis of Special Brasses and Bronzes (Withdrawn 2002)<sup>3</sup>

**E478** Test Methods for Chemical Analysis of Copper Alloys

### 3. General Requirements

3.1 The following sections of Specification **B249/B249M** constitute a part of this specification:

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee B05 on Copper and Copper Alloys and is the direct responsibility of Subcommittee B05.02 on Rod, Bar, Wire, Shapes and Forgings.

Current edition approved April 1, 2014. Published May 2014. Originally approved in 1965. Last previous edition approved in 2008 as B411/B411M – 08. DOI: 10.1520/B0411\_B0411M-14.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>3</sup> The last approved version of this historical standard is referenced on [www.astm.org](http://www.astm.org).

- 3.1.1 Terminology,
- 3.1.2 Workmanship, Finish, and Appearance,
- 3.1.3 Sampling,
- 3.1.4 Number of Tests and Retests,
- 3.1.5 Specimen Preparation,
- 3.1.6 Test Methods,
- 3.1.7 Significance of Numerical Limits,
- 3.1.8 Inspection,
- 3.1.9 Rejection and Rehearing,
- 3.1.10 Certification,
- 3.1.11 Mill Test Report,
- 3.1.12 Packaging and Package Marking, and
- 3.1.13 Supplementary Requirements.

3.2 In addition, when a section with a title identical to that referenced in 3.1 appears in this specification, it contains additional requirements which supplement those appearing in Specification **B249/B249M**.

### 4. Terminology

4.1 For the definition of terms related to copper and copper alloys, refer to Terminology **B846**.

### 5. Ordering Information

5.1 Include the following specified choices when placing orders for product under this specification, as applicable:

- 5.1.1 ASTM designation and year of issue (for example, B411/B411M – 06),
- 5.1.2 Copper alloy UNS No. designation,
- 5.1.3 Temper,
- 5.1.4 Product form (cross section such as round, hexagonal, square, and so forth),
- 5.1.5 Dimensions (diameter or distance between parallel surfaces, width, thickness),
- 5.1.6 Edge contours,
- 5.1.7 Length, nominal, and
- 5.1.8 Quantity; total weight, length, or number of pieces for each form and size.

5.2 The following options are available but may not be included unless specified at the time of placing the order, when required:

- 5.2.1 Certification (Specification **B249/B249M**),
- 5.2.2 Mill test report (Specification **B249/B249M**), and

\*A Summary of Changes section appears at the end of this standard