

ISO/~~FDIS~~ 965-5:2024

ISO/TC 1

Secretariat: SAC

Date: 2024-07-11-21

ISO general purpose metric screw threads — Tolerances —

Part 5:
Limits of sizes for internal threads to mate with hot-dip galvanized external threads with maximum size of tolerance position h before galvanizing

Filetages métriques ISO pour usages généraux — Tolérances —

Partie 5: Dimensions limites pour filetages intérieurs pour assemblages avec des filetages extérieurs galvanisés à chaud de position de tolérance maximale h avant galvanisation

ISO/FDIS 965-5

<https://standards.iteh.ai/catalog/standards/iso/63c1b0eb-3a3c-475c-9899-361000000000/iso-965-5-2024>

~~DIS~~FDIS stage

Warning for WD's and CD's

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Edited DIS - MUST BE USED FOR FINAL DRAFT

Style Definition: Heading 1: Indent: Left: 0 cm, First line: 0 cm

Style Definition: Heading 2: Indent: Left: 0 cm, First line: 0 cm

Style Definition: Heading 3: Indent: Left: 0 cm, First line: 0 cm

Style Definition: Heading 4: Indent: Left: 0 cm, First line: 0 cm

Style Definition: Heading 5: Indent: Left: 0 cm, First line: 0 cm

Style Definition: Cover Title_A2: Font: Space Before: 80 pt

Style Definition: Dimension_100: Font: Keep with next

Style Definition: Figure Graphic: Font: Keep with next

Style Definition: List Continue 2: Font: Indent: Left: 0.71 cm, Hanging: 0.71 cm

Style Definition: Table title: Font: Keep with next

Style Definition: p2: Font: 12 pt, Bold, (Asian) Japanese, (Other) Dutch (Netherlands), Level 2, Indent: Left: 0 cm, First line: 0 cm, Space Before: 3 pt, Line spacing: Exactly 12.5 pt, Outline numbered + Level: 2 + Numbering Style: 1, 2, 3, ... + Start at: 1 + Alignment: Left + Aligned at: 0 cm + Indent at: 1.02 cm, Don't hyphenate, Tab stops: 1.23 cm, Left

Style Definition ...

Style Definition ...

Style Definition ...

Style Definition ...

Style Definition: Body Text: Font: Space After: 12 pt

Style Definition ...

Style Definition ...

Style Definition ...

Style Definition ...

Style Definition: a2

Style Definition: a3

Style Definition: a4

Style Definition: a5

Style Definition: a6

Style Definition: ANNEX Head

Style Definition: ANNEXZ Head

Formatted: Font: Bold

Formatted ...

Formatted: Font color: Auto

ISO/FDIS 965-5:2024(en)

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: + 41 22 749 01 11
E-mail: copyright@iso.org
Website: www.iso.org

Published in Switzerland

iTeh Standards (<https://standards.iteh.ai>) Document Preview

ISO/FDIS 965-5

<https://standards.iteh.ai/catalog/standards/iso/63c1b0eb-3a3c-475c-9899-363300ce92c4/iso-fdis-965-5>

ISO/FDIS 965-5:2024(en)

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/FDIS 965-5

<https://standards.iteh.ai/catalog/standards/iso/63c1b0eb-3a3c-475c-9899-363300ce92c4/iso-fdis-965-5>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 1, *Screw threads*.

This second edition cancels and replaces the first edition (ISO 965-5:1998), which has been technically revised. It also incorporates the amendment ISO 965-5:1998/Amd.1:2021.

The main changes are as follows:

- in [Clauses 1](#) and [5](#), including [Table 1](#), “limit deviations” has been replaced by “fundamental deviations”;
- in [Table 1](#), a small pitch 1 has been added for the tolerance position AZ, and two pitches (1,25 and 1,5) have been deleted for the tolerance position AX;
- in [Table 2](#), the large nominal diameters (from 68 mm to 100 mm) and the two small nominal diameters (6 mm and 7 mm) have been added;
- in [Table 3](#), the large nominal diameters (from 68 mm to 100 mm) have been added, and two small nominal diameters (8 mm and 10 mm) have been deleted;
- in [Tables 2](#) and [3](#), the ~~columns of~~ minimum major diameter ~~columns~~ have been deleted, respectively.

A list of all parts in the ISO 965 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Formatted: English (United Kingdom)

Field Code Changed

Formatted: English (United Kingdom)

ISO general purpose metric screw threads — Tolerances —

Part 5:

Limits of sizes for internal threads to mate with hot-dip galvanized external threads with maximum size of tolerance position h before galvanizing

Formatted: Font: Bold

1 Scope

This document specifies the fundamental deviations and limits of sizes for the pitch and minor diameters of ISO general purpose metric internal threads (M) conforming to ISO 262 (M6 to M68 with the coarse pitches and M72 to M100 with pitch 6) having basic and design profiles in accordance with ISO 68-1.

This document is applicable to the metric internal threads oversized to tolerance class 6AZ or 6AX to mate with the hot-dip galvanized external threads with maximum size of tolerance position h before galvanizing.

This document is not applicable to internal threads with coating on thread surface. The limits of sizes before coating are decided by the agreement between manufacturer and purchaser.

Formatted: Body Text, Space After: 0 pt, Line spacing: single

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 965-1, *ISO general purpose metric screw threads — Tolerances — Part 1: Principles and basic data*

ISO 965-4, *ISO general purpose metric screw threads — Tolerances — Part 4: Limits of sizes for hot-dip galvanized external threads to mate with internal threads made to tolerance position H or G after galvanizing*

ISO 5408, *Screw threads — Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5408 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

4 General

There are two tolerance classes for internal threads: 6AZ and 6AX. Tolerance class 6AZ offers a smaller fundamental deviation intended to mate with hot-dip galvanized external threads having a thin coating. Tolerance class 6AX offers a larger fundamental deviation intended to mate with hot-dip galvanized external threads having a heavy coating.

Internal threads oversized to tolerance class 6AZ or 6AX according to this document, shall not be mated with external threads undersized to tolerance class 6az before galvanizing in accordance with ISO 965-4. Such combinations ~~will~~ create high probability for screw thread stripping.

Internal threads according to this document shall be made after the hot-dip galvanizing process has been completed, ~~therefore, Therefore,~~ no coating is present on the surface of internal threads.

The root contours and truncations of screw threads shall be according to ISO 965-1.

5 Fundamental deviations

The fundamental deviations for internal threads shall be as specified in Table_1.

The fundamental deviations, $E_{I_{AZ}}$ and $E_{I_{AX}}$, have been calculated according to Formulae (1) and (2), respectively:

$E_{I_{AZ}} = + (300 + 20P)$ (1)

NOTE 1 - This is not applicable to threads with $P < 1$ mm.

$E_{I_{AX}} = + (220P - 20)$ (2)

NOTE 2 - This is not applicable to threads with $P < 1,75$ mm.

where

E_I is the fundamental deviation, expressed in micrometres;

P is the pitch, expressed in millimetres.

Table_1 — Fundamental deviations for internal threads

Pitch P mm	Tolerance position AZ $E_{I_{AZ}}$ µm	Tolerance position AX $E_{I_{AX}}$ µm
1	+320	-
1,25	+325	-
1,5	+330	-
1,75	+335	+365
2	+340	+420
2,5	+350	+530
3	+360	+640
3,5	+370	+750
4	+380	+860
4,5	+390	+970
5	+400	+1_080
5,5	+410	+1_190
6	+420	+1_300

^a Use the tolerance position AZ.