

# INTERNATIONAL STANDARD

ISO  
3461-1

First edition  
1988-06-15



---

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION  
ORGANISATION INTERNATIONALE DE NORMALISATION  
МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

---

## General principles for the creation of graphical symbols —

### Part 1 :

Graphical symbols for use on equipment

*(<https://standards.iteh.ai>)*

*Principes généraux pour la création de symboles graphiques —*

*Partie 1 : Symboles graphiques utilisables sur le matériel*

*ITEH Standards*

*Document Preview*

[ISO 3461-1:1988](#)

<https://standards.iteh.ai/catalog/standards/iso/9a70d56a-1a3d-4364-8147-130804b6917ciso-3461-1-1988>

## Contents

	Page
Foreword .....	iii
1 Scope .....	1
2 References .....	1
3 Definitions .....	1
4 Meaning .....	1
5 Combination of graphical symbols .....	2
6 Shape .....	2
7 Design principles .....	2
8 Design procedure .....	2
9 Basic pattern .....	3
10 Use of graphical symbols .....	5
11 Designation systems .....	6

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

**Document Preview**  
 International Standard ISO 3461-1 was prepared jointly by Technical Committee ISO/TC 145, *Graphical symbols*, and Technical Committee IEC/TC 3, *Documentation and graphical symbols*, and is also published as IEC 416 : 1988.

ISO 3461-1 : 1988 and IEC 416 : 1988 cancel and replace ISO 3461 : 1976 and IEC 416 : 1972 which have been harmonized to produce this part of ISO 3461.

<https://standards.ieh.ai/catalog/standard/iso/9a70456a1a214364-8147-130804b6917/iso-3461-1-1988>  
 ISO 3461 consists of the following parts, under the general title *General principles for the creation of graphical symbols* :

- *Part 1 : Graphical symbols for use on equipment*
- *Part 2 : Graphical symbols for use in technical product documentation*

All standards are subject to revision, and users should note that at the time of publication, the editions of the standards referenced herein were valid. Members of IEC and ISO maintain registers of currently valid International Standards.

This page intentionally left blank

**iTeH Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[ISO 3461-1:1988](#)

<https://standards.iteh.ai/catalog/standards/iso/9a70d56a-1a3d-4364-8147-130804b6917/iso-3461-1-1988>

# General principles for the creation of graphical symbols —

## Part 1 : Graphical symbols for use on equipment

### 1 Scope

This part of ISO 3461 specifies the basis for the creation of graphical symbols for use on equipment. It contains rules for designing symbols, including their shape and size, and instructions for their application.

Graphical symbols for use on equipment may be employed

- to identify the equipment or a part of the equipment (e.g. a control or display);
- to indicate functional states (e.g. on, off, alarm);
- to designate connections (e.g. terminals, filling points);
- to provide information on packaging (e.g. identification of content, instructions for handling);
- to provide instructions for the operation of the equipment (e.g. warnings, limitations of use).

This part of ISO 3461 does not apply to graphical symbols primarily intended for

<https://standards.teh.ai/catalog/standards/iso/9a70d56a-1a-1988-01>

- use on drawings;
- use in technical product documentation;
- public information.

However, graphical symbols initially developed for such purposes (see IEC 617, ISO 3461-2, ISO 7001 and ISO/TR 7239) may be used on equipment, provided that they are drawn in accordance with the principles laid down in this part of ISO 3461.

### 2 References

IEC 27 (parts 1 to 4), *Letter symbols to be used in electrical technology*.

IEC 417 : 1973, *Graphical symbols for use on equipment — Index, survey and compilation of the single sheets*.

IEC 617 (parts 1 to 13), *Graphical symbols for diagrams*.

ISO 31 (parts 0 to 13), *Quantities, units and symbols*.

ISO 3461-2 : 1987, *General principles for the creation of graphical symbols — Part 2 : Graphical symbols for use in technical product documentation*.

ISO 3864 : 1984, *Safety colours and safety signs*.

ISO 4196 : 1984, *Graphical symbols — Use of arrows*.

ISO 7000 : 1984, *Graphical symbols for use on equipment — Index and synopsis*.

ISO 7001 : 1980, *Public information symbols*.

ISO/TR 7239 : 1984, *Development and principles for application of public information symbols*.

### 3 Definitions

For the purposes of this part of ISO 3461, the following definitions apply.

**3.1 graphical symbol** : Visually perceptible figure used to transmit information independently of language. It may be produced by drawing, printing or other means.

NOTE — Internationally standardized letter symbols according to ISO 31 and IEC 27 may be considered to be graphical symbols.

**3.2 graphical symbol elements** : Parts of a graphical symbol.

#### NOTES

1 A graphical symbol element with a specific meaning may be used to provide a common concept in the construction of a symbol family.

2 Letters, numerals, punctuation marks and mathematical symbols may be used as graphical symbol elements.

**3.3 (symbol) original** : Design of a graphical symbol, prepared in accordance with this part of ISO 3461, used for reference or reproduction purposes.

### 4 Meaning

The meaning assigned to each graphical symbol is expressed by its title which may be supplemented by an application note. The meaning shall be unambiguous and independent of terms related to a special technique or discipline.

The meaning of a graphical symbol may depend on its orientation and care shall be taken to avoid ambiguity (see 8.2).

## 5 Combination of graphical symbols

To represent certain concepts, graphical symbols or graphical symbol elements may be combined to form a new graphical symbol. The meaning assigned to the new graphical symbol shall be consistent with the meanings of the individual graphical symbols or graphical symbol elements used.

## 6 Shape

The shape of a graphical symbol should be

- simple, in order to facilitate perception and reproduction;
- readily distinguishable from those of other graphical symbols with which it may be used;
- easily associated with its intended meaning, i.e. either self-evident or easily learnt.


For the design of graphical symbols on safety signs, see ISO 3864.

## 7 Design principles


**7.1** A graphical symbol shall be designed within the basic pattern (see clauses 8 and 9, and figure 3).

**7.2** The shape of graphical symbols shall be such that it can be produced by the usual manufacturing methods (e.g. etching, engraving, printing and photographic means).

**7.3** In general, line thicknesses shall be either 2 mm or 4 mm on the symbol originals. For visual clarity, a combination of both line thicknesses may be used. Examples are shown in figure 1.



a) Microphone (basic symbol)



b) On/off (push button)



c) Horizontal picture shift (e.g. television screen)

Figure 1 — Examples of line-thickness combinations

**7.4** The minimum spacing between lines shall be chosen to take into account visual clarity and the reproduction methods to be used. As a guide, the minimum space between parallel lines should be not less than 1,5 times the minimum line thickness.

**7.5** Angles smaller than 30° should be avoided.

**7.6** Filled areas should be avoided.

**7.7** When designing graphical symbols which incorporate arrows, the principles established in ISO 4196 shall apply.

**7.8** A simple type-face should be used for constituent graphical symbol elements such as letters, numerals, punctuation marks and mathematical symbols. In the symbol original, the lettering height shall be at least 10 mm.

**7.9** The use of colours should be an additional aid rather than a basic informative element for the meaning of a graphical symbol.

## iTeh Standards Standards.it/ai)

## Document Preview

### 8 Design procedure

Graphical symbol design should follow the following procedure :

- a) identification of a need for a graphical symbol;
- b) clear and unambiguous description of the purpose of the graphical symbol and identification of any positioning factors (see 8.2);
- c) analysis of the environmental and application factors;
- d) consideration of existing or proposed graphical symbols in the same and/or related fields;
- e) design of the graphic form as described in clause 9;
- f) testing of the graphical symbol for legibility, comprehensibility, etc.;
- g) modification, if necessary.

### 8.2 Orientation of the graphical symbol

The majority of graphical symbols preserve their meaning in any orientation [see figure 2a)]. However, when the meaning of a graphical symbol does depend on its orientation, this shall be explicitly stated [see figure 2b)].