

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Luminaires –
Part 2-3: Particular requirements – Luminaires for road and street lighting**

**Luminaires –
Partie 2-3: Règles particulières – Luminaires d'éclairage public**

[IEC 60598-2-3:2002](https://standards.iteh.ai/catalog/standards/iec/b4a49ccb-4a7d-49dc-84fa-11a9262b25fb/iec-60598-2-3-2002)

<https://standards.iteh.ai/catalog/standards/iec/b4a49ccb-4a7d-49dc-84fa-11a9262b25fb/iec-60598-2-3-2002>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2011 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Central Office
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue

The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 15 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary

65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Catalogue IEC - webstore.iec.ch/catalogue

Application autonome pour consulter tous les renseignements bibliographiques sur les Normes internationales, Spécifications techniques, Rapports techniques et autres documents de l'IEC. Disponible pour PC, Mac OS, tablettes Android et iPad.

Recherche de publications IEC - www.iec.ch/searchpub

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études,...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et aussi une fois par mois par email.

Electropedia - www.electropedia.org

Le premier dictionnaire en ligne de termes électroniques et électriques. Il contient 20 000 termes et définitions en anglais et en français, ainsi que les termes équivalents dans 15 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

Glossaire IEC - std.iec.ch/glossary

65 000 entrées terminologiques électrotechniques, en anglais et en français, extraites des articles Termes et Définitions des publications IEC parues depuis 2002. Plus certaines entrées antérieures extraites des publications des CE 37, 77, 86 et CISPR de l'IEC.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: csc@iec.ch.



IEC 60598-2-3

Edition 3.1 2011-11
CONSOLIDATED VERSION

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Luminaire –
Part 2-3: Particular requirements – Luminaire for road and street lighting**

**Luminaire –
Partie 2-3: Règles particulières – Luminaire d'éclairage public**

IEC 60598-2-3:2002

<https://standards.iteh.ai/catalog/standards/iec/b4a49ccb-4a7d-49dc-84fa-11a9262b25fb/iec-60598-2-3-2002>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.140.40; 93.080.30

ISBN 978-2-8891-2737-5

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
3.1 Scope.....	5
3.2 General test requirements	5
3.3 Definitions	5
3.4 Classification of luminaires	6
3.5 Marking	7
3.6 Construction.....	7
3.7 Creepage distances and clearances	12
3.8 Provision for earthing	12
3.9 Terminals	12
3.10 External and internal wiring	12
3.11 Protection against electric shock	12
3.12 Endurance tests and thermal tests	13
3.13 Resistance to dust and moisture.....	13
3.14 Insulation resistance and electric strength	13
3.15 Resistance to heat, fire and tracking	13
Annex A (informative) Drag coefficient measurement.....	16
Annex B (normative) Schedule of amended clauses containing more serious/critical requirements which require products to be retested	17
Figure 1 – Different procedures for the static wind-force test	14
Figure 2 – Counting particles at the edge of the square	15

IEC 60598-2-3:2002

<https://standards.iteh.ai/catalog/standards/iec/b4a49ccb-4a7d-49dc-84fa-11a9262b25fb/iec-60598-2-3-2002>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LUMINAIRES –

**Part 2-3: Particular requirements –
Luminaires for road and street lighting**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60598-2-3 edition 3.1 contains the third edition (2002) [documents 34D/762/FDIS and 34D/772/RVD] and its amendment 1 (2011) [documents 34D/989/FDIS and 34D/1003/RVD].

A vertical line in the margin shows where the base publication has been modified by amendment 1. Additions and deletions are displayed in red, with deletions being struck through.

This International Standard IEC 60598-2-3 has been prepared by subcommittee 34D: Luminaires, of IEC technical committee 34: Lamps and related equipment.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This standard is to be read in conjunction with IEC 60598-1.

The changes to the text introduced by this new edition introduce requirements for column-integrated luminaires.

The text introduced by interpretation sheets IS 01 and IS 02 is contained in subclause 3.6.5 Note 1 and subclause 3.12.1, second paragraph, respectively.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh Standards

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

[IEC 60598-2-3:2002](https://standards.iteh.ai/catalog/standards/iec/b4a49ccb-4a7d-49dc-84fa-11a9262b25fb/iec-60598-2-3-2002)

<https://standards.iteh.ai/catalog/standards/iec/b4a49ccb-4a7d-49dc-84fa-11a9262b25fb/iec-60598-2-3-2002>

LUMINAIRES –

Part 2-3: Particular requirements – Luminaires for road and street lighting

3.1 Scope

This part of IEC 60598 specifies requirements for

- luminaires for road, street lighting and other public outdoor lighting applications;
- tunnel lighting;
- column-integrated luminaires with a minimum total height above normal ground level of 2,5 m;

and for use with electrical lighting sources on supply voltages not exceeding 1 000 V.

NOTE Column integrated luminaires with a total height below 2,5 m are under consideration.

3.1.1 Normative references

The normative references listed in Section 0 of IEC 60598-1 apply to this part as well as the following reference:

IEC 60068-3-76:1997, *Environmental testing – Part 2-75: Tests – Test Eh: Hammer tests*

IEC 60364-7-714, 1996, *Electrical installations of buildings – Part 7: Requirements for special installations or locations – Section 714: External lighting installations*

IEC 62262: 2002, Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts (IK code)

3.2 General test requirements

The provisions of Section 0 of IEC 60598-1 apply.

The tests described in each appropriate section of Part 1 shall be carried out in the order listed in this section of Part 2.

In order to facilitate testing, and due to the dimensions of the sample, it is allowed to make use of the appropriate parts of the luminaire only (this is mainly applicable to column-integrated luminaires).

3.3 Definitions

For the purposes of this section, the definitions of Section 1 of IEC 60598-1 apply together with the following definitions.

3.3.1

span wire

wire between main supports which carries the weight of the complete installation.

NOTE This may include several luminaires, supply cables and a stay wire.

3.3.2**suspension wire**

wire attached to the span wire and carrying the weight of the luminaire

3.3.3**stay wire**

tensioned wire between main supports to limit lateral and rotary movement of the suspended luminaires

3.3.4**column-integrated luminaires**

lighting systems formed with a luminaire integrated in a lighting column fixed in the ground

3.3.5**reflective or decorative external part of a column-integrated luminaire**

device reflecting the light in a fixed direction or with a decorative purpose, mounted outside the lamp compartment generally at the top of the column-integrated luminaire

NOTE Such devices are referred to in this standard as "external parts".

3.3.6**lighting column**

support intended to hold one or more luminaires, consisting of one or more parts: a post, possibly an extension piece, and if necessary a bracket. It does not include columns for catenary lighting

3.3.7**nominal height of a column-integrated luminaire**

distance between the centre line of the point of entry of the external part and the intended ground level, for column-integrated luminaires planted in the ground, or the bottom of the flange plate, for column-integrated luminaires with a flange plate

3.3.8**door opening of a column-integrated luminaire**

opening in the column of a column-integrated luminaire for access to electrical equipment

3.3.9**cable entry slot of a column integrated luminaire**

opening in the part of a column-integrated luminaire below ground for the cable entry

3.3.10**connection box of a column integrated luminaire**

box containing terminal blocks: protecting devices allowing the connection of a column-integrated luminaire to the mains and the looping of electricity supply cables

3.3.11**tunnel luminaires**

luminaires for lighting tunnels which are mounted direct or on frames to the wall or ceiling of the tunnel

3.4 Classification of luminaires

Luminaires shall be classified in accordance with the provisions of Section 2 of IEC 60598-1.

NOTE Luminaires for road and street lighting are normally suitable for one or more of the following modes of installation:

- a) on a pipe (bracket) or the like;
- b) on a mast (column) arm;
- c) on a post top;

- d) on span or suspension wires;
- e) on a wall.

3.5 Marking

The provisions of Section 3 of IEC 60598-1 apply. In addition, the following information shall be provided in the instruction leaflet supplied with the luminaire:

- a) design attitude (normal operating position);
- b) weight including control gear if any;
- c) overall dimensions;
- d) if intended for mounting more than 8 m above ground level, the maximum projected area subjected to wind force (see 3.6.3.1);
- e) the range of cross-sectional areas of suspension wires suitable for the luminaire, if applicable;
- f) suitability for use indoors provided the 10 °C, allowed for the effects of natural air movement, has not been deducted from measured temperature (see 3.12.1);
- g) dimensions of the compartment in which the connection box is placed;
- h) the torque setting in newton metres to be applied to any bolts or screws which fix the luminaire to its support;
- i) maximum mounting height relevant to the selected method for protection against the falling of glass particles.

3.6 Construction

The provisions of Section 4 of IEC 60598-1 apply together with the requirements of 3.6.1 to 3.6.5.

3.6.1 All luminaires shall have protection against ingress of moisture of at least IPX3, except for tunnel-lighting luminaires and glazing of column-integrated luminaires with an open-sided external part, for which IPX5 is required.

For column-integrated luminaires, door opening included, the IP classification shall be as follows:

- 1) parts below 2,5 m: IP3X (see IEC 60364-7-714)
- 2) parts above 2,5 m: IP2X (when the external part is open-sided, the IP classification of the glazing shall be 5X)

3.6.2 Luminaires for suspension on span wires shall be fitted with clamping devices for this purpose and the range of span-wire sizes for which the clamping devices are suitable shall be stated in the instruction leaflet supplied with the luminaire. The device shall clamp the span wire to prevent movement of the luminaire with respect to the span wire.

The suspension devices shall not damage the span wire during installation and during normal use of the luminaire.

Compliance is checked by inspection after fitting the luminaire to the smallest and largest span wires in the range stated by the luminaire manufacturer.

NOTE Care should be taken to avoid electrolytic corrosion between the clamping device and the span wire.

3.6.3 The means for attaching the luminaire or external part to its support shall be appropriate to the weight of the luminaire or external part. The connection shall be designed to withstand wind speeds of 150 km/h on the projected surface of the assembly without undue deflection.

Fixings which carry the weight of the luminaire or external part and internal accessories shall be provided with means to prevent the dislodgement of any part of the luminaire or external part by vibration, either in service or during maintenance.

Parts of luminaires or external parts which are fixed other than with at least two devices, for example, screws or equivalent means of sufficient strength, shall have such extra protection as to prevent those parts falling and endangering persons, animals and surroundings, should a fixing device fail under normal conditions.

Compliance is checked by inspection and, for mast-arm or post-top mounted luminaires or external parts, by the test of 3.6.3.1.

The wind-force test is not required to be performed on tunnel luminaires.

NOTE In considering the possible effects of vibration, the luminaire should be studied in conjunction with the lamp and the column with which it may be used.

3.6.3.1 Static load test for mast-arm or post-top mounted luminaires or external parts

The luminaire or external part is mounted in such a way that the most critical surface is loaded.

The most critical surface is determined by calculating the highest value of $Cd \times S$

where

Cd is the drag coefficient;

S is the area of the surface to be loaded (m^2).

The drag coefficient depends on the shape of the surface. For luminaires or external parts for which the Cd is not measured, the value of 1,2 shall be taken.

NOTE 1 See Annex A for measurement of Cd .

The means of attachment shall be secured in accordance with the manufacturer's instructions.

A constant evenly distributed load is applied for 10 min on the most critical surface.

NOTE 2 See Figure 1 for methods of equal distribution of the load. In cases where bags are used, these can be filled with sand, lead shot or small balls.

The load shall be equal to

$$F = 1/2 Rh \times S \times Cd \times V^2 \text{ (N)}$$

where

Rh is equal to $1,225 \text{ kg/m}^3$ (air volumic mass);

V is the wind speed (m/s).

The wind speeds relevant to the mounting heights of luminaires or external parts shall be

$V = 45 \text{ m/s}$ (163 km/h) for heights up to 8 m;

$V = 52 \text{ m/s}$ (188 km/h) for heights between 8 m and 15 m;

$V = 57 \text{ m/s}$ (205 km/h) for heights of more than 15 m.

NOTE 3 In some countries, the wind speed is determined by national rules (for example, Japan).

The drag coefficient is 1,2 (or the exact value measured in Annex A).

After the test, there shall be no visible failure impairing the safety, no permanent deformation from the attachment which exceeds a slope of more than 2 cm/m, and no rotation around the point of attachment.

3.6.4 If the use of a single lampholder does not ensure the correct position of the lamp, an adequate supporting device shall be provided.

For adjustable lampholders or optical parts, suitable reference marks shall be provided.

Compliance is checked by inspection.

~~3.6.5 Glass covers shall either consist of a glass that fractures into small pieces or shall be provided with a guard of sufficiently small mesh or a film-coated glass that retains glass fragments.~~

~~For flat glass covers compliance is checked by inspection and, if the glass is not provided with a guard, by the following test.~~

~~The glass component is supported over the whole area to ensure that particles will not be scattered upon fragmentation and that movement of the particles is prevented. Shatter the glass with a centre punch at a point 30 mm from the mid-point of one of the longer edges of glass towards the centre. Within 5 min of fracture, count the particles in a 50 mm square, located approximately at the centre of the area of coarsest fracture but always within the confines of the glass.~~

~~NOTE Where possible, the area of measurement should not be within 30 mm of any edge, hole or machining of the glass.~~

~~A glass is deemed to have passed the test if the number of particles in the 50 mm square is more than 60; glass splinters and pieces less than the full thickness of the glass being excluded from the count. For glass of smaller size where a 50 mm × 50 mm area is not possible, the number of pieces necessary in the count is proportionately reduced.~~

~~In the count of the total number of particles in the 50 mm square, the particles in the centre of the square plus those at the edge shall be taken into account. In order to count particles at the edge of the square, it is recommended that all pieces intersected by two adjacent sides be included and all particles intersected by the two other sides be ignored (see Figure 2).~~

~~A suitable method of counting the particles is to place a square of 50 mm side, of transparent material over the glass and mark a spot of ink as each particle within the square is counted.~~

~~NOTE 1 When the test sample remains as one sheet, the fragmentation lines would normally be used to indicate fractures and the size and number of particles would thus be evaluated, unless reinforcing or a film were employed.~~

~~NOTE 2 For glass covers formed from a flat plate, a test is under consideration.~~

3.6.5 In order to reduce the risk of injury caused by breaking glass, the following requirements, in relation to the intended mounting height of the luminaire, are applicable.

When luminaires are installed below 5 m, no additional requirements are requested on glass covers.

For tunnel luminaires, the requirements of 3.6.5.1 apply without exception.

When luminaires are installed above 5 m, glass covers shall be:

- a) constituted with a glass that fractures into small pieces, or
- b) constituted with a glass having a high impact shock resistance, or