First edition

lir

Si

Si

Si

Si

Si

Si

Si Si Si Si

Si

ISO/TC 23/SC 15

Secretariat: SFS

Date: 2024-11-15

Machinery for forestry — Forestry mulching equipment — Terms, definitions and commercial specifications

Machines forestières — Broyeurs — Termes, définitions et spécifications commerciales

iTeh Standards.iteh.ai)

PROOF

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8

CH-1214 Vernier, Geneva Phone: + 41 22 749 01 11 E-mail: copyright@iso.org Website: www.iso.org

Published in Switzerland

iTeh Standards (https://standards.iteh.ai) Document Preview

XO 21120

https://standards.iteh.ai/catalog/slx00rd-xo/24cb89b4-3f1b-474c-8c2a-182330c21074/iso-21120

Contents

Forev	vord	v
Introd	luction	vi
1	-Scope	1
		I
2	-Normative references	1
3	Terms and definitions	1
3.1—	-General terms	1
3.2	-Terms related to mulching attachment carrier	2
	-Terms related to to mulching attachment	<u> 2</u>
3.4—	-Terms related to mulching equipment type	 3
	Drive type	 3
	Rotor type	 3
	Tool type	3
3.4.4 -	Mount type	 4
	-Terms related to dimensional characteristics	 4
	Mulching attachment carrier	 4
	Mulching attachment	5
	-Mulching equipment	 6
3.6 —	-Terms related to masses	 6
4	-Commercial specifications	 6
	-Mulching attachment carrier	 6
4.1.1 -	Internal combustion engine	 6
	Electric motor	 7
4 .1.3	- Undercarriage	 7
4.1.4	Mulching attachment carrier mass	 7
	-Mulching attachment	 7
	Drive type	 7
	Rotor type	 8
	Dimensional characteristics	8
	- Mulching attachment mass	8
4.3	-Mulching equipment	8
Annes	x A (informative) Dimensional characteristics of forestry mulching equipment	9
A.1 —	-Dimensional characteristics of mulching attachment carrier	9
Figur e	e A.1 — Dimensional characteristics of mulching attachment carrier	<u>9</u>
۸ 2	-Dimensional characteristics of drum-type mulching attachment	0
Figur e	e A.2 — Dimensional characteristics of drum-type mulching attachment (shown with	L
	bar)	10
A.3	Dimensional characteristics of disc-type mulching attachment	10
rigure	A.3 — Dimensional characteristics of disc-type mulching attachment	10
A.4—	Dimensional characteristics of forestry mulching equipment for engagement with	
	materials	10
Figur	e A.4 — Example of reach measurement	11
•	•	
Figur e	e A.5 — Example of lift height and below-grade depth measurements	11
Annes	x B (informative) Nomenclature of forestry mulching equipment	12

B.1 Forestry mulching equipment1	2
Figure B.1 — Nomenclature of forestry mulching equipment1	2
B.2—Forestry mulching equipment mount types1	2
Figure B.2 — Nomenclature of forestry mulching equipment mount types1	3
B.3—Nomenclature of drum-type mulching attachment1	3
Figure B.3 — Nomenclature of drum-type mulching attachment (shown with push bar)	4
B.4—Nomenclature of disc-type mulching attachment1	4
Figure B.4 — Nomenclature of disc-type mulching attachment1	5
Bibliography1	-6
Foreword	
Introduction	v i
1 Scope	1
2 Normative references	1
3 Terms and definitions	_1
4 Commercial specifications	6
Annex A (informative) Dimensional characteristics of forestry mulching equipment	9
Annex B (informative) Nomenclature of forestry mulching equipment1	.4
Bibliography2	:1

https://standards.iteh.ai/catalog/stx/0xrds/izo/24cb89b4-3f1b-474c-8c2a-182330c21074/iso-21120

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 15, *Machinery for forestry*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The figures in this document are intended to illustrate machine concepts for rather than any existing machines or all possible configurations- (see Annexes A and B).

iTeh Standaxds (https://standaxos.iteh.ai) Document Preview

SO 21120

https://standards.iteh.ai/catalog/slx00/d5x0/24cb89b4-3f1b-474c-8c2a-182330c21074/iso-211200

Machinery for forestry — Forestry mulching equipment — Terms, definitions and commercial specifications

1 Scope

This document identifies and defines terms, specifies a means of classification, provides dimensional characteristics and commercial specifications, and gives a nomenclature of components for mulching equipment (in other words, mulching attachment carriers and mulching attachments) used in forestry and related operations. Its aim is to establish a uniform method of describing the various configurations of these types of forestry machines.

Machines for mulching which have been designed for feeding by hand are not covered by this document.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org/

3.1 General terms

3.1.1 3.1.1

mulching attachment carrier

self-propelled machine for carrying a mulching attachment (3.1.2)(3.1.2)

Note-1-to-entry:——_Mulching attachment carriers are defined by their design configuration and operational purpose.

st

3.

F

n

EXAMPLES: EXAMPLE Skid-steer loader, excavator, tractor with forestry application features.

3.1.2 3.1.2

mulching attachment

device affixed to and propelled by a *mulching attachment carrier* (3.1.1)(3.1.1) and designed for the purpose of *mulching* (3.1.3)(3.1.3)

3.1.3 3.1.3

mulching

reduction of trees, brush, or parts of trees on site with a grinding or shredding action, leaving the resulting material on the forest or worksite floor

[SOURCE: ISO 6814:2009, 2.16, modified to add: or worksite]

3.1.4 **3.1.4**

mulching equipment

mulching attachment carrier $\frac{(3.1.1)(3.1.1)}{(3.1.2)}$ equipped with a mulching attachment $\frac{(3.1.2)(3.1.2)}{(3.1.2)}$

ISO-7448/PRF 21120:2024(en)

Note 1-to-entry: Mulching equipment can be classified by how they are configured (for example, drive type, rotor type, tool type, mount type) and combination of these types. See 3.4See 3.4

3.2 Terms related to mulching attachment carrier

3.2.1 3.2.1

undercarriage

base of the *mulching equipment* (3.1.4)(3.1.4) that provides mobility

Note-1-to-entry:-An undercarriage typically has endless tracks or wheels, or a combination of both.

3.2.2 3.2.2

maximum ground speed

maximum forward speed able to be obtained on level ground based on the nominal design capacity of the *mulching attachment carrier* $\{3.1.1\}\{3.1.1\}$ with tyres or endless tracks

Note-1-to-entry:-The tyre size will be the largest diameter drive tyres as specified by the mulching attachment carrier manufacturer for the *mulching attachment carrier* (3.1.1).(3.1.1).

3.3 Terms related to to mulching attachment

3.3.1 3.3.1

rotor

rotating component with tools (3.3.2)(3.3.2) that strikes and reduces material it comes in contact with

Note-1-to-entry:-The rotor typically has an axis that is either horizontal (drum type) or vertical (disc type).

3.3.2 3.3.2

tool

material engaging element mounted to the rotor (3.3.1) (3.3.1) that grinds, shreds, tears, or cuts material

EXAMPLE Tooth, hammer.

3.3.3ttr 3.3.3 and ards. iteh. ai/catalog/s

anvil

reaction element or elements located close to the *rotor* (3.3.1)(3.3.1) which restrains engaged material while it is struck and reduced by the *tools* (3.3.2)(3.3.2)

3.3.4 3.3.4

rotor housing

enclosure containing the rotor (3.3.1)(3.3.1) and reactionary elements which limit and direct material discharge

3.3.5 3.3.5

debris sizing door

adjustable element mounted on the *rotor housing* (3.3.4)(3.3.4) that contributes to material reduction and directs material discharge

3.3.6 3.3.6

push bar

pushover bar

rigid or adjustable structure mounted on top of the *rotor housing* (3.3.4)(3.3.4) for manipulating and directing material that is standing or on the ground

3.3.7 3.3.7

skid shoe

adjustable or rigid mounted element mounted at the bottom of the *mulching attachment* (3.1.2)(3.1.2) outside of the *rotor housing* (3.3.4)(3.3.4) that regulates distance between the cutting element and the ground

3.3.8 3.3.8

mount

mechanical interface that connects the *mulching attachment* (3.1.2)(3.1.2) to the *mulching attachment carrier* (3.1.1)(3.1.1) typically by welding, bolting, or pinning

Note_1-_to__entry:-_Quick couplers and quick attach systems are other types of interfaces.

3.3.9 3.3.9

debris guard

devices affixed to the lower section of the *mulching attachment* (3.1.2)(3.1.2) that absorbs or deflects thrown debris

EXAMPLE Chains, protective skirt.

3.3.10 3.3.10

tool holder

device that affixes the tool (3.3.2)(3.3.2) to the drum (3.4.2.1)(3.4.2.1) or the disc (3.4.2.2)(3.4.2.2)

3.4 Terms related to mulching equipment type

3.4.1 Drive type

3.4.1.1 3.4.1.1

PTO drive

configuration where the *mulching attachment* (3.1.2)(3.1.2) is powered by the power take-off of the *mulcher attachment carrier* (3.1.1)(3.1.1)

3.4.1.2 3.4.1.2 ards.iteh.ai/catalog/st.fo.rds.yo/24cb89b4-3f1b-4/4c-8c2a-182330c210/4/iso-2112

hvdraulic drive

configuration where the *mulching attachment* (3.1.2)(3.1.2) is powered by hydraulic fluid supplied by the *mulching attachment carrier* (3.1.1)(3.1.1) to single or dual hydraulic motors of the *mulching attachment* (3.1.2)(3.1.2)

3.4.1.3 3.4.1.3

self-powered drive

configuration where the *mulching attachment* (3.1.2)(3.1.2) is configured with an on-board power source (for example, engine, electric motor, hydraulic motor), and is independent of any power from the *mulching attachment carrier* (3.1.1)(3.1.1) to the *rotor* (3.3.1)(3.3.1) of the *mulching attachment* (3.1.2)(3.1.2)

3.4.2 Rotor type

3.4.2.1 3.4.2.1

drum

configuration where the rotor of the *mulching attachment* (3.1.2)(3.1.2) is cylindrical and typically mounted with a horizontal shaft orientation within the *rotor housing* (3.3.4)(3.3.4)

<u>3.4.2.2</u> <u>3.4.2.2</u>

disc

configuration where the rotor of the *mulching attachment* $\frac{(3.1.2)(3.1.2)}{(3.1.2)}$ is a disc or disc-like assembly, and typically mounted with a vertical shaft orientation to the ground within the *rotor housing* $\frac{(3.3.4)(3.3.4)}{(3.3.4)}$

ISO-7448/PRF 21120:2024(en)

3.4.3 Tool type

3.4.3.1 3.4.3.1

fixed

configuration where a *tool* (3.3.2)(3.3.2) is rigidly mounted to the *rotor* (3.3.1)(3.3.1)

3.4.3.2 3.4.3.2

swing

flail

configuration where a tool (3.3.2)(3.3.2) that can swing or pivot independent of the rotor (3.3.1)(3.3.1)

3.4.4 Mount type

3.4.4.1 3.4.4.1

limited reach

mount (3.3.8)(3.3.8) configuration with a vertical lift capability typically less than 1,75 m

3.4.4.2 3.4.4.2

boom

mount (3.3.8)(3.3.8) configuration intended for mulching attachment carriers (3.1.1)(3.1.1) with lift and reach typically more than 4 m

Note-1-to-entry:——This configuration can include tilting and rotational elements for *mulching attachment* (3.1.2)(3.1.2) positioning.

3.4.4.3 3.4.4.3

loader

mount (3.3.8)(3.3.8) configuration intended for *mulching attachment carriers* (3.1.1)(3.1.1) with loader arm geometry that typically provides vertical lift less than 4 m

Note-1-to-entry:——Reach is typically fixed and cannot be adjusted in or out, but the loader can include tilting elements to independently position the *mulching attachment* (3.1.2)(3.1.2)

3.5 Terms related to dimensional characteristics 4-3flb-474c-8c2a-182330c21074/iso-21120

3.5.1 3.5.1

ground reference plane

GRP

hard, flat, horizontal surface on which the *mulching attachment carrier* (3.1.1)(3.1.1) and *mulching attachment* (3.1.2)(3.1.2) are placed for taking measurements

[SOURCE: ISO 13862:2022, modified — replaced "machine is" with "mulching attachment carrier (3.1.1) and mulching attachment (3.1.2) are".]

3.5.2 Mulching attachment carrier

3.5.2.1 3.5.2.1

height

 H_1

distance from *ground reference plane* (3.5.1.1)(3.5.1) to the top of the highest *mulching attachment carrier* (3.1.1)(3.1.1) element with the attachment lowered to the ground

3.5.2.2 3.5.2.2

width

 W_1

linear distance between each side-most *mulching attachment carrier* (3.1.1)(3.1.1) element