

© ISO 2024

~~Published in Switzerland~~ All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office

~~CP 401 • Ch. de Blandonnet 8 • CP 401~~

CH-1214 Vernier, Geneva, ~~Switzerland~~

~~Tel:Phone~~; + 41 22 749 01 11

Fax + 41 22 749 09 47

E-mail: copyright@iso.org

Website: www.iso.org

~~Published in Switzerland~~

Formatted: Font: Bold

Formatted: HeaderCentered

Formatted: Font: Cambria

Formatted: Left: 1.5 cm, Right: 1.5 cm, Top: 1.4 cm, Bottom: 1 cm, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Commented [eXtyle1]: The reference "ISO 2024" is to a withdrawn standard

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: No page break before, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: zzCopyright address, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria, French (France)

Formatted: Font: Cambria, French (France)

Formatted: zzCopyright address, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: Cambria

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

ISO/DTR 7035-2

<https://standards.iteh.ai/catalog/standards/iso/d93deab9-f571-4d08-9738-205ac762b349/iso-dtr-7035-2>

Formatted: FooterPageRomanNumber

Contents

Foreword..... v

Introduction vi

1 Scope..... 1

2 Normative references..... 1

3 Terms and definitions 2

4 General..... 2

5 Practices to set targets for water supplying system..... 3

5.1 Water quality..... 3

5.1.1 Materials 3

5.1.2 Prevention of back flow..... 3

5.1.3 Stagnation..... 3

5.1.4 Cross-connection with other systems..... 3

5.2 Design life 4

5.3 Demand for water..... 4

5.3.1 General..... 4

5.3.2 Water demand estimate 4

5.3.3 Water for fire-fighting..... 4

5.4 System security..... 4

6 Design..... 5

6.1 Hydraulic design 5

6.1.1 Sizing 5

6.1.2 Mains 5

6.1.3 Local main..... 7

6.1.4 Service pipes..... 7

6.2 Structural design..... 7

6.3 System layout design 7

6.3.1 Mains 7

6.3.2 Service pipes 8

6.3.3 Valves 8

6.3.4 Reservoirs..... 8

6.3.5 Pump stations..... 8

6.4 Protection against aggressive environment 9

6.4.1 General..... 9

6.4.2 External protection 9

6.4.3 Internal protection..... 9

7 Hydraulic thrust restraint design 10

7.1 Hydraulic thrust force and restraint principles 10

7.2 Thrust blocks solutions 10

7.3 Restrained joints solution 11

7.3.1 General..... 11

7.3.2 Restrained joint systems..... 11

8 Design of trenchless method..... 11

8.1 Pipe jacking..... 12

8.1.1 Survey..... 12

8.1.2 Pipe protection 12

8.1.3 Jacking procedure..... 13

8.2 Horizontal directional drilling..... 13

8.2.1 General..... 13

Formatted: Font: Cambria, 11 pt

Formatted: Font: Cambria, 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Left, Space After: 0 pt, Line spacing: single, Tab stops: Not at 0.71 cm

Formatted: Font: 10 pt

Formatted: FooterCentered, Left, Space Before: 0 pt, Tab stops: Not at 17.2 cm

Formatted: Font: 11 pt

Formatted: FooterPageRomanNumber, Left, Space After: 0 pt, Tab stops: Not at 17.2 cm

Formatted: Font: Bold
Formatted: HeaderCentered

8.2.2 Site investigation.....13

8.2.3 Pilot bore design13

8.2.4 Upsize the bore14

8.2.5 Pulling in14

8.2.6 Drilling fluid usage15

8.3 Design of casing method.....15

8.3.1 General.....15

8.3.2 Casing design15

8.3.3 Carrier design.....16

8.3.4 Installation16

8.4 Pipe bursting16

8.4.1 General.....16

8.4.2 Parameters.....16

8.4.3 Replacement pipe18

9 Design of pipelines on supports19

9.1 Pipelines on land.....19

9.1.1 Support design19

9.1.2 Loading and forces19

9.2 Other cases of supporting pipe20

10 Installation and hydrostatic test20

10.1 Installation20

10.2 Hydrostatic test20

10.2.1 General.....20

10.2.2 Basic design contents for hydraulic test.....21

11 Flushing and disinfection.....21

12 Operation.....22

12.1 Inspection and monitoring.....22

12.2 Maintenance and repair22

12.2.1 Maintenance22

12.2.2 Pierced pipe maintenance and repair.....22

12.2.3 Broken pipe maintenance and repair22

12.3 Maintenance and repair for a leaking junction23

Bibliography25

Formatted: FooterPageRomanNumber

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of a patent right. ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 5, *Ferrous metal pipes and metallic fittings*, Subcommittee SC 2, *Cast iron pipes, fittings and their joints*.

This document, ISO/TR 7035: Design and asset management of ductile iron pipe for water application, consists of the following parts:

- Part 1: Asset management;
- Part 2: Design, installation and operation.

A list of all parts in the ISO/TR 7035 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Formatted: Font: Cambria, 11 pt

Formatted: Font: Cambria, 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Left, Space After: 0 pt, Line spacing: single, Tab stops: Not at 0.71 cm

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Commented [eXtyle2]: The URL <https://www.iso.org/patents> has been redirected to <http://www.iso.org/iso-standards-and-patents.html>. Please verify the URL.

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Commented [eXtyle3]: The URL <https://www.iso.org/iso/foreword.html> has been redirected to <http://www.iso.org/foreword-supplementary-information.html>. Please verify the URL.

Formatted: Font: Cambria

Commented [eXtyle4]: Not found, but similar references exist ISO/TR 7035 (all parts), — Design and asset management of DIP for water application

Formatted: Font: 10 pt

Formatted: FooterCentered, Left, Space Before: 0 pt, Tab stops: Not at 17.2 cm

Formatted: Font: 11 pt

Formatted: FooterPageRomanNumber, Left, Space After: 0 pt, Tab stops: Not at 17.2 cm

Formatted: Font: Bold

Formatted: HeaderCentered

Introduction

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

According to the World Health Organization, since 2010, the majority of the world's population lives in cities. By 2030, six out of every 10 people will live in cities and, by 2050, this proportion will have increased to seven out of 10 people. The water and wastewater infrastructure of distribution and collection pipes may have between 5,000 km and 10,000 km of underground piping for water distribution, and a similar network for wastewater collection, for a city of 100,000 to 500,000 people.

In introducing the practices or known acknowledges of this document due regard has been taken of the possibility to use ductile iron pipe easily and quickly, as well as the importance of a reliable and safe supply of water for human consumption and the purpose of trade, industry, agriculture and fire-fighting.

Renovation and repair of pipelines is usually complicated, administratively and technically. In many cases damage and service interruptions are created to other infrastructure networks (not knowing where these services run). Along with deterioration of roads and sidewalks the perceived image of the city worsens, increasing the great list of indirect costs, which is why the long lasting and reliable pipelines like ductile iron pipes (offering the best cost-effectiveness results), when taken all performances are into account by the asset management tools, explained in [part 1 of this technical report ISO/TR 7035-1](#).

Formatted: Font: Cambria

Copyright notice

~~This ISO document is a Draft International Standard and is copyright protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.~~

~~Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.~~

ISO copyright office

Case postale 56 • CH-1211 Geneva 20

Tel. +41 22 749 01 11

Fax +41 22 749 09 47

E-mail copyright@iso.org

Web www.iso.org

~~Reproduction may be subject to royalty payments or a licensing agreement.~~

~~Violators may be prosecuted.~~

-

Formatted: FooterPageRomanNumber

Design and asset management of ductile iron pipe DIP for water application ~~Part 2: —~~

Part 2: Design, installation and operation

1 Scope

The objective of this document is to assist conceptors, engineering offices, water companies or project owners in the design, installation and operation of the ductile iron pipeline systems for water supply:

- ~~Introduce~~introduce practices for design, installation and operation of new ductile iron pipe water supply systems, rehabilitation or renovation;
- ~~Refers~~refers to existing standards that specify products' design, installation and site testing, materials and coatings.

This document gives efficient support to ~~Part 1: Asset management~~ISO/TR 7035-1, which indicates chapters here for readers' reference.

2 Normative references

The following ~~referenced~~ documents are ~~indispensable for~~referred to in the application text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

~~ISO 2531, Ductile iron pipes, fittings, accessories and their joints for water applications~~~~<std>~~ISO 10802, Ductile iron pipelines — Hydrostatic testing after installation</std>

~~<std>~~ISO 10803, Design method for ductile iron pipes</std>

~~<std>~~ISO 10804, Restrained joint systems for ductile iron pipelines — Design rules and type testing</std>

~~<std>~~ISO 13470, Trenchless applications of ductile iron pipes systems — Product design and installation</std>

~~<std>~~

ISO.16631, Ductile iron pipes, fittings, accessories and their joints compatible with plastic (PVC or PE) piping systems, for water applications and for plastic pipeline connections, repair and replacement</std>

~~<std>~~ISO 21051, Construction and installation of ductile iron pipeline system</std>

~~<std>~~ISO 21052, Restrained joint systems for ductile iron pipelines — Calculation rules for lengths to be restrained</std>

~~<std>~~ISO 2531, Ductile iron pipes, fittings, accessories and their joints for water applications</std>

Formatted: Left

Formatted: Font: Cambria

Formatted: Left: 1.5 cm, Right: 1.5 cm, Top: 1.4 cm, Bottom: 1 cm, Header distance from edge: 1.27 cm, Footer distance from edge: 0.5 cm

Formatted: Font: Cambria

Formatted: Main Title 2, Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: (Default) Cambria, (Asian) Japanese

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Commented [eXtyle5]: ISO 10803: current stage is 50.00

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Font: Cambria

Commented [eXtyle6]: The match came back with a different title. The original title was: Restrained joint system for Ductile Iron Pipe – Length calculations of restrained pipes and fittings

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: 11 pt

Formatted

ISO/DTR 7035-2:(en)

Formatted: Font: Bold

Formatted: HeaderCentered

<std>ISO 4179, Ductile iron pipes and fittings for pressure and non-pressure pipelines — Cement mortar lining</std>

<std>ISO 8179 1, Ductile iron pipes, fittings, accessories and their joints — External zinc based coating — Part 1: Metallic zinc with finishing layer</std>

<std>ISO 8179 2, Ductile iron pipes, fittings, accessories and their joints — External zinc based coating — Part 2: Zinc rich paint</std>

<std>ISO/TR 4340, Water aggressiveness evaluation and optimized lining choice</std>

3 Terms and definitions

Formatted: Font: Cambria

For the purposes of this document, the terms and definitions given in ISO 2531 and ISO 16631 definitions, and the following apply. Additional definitions apply also.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <https://www.electropedia.org/>

3.1

local main

water main which connects principal main(s) (3.2) with service pipes

Formatted: Font: Italic

3.2

principal main

water main serving as a principal distributor within the supply area, normally without direct consumer connections

3.3

Service service pipe

water pipe which supplies water from the local main (3.1) to the consumer

Formatted: Font: Italic

3.4

water distribution system

part of the water supply system comprising pipelines, service reservoirs, pumping stations and other assets by which water is distributed to the consumers-

Note 1 to entry: Note to entry 1: It begins at the outlet from the water treatment works (or source, if there is no treatment) and ends at the point of connection to the consumer's installation.

Formatted: Note

3.5

carrier pipe

a pipe inside a casing (3.6), which carries a product such as a gas or liquid-

Formatted: Font: Italic

3.6

casing

a metal pipe (as well as concrete pipe) used to protect the carrier pipe (3.5)

Formatted: Font: Italic

4 General

Formatted: Font: Cambria

Thanks to its excellent characteristics, the designs and the applications of ductile iron pipe networks for potable water purpose are quite simple. High mechanical performance (i.e., the robustness) of ductile iron pipe systems allows energy saving from the reduced mechanisation required during the installation (no

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: FooterPageRomanNumber

specialized equipment or on-site welding). Similarly, the need for the imported material for bed and surround is avoided or minimized, with the subsequent saving associated with the unnecessary use of natural resources and transport costs. Ductile iron pipes do not have the factor of time-dependent material creep deformation expressed as apparent stiffness as polymeric material pipes do.

Design processes normally start with the design/service objectives, which are related to the characteristics of the water supply systems in order to meet the targets outlined in [chapter 5 Clause 5](#) and the defined levels of service (see [ISO/TR 7035 Part 1](#)) over the range of operating conditions, having regards to all relevant economic considerations and environment [and](#) ecology consideration.

5 Practices to set targets for water supplying system

5.1 Water quality

5.1.1 Materials

Almost all the countries or areas have their rules to make all parts of water supply systems in contact with potable water to be designed and constructed by using components and materials which meet the national or area stands and regulations, such that there is no unacceptable deterioration on water quality. If that's not existing, a practical method is to refer to WHO's rules.

5.1.2 Prevention of back flow

Potable water supply systems are normally designed, equipped and installed to prevent the back flow. The air valves and washouts (with their operation and location) are usually used to avoid water entering the systems. In circumstances of particularly high risk of unacceptable deterioration of water quality, non-return valves would not be an effective method to prevent the back flow.

5.1.3 Stagnation

Potable water supply systems are principally designed installed and operated to minimize water stagnation (zones or points) which would lead to unacceptable deterioration of water quality.

The following arrangements are the main points or locations leading to stagnation:

- main with dead ends;
- branch with dead ends;
- spurs serving hydrants;
- un-isolated pipes laid in advance of development;
- sections with permanently low flow rates;
- enhanced pipe diameters required for fire-fighting or other non-permanent purposes.

In practice, facilities (for example, the level invert tees) are usually provided for main flushing.

5.1.4 Cross-connection with other systems

The interconnection of potable water supply systems is possible when the chemical and physical properties are compatible for blending and there is no unacceptable deterioration of water quality. Normally the potable water supply systems do not directly connect with the systems containing non-potable water, except a plan for the blending.

Formatted: Font: Cambria, 11 pt

Formatted: Font: Cambria, 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Left, Space After: 0 pt, Line spacing: single, Tab stops: Not at 0.71 cm

Formatted: Font: Cambria

Commented [eXtyle7]: Not found, but similar references exist

ISO/TR 7035 (all parts), — Design and asset management of DIP for water application

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: 10 pt

Formatted: FooterCentered, Left, Space Before: 0 pt, Tab stops: Not at 17.2 cm

Formatted: Font: 11 pt

Formatted

Formatted: Font: Bold
Formatted: HeaderCentered

Closed valves or non-return valves, except for air valves, washout and hydrant, normally do not constitute an effective means of separation for the purpose of the design.

5.2 Design life

Design life follows the requests and needs from the end users or authorities. For ductile iron pipes(buried) a service life of 100 years is commonly recognized in usual conditions thanks to the excellent mechanical properties and good internally and externally anti-corrosion solutions. Normally the design life of ductile iron pipeline systems is at least 50 years or is based on local national building codes.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Some components such as pumps and certain metering and control equipment are usually replaced earlier based on the replace time from national regulations.

5.3 Demand for water

5.3.1 General

The total demand of water depends on the elements the pipe systems service for. That includes volume for resident, factories & plants, municipal use, firefighting. The leakage volume of the pipelines is practically taken into account also, that depends on the experienced data of leakage ratio.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

5.3.2 Water demand estimate

The demand for water depends very much on local circumstances. The real measurement of consumption makes the estimate results accurate.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

In the absence of detail flow measurements or historical data the average daily of demand is practically obtained by estimating the domestic consumption per person per day (the per capita allowance) and multiplying it by the number of persons to be supplied. Some local criteria (such as GB 50013-2018) give quota data helping designing jobs.

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Where no better information exists, the overall allowance is usually taken as being between 150 and 250 l per person per day depending on social and climate conditions excluding specific industrial demands. In some areas consumption is up to 450 l per person per day.

The demand normally covers other use e.g., street cleaning and supplies to premises such as schools and hospitals which, added to the per capita allowance, give the overall allowance.

Regarding the peak flow factors, where water use is estimated on an average day basis, suitable factors are usually applied to give estimates of the expected demand in the peak week, peak day or hour. If no better information available, the multiplying factor for the peak day usually varies from 1,5 for populations above 10 000, to over two times (the average day demand) for population below 2 000. The peak hour rate in any day ranges from twice the average hour rate in that day for over 10 000 people to more than 5 times the average for less than 2 000. Where consumer storage is provided, the peak hour flow factors is usually significantly lower than those experienced data above.

5.3.3 Water for fire-fighting

The potential demand for water for fire-fighting purposes to be provided by the water supply system is very large in relation with rules from authorities. In these circumstances the authorities responsible for fire-fighting usually incline to seek alternative sources of emergency supply.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

5.4 System security

System security of water supply systems usually includes prevention of acts of vandalism, terrorism or other unlawful activity.

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: FooterPageRomanNumber

In general, the underground system will be secure, particular attention is given to above-ground pipework. Special designs are normally given to pumping station, service reservoirs and other above-ground structures, to deter unauthorized entry or interference with operation systems, as well as the possibility of contamination of potable water. Security fencing and monitoring systems are the practical ways for the places where risks are higher.

6 Design

6.1 Hydraulic design

6.1.1 Sizing

Mains and service ductile iron pipes are principally sized to meet the maximum specified flow rate having regard to the defined levels of service. Normally the capacity and flow requirements of the various system components depends much on the interaction of main, service reservoirs, pumping installations, optimum hydraulic and economic parameters like pumping cost and asset depreciation. In general, it is the local mains and principal mains used for direct supply which offer the capacity of sustaining peak flow rates or a subdivision thereof. Mains that supply reservoir is possible not to meet fully peak flow rates. National rules usually give the maximum and minimum flow rates. ISO 23991 also gives the experienced data.

In determining the capacity of a reservoir, a practical method is to take the balance between supply and demand into account. In addition, other aspects are usually considered as following (not limited):

- estimated time to repair bust main upstream;
- effect of pump or power failure;
- existence of alternative sources of supply;
- single or duplicate supply mains to storage;
- degree of telemetry monitoring;
- ratio of peak hour to average flow rate;
- demands with respect to water for industrial supplies, fire-fighting or other special circumstances.

6.1.2 Mains

6.1.2.1 General

Hydraulic calculations are the common jobs for designers to demonstrate that the system will:

- satisfy the estimated demand;
- operate at acceptable velocity; and
- operate within the required pressure range.

The designed diameters to satisfy the flow requirements for the hydraulic gradient are calculated by widely known calculation methods as following follow in this chapter clause.

The inner diameter of the pipe has a major influence on the pressure loss and therefor on the pumping energy consumptions. The greater internal diameter of the ductile iron pipe in comparison to the equivalent nominal diameter provides better economic results.

Formatted: Font: Cambria, 11 pt

Formatted: Font: Cambria, 11 pt

Formatted: Font: 11 pt

Formatted: HeaderCentered, Left, Space After: 0 pt, Line spacing: single, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Default Paragraph Font, Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.71 cm + 0.99 cm + 1.27 cm + 1.55 cm + 1.9 cm

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Adjust space between Latin and Asian text, Adjust space between Asian text and numbers, Tab stops: Not at 0.7 cm + 1.4 cm + 2.1 cm + 2.8 cm + 3.5 cm + 4.2 cm + 4.9 cm + 5.6 cm + 6.3 cm + 7 cm

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted

Formatted: Font: Cambria

Formatted: Font: Cambria

Formatted: Font: 10 pt

Formatted

Formatted: Font: 11 pt

Formatted