

FINAL DRAFT Technical Report

ISO/DTR 18146

ISO/TC 20/SC 14

Secretariat: ANSI

Voting begins on: 2025-04-18

Voting terminates on: 2025-06-13

Space systems — Space debris mitigation design and operation manual for spacecraft

Systèmes spatiaux — Conception de réduction des débris spatiaux a se te manuel d'utilisation pour les engins spatiaux

Document Preview

ISO/DTR 18146

https://standards.iteh.ai/catalog/standards/iso/b369c350-edce-4597-b03d-dfee88d512d7/iso-dtr-18146

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNO-LOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ISO/DTR 18146</u>

https://standards.iteh.ai/catalog/standards/iso/b369c350-edce-4597-b03d-dfee88d512d7/iso-dtr-18146



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office CP 401 • Ch. de Blandonnet 8 CH-1214 Vernier, Geneva Phone: +41 22 749 01 11 Email: copyright@iso.org Website: www.iso.org Published in Switzerland

Contents

Fore	word		vi	
Intro	oductio	n	viii	
1	Scop	е	1	
2	Normative reference			
3	Terms and definitions			
4	Abbroviated terms			
-	System lovel activities			
5	5 1	Conoral	<u>2</u> 2	
	5.2	Design for limiting the release of objects	3	
	5.2	5.2.1 Intents of requirements in ISO 24113 ^[1]	3	
		5.2.2 Work breakdown	3	
		5.2.3 Identification of released objects and design measures	4	
		5.2.4 Design measures	5	
		5.2.5 Monitoring during operation	5	
		5.2.6 Preventing failure	5	
	5.3	Prevention of break-up	5	
		5.3.1 General	5	
		5.3.2 Break-up caused by intentional behaviour or stored energy	6	
		5.3.3 Break-up caused by a collision with catalogued objects	7	
		5.3.4 Break-up caused by the impact of debris or meteoroid		
	5.4	Disposal after the end of mission to minimize interference with the protected regions	18	
		5.4.1 Intents of requirements in ISO 24113:2023	10	
		5.4.2 WORK Dreakdown	18 20	
		5.4.5 Procedure for determination of mission extension of termination	20	
		5.4.4 Disposal plan	22	
		5.4.6 Design of the function to remove spacecraft from the protected regions	23 24	
		5.4.7 Assurance of resources for disposal manoeuvre	24	
		5.4.8 Calculated reliability of disposal function up to the design life		
		5.4.9 Useful life limited items	4625	
		5.4.10 Health assessment procedure and contingency planning	25	
		5.4.11 Design the monitoring system to monitor the critical parameters	26	
		5.4.12 Assessment of the risk of debris impact	26	
		5.4.13 Operational remediations	27	
		5.4.14 Decision-making to extend or terminate the mission	28	
		5.4.15 Disposal	28	
		5.4.16 Registration of objects launched into outer space complying with the UN treaty	28	
		5.4.17 Specific subjects for GEO mission	28	
		5.4.18 Specific subjects for LEO mission	29	
		5.4.19 High elliptical orbit mission	29	
	5.5	Ground safety from re-entering objects	29	
		5.5.1 Intents of requirements in ISO 24113 ^[1]	29	
		5.5.2 WOIR DI EdRUOWII.	29	
		5.5.5 Identification of requirements	30 20	
		5.5.5 Design measures	30	
		5.5.6 Specific design for controlled re-entry in subsystem level	31	
		5.5.7 Notification	32	
		5.5.8 Conduct controlled re-entry and monitoring		
	5.6	Space debris mitigation plan		
	5.7	Quality and reliability assurance		
6	Dak	is related work in the development evelo	25	
0		Is-related work in the development cycle	33 25	
	0.1			

	6.2	Concept of debris-related work in phased planning	
	6.3	Mission analysis phase (phase 0 or pre-phase A)	
		6.3.1 General	
		6.3.2 Debris-related work	
	6.4	Feasibility phase (phase A)	
	6.5	Definition phase (phase B)	
		6.5.1 Work in phase B	
		6.5.2 WORK procedure	
	0.0	Development phase (phase C)	
		6.6.2 Conditions	
	67	Droduction phase (phase D)	
	0.7	671 Work in phase D	
		672 Qualification review	
	68	Utilization phase (phase F)	44
	0.0	6.8.1 Launch preparation	44
		6.8.2 Lift-off time	44
		6.8.3 Initial operation	45
		6.8.4 Normal operation	45
		6.8.5 Decision to terminate or extension of operations	
	6.9	Disposal phase (phase F)	
-	C		10
7	Syst	em-level information	
	/.1	Mission design	
	7.Z	Mass allocation	
	7.5	Propendit anotation	
	7.4		
8	Subs	system/component design and operation	
	8.1	General	
	8.2	Debris-mitigation measures and subsystem-level actions for realizing them	
	8.3	Propulsion subsystem	
		8.3.1 General	
		8.3.2 Debris-related design	
		8.3.3 Information of propulsion subsystems	
	tps://sta	8.3.4 Information in component design	tr=1814652
	8.4	Attitude and orbit control subsystem.	
		8.4.1 Debris-related designs	
		8.4.2 Information of AUCS	
	0 5	8.4.3 Information of component design	
	8.5	Power-supply subsystem	
		8.5.1 Debris-related designs	
		8.5.2 Information of power-supply subsystems	
	0.6	8.5.3 Information of component design	
	0.0	9.6.1 Debris related designs	
		0.0.1 DEDITS-TETALEU UESIGIIS	
		9.6.2 Information of component design	
	87	Structural subsystem	
	0.7	871 Dehris-related design	59
		872 Information of structural subsystems	59
	88	Thermal-control subsystem	60
	0.0	8.8.1 Debris-related design	60 60
		8.8.2 Information of thermal-control subsystem	60 60
Ann	ex A (ir	formative) Tabulated values of the optimal eccentricity vector	
Ann	ex B (ir	iformative) Optimal manoeuvre sequences	
Ann	ex C lin	formative) Example calculations	82
Ann	ex D (ir	formative) Disposal strategy and analysis for sample GEO satellite	88
	(m		

Annex E (informative) Sample format of space debris mitigation management plan prepared by owner (for phase B)	
Annex F (informative) Sample format of space debris mitigation plan prepared by contractor (for phase C)	
Bibliography	

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/DTR 18146

https://standards.iteh.ai/catalog/standards/iso/b369c350-edce-4597-b03d-dfee88d512d7/iso-dtr-18146

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 14, *Space systems and operations*.

This third edition cancels and replaces the second edition (ISO/TR 18146:2020), which has been technically revised.

The main changes compared to the previous edition are as follows:

- text has been updated to be aligned with ISO 24113:2023^[1];
- ISO 16127 was cancelled and requirements relating to prevention of break-up have been transferred to ISO 23312^[4]; references to ISO 16127 have been replaced by ISO 23312^[4];
- ISO 16164 was cancelled and requirements relating to disposal of satellites operating in or crossing low Earth orbit have been transferred to ISO 23312^[4]; references to ISO 16164 have been replaced by ISO 23312^[4];
- ISO 23339 was cancelled and requirements relating to mass estimation for residual propellant for disposal manoeuvres have been transferred to ISO 23312^[4]; references to ISO 23339 have been replaced by ISO 23312^[4];
- ISO 26872 was cancelled and requirements relating to disposal of satellites operating at geosynchronous altitude have been transferred to ISO 23312^[4]; references to ISO 26872 have been replaced by ISO 23312^[4] and ISO 26872:2019, Annexes A, B, C and D have been transferred to this document;
- in <u>5.3.2</u>, the rationale to restrict anti-satellite missile testing as a mean of intentional destruction has been added;
- in <u>5.3.4</u>, the methods to assess the probability of break-up caused by impact of debris have been added corresponding to the requirement of ISO 24113:2023,^[1] 7.3.1.2;
- characteristics of the space debris mitigation plan have been explained in detailed and <u>Annexes E</u> and <u>F</u> have been added to show the examples;

— other information relating to the changes in ISO 24113^[1] has been added.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at <u>www.iso.org/members.html</u>.

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ISO/DTR 18146</u>

https://standards.iteh.ai/catalog/standards/iso/b369c350-edce-4597-b03d-dfee88d512d7/iso-dtr-18146

Introduction

Coping with debris is essential to preventing the deterioration of the orbital environment and ensuring the sustainability of space activities. Effective actions are also taken to ensure the safety of those on the ground from re-entering objects that were disposed of from low Earth orbit.

Recently, the orbital environment has become so deteriorated by debris that actions are taken to prevent damage due to the impact. Collision avoidance manoeuvres are taken to avoid large debris (e.g. larger than 10 cm), which can be observed from the ground. Spacecraft design protects against micro-debris (even smaller than 1 mm) that can cause critical damage to vulnerable components.

This document explains the rationale of requirements in ISO $24113^{[1]}$ and provides information on the process or works to conform to those requirements. <u>Clause 5</u> informs the major space debris mitigation requirements.

In <u>Clause 6</u>, the information of life-cycle implementation of space debris mitigation related activities is provided.

In <u>Clause 7</u>, the system level aspects stemming from the space debris mitigation requirements are highlighted; while in <u>Clause 8</u>, the impacts at subsystem and component levels are detailed.

This document provides comprehensive information on the requirements and recommendations from ISO documents on the design and operation of the launch vehicles.

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO/DTR 18146

https://standards.iteh.ai/catalog/standards/iso/b369c350-edce-4597-b03d-dfee88d512d7/iso-dtr-18146

Space systems — Space debris mitigation design and operation manual for spacecraft

1 Scope

This document contains information on the design and operational practices for launch vehicle orbital stages for mitigating space debris.

This document provides information to engineers on what are required or recommended in documents on space debris mitigation developed by ISO/TC 20/SC 14 to reduce the growth of space debris by ensuring that spacecraft is designed, operated, and disposed of in a manner that prevents them from generating debris throughout their orbital lifetime.

2 Normative reference

There are no normative references in this document.

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>
- IEC Electropedia: available at <u>https://www.electropedia.org/</u>

ISO/DTR 18146

4 htAbbreviated terms atalog/standards/iso/b369c350-edce-4597-b03d-dfee88d512d7/iso-dtr-18146

A/M	area-to-mass
AOCS	attitude and orbit control system
CDR	critical design review
CFRP	carbon-fibre-reinforced plastic
CNES	Centre National d'Etudes Spatiales
CSpOC	Combined Space Operations Center (USA)
DAS	debris assessment software (NASA)
COTS	commercial off-the-shelf
DRAMA	debris risk assessment and mitigation analysis (ESA)
ESA	European Space Agency
FDIR	failure detection, isolation, and recovery
FMEA	failure mode and effect analysis

GEO	geosynchronous Earth orbit
GPSR	global positioning system receiver
IADC	Inter-Agency Space Debris Coordination Committee
IRU	inertial reference unit
LEO	low Earth orbit
MASTER	meteoroid and space debris terrestrial environment reference
NOTAM	notice to airmen and notice to mariners
OLI	operation time limited item
ORDEM	orbital debris engineering model
PDR	preliminary design review
PNF	probability of no failures
QA	quality assurance
QR	qualification review
RCS	reaction control system
SDA	Space Data Association Standards
SDR	system definition review and ards.iteh.ai
SDMP	space-debris-mitigation plan
STELA	semi-analytic tool for end of life analysis (CNES)
USSTRATCOM	United States strategic command
TCBM	transparency and confidence building measures
TLE	two-line element set
TT&C	telemetry tracking and command
UN	United Nations

5 System-level activities

5.1 General

To accomplish comprehensive activities for debris mitigation and protection work, the following steps are considered:

- a) identifying debris-related requirements, recommendations, and best practices;
- b) determining how to conform to these requirements, recommendations, and best practices;
- c) applying those methods early and throughout development and manufacturing to ensure sound debris mitigation capability in the final product;
- d) applying appropriate quality assurance and qualification program to ensure conformity with debris mitigation requirements;

e) applying appropriate procedures during operation/utilisation and disposal to implement proper space debris mitigation and protection.

This clause provides information useful for taking comprehensive actions at the system level. More detailed information for actions at subsystem and component levels is provided in <u>Clause 6</u>. The following specific subjects are emphasized:

- limiting the release of objects in protected orbital regions;
- preventing fragmentation in orbit (including intentional break-ups, and accidental break-ups caused by collision with trackable objects, impact of tiny debris, and stored energy);
- proper disposal at the end of operation;
- minimization of hazard on the ground from re-entering debris;
- quality, safety, and reliability assurance.

5.2 Design for limiting the release of objects

5.2.1 Intents of requirements in ISO 24113^[1]

ISO 24113:2023,^[1] 7.1 requires avoiding the intentional release of space debris into Earth orbit during normal operations, including general objects such as fasteners, fragments from pyrotechnics, slag from solid rocket motors, etc.

The following objects are of concern from an orbital debris mitigation standpoint:

- a) objects released as directed by mission requirements (not directly indicated in ISO 24113:2023,^[1] 7.1.1.1);
- b) mission-related objects, such as fasteners, apogee motor cases (ISO 24113:2023,^[1] 7.1.1.1);
- c) fragments and combustion products from pyrotechnic devices (ISO 24113:2023,^[1] 7.1.2.1);
- d) slag ejected from solid motors (ISO 24113:2023,^[1] 7.1.2.2).

It implies that if objects are unavoidably released despite requirements in ISO 24113:2023,^[1] 7.1.1.1, the orbital lifetime of such objects in LEO and interference with GEO is limited as described in ISO 24113:2023,^[1] 7.1.1.3.

5.2.2 Work breakdown

<u>Table 1</u> shows the work breakdown for the actions required to prevent the releasing of debris.

Process	Subjects	Major work
Preventive measures	Identification of released objects and design measures	 a) In the mission, which releases objects required by mission objectives, the effect on the orbital environment and the expected benefit for the mission are assessed." b) Taking preventive design to avoid releasing objects turning into space debris (ISO 24113:2023,^[1] 7.1). c) If objects might be released unintentionally, designers investigate design problems and take appropriate action during design phase (e.g. insulators). d) If release is unavoidable, designers estimate the orbital lifetime of released objects and check conformity with ISO 24113:2023,^[1] 7.1.1.3.
		e) When applying the solid motors, the possible generation of slag and its risk posed to space activities are assessed.
Risk detection	Monitoring during operation	a) Confirming that the orbiting characteristics of released parts are as estimated, if needed.b) If an unexpected object is detected, the origin of the objects is confirmed.
Countermeasures	Preventive measures	If an object is released unexpectedly, it is investigated, and appropriate action is taken to avoid repeating the release in the following missions.

Table 1 — Work breakdown for preventing the release of objects

5.2.3 Identification of released objects and design measures

The designed parts that are released are identified. Their orbital lifetimes are estimated. The propriety of their release is determined.

a) Mission requirements that require dispersing objects

Assessing the effects of proposed mission requirements on the environment. If the proposed mission can deteriorate the environment more than justified by its benefit, system engineering can suggest alternative approaches.

htExamples are: iteh.ai/catalog/standards/iso/b369c350-edce-4597-b03d-dfee88d512d7/iso-dtr-18146

- 1) The experiment called "WESTFORD NEEDLES," conducted in *1961 and* 1963, scattered 480 million needles in orbit. More than 100 clumps of needles have been registered and many of them are still in orbit. NASA, JSC, Orbital Debris Quarterly News, Volume 17^[2] reported that :"the legacy of Project West Ford can still be found in international policies, including the first major United Nations accord on activities in outer space that calls for international consultations before undertaking an experiment which might cause potentially harmful interference with activities of other State Parties in the peaceful exploration and use of outer space."
- 2) Missions that conduct intentional fragmentation (one of the major causes of deterioration of the orbital environment).
- b) Mission-related objects

Release of the following objects are avoided by appropriate mission and spacecraft design (ISO 24113:2023,^[1] 7.1.1):

- 1) fasteners for deploying and holding devices for panels or antennas;
- 2) nozzle closures and igniters of solid motors;
- 3) clamp bands that tie spacecraft and launch vehicles (usually as launch vehicle components).

NOTE The structural elements which support upper spacecraft used in the multi-payloads launching missions can be released due to their unavoidability. Disposal orbits of these elements are in accordance with ISO 24113:2023,^[1] 7.1.1.2. (These elements usually belong to the launch vehicle, not the spacecraft.)

c) Fragments and combustion products from pyrotechnic devices

Devices are selected and/or designed to avoid the production and release of the fragments of parts or the combustion by-products. Employing vehicle components that trap all fragments and combustion products inside for segregation (ISO 24113:2023,^[1] 7.1.2.1).

d) Combustion products from solid motors

Solid motors are designed not to generate slag in both GEO and LEO protected regions (higher than the manned orbit, approximately 400 km). (ISO 24113:2023,^[1] 7.1.2.2)

5.2.4 Design measures

In general, only devices that do not release parts into the space environment are selected.

CSpOC sometimes detects released cases of the apogee kick motors. The solid motors are not used for the apogee kick motors if they generate slag. Furthermore, it is refrained from disposing the motor cases into the orbit crossing the GEO protected region.

If parts would be released due to unavoidable reasons, the orbital lifetime of the parts and the risk of impact on another spacecraft are assessed. The orbital lifetime can be assessed according to ISO 27852^[3], which does not designate a specific analysis tool but rather expects that the users employ their reliable techniques depending upon orbit regime, so that designers can select any tool(s) which adhere to ISO 27852^[3] approved techniques. Available simplified tools that can be used to estimate the long term orbital lifetime are, for instance: NASA DAS (https://orbitaldebris.jsc.nasa.gov/mitigation/debris-assessment-software.html), ESA DRAMA (after creating an account at https://sdup.esoc.esa.int/ one can obtain a license before downloading), or CNES STELA (https://www.connectbycnes.fr/stela).

5.2.5 Monitoring during operation cument Preview

The released objects, if they are larger than 10 cm, are confirmed with ground-based space tracking facilities to ensure that they are released as expected and that their orbital lifetimes are sufficiently short. The space situation report provided by the CSpOC provides a good reference.

5.2.6 Preventing failure

If objects are released unexpectedly, the origin of the objects can be identified to help prevent recurrence in future missions. Because such phenomena can indicate a malfunction, the situation is reviewed carefully, and appropriate action taken to prevent further abnormal conditions.

5.3 Prevention of break-up

5.3.1 General

ISO 24113:2023,^[1] 7.2 requires the prevention of break-ups caused by intentional behaviour, stored energy, collision with catalogued objects, and impact of debris or meteoroid. In <u>5.3.2</u>, the first two subjects are discussed. The collision with catalogued objects is addressed in <u>5.3.3</u>; and the impact of debris and meteoroid in <u>5.3.4</u>.

ISO 23312:2022,^[4] 6.2 provides detailed requirements and procedures.

5.3.2 Break-up caused by intentional behaviour or stored energy

5.3.2.1 Work breakdown for preventing orbital break-up caused by intentional behaviour or stored energy

Table 2 shows the work breakdown for preventing orbital break-up caused by intentional behaviour or stored energy.

Table 2 — Work breakdown for preventing orbital break-ups caused by intentional behaviour or stored energy

Process	Subjects	Major work
Preventive measures	Mission assessment	Mission which involves the intentional break-up is assessed to justify its intention is essential for peaceful use of space, and its effect on the environment can be controllable. However, according to the resolution of G7 2023 held in Hiroshima, it is recognised that destructive direct-ascent anti-satellite missile testing can be refrained in terms of preservation of orbital environment and TCBM.
	Identification of sources of breakup	Identifying components that can cause fragmentation during or after oper- ation.
	Design measures	 a) Missions that involve intentional break-ups are not designed. b) Taking preventive design to limit the probability of accidental break-up. Confirm it in FMEA. c) Providing functions for to prevent break-ups after disposal.
Risk detection	Monitoring during operation	 a) Providing functions to monitor symptoms of break-up. b) Monitoring the critical parameters periodically. c) Taking immediate actions if the symptom of a malfunction that can lead to a breakup is detected.
Countermeasures	Preventive meas- ures for break-up	Performing the disposal operations to eliminate the risk of break-ups.

5.3.2.2 Identification of the sources of break-up

For post-operation break-ups, ISO 23312:2022^[4].6.2.2, identifies the following components as the most likely causes of the break-up of spacecraft:

- a) batteries in the electrical subsystem;
- b) propulsion mechanisms and associated components (such as engines, thrusters);
- c) pressurized components (such as tanks or bottles in the propulsion subsystems, or pneumatic control system, and heat pipes);
- d) rotating mechanisms.

5.3.2.3 Design measures

a) Intentional break-up

Missions that involve intentional break-ups are prohibited if the fragments would be ejected outer space. This includes attacks from the ground or airplane as well as self-destruction in orbit. For the case that there would be justification to conduct intentional destruction to improve ground safety, IADC Space Debris Mitigation Guidelines ^[5] state that it is conducted at sufficiently low altitudes so that orbital fragments are short-lived.