


Edition 4.2 2009-10

INTERNATIONAL STANDARD





THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2009 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester.

If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office 3, rue de Varembé CH-1211 Geneva 20 Switzerland Email: inmail@iec.ch

Email: inmail@iec.cl Web: www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Rease make sure that you have the latest edition, a corrigenda or an amendment might have been published.

■ Catalogue of IEC publications: <u>www.iec.ch/searchpub</u>

The IEC on-line Catalogue enables you to search by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, withdrawn and replaced publications.

■ IEC Just Published: www.iec.ch/online news/justpub

Stay up to date on all new IEC publications. Just Published details twice a month all new publications released. Available on-line and also by email.

■ Electropedia: <u>www.electropedia.org</u>

The world's leading online dictionary of electronic and electrical terms containing more than 20 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary online.

Customer Service Centre: www.ies.ch/webstore/custserv

If you wish to give us your feedback on this publication or need further assistance, please visit the Customer Service Centre FAQ or contact us:


Email: csc@iec.ch

Tel.: +41 22 919 02 11 Fax: +41 22 919 03 00



Edition 4.2 2009-10

INTERNATIONAL STANDARD



Electric irons for household or similar use - Methods for measuring performance



INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 97.060 ISBN 978-2-88910-102-3

CONTENTS

FO	REWORD	4
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Measurements for various types of irons	9
5	General conditions for measurements	10
	5.1 Ambient conditions	10
	5.2 Voltage for measurements	11
	5.4 Iron support for measurements	11
	5.5 Temperature measurement	11
	5.6 Cordless irons having a mains supply attachment	11
	5.7 Irons fitted with separate steam generator/boiler 5.8 Irons fitted with auto switch-off devices	11
		11
	5.9 Test sample	11
6	General requirements	11
U	6.1 Determination of mass	12
	6.2 Measurement of length of the supply cord	12 12
7	6.2 Measurement of length of the supply cord Temperature measurements	12
•	7.1 Measurement of heating-up time	12
	7.2 Measurement of initial overswing temperature and heating-up excess	12
	temperature	12
	7.3 Measurement of sole-plate temperature	13
	7.4 Determination of the hottest point 123ce-d1dd-4399-a3c9-9df29a8f9242/lec-6f	
	7.5 Measurement of temperature distribution	
_	7.6 Measurement of cyclic fluctuation of temperature of the hottest point	
8	Assessment of the spray function	
	8.1 Determination of the mass of spray	
^	8.2 Determination of the spray pattern	
9	Measurements concerning steaming operation	
	9.1 Measurement of heating-up time for steaming operation	
	9.2 Measurement of steaming time, steaming rate and water leakage rate9.3 Determination of mass of a shot of steam	
10	Assessment of smoothing	
.0	10.1 Creasing of test cloth	
	10.2 Conditioning of the iron	
	10.3 Ironing	
	10.4 Ironing with shot of steam	
	10.5 Evaluation	
11	Measurement of input power and energy consumption	23
	11.1 Measurement of input power	23
	11.2 Measurement of energy consumption	
	11.3 Ironing efficiency	24

12	Asse	ssment of sole-plate	24
	12.1	Determination of smoothness of the sole-plate	24
	12.2	Measurement of scratch resistance of sole-plate	25
	12.3	Determination of adhesion of polytetrafluorethylene	0.7
40	Maga	(PTFE) coating or similar coating on sole-plate	
13		surement of thermostatic stability	
		Heating test	
		Determination of drift of thermostat	
14		rmination of total steaming time for hard water	_
		For non-pressurised steam irons	
		For pressurised steam irons or instantaneous steam irons	
15			31
16		mation at the point of sale	31
		(informative) Measurement of steaming time, steaming rate and water	
	-	ate for pressurized steam irons or instantaneous steam irons	
		(normative) Ironing board	46
		(normative) Cotton cloth	
Ann	nex D	(informative) Classification of electric irons	50
	4		
_		 Arrangement for measuring the sole-plate temperature 	
		– Variation of sole-plate temperature after switching-on	
Figu	ure 3	– Determination of spray pattern	34
Figu	ure 4	– Test apparatus	35
Figu	ure 5	- Creasing tool - Wrapping rod and pencil	36
Figu	ure 7	Circular and rectangular blocks	37
Figu	ure 8	- Conditioning of the iron	37
Figu	ure 9	- Ironing	38
Figu	ure 10	- Ironing	38
Figu	ure 11	Comparison charts	39
Figu	ure 12	2 – Test apparatus for smoothness of sole-plate	41
Figu	ure 13	3 – Scratch	42
Figu	ure 14	I – Positions of cutting area	43
•		5 – Apparatus for drop test	
		6 – Test apparatus for total steaming time	
_		1 – Measurements concerning steaming operation	
_		1 – Example of construction of the ironing-board	
ı ıyı	uie D.	T - Example of construction of the fronting-board	∓0
Tab	le 1 –	- Measurements of various types of irons	9
		- Classes of scratch resistance	26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTRIC IRONS FOR HOUSEHOLD OR SIMILAR USE – METHODS FOR MEASURING PERFORMANCE

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter
- 5) IEC itself does not provide any attestation of conformity Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- All users should ensure that they have the latest edition of this publication. 3c9-9df29a8f9242/iec-603 II-2002
 - 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60311 has been prepared by subcommittee 59E: Ironing and pressing appliances, of IEC technical committee 59: Performance of household electrical appliances.

This consolidated version of IEC 60311 consists of the fourth edition (2002) [documents 59E/148/FDIS and 59E/149/RVD], its amendment 1 (2005) [documents 59L/22/FDIS and 59L/24/RVD] and its amendment 2 (2009) [documents 59L/67/FDIS and 59L/68/RVD].

The technical content is therefore identical to the base edition and its amendments and has been prepared for user convenience.

It bears the edition number 4.2.

A vertical line in the margin shows where the base publication has been modified by amendments 1 and 2.

Annexes B and C form an integral part of this standard.

Annexes A and D are for information only.

In this standard, the following print types are used:

– test specifications: in italic type

notes: in small roman typeother texts: in roman type

Words in **bold** in the text are defined in clause 3.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- · amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The "colour inside" logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

IEC 60811:200

nttps://standards.iteh.a/wix/a/stan/ardXiec/75123ce-d1dd-4399-a3c9-9df29a8f9242/iec-60311-200

ELECTRIC IRONS FOR HOUSEHOLD OR SIMILAR USE – METHODS FOR MEASURING PERFORMANCE

1 Scope

This International Standard applies to electric irons for household or similar use.

The purpose of this standard is to state and define the principal performance characteristics of electric irons for household or similar use which are of interest to the user and to describe the standard methods for measuring these characteristics.

Electric irons covered by this standard include

- dry irons;
- steam irons:
- vented steam irons with motor pump;
- spray irons;
- steam irons with separate water reservoir or boiler/generator having a capacity not exceeding 5 l.

This standard is concerned neither with safety nor with performance requirements.

NOTE The primary characteristic to be taken into account in assessing the performance of an electric iron is its basic ability to produce a smooth finish to textile materials, without risk of scorching or other damage. It has not proved possible to devise a single method which will measure this characteristic in a consistently reproducible way and measurements have therefore been included to check certain factors, such as the temperature of the sole-plate at the mid-point, sole-plate temperature distribution, etc., which affect the basic characteristic. In evaluating the results, it must be realized that, while a very exceptional result in any one of them may significantly affect performance, there is considerable latitude in the combination of results which will give satisfactory ironing performance, and too much significance should not be attached to minor differences in any one result.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60051-1:1997. Direct acting indicating analogue electrical measuring instruments and their accessories – Part 1: Definitions and general requirements common to all parts

IEC 60454-3-3:1998, Pressure-sensitive adhesive tapes for electrical purposes — Part 3: Specifications for individual materials — Sheet 3: Polyester film tapes with rubber thermoplastic adhesive

IEC 60734:2001, Household electrical applicances – Performance – Hard water for testing

ISO 105-F:1985, Textiles – Tests for colour fastness – Part F: Standard adjacent fabrics

ISO 1518:1992, Paints and varnishes – Scratch test

ISO 2409:1992, Paints and varnishes - Cross-cut test

ISO 3758:1991, Textiles – Care labelling code using symbols

ISO 3801:1977, Textiles – Woven fabrics – Determination of mass per unit length and mass per unit area

ISO 6330:2000, Textiles - Domestic washing and drying procedures for textile testing

ISO 7211-2:1984, Textiles – Woven fabrics – Construction – Methods of analysis – Part 2: Determination of number of threads per unit length

ISO 9073-2: 1995, Textiles – Test methods for nonwovens – Part 2: Determination of thickness

ISO 13934-1:1999, Textiles – Tensile properties of fabrics – Part 1: Determination of maximum force and elongation at maximum force using the strip method

3 Terms and definitions

For the purposes of this standard the following definitions apply.

3.1

electric iron

portable appliance, which has an electrically heated sole-plate and is used for ironing textile materials

NOTE In this standard, "electric iron" is referred to as "iron".

3.2

thermostatic iron

iron fitted with a thermostat, the setting of which can be adjusted manually to alter the soleplate temperature over a range and maintain it within certain limits

3.3

electric iron with non-self-resetting thermal cut-out

iron fitted with a non-self-resetting thermal cut-out, such as a fusible link, for the purpose of disconnecting the heating element if the iron attains excessive temperature

3.4

dry iron

iron having neither means to produce and supply steam nor to spray water onto textile materials while ironing

3.5

steam iron

iron having means to produce and supply steam to textile materials while ironing. It can be provided with means to supply a shot of steam

3.5.1

shot-of-steam iron

iron provided with means to supply a shot of steam to textile materials while ironing

3.5.2

shot of steam

single emission of an increased volume of steam from the sole-plate for a short duration

3.5.3

vented steam iron

steam iron in which steam is produced when the water contacts the sole-plate, the water reservoir being at atmospheric pressure.

NOTE The water reservoir may be incorporated in the iron or connected by a hose to the iron.

3.5.4

pressurized steam iron

steam iron in which steam is produced in a boiler at a pressure exceeding 50 kPa

NOTE The boiler may be incorporated in the iron or connected by a hose to the iron.

3.5.5

instantaneous steam iron

steam iron in which small quantities of water are pumped from the water reservoir and in which steam is produced when the water contacts the walls of the boiler/generator, the water reservoir being at atmospheric pressure

NOTE The water reservoir and the boiler are connected to the iron by a tube.

3.5.6

vented steam iron with motor pump

vented steam iron in which the water is pumped from the internal water reservoir to the steam chamber by means of an (electric) motor pump

3.6

spray iron

iron provided with means to spray water onto textile materials while ironing

3.7

rated voltage

3.7.1

rated voltage

voltage assigned to the iron by the manufacturer

3.7.2

rated voltage range

range of voltage assigned to the iron by the manufacturer, expressed in terms of its lower and upper limits

3.8

rated input

input power of the iron under normal operating conditions assigned by the manufacturer

3.9

sole-plate

flat surface of the iron, which is heated electrically and pressed against textile materials while ironing

3.10

mid-point

point of the sole-plate in the geometrical centre of the centre-line of the sole-plate.

If this point is on a steam outlet, a groove or a cover, the nearest point of the sole-plate on the centre-line as is practicable is chosen

3.11

upright position

vertical still position for a heel-standing iron or normal resting position according to the manufacturer's instructions for other than a heel-standing iron

3.12

cordless iron

3.12.1

cordless iron

iron which is connected to the supply mains only when placed on its stand

3.12.2

cordless iron having a mains supply attachment

cordless iron which is provided, in addition, with a detachable part to which the supply cord is fixed, and which can be connected to the supply mains directly during ironing

3.13

auto switch-off device

device provided by the manufacturer to switch off the heating element if the iron is not moved for a stated period of time and not intended to activate a 'standby mode' or any kind of 'low power mode'

4 Measurements for various types of irons

The performance of the iron is determined by the measurements indicated in Table 1. Relevant measurements for various types of irons are indicated in Table 1 by x.

Measurements are performed in the order given in Table 1.

Table 1 - Measurements of various types of irons

	Item of measurement	Thermo- static dry irons	Thermostatic dry irons with non-self-resetting thermal cut out	Thermostatic steam irons and vented steam irons with a motor pump	Thermo- static steam irons with non-self resetting thermal cut out	Cordless irons	Cordless irons having a mains supply attach- ment
6.1	(Determination of mass)	LDX-//2	(X U X	VI X ILL	x	х	х
6.2	(Measurement of length of the supply cord)	Dxcu	dex)	Peviev	V x	х	х
7.1	(Measurement of heating-up time)	/x (X 60211-2	x	х	х	х
7.2	(Measurement of initial overswing temperature and heating-up excess temperature)	/stanlard/i	x 123ce-	d1dd-4399-a. x	3c9-9df29a x	18f9242/ie x	c-60311-200
7.3	(Measurement of sole plate temperature)	X	х	х	х	х	х
7.4	(Determination of the hottest point)	x	х	х	х	х	х
7.5	(Measurement of temperature distribution)	х	х	х	х	х	х
7.6	(Measurement of cyclic fluctuation of temperature of the hottest point)	х	х	х	х	х	х
8	(Assessment of spray function)	(x)	(x)	(x)	(x)	(x)	(x)
9.1	(Measurement of heating-up time for steaming operation)	х	х	х	х	х	х
9.2	(Measurement of steaming time)			х	х		х

ı	tem of measurement	Thermo- static dry irons	Thermostatic dry irons with non-self-resetting thermal cut out	Thermostatic steam irons and vented steam irons with a motor pump	Thermo- static steam irons with non-self resetting thermal cut out	Cordless irons	Cordless irons having a mains supply attach- ment
9.2	(Measurement of steaming rate)			х	х	х	х
9.3	(Determination of mass of a shot of steam)			(x)	(x)	(x)	(x)
10	(Assessment of smoothing)	х	х	х	x	X	х
10.4	(Ironing with shot of steam)			(x)	(X)	(x)	(x)
11.1	(Measurement of input power)	х	х	x	1	x	х
11.2	(Measurement of energy consumption)	х	х	×	X	X	х
12.1	(Determination of smoothness of the sole-plate)	х	x	(*)	x	x	х
12.2	(Measurement of scratch resistance of sole-plate)	x	×	(x)	×	х	х
12.3	(Determination of adhesion of polytetra-fluorethylene (PTFE) coating or similar coating on sole-plate)	tps://s	(3 × 0)	axite	h.xi)	х	х
13	(Measurement of thermostatic stability)	x	X	x	х	х	х
14 s://st	(Determination of total steaming time for hard water)	/standard/i	IEC 60811:2	002 d1dd-4399-a	x 3c9-9df29a	18f9242/ie	x c-60311-2(

NOTE 1 Measurements for the spray iron are determined according to the table, whether it is of thermostatic type, steam or shot of-steam-producing type, cordless iron type, or cordless iron having mains supply attachment type.

For the non-steam-producing spray irons, the measurements for dry irons are applied.

Steam and spray irons are tested with water container empty.

NOTE 2 (x) means if applicable.

NOTE 3 Reporting the data should be made according to the testing authorities.

5 General conditions for measurements

Unless otherwise specified, the measurements are conducted under the following conditions.

5.1 Ambient conditions

The measurements are conducted at an ambient temperature of 20 °C \pm 5 °C, and the place for the measurements shall be free from any draughts.

5.2 Voltage for measurements

The voltage to be applied to the iron under measurement is that required to give the rated input under steady conditions. If an input power range is marked on the iron, the voltage is that required to give the mean of the input power range.

5.3 Steady conditions

The steady conditions for measurements are considered to be reached 30 min after switchingon of the iron or when the thermostat has operated four times, if this occurs earlier.

5.4 Iron support for measurements

The iron is placed on the three pointed metallic supports while under measurement. The three pointed supports are constructed so that they support the sole-plate of the iron horizontally at least 100 mm above the base surface on which the iron is placed.

For cordless irons, the iron is placed on its stand.

5.5 Temperature measurement

The temperature of the iron is measured by a fine-wire thermocouple, the wire diameter of which shall not exceed 0,3 mm.

Accuracy of the measuring instrument shall be better than, or equal to, class 1 in IEC 60051-1.

A movable silver disk, having a diameter of 10 mm and a thickness of 1 mm, rests on the top of a pointed ceramic tube which contains the thermocouple wires in two separate bores. An example of the arrangement is shown in Figure 1

The centre of the silver disk is pressed on to the sole-plate of the iron by applying a force of at least 1 N. In order to improve the heat transfer between the silver disk and the sole-plate, silicone grease or heat transfer paste can be used.

For the measurement of cordless irons, except cordless irons having a mains supply attachment, a thermocouple with silver disk as shown in Figure 1 is attached to the sole-plate directly.

5.6 Cordless irons having a mains supply attachment

Cordless irons having a mains supply attachment are tested as conventional irons. 100-603 II -2002

5.7 Irons fitted with separate steam generator/boiler

Irons fitted with separate steam generator/boiler have to be kept in ironing mode under measurements.

5.8 Irons fitted with auto switch-off devices

Irons fitted with auto switch-off devices have to be kept in ironing mode under measurements.

5.9 Test sample

A new sample is used for the test of clause 13.

5.10 Irons with additives

If the manufacturer requires the use of specific additives as an integral part of the functioning of the iron, then the iron shall be tested using the additives.

6 General requirements

6.1 Determination of mass

For all types of irons without separate water reservoir or boiler/generator, the mass is measured without the supply cord. The supply cord is removed from the iron by disconnection from the terminals or by removing the connector.

For steam irons with a separate water reservoir or boiler/generator, the mass is measured in two steps:

- the total mass of the system, not filled up with water, and
- the iron with the interconnection hose.

The mass is expressed in grams, rounded off to one decimal place.

For cordless irons, the mass is measured without its stand.

6.2 Measurement of length of the supply cord

The length of the supply cord of irons without separate water reservoir or boiler/generator is measured from the inlet point of the iron or connector to the inlet point of the plug including any cord guards.

The length is expressed in meters, rounded off to the nearest 50 mm.

7 Temperature measurements

7.1 Measurement of heating-up time

The iron is placed on the three metallic supports; for cordless irons, the iron is placed on its stand (see 5.4), and the thermosouple is attached at the mid-point of the sole-plate.

Starting from ambient temperature, the iron is heated up with the voltage specified in 5.2, the thermostat, if any, set at the highest temperature.

The time necessary for the temperature to exceed the ambient temperature by 180 K is measured, and is expressed in minutes and seconds.

7.2 Measurement of initial overswing temperature and heating-up excess temperature

The iron is placed on the three metallic supports, for cordless irons, the iron is placed on its stand (see 5.4), and a thermocouple is attached at the mid-point of the sole-plate.

The iron is switched on, with the voltage specified in 5.2.

Using a recording-type instrument, the time and temperature are measured at the mid-point with the thermostat set at the 1 dot marking position and at the highest position over five successive cycles to produce a graph of the type shown in Figure 2.

The thermostat is first set to the 1 dot marking position. If there is no dot marking, the thermostat is so adjusted as to obtain an average temperature of the sole-plate as close as possible to 95 °C under steady conditions.