



Designation: **D2974—13** **D2974 – 14**

Standard Test Methods for Moisture, Ash, and Organic Matter of Peat and Other Organic Soils¹

This standard is issued under the fixed designation D2974; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 These test methods cover the measurement of moisture content, ash content, and organic matter in peats and other organic soils, such as organic clays, silts, and mucks. Test Method **D2216** provides an alternative method for determining moisture content in mineral soils and rock.

1.1.1 *Test Method A*—Moisture is determined by drying peat or organic sample at $110 \pm 5^\circ\text{C}$.

1.1.2 *Test Method B*—Alternative moisture method which removes the total moisture in two steps: (1) evaporation of moisture at room temperature, (2) subsequent oven drying of air dried sample at $110 \pm 5^\circ\text{C}$. This method is used when the peat is to be used as fuel.

1.1.3 *Test Method C*—Ash content of a peat or organic soil sample, for general purposes, is determined by igniting oven dried sample from moisture content determination in a furnace at $440 \pm 40^\circ\text{C}$.

1.1.4 *Test Method D*—Ash content of a peat or organic soil sample, for materials used for fuel, is determined by igniting oven dried sample from moisture content determination in a furnace at $750 \pm 38^\circ\text{C}$.

1.2 Test Method A should be used for general classification, except for use of the peat as a fuel. Test Method B should be used when peats are being evaluated for use as a fuel.

1.3 The values stated in SI units are to be regarded as the standard. No other units of measurement are included in this standard. Use Practice **D6026** for determining significant digits to report.

1.4 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice **D6026**.

1.4.1 The procedures used to specify how data are collected/recorded or calculated in this standard are regarded as the industry standard. In addition, they are representative of the significant digits that generally should be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user's objectives; and it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope of this standard to consider significant digits used in analysis methods for engineering design.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This test method offers a set of instructions for performing one or more specific operations. This document cannot replace education or experience and should be used in conjunction with professional judgment. Not all aspects of this test method may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care by which the adequacy of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D653 Terminology Relating to Soil, Rock, and Contained Fluids

¹ These test methods are under the jurisdiction of ASTM Committee **D18** on Soil and Rock and are the direct responsibility of Subcommittee **D18.22** on Soil as a Medium for Plant Growth.

Current edition approved ~~June 1, 2013~~ Nov. 1, 2014. Published ~~July 2013~~ November 2014. Originally approved in 1971. Last previous edition approved in ~~2007~~ 2013 as **D2974—07a** **D2974 – 13**. DOI: ~~10.1520/D2974-13~~ 10.1520/D2974-14.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard

[D2216 Test Methods for Laboratory Determination of Water \(Moisture\) Content of Soil and Rock by Mass](#)

[D2944 Practice of Sampling Processed Peat Materials](#)

[D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction](#)

[D4753 Guide for Evaluating, Selecting, and Specifying Balances and Standard Masses for Use in Soil, Rock, and Construction Materials Testing](#)

[D6026 Practice for Using Significant Digits in Geotechnical Data](#)

[E145 Specification for Gravity-Convection and Forced-Ventilation Ovens](#)

3. Terminology

3.1 Definitions:

3.1.1 For ~~common~~ definitions of common technical terms in this standard, refer to Terminology [D653](#).

4. Summary of Test Methods

4.1 *Test Method A*—Moisture is determined by drying a peat or organic soil sample at $110 \pm 5^\circ\text{C}$. The moisture content is expressed as a percent of the oven dry mass.

4.2 *Test Method B*—This is an alternative moisture method which removes the total moisture in two steps: (1) evaporation of moisture in air at room temperature (air-drying), and (2) the subsequent oven drying of the air-dried sample at $110 \pm 5^\circ\text{C}$. This method is used when the peat is to be used as fuel. The moisture content is expressed as both a percent of the oven dry mass and of the as received mass.

4.3 *Test Methods C and D*—Ash content of a peat or organic soil sample is determined by igniting the oven-dried sample from the moisture content determination in a furnace at $440 \pm 40^\circ\text{C}$ (Test Method C) or $750 \pm 38^\circ\text{C}$ (Test Method D). The substance remaining after ignition is the ash. The ash content is expressed as a percentage of the mass of the oven-dried sample.

4.4 Organic matter is determined by subtracting percent ash content from one hundred.

5. Significance and Use

5.1 This test method can be used to determine the moisture content, ash content, and percent organic matter in soil.

5.2 The percent organic matter is important in the following: (1) classifying peat or other organic soil, (2) geotechnical and general classification purposes, and (3) when peats are being evaluated as a fuel.

NOTE 1—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice [D3740](#) are generally considered capable of competent and objective testing/sampling/inspection/etc. Users of this standard are cautioned that compliance with Practice [D3740](#) does not in itself assure reliable results. Reliable results depend on many factors; Practice [D3740](#) provides a means of evaluating some of those factors.

6. Apparatus

6.1 *Oven*, meeting the requirements of [E145](#) and capable of being regulated to a constant temperature of $110 \pm 5^\circ\text{C}$.

6.2 The temperature of $110 \pm 5^\circ\text{C}$ is quite critical for organic soils. The oven should be checked for “hot spots” to avoid possible ignition of the specimen.

6.3 *Furnace*, capable of producing constant temperatures of $440 \pm 40^\circ\text{C}$ and $750 \pm 38^\circ\text{C}$.

6.4 *Balance or Scale*, a balance or scale for determining the mass of the soil having a minimum capacity of 500 g and meeting the requirements of Guide [D4753](#) for a balance or scale of 0.01 g readability.

6.5 *Rubber Sheet, Oil Cloth*, or other non-absorbent material.

6.6 *Evaporating Dishes*, of high silica or porcelain of not less than 100-mL capacity.

6.7 *Aluminum Foil*, heavy-duty.

6.8 *Porcelain Pan, Spoons*, and equipment of the like.

6.9 *Desiccator*.

7. Sampling and Test Specimens

7.1 Place a representative field sample on a rubber sheet, oil cloth, or equivalent material and mix thoroughly.

7.2 Reduce the sample to the quantity required for a test specimen by quartering.

7.3 Place the test specimen and the remaining sample in separate waterproof containers.

7.4 Work rapidly to prevent moisture loss or perform the operation in a room with a high humidity.