



Designation: **D2028/D2028M – 10 D2028/D2028M – 15**

Standard Specification for Cutback Asphalt (Rapid-Curing Type)¹

This standard is issued under the fixed designation D2028/D2028M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

1. Scope

1.1 This specification covers cutback petroleum asphalts of the rapid-curing type for use in the construction and treatment of pavements.

1.2 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

2. Referenced Documents

2.1 *ASTM Standards:*²

[D5 Test Method for Penetration of Bituminous Materials](#)

[D95 Test Method for Water in Petroleum Products and Bituminous Materials by Distillation](#)

[D113 Test Method for Ductility of Bituminous Materials](#)

[D140 Practice for Sampling Bituminous Materials](#)

[D402 Test Method for Distillation of Cutback Asphalt](#)

[D2042 Test Method for Solubility of Asphalt Materials in Trichloroethylene](#)

[D2170 Test Method for Kinematic Viscosity of Asphalts \(Bitumens\)](#)

[D2171 Test Method for Viscosity of Asphalts by Vacuum Capillary Viscometer](#)

[D3143 Test Method for Flash Point of Cutback Asphalt with Tag Open-Cup Apparatus](#)

[D7553 Test Method for Solubility of Asphalt Materials in N-Propyl Bromide](#)

3. Properties

3.1 The cutback asphalt shall not foam when heated to application temperature and shall conform to the requirements prescribed in [Table 1](#).

4. Test Methods

4.1 The material shall be sampled in accordance with Practice [D140](#), and the properties enumerated in this specification shall be determined in accordance with the following ASTM methods:

4.1.1 *Flash Point (Tag Open-Cup)*—Test Method [D3143](#).

4.1.2 *Viscosity, Kinematic*—Test Method [D2170](#).

4.1.3 *Viscosity, at 60°C [140°F]*—Test Method [D2171](#).

4.1.4 *Distillation*—Test Method [D402](#).

NOTE 1—If a 100-mL graduate does not permit sufficiently close readings to determine conformity to these specifications with the desired accuracy, receivers graduated in 0.1-mL divisions shall be used.

4.1.5 *Penetration*—Test Method [D5](#).

4.1.6 *Ductility*—Test Method [D113](#).

4.1.7 *Solubility in Trichloroethylene*—*Trichloroethylene or N-Propyl Bromide*—Test Method [D2042/D7553](#).

4.1.8 *Water*—Test Method [D95](#).

¹ This specification is under the jurisdiction of ASTM Committee [D04](#) on Road and Paving Materials and is the direct responsibility of Subcommittee [D04.40](#) on Asphalt Specifications.

Current edition approved ~~June 1, 2010~~Jan. 1, 2015. Published ~~June 2010~~January 2015. Originally approved in 1963. Last previous edition approved in ~~2004~~2010 as ~~D2028-97(2004)~~D2028/D2028M – 10. DOI: ~~10.1520/D2028-10~~10.1520/D2028_D2028M-15.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.