



Designation: **C785 – 08 C785 – 08 (Reapproved 2015)**

Standard Specification for Nuclear-Grade Aluminum Oxide Pellets¹

This standard is issued under the fixed designation C785; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification applies to pellets of aluminum oxide that may be ultimately used in a reactor core, for example, as filler or spacers within fuel, burnable poison, or control rods. In order to distinguish between the subject pellets and “burnable poison” pellets, it is established that the subject pellets are not intended to be used as neutron-absorbing material.

1.2 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

2. Referenced Documents

2.1 *ASTM Standards:*²

[C559 Test Method for Bulk Density by Physical Measurements of Manufactured Carbon and Graphite Articles](#)

[C809 Test Methods for Chemical, Mass Spectrometric, and Spectrochemical Analysis of Nuclear-Grade Aluminum Oxide and AluminumOxide-Boron Carbide Composite Pellets](#)

[C859 Terminology Relating to Nuclear Materials](#)

[C1233 Practice for Determining Equivalent Boron Contents of Nuclear Materials](#)

[E105 Practice for Probability Sampling of Materials](#)

2.2 *ANSI Standard:*

[ANSI/ASME NQA-1 Quality Assurance Requirements for Nuclear Facility Applications](#)³

2.3 *U.S. Government Document:*

[Code of Federal Regulations, Title 10, Part 50, Energy \(10CFR50\) Domestic Licensing of Production and Utilization Facilities](#)⁴

3. Terminology

3.1 *Definitions*—Terms shall be defined in accordance with Terminology [C859](#) except for the following:

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *buyer*—organization issuing the purchase order.

3.2.2 *pellet*—fabricated geometric shape of aluminum oxide having a chemical composition as described in Section 4.

3.2.3 *pellet lot*—that quantity of pellets produced from one aluminum oxide powder lot using one set of process parameters whose limits have been agreed upon between the seller and the buyer.

3.2.4 *powder lot*—a specified quantity of aluminum oxide powder made up of powders from one or more sources, blended together such that samples taken in accordance with 7.1 can be considered as representative of the entire specified quantity.

3.2.5 *seller*—aluminum oxide pellet supplier.

4. Chemical Composition

4.1 Use analytical chemistry methods in accordance with Methods [C809](#) or alternate methods agreed upon between the buyer and the seller.

¹ This specification is under the jurisdiction of ASTM Committee C26 on Nuclear Fuel Cycle and is the direct responsibility of Subcommittee C26.03 on Neutron Absorber Materials Specifications.

Current edition approved Dec. 1, 2008; Jan. 1, 2015. Published December 2008/January 2015. Originally approved in 1976. Last previous edition approved in 1993/2008 as C785 – 93/C785 – 08, ^{ε1} which was withdrawn May 2002 and reinstated in December 2008. DOI: 10.1520/C0785-08; DOI: 10.1520/C0785-08R15.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, <http://www.ansi.org>.

⁴ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, <http://www.access.gpo.gov>.