



Designation: D5088 – 15

## Standard Practice for Decontamination of Field Equipment Used at Waste Sites<sup>1</sup>

This standard is issued under the fixed designation D5088; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reappraisal.

### 1. Scope\*

1.1 This practice covers the decontamination of field equipment used in the sampling of soils, soil gas, sludges, surface water, and groundwater at waste sites which are to undergo both physical and chemical analyses.

1.2 This practice is applicable only at sites where chemical (organic and inorganic) wastes are a concern. It is not intended for use at radiological, mixed (chemical and radiological), or biohazard sites. This practice does not address regulatory requirements for the handling, labeling, shipping, or storing of wastes or samples.

1.3 Practices are included for the decontamination of equipment which comes into contact with the sample matrix (sample contacting equipment) and for ancillary equipment that has not contacted the portion of sample to be analyzed (non-sample contacting equipment), but which must be cleaned to avoid spreading of contamination.

1.4 This practice is intended for use when field equipment used for sampling will be decontaminated in the field or returned from the field. Information on the construction of field decontamination facilities and non-sample contacting equipment decontamination is also provided.

1.5 This practice is based on commonly recognized methods by which equipment may be decontaminated. The practices described for sample contacting equipment are commonly prescribed. Background studies are included in the References at the end of this standard (**12345**). The user is reminded of the importance of proper decontamination planning to minimize the amount of decontamination wastes generated and to reduce or eliminate the use of cleaning agents that are themselves hazardous. Quality Assurance/Quality Control (QA/QC) samples that document decontamination effectiveness can be used to modify or enhance decontamination techniques. Decontamination at radiologically contaminated sites should refer to Practice **D5608**.

1.6 This practice is applicable to most conventional sampling equipment constructed of metallic and synthetic materials. The manufacturer of a specific sampling apparatus should be contacted or the manufacturer's manuals reviewed if there is concern regarding the reactivity of a decontamination rinsing agent or the temperatures that could affect the equipment. Plastic components and gasket materials could be damaged by some of the stronger reagents or high temperatures.

1.7 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.8 *This practice offers an organized collection of information or a series of options and does not recommend a specific course of action. This document cannot replace education or experience and should be used in conjunction with professional judgment. Not all aspects of this practice may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care by which the adequacy of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process.*

1.9 *This standard does not purport to address the safety problems associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

### 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

**D653 Terminology Relating to Soil, Rock, and Contained Fluids**

**D5608 Practices for Decontamination of Field Equipment Used at Low Level Radioactive Waste Sites**

### 3. Terminology

3.1 *Definitions:*

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee **D18** on Soil and Rock and is the direct responsibility of Subcommittee **D18.21** on Groundwater and Vadose Zone Investigations.

Current edition approved Jan. 15, 2015. Published February 2015. Originally approved in 1990. Last previous edition approved in 2008 as D5088 – 02(2008). DOI: 10.1520/D5088-15.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

\*A Summary of Changes section appears at the end of this standard

3.1.1 For definitions of general technical terms used within this Practice refer to Terminology **D653**.

3.2 *Definitions Specific to this Practice:*

3.2.1 *equipment rinsate blank*—a sample collected by using analyte-free water rinsed over/through equipment that has been decontaminated, and is analyzed for the parameters of interest.

3.2.2 *field cleaning*—the process of cleaning dirty sampling equipment so it can be returned or moved to a final decontamination in a condition that will minimize the potential of contaminant transfer from a site. At a minimum, this should consist of washing with soap and water, and rinsing with tap water.

3.2.3 *potable water*—water that is safe and satisfactory for drinking and cooking.

3.2.4 *sample contacting equipment*—equipment that comes in direct contact with the sample or portion of sample that will undergo chemical analyses or physical testing (for example, a bailer used to sample a groundwater well, split-spoon sampler, soil gas sampling probe, tubing used to bring a groundwater sample to the surface, etc.).

#### 4. Summary of Practice

4.1 When decontaminating equipment, the user will need to evaluate whether the equipment materials are plastics or metals, the types of contaminants (inorganic vs. organic) that will be analyzed for, whether the equipment contacts the sample, the type of exposure (for example, whether exposed to oils, grease, tars, soils, or simply water), and the data-quality objectives. These issues will help to determine the practices to be used to decontaminate the equipment. The decontamination process should use the minimum effort and materials demonstrated to satisfy that the required decontamination has been achieved. The use of hazardous materials should be used only when additional rinses, heat, and other techniques have been found inadequate and the equipment cannot be substituted with disposable or dedicated equipment.

4.2 Two different practices are presented for the decontamination of sample-contacting and non-sample contacting equipment. The practices have been developed based on a review of research studies, current state and federal guidelines. In general, sample contacting equipment should be washed with a detergent solution followed by a series of control water and deionized water rinses. Non-sample contacting equipment should be washed with water or without a detergent solution depending on the type and degree of contaminants and rinsed with control water. Although such techniques may be difficult to perform in the field, they may be necessary to most accurately evaluate low concentrations of the chemical constituent(s) of interest. Additional enhancements to the decontamination process include the use of hot water or steam for cleaning and or rinsing the equipment, and in some cases the use air drying or the use of heat near 100°C for a period of time

4.3 Prior to initiating a field program that will involve equipment decontamination, a site specific equipment decontamination protocol should be prepared for distribution to the individuals involved with the particular sampling program. Information to be presented in the protocol should include:

4.3.1 Site location and description,

4.3.2 Statement of the sampling program objectives and desired precision and accuracy, that is, is sampling effort for gross qualitative evaluation or for trace concentration, parameter specific evaluations,

4.3.3 Summary of available information regarding soil types, hydrogeology and anticipated chemistry of the materials to be sampled,

4.3.4 Listing of equipment that will be used for sampling and the materials or equipment that will be needed for decontamination,

4.3.5 An evaluation of the costs of the decontamination process including disposal, personnel time, Personal Protective Equipment (PPE) and other costs versus the use of less hazardous materials, the use of dedicated equipment, or use of disposable equipment.

4.3.6 Detailed step by step procedure for equipment decontamination for each piece or type of equipment to be utilized and practices for rinse fluids containment and disposal as appropriate,

4.3.7 Summary of QA/QC procedures and QA/QC samples to be collected to document decontamination completeness including specific type of chemical analyses and their associated detection limit, and

4.3.8 Outline of equipment decontamination verification report.

#### 5. Significance and Use

5.1 An appropriately developed, executed and documented equipment decontamination practice is an integral and essential part of waste site investigations. The benefits of its use include:

5.1.1 Minimizing the spread of contaminants within a study area and from site to site,

5.1.2 Reducing the potential for worker exposure by means of contact with contaminated sampling equipment or hazardous materials,

5.1.3 Improved data quality and reliability.

5.1.4 Minimizing the amount of decontamination fluids or wastes generated.

5.1.5 Reducing personnel exposures to chemicals used in, or released by decontamination.

5.1.6 Minimizing or eliminating the use of hazardous materials in the decontamination process, and

5.1.7 Selecting equipment based on total life-cycle costs including labor, waste containment, disposal, treatment and additional analytical costs, such as using dedicated or disposable equipment rather than decontaminating between uses.

5.2 This practice is not a substitute for a well-documented Quality Assurance/Quality Control (QA/QC) program. Because the ultimate test of a decontamination process is its ability to minimize erroneous data, a reasonable QA/QC program must be implemented.

5.3 This practice may not be applicable to all waste sites. When a sampling effort is completed to determine only the general range of chemical concentrations of interest, then less rigorous decontamination processes can be adequate. Less rigorous decontamination procedures may also be used when cleaning non-porous surfaces, such as metal surfaces as well.

Investigators should have the flexibility to modify the decontamination process with due consideration for the sampling objective or if QA/QC documentation supports alternative decontamination methods.

5.4 At sites where the reactivity of sampling equipment to decontamination washes creates concern for the generation of undesirable chemical by-products, or will potentially damage the equipment surfaces, for example, the use of an acid rinse on metal equipment, then use of dedicated sampling equipment should be considered.

5.5 This practice, where applicable, should be used before, between, and after the completion of sampling events.

5.6 This practice is appropriate for use at sites where chemical (organic and inorganic) contamination is known or expected. The application of this practice to other types of sites radiological, mixed (radiological and chemical), or biohazard contaminated sites is not applicable. The application of this practice to these types of sites should be undertaken with care and consideration, along with QA/QC documentation that supports the effectiveness of these decontamination techniques.

## 6. Reagents

6.1 *Detergent*, non-phosphate detergent solution.<sup>3</sup>

6.2 *Acid Rinse (inorganic desorbing agent)*, 10 % nitric or hydrochloric acid solution—made from reagent grade nitric or hydrochloric acid and deionized water (1 % is to be applied to low-carbon steel equipment). These materials are hazardous themselves and use should be minimized or eliminated when possible.

6.3 *Solvent Rinse (organic desorbing agent)*, isopropanol, acetone, or methanol; pesticide grade. These materials are hazardous themselves and use should be minimized or eliminated when possible.

6.4 *Control Rinse Water*, preferably from a water system of known chemical composition. In most cases, potable water is suitable for non-contacting equipment.

6.5 *Deionized Water*, water that is organic-free and deionized. Tap water that has been treated by passing through a standard deionizing resin column. As a minimum, the finished water should contain no detectable heavy metals or other inorganic compounds.

6.6 The use of acids, bases, and organic solvents requires that personnel have the appropriate Safety Data Sheets, be properly trained in their handling, have the appropriate PPE including appropriate respiratory protection, and have appropriate first-aid training and response equipment. The shipping and handling of these materials are regulated because of the hazardous nature of these materials. When these materials are used for decontamination, they can generate larger amounts of hazardous wastes that must be collected, properly containerized, stored and labeled, shipped and/or disposed.

<sup>3</sup> Liquinox or Detergent 8 or similar solution has been found suitable for this purpose. Detergent 8 is recommended for spray cleaning.

## 7. Apparatus

7.1 *Pressure Washer (Cold Water) or Steam Cleaner (Hot Water)*—Commercially available washers providing low volumes of water at high pressure. The hot water washers may be electrically powered or fueled for remote operation. Most pressure washers have the capability to inject detergents into the system.

NOTE 1—The use of pressure washers should consider the safety and protection of the personnel using them. Manufacturer operating literature or manuals typically contain safety precautions for the use of the equipment. Personnel may be exposed to backsplash, slippery surfaces or other hazards and should be appropriately protected. The use of high temperature water or steam can also result in burns.

7.2 *Ovens or Other Heat Sources*—For some equipment, extended drying (for example, 24 hours) at higher than room temperatures may be needed. Dependent on the equipment size and configuration standard laboratory draft ovens may be used. For field use, commercially available heated air handlers can be used.

NOTE 2—The use of ovens or air handlers should exchange fresh heated air to the equipment and not provide air that contains carbon fuel combustion or other contaminants that will contaminate the equipment being dried. Venting of the heated air should not be into an area occupied by personnel.

7.3 Standpipes, buckets, tubs, portable light-weight sinks, commercially available containers of adequate size for soaking, cleaning and rinsing equipment.

7.4 Scrub brushes, metal brushes.

7.5 *Decontamination Pad/Materials Collection*—Impermeable materials that can be placed on the ground to capture decontamination fluids of a size appropriate to the equipment and volumes. These can be polyethylene, HDPE, sheeting or other materials. Pre-formed and seamed liners are commercially available. Equipment to recover the fluids, such as pumps may also be required, along with tools or materials to repair any damage to the liner. For smaller items and volumes, a child swimming pool or equivalent can be used to contain decontamination fluids.

7.6 Materials to soak up spills, kitty litter, absorbent pads, etc.

7.7 Drums or buckets for decon fluids.

## 8. Field Decontamination Pad Construction

8.1 The design and construction of a decontamination pad should factor in the type of equipment, contaminants and amount of use the planned for the pad.

8.1.1 The decontamination pad should be sized to accommodate the equipment to be decontaminated while containing overspray or splashing or windblown particles.

8.1.2 The decontamination pad should not leak. When possible, the floor should be sloped to allow for the collection of fluids. Repair materials should be on hand for repair of the liner should damage occur.

8.1.3 Planning should include racks, stands, or other equipment needed during decontamination. If personnel will be in the pad, raised grates or other methods may be appropriate to prevent personnel slips and falls and to prevent damage to the