

# SLOVENSKI STANDARD SIST ISO 3657:1998

01-december-1998

## þ]j Ưg\_Y`]b`fUgh`]bg\_Y`a Uý cVY`]b`c`^U!`8 c`c Yj Ub^Y`ýhYj ]`U`i a ]`^Yb^U

Animal and vegetable fats and oils -- Determination of saponification value

Corps gras d'origines animale et végétale -- Détermination de l'indice de saponification

# Ta slovenski standard je istoveten z: ISO 3657:1988

	<u>SIST ISO 3657:1998</u>	
	https://standards.iteh.ai/catalog/standards/sist/a517f9e7-00c0-4c51-b354- 25bebdfa5855/sist-iso-3657-1998	
<u>ICS:</u> 67.200.10	Üæ•dậ•∖^ÁşiÁ0ãçæ†•∖^ {æz[à^ÁşiÁį bæ	Animal and vegetable fats and oils

SIST ISO 3657:1998

en



# iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 3657:1998 https://standards.iteh.ai/catalog/standards/sist/a517f9e7-00c0-4c51-b354-25bebdfa5855/sist-iso-3657-1998

# INTERNATIONAL STANDARD



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION ORGANISATION INTERNATIONALE DE NORMALISATION МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ

# Animal and vegetable fats and oils – Determination of saponification value

Corps gras d'origines animale et végétale + Détermination de l'indice de saponification

# (standards.iteh.ai)

<u>SIST ISO 3657:1998</u> https://standards.iteh.ai/catalog/standards/sist/a517f9e7-00c0-4c51-b354-25bebdfa5855/sist-iso-3657-1998

ISO

3657

Second edition 1988-12-15

Reference number ISO 3657 : 1988 (E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at VIEW least 75 % approval by the member bodies voting.

International Standard ISO 3657 was prepared by Technical Committee ISO/TC 34, Agricultural food products. SIST ISO 3657:1998

https://standards.iteh.ai/catalog/standards/sist/a517f9e7-00c0-4c51-b354-

This second edition cancels and replaces the first edition (ISO 3657/31977) of which it constitutes a technical revision.

© International Organization for Standardization, 1988 •

## Animal and vegetable fats and oils – Determination of saponification value

## 1 Scope

This International Standard specifies a method for the determination of the saponification value of animal and vegetable fats and oils.

If mineral acid is present, the results given by this method are not interpretable unless the mineral acids are determined separately.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 661 : 1980, Animal and vegetable fats and oils — Preparation of test sample.

ISO 5555 : 1983, Animal and vegetable fats and oils – Sampling.

#### 3 Definition

For the purposes of this International Standard, the following definition applies.

**saponification value**: The number of milligrams of potassium hydroxide required to saponify 1 g of fat under the conditions specified in this International Standard.

### 4 Principle

Boiling of a sample under reflux with ethanolic potassium hydroxide solution, followed by titration of the excess potassium hydroxide with standard volumetric hydrochloric acid solution.

### 5 Reagents

All reagents shall be of recognized analytical grade and the water used shall be distilled water or water of equivalent purity.

**5.1** Potassium hydroxide,  $c(KOH) \approx 0.5 \text{ mol/l solution in}$ 95 % (V/V) ethanol.

This solution shall be colourless or straw yellow. A stable (standards, procedures, proced

A supernative the required amount of potassium hydroxide and 5 g of aluminium pellets for 1 h, then distil immediately. Dissive the required amount of potassium hydroxide in the distillate. Allow to stand for several days, then decant the clear supernatant liquid from the potassium carbonate deposited.

b) Add 4 g of aluminium tertbutylate to 1 litre of ethanol and allow the mixture to stand for several days. Decant the supernatant liquid and dissolve in it the required amount of potassium hydroxide. Allow to stand for several days, then decant the clear supernatant liquid from the potassium carbonate deposited.

Store this solution in a brown or yellow glass bottle fitted with a rubber stopper, and decant it for use.

**5.2** Hydrochloric acid, standard volumetric solution, c(HCI) = 0.5 mol/I.

**5.3** Phenolphthalein, 10 g/l solution in 95 % (V/V) ethanol, or alkali blue 6B, 20 g/l solution in 95 % (V/V) ethanol.

5.4 Boiling aids.

#### 6 Apparatus

Usual laboratory apparatus and, in particular, the following.

**6.1 Conical flask**, of 250 ml capacity, made of alkaliresistant glass and having a ground neck.

9.3 Blank test

tion (5.1) but omitting the test portion.

10 Expression of results

 $I_{\rm s} = \frac{(V_0 - V_1) \times c \times 56,1}{m}$ 

Number of determinations

Carry out two determinations on the same test sample.

The saponification value  $I_s$  is given by the formula

6.2 Reflux condenser, with a ground glass joint which fits the conical flask (6.1).

Heating device (e.g. a water-bath, electric hot-plate or 6.3 other suitable apparatus). A naked flame is not suitable.

Burette, of 50 ml capacity, graduated in 0,1 ml divi-6.4 sions.

Pipette, of 25 ml capacity. 6.5

#### 7 Sampling

Sampling shall be carried out in accordance with ISO 5555.

#### Preparation of the test sample 8

Prepare the test sample in accordance with ISO 661.

#### Procedure 9

#### **Test portion** 9.1

where

9.4

 $V_0$  is the volume, in millilitres, of the standard volumetric hydrochloric acid solution (5.2) used for the blank test;

Carry out a blank test following the procedure specified in 9.2, using again 25,0 ml of the ethanolic potassium hydroxide solu-

is the volume, in millilitres, of the standard volumetric hydrochloric acid solution (5.2) used for the determination;

c is the exact concentration, in moles per litre, of the staniTeh STANDAR dard volumetric hydrochloric acid solution (5.2);

 $m_{\rm c}$  is the mass, in grams, of the test portion (9.1).

(standards liten.al

Take as the result the arithmetic mean of the two determina-

Weigh, to the nearest 5 mg, about 2 g of the test sample ISO 3(clause 11) is satisfied. tions, provided that the requirement for repeatability

(clause 8) into a conical flask (6.1) https://standards.iteh.ai/catalog/standards/sist/a517f9e7-00c0-4c51-b354-

NOTE – The test portion of 2 g has been determined on the basis of saponification values of 170 + 200 -

saponification values of 170 to 200. For other saponification values, the mass should be altered accordingly so that about half the ethanolic potassium hydroxide solution is neutralized.

#### 9.2 Determination

9.2.1 Using a pipette (6.5), add to the test portion 25,0 ml of the ethanolic potassium hydroxide solution (5.1) and some boiling aids (5.4). Connect the reflux condenser (6.2) to the flask, place the flask on the heating device (6.3) and boil gently, shaking from time to time, for 60 min or for 2 h in the case of oils and fats having a high melting point and which are difficult to saponify.

9.2.2 Add to the hot solution 0,5 ml to 1 ml of the phenolphthalein solution (5.3) and titrate with the standard volumetric hydrochloric acid solution (5.2) until the pink colour of the indicator just disappears. If the solution is strongly coloured, use 0.5 ml to 1 ml of alkali blue 6B solution (5.3).

#### 11 Repeatability

The difference between the values of two determinations, carried out in rapid succession (or simultaneously) by the same analyst using the same apparatus on the same test sample, shall not exceed 0,5 % (relative) of the arithmetic mean value.

NOTE - This figure for repeatability has been accepted historically.

#### 12 Test report

The test report shall specify the method used and the result obtained. It shall also mention all operating details not specified in this International Standard, or regarded as optional, together with details of any incidents which may have influenced the result.

The test report shall include all information necessary for the complete identification of the sample.

### UDC 665.2/.3:543.851.5

Descriptors : animal fats, vegetable fats, animal oils, vegetable oils, chemical analysis, determination, saponification number.

Price based on 2 pages