



Designation: D6711 – 15

Standard Practice for Specifying Rock to Fill Gabions, Revet Mattresses, and Gabion Mattresses¹

This standard is issued under the fixed designation D6711; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers the sizes and quality of rock to fill gabions and mattresses. The term mattress as used in this standard shall include the terminology of gabion mattresses and revet mattresses used in Specifications [A974](#) and [A975](#).

1.2 This practice does not cover the sizes and quality of rock for other erosion control uses such as riprap or drainage.

1.3 This practice does not cover the material properties or construction of gabions or mattresses.

1.4 The values in this practice are in English units and are to be regarded as the standard. SI units are given.

1.5 *This practice offers a set of instructions for performing one or more specific operations. This document cannot replace professional judgment. Not all aspects of this practice may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care by which the adequacy of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process.*

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

[A974 Specification for Welded Wire Fabric Gabions and Gabion Mattresses \(Metallic-Coated or Polyvinyl Chloride \(PVC\) Coated\)](#)

¹ This practice is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.25 on Erosion and Sediment Control Technology.

Current edition approved May 1, 2015. Published June 2015. Originally approved in 2001. Last previous edition approved in 2008 as D6711 – 01 (2008). DOI: 10.1520/D6711-15.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

[A975 Specification for Double-Twisted Hexagonal Mesh Gabions and Revet Mattresses \(Metallic-Coated Steel Wire or Metallic-Coated Steel Wire With Poly\(Vinyl Chloride\) \(PVC\) Coating\)](#)

[D4992 Practice for Evaluation of Rock to be Used for Erosion Control](#)

[D5519 Test Methods for Particle Size Analysis of Natural and Man-Made Riprap Materials](#)

3. Terminology

3.1 *gabion, n—in erosion control*, a wire mesh container of variable size and interconnected with other similar containers. It is filled with rock to form flexible, permeable, monolithic structures.

3.2 *mattress, n—in erosion control*, a wire mesh container uniformly partitioned into internal cells with relatively small height in relation to other dimensions. Mattresses have smaller mesh openings than the mesh used for gabions.

4. Summary of Practice

4.1 The designer shall establish the suitable sizes, weight, and quality of rock for project use, and examine sources to ensure that the required rock is available.

4.2 Rock shall be delivered to the work site in a manner to minimize its reduction in sizes (breakdown) during the handling of the rock, and then placed and secured within the assembled and interconnected gabion or mattress.

NOTE 1—Clean crushed concrete may be used as an alternative when rock is not available.

5. Significance and Use

5.1 Gabions and mattresses, described in Specifications [A974](#) and [A975](#), are placed on sites for soil stabilization and to prevent soil erosion. Their ability to function properly depends on their stability, which is partly dependent upon the rocks filling them. Rock sizes should be chosen to prevent individual rocks from falling through the mesh of the gabions or mattresses. The rock also has to withstand natural weathering processes during the life of the project that would cause it to breakdown to sizes smaller than the wire mesh opening dimensions.

6. Bulk Filling Materials

6.1 Rock to fill gabions or mattresses may be any natural deposit of the required sizes or may be crushed rock produced by any suitable method and by the use of any device that yields the required size limits chosen in Section 7.

6.2 Rocks shall be hard, angular to round, durable, and of such quality that they shall not disintegrate on exposure to water or weathering during the life of the structure. Guidance for selecting durable rock is given in Practice D4992.

7. Standard Sizes of Rock

7.1 Guidance for measurement of rock sizes is given in Test Method D5519. Sizes of rock to fill gabions and mattresses are chosen on the basis of the mesh sizes, the structure's thickness, and the limits shown in 7.4. Fabrication of sieves to determine particle size is given in Test Method D5519.

7.2 Within each range of sizes, the rock shall be large enough to prevent individual pieces from passing through the mesh openings stated in Specifications A974 and A975. Each range of sizes may allow for a variation of 5% oversize rock by number of particles, or 5% undersize rock by number of particles, or both.

7.3 In all cases, the sizes of any oversize rock shall allow for the placement of two or more layers of rock within each gabion

compartment, and two or more layers of rock within each mattress compartment dependent upon the height of the mattresses. In all cases, undersize and oversize rock shall be placed within the interior of the gabion or mattress compartment and shall not be placed on the exposed surface of the structure. There shall be a maximum limit of 5% undersize or 5% oversize rock, or both, within each gabion or mattress compartment.

7.4 The recommended dimensions of rock are given in the following:

Type of Structure	Nominal Thickness		Rock Sizes	
	in.	(m)	in.	(mm)
Gabion Mattress or Revet Mattress	6	(0.17)	3–5	76–127
Gabion Mattress or Revet Mattress	9	(0.23)	3–5	76–127
Gabion Mattress or Revet Mattress	12	(0.30)	4–8	102–203
Gabion	12	(0.30)	4–8	102–203
Gabion	18	(0.50)	4–8	102–203
Gabion	36	(1.00)	4–8	102–203

7.5 Within the table, there shall be a full range of sizes between the upper and lower limits.

8. Keywords

8.1 erosion control; gabions; mattresses; rock

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/