



SLOVENSKI STANDARD
SIST EN 301 087 V7.2.1:2003

01-december-2003

8][JhUb]WW] b] hYY_ca i b] UWg] g]ghYa fUhU&]b ZUhU&žlE GdYWZ UWU nU
cdfYa c g]ghYa UVUhb] dcgHUf6 GGLE'F UX]g_]j]X]_f GA %&%&%fUh] JWU+&%%ž
]nXU% - , Ł

Digital cellular telecommunications system (Phase 2 and Phase 2+) (GSM); Base Station System (BSS) equipment specification; Radio aspects (GSM 11.21 version 7.2.1 Release 1998)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 087 V7.2.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/bf25811b-78b9-436e-8ba8-882e9276d80c/sist-en-301-087-v7-2-1-2003>

Ta slovenski standard je istoveten z: EN 301 087 Version 7.2.1

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---	--

SIST EN 301 087 V7.2.1:2003

en

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 087 V7.2.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/bf25811b-78b9-436e-8ba8-882e9276d80e/sist-en-301-087-v7-2-1-2003>

ETSI EN 301 087 V7.2.1 (2000-04)

European Standard (Telecommunications series)

**Digital cellular telecommunications system (Phase 2 & Phase 2+);
Base Station System (BSS) equipment specification;
Radio aspects
(GSM 11.21 version 7.2.1 Release 1998)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)



[SIST EN 301 087 V7.2.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/bf25811b-78b9-436e-8ba8-882e9276d80c/sist-en-301-087-v7-2-1-2003>



Reference

REN/SMG-021121Q7R1

Keywords

Digital cellular telecommunications system,
 Global System for Mobile communications (GSM)

ETSI

650 Route des Lucioles
 F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
 Association à but non lucratif enregistrée à la
 Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 087 V7.2.1:2003](#)
<https://standards.iteh.ai/catalog/standards/sist/bf25811b-78b9-436e-8ba8-882e9276d80c/sist-en-301-087-v7-2-1-2003>

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).
 In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
 Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
 The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
 All rights reserved.

Contents

Intellectual Property Rights	8
Foreword	8
1 Scope	9
2 References	10
3 Definitions, abbreviations, frequency bands and channels	11
3.1 Definitions	11
3.2 Abbreviations	12
3.3 Frequency bands and channels	12
3.3.1 Frequency bands	12
3.3.2 Channels and channel numbering	12
4 General test conditions and declarations.....	13
4.1 Output power and determination of power class	13
4.2 Specified frequency range	13
4.3 Frequency hopping	14
4.4 RF power control.....	14
4.5 Downlink discontinuous transmission (DTX)	14
4.6 Test environments	14
4.6.1 Normal test environment.....	14
4.6.2 Extreme test environment	15
4.6.2.1 Extreme temperature	15
4.6.3 Vibration.....	15
4.6.4 Power supply	15
4.7 Acceptable uncertainty of measurement equipment	16
4.8 Interpretation of measurement results.....	19
4.9 Selection of configurations for testing	20
4.10 BTS Configurations.....	20
4.10.1 Receiver diversity	20
4.10.2 Duplexers.....	20
4.10.3 Power supply options.....	21
4.10.4 Ancillary RF amplifiers	21
4.10.5 BSS using antenna arrays.....	22
5 Format and interpretation of tests	23
6 Transmitter	24
6.1 Static Layer 1 functions	24
6.1.1 Test purpose.....	24
6.1.2 Test case	24
6.1.3 Essential conformance	25
6.1.4 Complete conformance	25
6.1.5 Requirement reference	25
6.2 Phase error and mean frequency error	25
6.2.1 Test purpose.....	25
6.2.2 Test case	25
6.2.3 Essential conformance	26
6.2.4 Complete conformance	26
6.2.5 Requirement reference	27
6.3 Mean transmitted RF carrier power	27
6.3.1 Test purpose.....	27
6.3.2 Test case	27
6.3.3 Essential conformance	27
6.3.4 Complete conformance	28
6.3.5 Requirement reference	28

6.4	Transmitted RF carrier power versus time.....	28
6.4.1	Test purpose.....	28
6.4.2	Test case	28
6.4.3	Essential conformance	29
6.4.4	Complete conformance.....	29
6.4.5	Requirement reference	30
6.5	Adjacent channel power	30
6.5.1	Spectrum due to modulation and wideband noise.....	30
6.5.1.1	Test purpose	30
6.5.1.2	Test case.....	30
6.5.1.3	Essential Conformance.....	31
6.5.1.4	Complete conformance.....	33
6.5.1.5	Requirement reference	33
6.5.2	Switching transients spectrum.....	33
6.5.2.1	Test purpose	33
6.5.2.2	Test case.....	33
6.5.2.3	Essential conformance.....	35
6.5.2.4	Complete conformance.....	35
6.5.2.5	Requirement reference	35
6.6	Spurious emissions from the transmitter antenna connector.....	35
6.6.1	Conducted spurious emissions from the transmitter antenna connector, inside the BTS transmit band.....	36
6.6.1.1	Test Purpose.....	36
6.6.1.2	Test Case.....	36
6.6.1.3	Essential conformance.....	36
6.6.1.4	Complete conformance.....	36
6.6.1.5	Requirement Reference.....	36
6.6.2	Conducted spurious Emissions from the transmitter antenna connector, outside the BTS transmit band	36
6.6.2.1	Applicability (Phase 2)	36
6.6.2.1.1	Test Purpose	37
6.6.2.1.2	Test Case	37
6.6.2.1.3	Essential conformance	38
6.6.2.1.4	Complete conformance	38
6.6.2.1.5	Requirement Reference	38
6.6.2.2	Applicability (Phase 2+)	38
6.6.2.2.1	Test Purpose	38
6.6.2.2.2	Test Case	39
6.6.2.2.3	Essential conformance	39
6.6.2.2.4	Complete conformance	40
6.6.2.2.5	Requirement Reference	40
6.7	Intermodulation attenuation.....	40
6.7.1	Test purpose.....	40
6.7.2	Test case	41
6.7.3	Essential Conformance	42
6.7.4	Complete conformance	42
6.7.5	Requirement reference	43
6.8	Intra Base Station System intermodulation attenuation	43
6.8.1	Test purpose.....	43
6.8.2	Test case	43
6.8.3	Essential conformance	44
6.8.4	Complete conformance	44
6.8.5	Requirement reference	44
7	Receivers	45
7.1	Static Layer 1 receiver functions (nominal error ratios)	45
7.1.1	Test Purpose	45
7.1.2	Test Case.....	45
7.1.3	Essential conformance	46
7.1.4	Complete conformance	46
7.1.5	Requirement Reference	47
7.2	Erroneous Frame Indication Performance	47

7.2.1	Test Purpose	47
7.2.2	Test Case.....	47
7.2.3	Essential conformance	48
7.2.4	Complete conformance	48
7.2.5	Requirement reference	48
7.3	Static Reference Sensitivity Level.....	48
7.3.1	Test Purpose	48
7.3.2	Test Case.....	48
7.3.3	Essential conformance	49
7.3.4	Complete conformance	49
7.3.5	Requirements Reference	51
7.4	Multipath Reference Sensitivity Level	51
7.4.1	Test Purpose	51
7.4.2	Test Case.....	51
7.4.3	Essential conformance	53
7.4.4	Complete conformance	53
7.4.5	Requirement Reference	58
7.5	Reference interference level	58
7.5.1	Test Purpose	58
7.5.2	Test Case.....	58
7.5.3	Essential conformance	60
7.5.4	Complete conformance	62
7.5.5	Requirements Reference	67
7.6	Blocking Characteristics.....	67
7.6.1	Test Purpose	67
7.6.2	Test Case.....	67
7.6.3	Essential conformance	70
7.6.4	Complete conformance	70
7.6.5	Requirements reference	70
7.7	Intermodulation characteristics.....	70
7.7.1	Test Purpose	70
7.7.2	Test Case..... https://standards.iteh.ai/catalog/standard/list/25811b-78b9-436e-8ba8-882e9276d80c/sist-en-301-087-v7-2-1-2003	70
7.7.3	Essential conformance	72
7.7.4	Complete conformance	72
7.7.5	Requirement Reference	72
7.8	AM suppression.....	73
7.8.1	Test Purpose	73
7.8.2	Test Case.....	73
7.8.3	Essential conformance	74
7.8.4	Complete conformance	74
7.8.5	Requirement Reference	74
7.9	Spurious emissions from the receiver antenna connector	74
7.9.1	Test Purpose	74
7.9.2	Test Case.....	74
7.9.3	Essential conformance	74
7.9.4	Complete conformance	75
7.9.5	Requirement Reference	75
8	Radiated spurious emissions	75
8.1	Test Purpose	75
8.2	Test Case	75
8.3	Essential conformance	76
8.4	Complete conformance	77
8.5	Requirement reference	77
9	Radio link management.....	77
9.1	General	77
9.2	Synchronization	77
9.2.1	Timing Tolerance.....	78
9.2.1.1	Test purpose	78
9.2.1.2	Test case	78

9.2.1.3	Essential conformance	78
9.2.1.4	Complete conformance	78
9.2.1.5	Requirement reference	78
9.3	Frame structure	79
9.3.1	BCCH Multiframe	79
9.3.1.1	Test purpose	79
9.3.1.2	Test case	79
9.3.1.3	Essential conformance	79
9.3.1.4	Complete conformance	79
9.3.1.5	Requirement reference	79
9.3.2	TDMA-frame structure	79
9.3.2.1	Test purpose	79
9.3.2.2	Test case	80
9.3.2.3	Essential conformance	80
9.3.2.4	Complete conformance	80
9.3.2.5	Requirement reference	80
9.4	Radio link measurements	80
9.4.1	Signal Strength	81
9.4.1.1	Measurement Accuracy	81
9.4.1.1.1	Test purpose	81
9.4.1.1.2	Test case	81
9.4.1.1.3	Essential conformance	81
9.4.1.1.4	Complete conformance	81
9.4.1.2	Selectivity of signal strength measurements	82
9.4.1.2.1	Test purpose	82
9.4.1.2.2	Test case	82
9.4.1.2.3	Essential conformance	83
9.4.1.2.4	Complete conformance	83
9.4.1.2.5	Requirement reference	83
9.4.2	Signal quality	84
9.4.2.1	Test purpose	84
9.4.2.2	Test case	84
9.4.2.3	Essential conformance	84
9.4.2.4	Complete conformance	84
9.4.2.5	Requirement reference	85
9.4.3	Idle channel signal level	85
9.4.3.1	Test purpose	85
9.4.3.2	Test case	86
9.4.3.3	Essential conformance	86
9.4.3.4	Complete conformance	86
9.4.3.5	Requirement reference	86
9.5	Adaptive frame alignment	86
9.5.1	Test purpose	86
9.5.2	Test case	87
9.5.3	Essential conformance	87
9.5.4	Complete conformance	88
9.5.5	Requirement reference	88
Annex A (informative): Testing of statistical parameters		89
A.1	General theoretical methodology	89
A.2	Detailed theoretical methodology	90
A.3	Limitations and corrections to the theoretical methodology	91
A.3.1	Independent errors	92
A.3.2	Gaussian distribution	92
A.3.3	Stationary random processes	92
A.3.4	Low error ratios	93
A.3.5	Total corrections	93

A.4	Alternative experimental methodology	93
A.5	Detailed definition of error events	94
Annex B (informative):	Description of special test equipment	95
B.1	Base Station System Test Equipment (BSSTE).....	95
B.1.1	Fading and multipath propagation simulator	95
B.2	Measurement set ups for TX intermodulation	95
B.2.1	Test set-up for Intermodulation Attenuation (6.7).....	96
B.2.1.1	RX-Band	96
B.2.1.2	Outside RX Band	96
B.2.2	Test set-up for Intra BSS Intermodulation Attenuation (6.8.)	97
B.2.2.1	RX-Band	97
B.2.2.2	TX-Band	97
Annex C (informative):	Number of samples needed for statistical testing	98
C.1	GSM 900; Number of samples for testing	98
C.2	DCS 1800; Number of Samples for Testing	118
Annex D (informative):	Change history	141
History		143

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 087 V7.2.1:2003](#)

<https://standards.iteh.ai/catalog/standards/sist/bf25811b-78b9-436e-8ba8-882e9276d80e/sist-en-301-087-v7-2-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by the Special Mobile Group (SMG).

The present document specifies the Radio Frequency (RF) test methods and conformance requirements for GSM 900 and DCS 1800 Base Station Systems (BSS)s. within the Digital cellular telecommunications system (Phase 2+).

The contents of the present document may be subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document, it will be resubmitted for formal approval procedure by ETSI with an identifying change of release date and an increase in version number as follows:

Version 7.x.y

iTeh STANDARD PREVIEW (standards.iteh.ai)

7 indicates Release 1998 of GSM Phase 2+.

[SIST EN 301 087 V7.2.1:2003](#)

x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
<https://standards.iteh.ai/digital-standards/gsm-900-and-dcs-1800-base-station-systems-phase-2-plus/>
882e9276d80c/sist-en-301-087-v7-2-1-2003

y the third digit is incremented when editorial only changes have been incorporated in the specification.

NOTE: The present document contains both essential conformance requirements and complete conformance requirements. Essential conformance requirements are those requirements which may be deemed sufficient for radio type approval purposes, complete conformance requirements cover all conformance aspects.

National transposition dates	
Date of adoption of this EN:	31 March 2000
Date of latest announcement of this EN (doa):	30 June 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2000
Date of withdrawal of any conflicting National Standard (dow):	31 December 2000

1 Scope

The present document specifies the Radio Frequency (RF) test methods and conformance requirements for GSM 900 and DCS 1800 Base Station Systems (BSS)s. These have been derived from, and are consistent with, the core GSM specifications specified in the requirements reference subclause of each test.

The present document is applicable to BSS meeting the requirements of either GSM Phase 2 or GSM Phase 2+. Unless otherwise stated, all tests are applicable to BSS meeting Phase 2 and/or Phase 2+ GSM requirements, because the requirements of the Phase 2 and Phase 2+ core GSM specifications which are referenced in the test are consistent. Most differences between Phase 2 and Phase 2+ requirements represent Phase 2+ features which are optional for the BSS to support.

For each test, two conformance requirements are specified:

- essential conformance requirements;
- complete conformance requirements.

Essential conformance requirements are those which are required:

- a) to ensure compatibility between the radio channels in the same cell;
- b) to ensure compatibility between cells, both co-ordinated and unco-ordinated;
- c) to ensure compatibility with existing systems in the same or adjacent frequency bands;
- d) to verify the important aspects of the transmission quality of the system.

iTech STANDARD PREVIEW

Essential conformance requirements are sufficient to verify the performance of the equipment for radio type approval purposes, in countries where this is applicable.

Complete conformance requirements may be tested to verify all aspects of the performance of a BSS. These requirements are intended to be used by manufacturers and operators to allow conformance and acceptance testing to be performed in a consistent manner; the tests to be performed should be agreed between the parties.

In some tests there are separate requirements for micro-BTS and BTS. If there is no separate requirement for a micro-BTS, the requirements for the BTS apply to a micro-BTS.

In the present document, the reference point for RF connections (except for the measurement of mean transmitted RF carrier power) is the antenna connector, as defined by the manufacturer. The present document does not apply to repeaters or RF devices which may be connected to an antenna connector of a BSS, except as specified in subclause 4.10.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
 - For a specific reference, subsequent revisions do not apply.
 - For a non-specific reference, the latest version applies.
 - A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
 - For this Release 1998 document, references to GSM documents are for Release 1998 versions (version 7.x.y).
- [1] GSM 01.04 (ETR 350): "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 04.22 (ETS 300 946): "Digital cellular telecommunications system (Phase 2+); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [3] GSM 05.01: "Digital cellular telecommunications system (Phase 2); Physical layer on the radio path; General description".
THE STANDARD PREVIEW
(standards.iteh.ai)
- [4] GSM 05.02 (ETS 300 574): "Digital cellular telecommunications system (Phase 2); Multiplexing and multiple access on the radio path".
- [5] GSM 05.03 (ETS 300 575): "Digital cellular telecommunications system (Phase 2); Channel coding".
<https://standards.iteh.ai/catalog/standards/sist/bf25811b-78b9-436e-8ba8-882c9276d80/sist-en-301-087-v7-2-1-2003>
- [6] GSM 05.04 (ETS 300 576): "Digital cellular telecommunications system (Phase 2); Modulation".
- [7] GSM 05.05 (ETS 300 577): "Digital cellular telecommunications system (Phase 2); Radio transmission and reception".
- [8] GSM 05.08 (ETS 300 578): "Digital cellular telecommunications system (Phase 2); Radio subsystem link control".
- [9] GSM 05.10 (ETS 300 579): "Digital cellular telecommunications system (Phase 2); Radio subsystem synchronization".
- [10] GSM 08.20: "Digital cellular telecommunications system (Phase 2); Rate adaption on the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [11] ETS 300 019-1: "Equipment Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment Part 1-0: Classification of environmental conditions Introduction".
- [12] IEC 68-2: "Basic environmental testing procedures; Part 2: Tests".
- [13] IEC 721: "Classification of environmental conditions".
- [14] ETR 027: "Radio and Equipment Systems; methods of measurement for mobile radio equipment".
- [15] ETR 028: "Radio and Equipment Systems; Uncertainties in the measurement of mobile radio equipment characteristics".
- [16] ETS 300 113: "Radio Equipment and Systems; Land mobile service; Technical characteristics and test conditions for radio equipment intended for transmission of data (and speech) and having an antenna connector".

- [17] GSM 04.22 (ETSI 300 563): "Digital cellular telecommunications system (Phase 2); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [18] GSM 05.01: "Digital cellular telecommunications system (Phase 2+); Physical layer on the radio path; General description".
- [19] GSM 05.02 (ETSI 300 908): "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path".
- [20] GSM 05.03 (ETSI 300 909): "Digital cellular telecommunications system (Phase 2+); Channel coding".
- [21] GSM 05.04 (ETSI 300 959): "Digital cellular telecommunications system (Phase 2+); Modulation".
- [22] GSM 05.05 (ETSI 300 910): "Digital cellular telecommunications system (Phase 2+); Radio transmission and reception".
- [23] GSM 05.08 (ETSI 300 911): "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control".
- [24] GSM 05.10 (ETSI 300 912): "Digital cellular telecommunications system (Phase 2+); Radio subsystem synchronization".

3 Definitions, abbreviations, frequency bands and channels *(The STANDARD PREVIEW (standards.iteh.ai))*

3.1 Definitions SIST EN 301 087 V7.2.1:2003

For the purposes of the present document, the following terms and definitions apply:

Carrier Frequency: The centre of the ARFCN under test.

GSM: Unless otherwise specified, references to GSM include both GSM 900 and DCS1800.

BSS: In the present document, the term BSS (or base station subsystem) applies to both a BTS and integrated BSS. If a separate BSC is required to perform tests on a BTS, the BSC may be regarded as test equipment and the environmental conditions of the BSC need not be controlled.

pico-BTS: As defined in GSM 05.05 (Ref: TBD). In this EN, this also includes a BSS which incorporates a pico-BTS.

micro-BTS: As defined in GSM 05.05 (ETSI 300 577 [7] and ETSI 300 910 [22]). In this EN, this also includes a BSS which incorporates a micro-BTS.

normal BTS: Any BTS or BSS as defined by GSM 05.05 (ETSI 300 910) [7] which is not a micro-BTS.

BSSTE: Base Station System Test Equipment; see annex B.

manufacturer: In this EN, a reference to a manufacturer shall also apply to an agent of the manufacturer.

P-GSM: The primary GSM 900 band.

E-GSM: The extended GSM 900 band (includes P-GSM band).

R-GSM: The Railways GSM 900 band (includes P-GSM band and E-GSM band).

Relevant TX band (or relevant transmit band): The transmit band defined in subclause 3.3.1 for the frequency band of BTS declared by the manufacturer

Relevant RX band (or relevant receive band): The receive band defined in subclause 3.3.1 for the frequency band of BTS declared by the manufacturer

Operating band: The transmit and receive operating bands together comprise the frequency band supported by the BSS; (see subclause 4.2)

Circuit switched logical channels: All the standard GSM logical channels, including traffic channels (TCH), common control channels (RACH) and dedicated control channels (SDCCH, SACCH).

Packet switched logical channels: All the General Packet Radio Services (GPRS) packet data logical channels, including packet traffic channels (PDTCH and PACCH) and packet common control channels (PRACH).

3.2 Abbreviations

Unless otherwise stated, abbreviations used in the present document shall have the meaning given in GSM 01.04 (ETR 350) [1].

B	"Bottom"; the lowest frequency on which a test is performed.
M	"Middle"; a frequency in the middle portion of the operating band of the BSS on which a test is performed.
T	"Top"; the highest frequency on which a test is performed.

3.3 Frequency bands and channels

3.3.1 Frequency bands

The frequency bands for the Base Station System are given in table 1
ITEN STANDARD PREVIEW
(standards.iteh.ai)

Table 1: Frequency bands for GSM900 and DCS1800 Base Station Systems
SIST EN 301 087 V7.2.1:2003

	TX: 882e9276d935-960 MHz	RX: v7-2 890-915 MHz
P-GSM900	935-960 MHz	890-915 MHz
DCS1800	1805-1880 MHz	1710-1785 MHz
E-GSM900	925-960 MHz	880-915 MHz
R-GSM900	921-960 MHz	876-915 MHz

NOTE: It is up to the operator to choose any subset of these bands (or the complete band) on a location basis within a frequency band assigned to the operator by the authority responsible for frequency management issues.

3.3.2 Channels and channel numbering

The channel numbers (ARFCN) for the carrier frequencies (RF channels) within the frequency bands defined above (as defined in GSM 05.05 (ETSI 300 910) [7]), are given in table 2. Fl(n) is the frequency of the centre of the RF channel n in the lower band (=RX) and Fu(n) the corresponding frequency in the upper band (=TX).

Table 2: Channel Numbering: Frequencies are in MHz

P-GSM900	Fl(n)=890+0.2*n	1<=n<=124	Fu(n)=Fl(n)+45
E-GSM900	Fl(n)=890+0.2*n Fl(n)=890+0.2*(n-1024)	0 <=n<=124 975<=n<=1023	Fu(n)=Fl(n)+45
R-GSM900	Fl(n)=890+0.2*n Fl(n)=890+0.2*(n-1024)	0 <=n<=124 955<=n<=1023	Fu(n)=Fl(n)+45
DCS1800	Fl(n)=1710.2+0.2*(n-512)	512<=n<=885	Fu(n)=Fl(n)+95

4 General test conditions and declarations

The requirements of this clause apply to all tests in the present document, when applicable.

The general conditions during the tests should be according to the relevant parts of ETR 027 [14] (methods of measurement for mobile radio equipment) with the exceptions and additions defined in the individual tests.

Many of the tests in the present document measure a parameter relative to a value which is not fully specified in the GSM specifications. For these tests, the conformance requirement is determined relative to a nominal value specified by the manufacturer.

Certain functions of a BTS are optional in the GSM specifications.

When specified in a test, the manufacturer shall declare the nominal value of a parameter, or whether an option is supported.

4.1 Output power and determination of power class

The manufacturer shall declare the rated maximum power per TRX. For a micro or pico-BTS, this shall be specified at the antenna connector. For a normal BTS, it shall be stated whether this is specified at the input to the combiner or at the antenna connector of the BSS.

For a micro-BTS, the class of the micro-BTS shall be determined from the declared maximum power, according to table 3. Where applicable, the manufacturer shall declare whether the BTS meets the requirements of a micro or pico-BTS.

iTeh STANDARD PREVIEW

Table 3: Micro and pico-BTS Power Classes

TRX power class	GSM 900 micro and pico-BTS Maximum output power	DCS1800 micro and pico-BTS Maximum output power
M1	(>19)-24 dBm	(>27)-32 dBm
M2	(>14)-19 dBm	(>22)-27 dBm
M3	(>9)-14 dBm	(>17)-22 dBm
P1	(>13)-20 dBm	(>16)-23 dBm

NOTE: For a normal BTS, the TRX power class can be determined from the manufacturers declared output power per TRX measured at the input to the combiner, according to the tables of TRX power classes in ETS 300 910 [22]. The test requirements for a normal BTS do not vary in this [EN] with TRX power classes. The definition of TRX power class only relates to the declared power per TRX and does not impose any requirement on the measured output power of the BTS.

4.2 Specified frequency range

The manufacturer shall declare:

- which of the frequency bands defined in subclause 3.3.1 is supported by the BSS; a BSS may support the DCS 1800 band and one of the GSM 900 bands, but shall not be defined as supporting more than one of the GSM 900 bands.
- the frequency range within the above frequency band(s) supported by the BSS; This frequency range comprises the transmit and receive operating bands

Many tests in the present document are performed with appropriate frequencies in the bottom, middle and top of the operating frequency band of the BTS. These are denoted as RF channels B (bottom), M (middle) and T (top).

When a test is performed by a test laboratory, the ARFCNs to be used for RF channels B, M and T shall be specified by the laboratory. The laboratory may consult with operators, the manufacturer or other bodies.

When a test is performed by a manufacturer, the ARFCNs to be used for RF channels B, M and T may be specified by an operator.