INTERNATIONAL

Designation: F 1000 - 95

An American National Standard

Standard Practice for Piping System Drawing Symbols¹

This standard is issued under the fixed designation F 1000; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

- 1.1 This practice establishes piping system drawing symbols for marine use.
- 1.2 This set of standard symbols is intended for use on piping system diagrammatics and arrangements for ships.
- 1.3 Where graphical symbols are required for an item or equipment not covered by this practice, the form and character of the symbol will be left to the discretion of the activity concerned, provided that the symbol used does not duplicate any of those contained herein, and is clearly understandable, subject to one interpretation only, or explained by a suitable note on the drawing when necessary.
- 1.4 Since symbolic representation does not usually involve exact or scale layout or the actual run or leads of piping, the same symbol may be used for all projections of the system (plan, elevations, and sections).
- 1.5 Symbols for fluid power, heating, ventilation, and air conditioning (HVAC), and Navy damage control diagrams are not included in this practice.

2. Significance and Use

2.1 Fig. 1 provides symbols for strainers, separators, and filters.

- 2.2 Fig. 2 provides symbols for valves. Valves are categorized under the following headings: globe, angle, check, ball, butterfly, gate, relief, manifolds, control, noise control, and miscellaneous.
- 2.3 Fig. 3 provides symbols for valve appendages such as actuators and locking devices. Symbols shown on Fig. 3 are to be combined with the appropriate symbol from Fig. 2.
- 2.4 Fig. 4 provides symbols for piping system–related instrumentation. These symbols are categorized under the following headings: pressure, temperature, flow, level, switches, alarms, and miscellaneous.
 - 2.5 Fig. 5 provides symbols for fans, pumps, and turbines.
 - 2.6 Fig. 6 provides symbols for plumbing components.
- 2.7 Fig. 7 provides symbols for pipe and pipe fittings.
- 2.8 Fig. 8 provides symbols for noise control components and designations. These symbols are generally used for submarine design.
- 2.9 Fig. 9 provides symbols for transitions. These symbols identify transitions such as pipe material or pipe schedule changes.
- 2.10 Fig. 10 provides symbols for miscellaneous components. These are components which could not be classified under the above categories. Examples include heat exchangers, flasks, and sea chests.
 - 2.11 Fig. 11 provides symbols for grooved piping.

3. Keywords

3.1 drawing symbols; piping; piping drawings; piping symbols

¹ This practice is under the jurisdiction of ASTM Committee F-25 on Shipbuilding and is the direct responsibility of Subcommittee F25.13 on Piping Systems.

Current edition approved Nov. 10, 1995. Published May 1996. Originally published as F 1000-86. Last previous edition F 1000-92.

| | Number | Title | Symbol | Notes |
|--|----------------------|-------------------------------|-----------------|--|
| | 1 | Strainer, duplex basket type | <u>B</u> | |
| | 2 | Strainer, duplex edge type | E) | |
| | 3 | Strainer, duplex magnetic | 8 | |
| | 4 | Strainer, Y-type basket | B | |
| | 5 | Strainer, Y-type edge | Ę | |
| | 6 | Strainer, simplex basket type | -⊗ ^B | |
| | 7 | Strainer, simplex edge type | - <u>⊗</u> E | h.ai) |
| | 8 | Strainer, box type | Ршје | W |
| htt | 9 ps://standards. | Strainer, basket type, steam | /s/ | 12a-d418a1b9cc7e/astm-f1000-95 |
| | 10 | Strainer, sea chest | | To be combined with the symbol for sea chest (Fig. 10, no. 24) |
| | 11 | Separator, moisture | Ţ | |
| the state of the s | 12 | Separator, cyclone | (') | |
| | 13 | Separator, oil-water | -4 | Parallel plate type |
| | 14 | Filter | F | |

FIG. 1 Strainers, Separators and Filters

| Number | Title | Symbol | Notes |
|--------------------------|---|-----------|----------------------------------|
| 15 | Filter with shielded container | F | |
| 16 | Filter with mechanical differential pressure indicator | F | |
| 17 | Filter with mechanical differential pressure indicator and automatic bypass | F | |
| 18 | Filter, oil, cartridge type | — | |
| 19 | Filter, coalescing | Ū | |
| 20 | Filter, duplex iTeh Star | | |
| 21 | Filter, charcoal //standa | rds. te | h.ai) |
| 22 | Precipitator, electrostatic | They | |
| os://st 23 dards. | Centrifugal purifier \$1/238057a5 | 8880411-9 | 02a-d418a1b9cc7e/astm-f1000-95 |
| 24 | Screen | | Typically used on blower intake. |

FIG. 1 (continued)

| | 1. G | lobe | |
|--------|--|---------------|--|
| Number | Title | Symbol | Notes |
| 1.1 | Valve, globe | \bowtie | |
| 1.2 | Valve, globe with flow control device | | |
| 1.3 | Valve, globe, stop check | ightharpoonup | |
| 1.4 | Valve, globe, positive stop | IJ. | |
| 1.5 | Valve, globe, combined spring-loaded exhaust and relief | | |
| 1.6 | Valve, globe, Y-pattern | | |
| 1.7 | Valve, globe, gtop check, Y- pattern | × | h.ai) w |
| 1.8 | Valve, globe, reverse seated ASTM F10 teh.ai/catalog/standards/sist/2380b7a5 | No. | 2a-d418a1b9cc7e/astm-f1000-95 |
| 1.9 | Bridgewall [><] Note 1 Note 2 | | Note 1: Fluid in pipe on this side of valve is isolated from stem packing with valve shut. Note 2: Fluid in pipe on this side of valve is in contact with stem packing with valve shut. |
| | 2. A | ngle | |
| 2.1 | Valve, angle | | |
| 2.2 | Valve, angle, bellows packless | ₩ | |

FIG. 2 Valves

| | 2. Angle — | - Continued | |
|---------------|---|-------------|---|
| Number | Title | Symbol | Notes |
| 2.3 | Valve, angle, diaphragm packless | Ŕ | |
| 2.4 | Valve, angle, stop check | 14 | |
| 2.5 | Valve, angle, needle or throttling | Â | |
| 2.6 | Valve, angle, check | 7 | |
| 2.7 | Valve, angle, solenoid | 2000 | "Solenoid Valve" shown as example. See Fig. 3 for other operators. |
| 2.9 | Valve, angle, with lock box 1 Teh Stal | dZds | |
| 2.10 | Valve, angle, capped | Z · | h.ai) |
| 2.11 | Valve, angle, ball ASTM F10 | <u> </u> | |
| ndards iteh.a | Valve, angle, lift check | | 2a-d418a169cc7e/astm-f1000- |
| | 3. (| Check | |
| 3.1 | Valve, swing check | 7 | |
| 3.2 | Valve, lift check | 7 | |
| 3.3 | Valve, vented swing check | 1 | |
| 3.4 | Valve, check, spring loaded | AND + | Include normally shut or normally open as shown on lines 11.38 or 11.39; as applicable. |

FIG. 2 (continued)

| | 3. Check — Continued | | | | | | |
|--------|---|-------------|--------------------------------------|--|--|--|--|
| Number | Title | Symbol | Notes | | | | |
| 3.5 | Valve, swing check, Y-pattern | 47 | | | | | |
| 3.6 | Valve, check, hydraulic | 1 | | | | | |
| 3.7 | Valve, check, hydraulic with external loading | → | | | | | |
| 3.8 | Valve, check in-ball or poppet | \$ | | | | | |
| 3.9 | Valve, check, in-line ball or poppet, spring loaded | ₹ | | | | | |
| 3.10 | Valve, wafer check Teh Stan | da | | | | | |
| 3.11 | Valve, check, with manual gaging provision | rotite | h.ai) v | | | | |
| 3.12 | Valve, check, flow limiting ASTM F100 | 0-95 | - 1410-1107-/ | | | | |
| 3.13 | Valve, check, counterbalanced with external weights | 1 21 | arayrodrayooyo, asan iroooy | | | | |
| 3.14 | Valve, flapper | | | | | | |
| 3.15 | Valve, check, swing, with integral orifice | | This valve permits limited backflow. | | | | |
| | 4. Ball | | | | | | |
| 4.1 | Valve, ball | M | | | | | |
| 4.2 | Valve, ball, bleed port | | | | | | |

FIG. 2 (continued)

| | 4. Ball - C | Continued | | | |
|--------------------------|--|----------------|--|--|--|
| Number | Title | Symbol | Notes | | |
| 4.3 | Valve, ball, three port | A | | | |
| 4.4 | Valve, ball, three port, normally shut | | | | |
| 4.5 | Valve, ball, three port - showing other than normally shut | | | | |
| 4.6 | Valve, ball, spring return | San | | | |
| 4.7 | Valve, ball check | 13 | Combination of ball and swing check. | | |
| 4.8 | Valve, ball, four port | 母 | ah ai) | | |
| 5. Butterfly | | | | | |
| 5.1 | Valve, butterfly | B ✓ | W | | |
| ps://s 5.2 lards. | Valve, butterfly, locked open | B _O |)2a-d418a1b9cc7e/astm-f1000-95 | | |
| 5.3 | Valve, butterfly, locked shut | ₿. | | | |
| | 6. (| Jate | | | |
| 6.1 | Valve, gate | ₩ | | | |
| 6.2 | Valve, gate, double disc with internal bypass | M | Space between discs vents to side with mark. | | |
| 6.3 | Valve, gate, with three-way bypass | T T | | | |

FIG. 2 (continued)

| 7. Pressure Relief | | | | |
|--------------------|--|------------------------|------------------------------|--|
| Number | Title | Symbol | Notes | |
| 7.1 | Valve, angle, pressure relief (self actuated) | | | |
| 7.2 | Valve, angle, pressure relief, differential | | | |
| 7.3 | Valve, angle, pilot-actuated pressure relief | | | |
| 7.4 | Valve, inward pressure relief, high capacity gas flow | _ _ _ | | |
| 7.5 | Valve, outward pressure relief, high capacity gas flow |) | | |
| 7.6 | Valve, self-actuated pressure relief, globe | | | |
| 7.7 | Valve, pilot-actuated pressure relief, globe | | m.at) W | |
| 7.8 | Valve, pressure relief, angle, diaphragm ASIM F10 | ■ 0-95 № | 2a-d418a1b9cc7e/astm-f1000-9 | |
| 7.9 | Valve, boiler safety | N IIII | | |
| 7.10 | Valve, relief, superheater safety, pilot actuated | | | |
| | 8. Ma | nifolds | | |
| 8.1 | Manifold, single row | | | |
| 8.2 | Manifold, double row | - | | |

FIG. 2 (continued)

| 8. Manifolds - Contined | | | | | |
|-------------------------|--|--------|-------------------------------|--|--|
| Number | Title | Symbol | Notes | | |
| 8.3 | Manifold, single row, stop check valves | - | | | |
| 8.4 | Manifold, double row, "●" locked shut | - | | | |
| 8.5 | Manifold, double row, " | - | | | |
| 8.6 | Manifold, single row, interlocked | - | | | |
| | 9. Co | ntrol | | | |
| 9.1 | Valve, control, pilot actuated (increased actuating pressure closes valve) | X4 | | | |
| 9.2 | Valve, control, pilot actuated (increased actuating pressure opens valve) | | h.ai) | | |
| 9.3 | Valve, pressure reducing (increase of downstream pressure shuts valve) | Pipie | W | | |
| s://s 9.4 ards. | Valve, pressure regulating 57a5 (increase of upstream pressure opens valve) | | 2a-d418a1b9cc7e/astm-f1000-95 | | |
| 9.5 | Valve, priority (decrease of upstream pressure shuts valve) | | | | |
| 9.6 | Valve, pressure reducing, diaphragm (increase of downstream pressure shuts valve) | | | | |

FIG. 2 (continued)

| | 9. Co | ontrol | |
|------------------------|---|--|--------------------------------|
| Number | Title | Symbol | Notes |
| 9.7 | Valve, pressure regulating, diaphragm (increase of upstream pressure opens valve) | | |
| 9.8 | Valve, control, diaphragm, pilot actuated (increased actuating pressure closes valve) | ₩ N | |
| 9.9 | Valve, control, diaphragm, pilot actuated (increased actuating pressure opens valve) | o l ✓ | |
| 9.10 | Valve, control, diaphragm, pilot actuated (increased actuating pressure closes valve) with check feature | ldards | |
| 9.11 | Valve, control, diaphragm, pilot actuated (increased actuating pressure opens valve) with check feature | | n.ai) w |
| 9.12 s://standards. | Valve, thermostatic expansion | | 12a-d418a1b9cc7e/astm-f1000-95 |
| 9.13 | Valve, thermostatic control | \Box | |
| 9.14 | Valve, thermostatic control, three-way | K | |
| 9.15 | Valve, temperature control | | |
| 9.16 | Valve, three-way modulating temperature control | S. S | |

FIG. 2 (continued)

| 9. Control - Continued | | | | |
|------------------------|--|---------|--------------------------------|--|
| Number | Title | Symbol | Notes | |
| 9.17 | Valve, three-way modulating (pressure sensing) | 松 | | |
| 9.18 | Valve, back pressure regulator with remote sensing | 松 | | |
| 9.19 | Valve, regulator, back pressure | *** | | |
| 9.20 | Valve, feedwater regulator, motor or manual operation | ₩X | | |
| 9.21 | Valve, boiler feedwater regulator with manual control | ⊠. X | | |
| 9.22 | Valve, compressed gas cylinder regulator | H | h.ai) | |
| 9.23 | Valve, proportioning, automatic | Pie | Two inlets, one outlet | |
| 9.24 s://standards. | Valve, temperature pilot MF10 control og/standards/sist/2380b7a5 | TPC |)2a-d418a1b9cc7e/astm-f1000-95 | |
| 9.25 | Valve, level pilot control | LPC | | |
| 9.26 | Valve, pressure pilot control | PPC | | |
| 9.27 | Valve, manual opening automatic closing | | | |
| 9.28 | Valve, regulated bypass | | | |
| 9.29 | Valve, hydraulically operated flow control w/pilot | —(PTH)— | | |

FIG. 2 (continued)

| | 9. Control - Continued | | | | |
|--------|---|------------------------------------|-------------------------------|--|--|
| Number | Title | Symbol | Notes | | |
| 9.30 | Valve, globe, relief, adjustable or spring loaded, reducing | | | | |
| 9.31 | Valve, hydraulic control, three-way | | Water pressure actuates valve | | |
| 9.32 | Valve, micrometer | M | | | |
| 9.33 | Valve, unloading | 以 | | | |
| 9.34 | Valve, governor | $\stackrel{\diamondsuit}{\bowtie}$ | | | |
| 9.35 | Valve, capacity control Star | deds | k oi) | | |
| 9.36 | Valve, control, balanced pressure proportioning | P Die | W | | |
| 9.37 | Valve, typical control valve, with test fitting | ₹ K | 2a-d418a1b9cc7e/astm-f1000-95 | | |

FIG. 2 (continued)

| | 10. Noise | Control | |
|-----------------|--|-----------|---|
| Number | Title | Symbol | Notes |
| 10.1 | Valve, quiet throttling | | In general, symbols for quiet valves are accompanied by |
| 10.2 | Valve, quiet vent | 藁 | the quiet component symbol: |
| 10.3 | Valve, vent, quiet air throttling with shroud | 園 | |
| 10.4 | Valve, quiet reducing | | |
| 10.5 | Valve, quiet reducing, pilot operated | | |
| 10.6 | Valve, standard, with attached quieting orifice | | |
| 10.7 | Valve, quiet automatic 2002 balancing | rd#.ite | h.ai) w |
| 10.8 | Valve, quiet throttling, tank mounted | 10-95 | |
| os://standards. | 11. Misce | ellaneous | 12a-0418a1b9cc/e/astm-11000-95 |
| 11.1 | Valve, frictional throttle | # | |
| 11.2 | Valve, priming, float type | | |
| 11.3 | V£.lve, needle | | |
| 11.4 | Valve, three-way, two position | | |
| 11.5 | Valve, gage, with test connection | | |

FIG. 2 (continued)

| 11. Miscellaneous - Continued | | | |
|-------------------------------|--|---|--------------------------------|
| Number | Title | Symbol | Notes |
| 11.6 | Valve, minimum volume vent with cap | | |
| 11.7 | Valve, minimum volume drain with cap | | |
| 11.8 | Valve, minimum volume vent without cap | Image: section of the content of the | |
| 11.9 | Valve, minimum volume drain without cap | P | |
| 11.10 | Valve, foot | 立 | |
| 11.11 | Valve, four way | | |
| 11.12 | Valve, double ball, combination hull & backup | 80 | h.ai) w |
| 11.13 | Valve, combination poppet hull and ball backup ASTM F10 | 87 10-9-24 00 | 20. 4419.0150.07-/ |
| 11.14 | Valve, angle, hull | | 24 341041090070/astiiF11000-73 |
| 11.15 | Valve, double-poppet hull and backup | <u> </u> | |
| 11.16 | Valve, poppet, hull | <u>R</u> | |
| 11.17 | Valve, angle, ball, hull | <u>R</u> | |

FIG. 2 (continued)