



Designation: E2844 – 15^{ε1}

Standard Specification for Demonstrating That a Building's Location Provides Access to Public Transit¹

This standard is issued under the fixed designation E2844; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

^{ε1} NOTE—Keywords in Section 7 were corrected editorially in September 2015.

1. Scope

1.1 This specification provides requirements for demonstrating that a building's location provides a minimal level of access to public transit such that building occupants can rely on public transit to travel to places of employment and to run typical errands.

1.2 This specification addresses a single indicator regarding the environmental performance related to a building's location. It provides one option for evaluating whether a building is located in such a way as to minimize the impacts associated with occupants' travel.

NOTE 1—The indicator in and of itself is insufficient to imply any level of "sustainability" for the building or the neighborhood. Similarly, a building's failure to meet this specification does not necessarily signify a lack of sustainability. Other indicators may be more appropriate for that building or region; those indicators are outside the scope of this specification.

1.3 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

[E631 Terminology of Building Constructions](#)

[E2114 Terminology for Sustainability Relative to the Performance of Buildings](#)

¹ This specification is under the jurisdiction of ASTM Committee E60 on Sustainability and is the direct responsibility of Subcommittee E60.01 on Buildings and Construction.

Current edition approved Aug. 1, 2015. Published August 2015. DOI: 10.1520/E2844-15E01.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

3. Terminology

3.1 *Definitions:*

3.1.1 For terms related to building, refer to Terminology [E631](#).

3.1.2 For terms related to sustainability relative to the performance of buildings, refer to Terminology [E2114](#).

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *access location, n*—closest point for the public to board a transit vehicle on a given route.

3.2.2 *headway, n*—time interval between public transit vehicles moving in the same direction on a particular route.

3.2.2.1 *Discussion*—If multiple routes at a given stop share 60 % or more of their route, they can be viewed as the same route for purposes of calculating headways.

3.2.3 *local transit, n*—public transit that meets one or both of the following characteristics: (1) operates within the same right-of-way as automobile traffic or (2) the distance between its access locations averages less than 1/3 mile (0.5 km).

3.2.3.1 *Discussion*—Transit types that typically meet this definition include local bus and streetcar.

3.2.4 *off-peak hours, n*—all hours that are not peak hours.

3.2.5 *peak hours, n*—hour(s) of greatest commuting in the region in the morning and evening as identified by the local jurisdiction.

3.2.6 *public transit, n*—transportation by a land, aerial, or water conveyance that provides to the public regular and continuing transportation over fixed routes but does not include private shuttle, school or charter bus, or intracity transportation such as a taxi.

3.2.7 *rapid transit, n*—public transit that has both of the following characteristics: (1) it operates within a dedicated right-of-way and (2) the average distance between its access locations is greater than 1/3 mile (0.5 km).

3.2.7.1 *Discussion*—Transit types that typically meet this definition include bus rapid transit, light rail, heavy or passenger rail, and ferry service.