This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.



Designation: F2576 - 13 F2576 - 15

Standard Terminology Relating to Declarable Substances in Materials¹

This standard is issued under the fixed designation F2576; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This terminology standard contains terms, definitions, descriptions of terms, nomenclature, and explanations of acronyms and symbols specifically associated with standards under the jurisdiction of ASTM International Committee F40 on Declarable Substances in Materials.

1.2 This terminology may also be applicable to documents not under the jurisdiction of ASTM F40, in which case this terminology may be referenced in those documents.

2. Referenced Documents

2.1 ASTM Standards:²
E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
2.2 Other References:
ASTM Dictionary of Engineering Science & Technology³
ISO 472 Plastics—Vocabulary⁴
ISO/IEC Guide 2 Standardization and Related Activities—General Vocabulary⁵
International Vocabulary of Basic and General Terms in Metrology (VIM)⁶
Nomenclature in Evaluation of Analytical Methods Including Detection and Quantification Capabilities⁷

3. Significance and Use

3.1 Definitions, acronyms, and units given in Section 4 of this terminology are intended for use in all standards for declarable substances in materials. The definitions shall be used uniformly and consistently. The purpose of this terminology is to promote clear understanding and interpretation of the standards in which those definitions, acronyms, and units are used.

3.2 A terminology section is required in all F40 standards. This section shall contain terms specific to the standard or a reference to this terminology, or both.

3.3 All terms used within a standard that are unique to it shall be defined within the standard. Terms that are of more general application shall be defined in this terminology. If the technical subcommittee responsible for the standard feels that it is appropriate, the term and its definition may appear in both the standard and in this terminology.

3.4 The Subcommittee shall consult the ASTM Dictionary of Engineering Science & Technology or a standard dictionary, or both, prior to creating a new definition to determine if a suitable definition already exists. Other terminology documents, such as ISO 472 Plastics—Vocabulary, may also be consulted.

4. Terminology

absolute method, *n*—*in conformity assessment*, a practice requiring that results are not rounded prior to assessing conformance to limits.

¹ This terminology is under the jurisdiction of ASTM Committee F40 on Declarable Substances in Materials and is the direct responsibility of Subcommittee F40.91 on Terminology.

Current edition approved May 1, 2013 May 15, 2015. Published June 2013 July 2015. Originally approved in 2006. Last previous approved in 20112013 as F2576-11:-13. DOI: 10.1520/F2576-13:10.1520/F2576-15.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

³ Sponsored by ASTM Committee E02 on Terminology; available from ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959; ASTM Stock Number: DEF00.

⁴ Standard ISO 472 is under the jurisdiction of ISO TC 61 on Plastics and is the direct responsibility of ISO TC 61 SC 1 on Terminology.

⁵ ISO/IEC Guide 2 is under the jurisdiction of the ISO Technical Management Board.

⁶ VIM is under the jurisdiction of the Joint Committee for Guides in Metrology (JCGM) and is the direct responsibility of JCGM-WG2.

⁷ Currie, Lloyd A., Pure & Applied Chemistry, Vol 67, No. 10, pp. 1699–1723, 1995, (IUPAC).



DISCUSSION-

For further information on absolute and rounding methods of conformity assessment see Practice E29.

chemical measurement process, *n*—a fully specified analytical method that is in a state of statistical control.

conformity assessment, *n*—any activity concerned with determining directly or indirectly that relevant requirements are fulfilled.

DISCUSSION-

Definition comes from ISO/IEC Guide 2.

contaminant, n—a substance or material not intended to be present within or on another substance, material or object.

- **conflict metal**, *n*—a metal derived from a conflict mineral sourced from the Democratic Republic of Congo or an adjoining country as defined in the United States by H. R. 4173 ('Dodd-Frank Wall Street Reform and Consumer Protection Act'), section 1502.
- **conflict mineral**, *n*—a mineral sourced from the Democratic Republic of Congo or an adjoining country as defined in the United States by H. R. 4173 ('Dodd-Frank Wall Street Reform and Consumer Protection Act'), section 1502.

DISCUSSION-

Conflict minerals are identified in section 1502 (opus cit.) as (A) columbite-tantalite (coltan), cassiterite, gold, wolframite, or their derivatives; or (B) any other mineral or its derivatives determined by the Secretary of State to be financing conflict in the Democratic Republic of the Congo or an adjoining country.

- **conflict mineral free article,** *n*—an article not containing conflict minerals (or metals derived from conflict minerals) as defined in the United States by H. R. 4173 ('Dodd-Frank Wall Street Reform and Consumer Protection Act'), section 1502.
- **de minimus limit**, *n*—from Latin '*de minimus*' meaning of no significant consequence; in regulatory contexts, the maximum amount that evokes no legal consequence, that is, the maximum allowed amount.
- **detection limit**, *n*—the smallest net signal or the derived concentration that can be distinguished from the background signal or blank at a specified confidence level using a specified measurement process.

DISCUSSION-

<u>ASTM F2576-15</u>

IUPAC definition per Lloyd A. Currie, Nomenclature in Evaluation of Analytical Methods Including Detection and Quantification Capabilities.

intentionally added substance, *n*—a chemical element, compound or ion that is purposely included within or on a substance, material or object.

percent by mass, *n*—units expressing the ratio of analyte mass to sample mass multiplied by 100.

DISCUSSION-

For expression in SI units, the simple ratio of mass units (for example, mg/kg) is to be preferred over percent by mass. However, percent by mass (also written as % mass or mass %) is commonly used. In addition, the expressions weight % and % by weight are often substituted as synonyms for the more correct % mass. Definition comes from the International Vocabulary of Basic and General Terms in Metrology (VIM).

percent by weight, *n*—see percent by mass.

quantification limit, *n*—performance characteristic that marks the ability of a chemical measurement process to adequately "quantify" an analyte.

DISCUSSION-

The ability to quantify is generally expressed in terms of the signal or analyte value that will produce estimates having a specified relative standard deviation, commonly 10 %. IUPAC definition per Lloyd A. Currie, *Nomenclature in Evaluation of Analytical Methods Including Detection and Quantification Capabilities*

rare earth elements, *n*—as defined by IUPAC, any of the following seventeen chemical elements: scandium, yttrium, lanthanum, cerium, praseodymium, neodymium, promethium, samarium, europium, gadolinium, terbium, dysprosium, holmium, erbium, thulium, ytterbium, and lutetium.