



SLOVENSKI STANDARD
SIST EN 301 003-5 V1.2.1:2004
01-april-2004

ü]fc_cdUgcj bc`X][]HJbc`ca fYy`Y`n`]bhY[f]fUbj]a]`g]cf]hj Ua]`f6 !=G8 BŁ!`Dfchc_c`
 X][]HJbY`bUfc b]y`Y`g][bU]nUWY`Y`yH`&fB GG&Ł!`? UfU_hyf]gh_Y`nj YnY!`Df]U] UUb`Y`
 hYa Ybg_Y`WY`] bY\]]fcgh]`df]`Uglb]_i`nj YnY!)`"XY.`N[fUXVUdfYg_i yUby[Ub]nU]b
 bUa Yb`dfYg_i yUb`U`fHGG/ HDŁ!`GdYVWZ_UWY`UnU`ca fYy`Y`

Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Peak cell rate modification by the connection owner; Part 5: Test Suite Structure and Test Purposes (TSS&TP) specification for the network

STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/3f33feb7-2b58-4b94-a9a8-741c3111e745/sist-en-301-003-5-v1-2-1-2004>

Ta slovenski standard je istoveten z: EN 301 003-5 Version 1.2.1

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST EN 301 003-5 V1.2.1:2004 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 003-5 V1.2.1:2004](https://standards.iteh.ai/catalog/standards/sist/3f33feb7-2b58-4b94-a9a8-741c3111e745/sist-en-301-003-5-v1-2-1-2004)

<https://standards.iteh.ai/catalog/standards/sist/3f33feb7-2b58-4b94-a9a8-741c3111e745/sist-en-301-003-5-v1-2-1-2004>

ETSI EN 301 003-5 V1.2.1 (2000-10)

European Standard (Telecommunications series)

**Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling System No. two (DSS2) protocol;
Connection characteristics;
Peak cell rate modification by the connection owner;
Part 5: Test Suite Structure and Test Purposes (TSS&TP)
specification for the network**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 003-5 V1.2.1:2004](https://standards.iteh.ai/catalog/standards/sist/3f33feb7-2b58-4b94-a9a8-741c3111e745/sist-en-301-003-5-v1-2-1-2004)

<https://standards.iteh.ai/catalog/standards/sist/3f33feb7-2b58-4b94-a9a8-741c3111e745/sist-en-301-003-5-v1-2-1-2004>



Reference

REN/SPAN-05242-5

Keywords

ATM, B-ISDN, DSS2, TSS&TP

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 003-5 V1.2.1:2004

<https://standards.iteh.ai/catalog/standards/sist/3f33feb7-2b58-4b94-a9a8-741c3111e745/sist-en-301-003-5-v1-2-1-2004>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.1.1 Definitions related to conformance testing	6
3.1.2 Definitions related to EN 301 003-1	6
3.2 Abbreviations	6
4 Test Suite Structure (TSS).....	7
5 Test Purposes (TP)	7
5.1 Introduction	7
5.1.1 TP naming convention	7
5.1.2 Source of TP definition.....	8
5.1.3 Test strategy.....	8
5.1.4 Test of call states	8
5.2 TPs for the Peak cell rate modification, network	8
5.2.1 Signalling procedures at the coincident S_B/T_B and at the T_B reference points	8
5.2.1.1 Modification procedures at the requesting entity	8
5.2.1.1.1 Valid behaviour (01).....	8
5.2.1.1.2 Handling of errors conditions (02).....	9
5.2.1.1.3 Timers (03).....	12
5.2.1.2 Modification procedures at the responding entity.....	12
5.2.1.2.1 Valid behaviour (04).....	12
5.2.1.2.2 Handling of error conditions (05).....	13
6 Compliance.....	17
7 Requirements for a comprehensive testing service	17
Bibliography	18
History	19

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

The present document is part 5 of a multi-part standard covering the Digital Subscriber Signalling System No. 2 (DSS2) protocol specification for the B-ISDN Peak cell rate modification by the connection owner, as identified:

- Part 1: "Protocol specification [ITU-T Recommendation Q.2963.1 [8] (1996), modified]";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";**
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

National transposition dates

Date of adoption of this EN:	29 September 2000
Date of latest announcement of this EN (doa):	31 December 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 June 2001
Date of withdrawal of any conflicting National Standard (dow):	30 June 2001

1 Scope

This fifth part of EN 301 003 specifies the network Test Suite Structure and Test Purposes (TSS&TP) for the T_B reference point or coincident S_B and T_B reference point (as defined in ITU-T Recommendation I.413 [[5]) of implementations conforming to the standards for the signalling user-network layer 3 specification for Peak cell rate modification by the connection owner of the Digital Subscriber Signalling System No. 2 (DSS2) protocol for the pan-European Broadband Integrated Services Digital Network (B-ISDN), EN 301 003-1 [3].

A further part of the present document specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma based on the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- [1] ETSI ETS 300 406: "Methods for Testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [2] ETSI EN 300 443-1 (V1.3): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".
- [3] ETSI EN 301 003-1 (V1.1): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Peak cell rate modification by the connection owner; Part 1: Protocol specification [ITU-T Recommendation Q.2963.1 (1996), modified]".
- [4] ETSI EN 301 003-2 (V1.1): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Peak cell rate modification by the connection owner; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [5] ITU-T Recommendation I.413 (1993): "B-ISDN user-network interface".
- [6] ISO/IEC 9646-1: "Information Technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [7] ISO/IEC 9646-2: "Information Technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract Test Suite specification".
- [8] ITU-T Recommendation Q.2963.1: "Digital Subscriber Signalling System No. 2 - Connection modification: Peak cell rate modification by the connection owner".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in EN 301 003-1 [3] and EN 300 443-1 [2] and the following apply:

3.1.1 Definitions related to conformance testing

abstract test case: refer to ISO/IEC 9646-1 [6]

Abstract Test Method (ATM): refer to ISO/IEC 9646-1 [6]

Abstract Test Suite (ATS): refer to ISO/IEC 9646-1 [6]

Implementation Under Test (IUT): refer to ISO/IEC 9646-1 [6]

lower tester: refer to ISO/IEC 9646-1 [6]

Protocol Implementation Conformance Statement (PICS): refer to ISO/IEC 9646-1 [6]

PICS proforma: refer to ISO/IEC 9646-1 [6]

Protocol Implementation eXtra Information for Testing (PIXIT): refer to ISO/IEC 9646-1 [6]

PIXIT proforma: refer to ISO/IEC 9646-1 [6]

Test Purpose (TP): refer to ISO/IEC 9646-1 [6]

3.1.2 Definitions related to EN 301 003-1

network: DSS2 protocol entity at the Network side of the user-network interface where a T_B reference point or coincident S_B and T_B reference point applies

network (S_B/T_B): DSS2 protocol entity at the Network side of the user-network interface where a coincident S_B and T_B reference point applies

network (T_B): DSS2 protocol entity at the Network side of the user-network interface where a T_B reference point applies (user is the private ISDN)

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
B-ISDN	Broadband Integrated Services Digital Network
CR	Call Reference
DSS2	Digital Subscriber Signalling System No. two
IE_AI	Information element action indicator
IE_flag	Information element instruction indicator flag
IUT	Implementation Under Test
N0	Null link state
N1	Call Initiated link state
N10	Active link state
N12	Disconnect Indication call state
N3	Outgoing Call Proceeding link state
N4	Call Delivered link state
N6	Call Present link state
N7	Call Received link state

N9	Incoming Call Proceeding link state
PCR	Peak Cell Rate
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
TP	Test Purpose
TSS	Test Suite Structure

4 Test Suite Structure (TSS)

Signalling procedures at the coincident S_B/T_B and at the T_B reference points

Modification procedures at the requesting entity.	
Valid behaviour	(01)
Handling of error conditions	(02)
Timers	(03)
Modification procedures at the responding entity.	
Valid behaviour	(04)
Handling of error conditions	(05)

Figure 1: Test suite structure

5 Test Purposes (TP)

5.1 Introduction

For each test requirement a TP is defined.

5.1.1 TP naming convention

TPs are numbered, starting at 01, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite (see table 1).

Table 1: TP identifier naming convention scheme

Identifier:	<suite_id>_<group>_<nnn>		
<suite_id>	=	service + type of IUT:	"MODN" for modification, IUT = Network
<group>	=	group number:	two character field representing the group reference according to TSS
<nn>	=	sequential number:	(01-99)

5.1.2 Source of TP definition

The TPs are based on EN 301 003-1 [3].

5.1.3 Test strategy

As the base standard EN 301 003-1 [3] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the PICS specification EN 301 003-2 [4].

The TPs are only based on conformance requirements related to the externally observable behaviour of the IUT, and are limited to conceivable situations to which a real implementation is likely to be faced (ETS 300 406 [1]).

5.1.4 Test of call states

Many TPs include a reference to the IUT's final call state after the realization of the TP. In these cases the TP includes the requirement to ensure that the IUT has entered this particular final call state. Ensuring that the IUT is in a particular call state shall be realized by following the procedures described in clause 5.6.11 of EN 300 443-1 [2]. According to these procedures, the IUT on receipt of a STATUS ENQUIRY message, shall respond with a STATUS message indicating, in the fifth octet of the Call state information element, the current call state of the IUT. This exchange of messages is not mentioned explicitly in each TP but is considered to be implicit in the reference to the final call state. This way of phrasing the TPs has been used to avoid over-complicating the text and structure of the TPs and to improve the readability.

5.2 TPs for the Peak cell rate modification, network

All PICS items referred to in this clause are as specified in EN 301 003-2 [4] unless indicated otherwise by another numbered reference.

Unless specified:

- the messages indicated are valid and contain at least the mandatory information elements and possibly optional information elements;
- the information elements indicated are valid and contain at least the mandatory parameters and possibly optional parameters.

5.2.1 Signalling procedures at the coincident S_B/T_B and at the T_B reference points

NOTE: Unless otherwise specified, the connection defined by the requested ATM traffic descriptor is available for use.

5.2.1.1 Modification procedures at the requesting entity

Test purposes for EN 301 003-1 [3] clause 9.1.

Selection: The iut support the requirements for the modification requesting entity. PICS: R 2.1.

5.2.1.1.1 Valid behaviour (01)

MODN_01_01

Ensure that the IUT in N10, to indicate that a PCR modification has been requested,

- sends a MODIFY REQUEST message and enters N13.

MODN_01_02

Ensure that the IUT in N13, on receipt of a MODIFY ACKNOWLEDGE message including a Broadband report type information element, with type of report field different from "Modification confirmation"

- sends no message or optionally send a STATUS message (cause value: 100, call state: 10) and enters N10.

MODN_01_03

Ensure that the IUT in N13, on receipt of a MODIFY ACKNOWLEDGE message without broadband report type information element,

- sends no message and enters N10.

MODN_01_04

Ensure that the IUT in N13, on receipt of a MODIFY ACKNOWLEDGE message including an empty Broadband report type information element,

- sends no message and enters N10.

MODN_01_05

Ensure that the IUT in N10, having received a MODIFY ACKNOWLEDGE message, including a broadband report type information element requesting confirmation, to indicate that the modification of the connection has been confirmed by the remote user,

- sends a CONNECTION AVAILABLE message and remains in N10.

MODN_01_06

Ensure that the IUT in N13, on receipt of a MODIFY REJECT message,

- sends no message and enters N10.

MODN_01_07

Ensure that the IUT in N13, on receipt of a STATUS message (call state: 10, cause value: 97) with diagnostic identifying of the MODIFY REQUEST message,

- sends no message and enters N10.

MODN_01_08

Ensure that the IUT in N13, on receipt of a STATUS message (call state: 10, cause value: 97 or 101) without diagnostic identifying of the MODIFY REQUEST message,

- sends a STATUS ENQUIRY message and remains in N13.

MODN_01_09

Ensure that the IUT in N13, (having sent a STATUS ENQUIRY message), on receipt of a STATUS message (call state: 14),

- sends no message and remains in N13.

MODN_01_10

Ensure that the IUT in N13, (having sent a STATUS ENQUIRY message), on receipt of a STATUS message (call state: 10),

- sends no message and enters N10.

MODN_01_11

Ensure that the IUT in N13, on receipt of a RELEASE message,

- enters N11.

MODN_01_12

Ensure that the IUT in N13, on receipt of a clearing indication at the remote interface,

- sends a RELEASE message and enters N12.

5.2.1.1.2 Handling of errors conditions (02)

MODN_02_01

Ensure that the IUT in N13, on receipt of a MODIFY ACKNOWLEDGE message with a protocol discriminator other than '09'0,

- sends no message and remains in N13.

MODN_02_02

Ensure that the IUT in N13, on receipt of a MODIFY ACKNOWLEDGE message with an unused Call Reference (CR),

- sends a RELEASE COMPLETE message (CR of the MODIFY ACKNOWLEDGE message, cause value: 81) and remains in N13.

MODN_02_03

Ensure that the IUT in N13, on receipt of a MODIFY ACKNOWLEDGE message with a non mandatory IE content error (Broadband report type; IE_flag = 0),

- sends a STATUS message (cause value: 100, call state: 10) and enters N10.