



# Standard Specification for Aviation Turbine Fuel Containing Synthesized Hydrocarbons<sup>1</sup>

This standard is issued under the fixed designation D7566; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the U.S. Department of Defense.*

## 1. Scope\*

1.1 This specification covers the manufacture of aviation turbine fuel that consists of conventional and synthetic blending components.

1.2 This specification applies only at the point of batch origination, as follows:

1.2.1 Aviation turbine fuel manufactured, certified, and released to all the requirements of Table 1 of this specification (D7566), meets the requirements of Specification D1655 and shall be regarded as Specification D1655 turbine fuel. Duplicate testing is not necessary; the same data may be used for both D7566 and D1655 compliance. Once the fuel is released to this specification (D7566) the unique requirements of this specification are no longer applicable: any recertification shall be done in accordance with Table 1 of Specification D1655.

1.2.2 Field blending of synthesized paraffinic kerosine (SPK) blendstocks, as described in Annex A1 (FT SPK), Annex A2 (HEFA SPK), Annex A3 (SIP), or synthesized paraffinic kerosine plus aromatics (SPK/A) as described in Annex A4 with D1655 fuel (which may on the whole or in part have originated as D7566 fuel) shall be considered batch origination in which case all of the requirements of Table 1 of this specification (D7566) apply and shall be evaluated. Short form conformance test programs commonly used to ensure transportation quality are not sufficient. The fuel shall be regarded as D1655 turbine fuel after certification and release as described in 1.2.1.

1.2.3 Once a fuel is redesignated as D1655 aviation turbine fuel, it can be handled in the same fashion as the equivalent refined D1655 aviation turbine fuel.

1.3 This specification defines specific types of aviation turbine fuel that contain synthesized hydrocarbons for civil use in the operation and certification of aircraft and describes fuels found satisfactory for the operation of aircraft and engines. The

specification is intended to be used as a standard in describing the quality of aviation turbine fuels and synthetic blending components at the place of manufacture but can be used to describe the quality of aviation turbine fuels for contractual transfer at all points in the distribution system.

1.4 This specification does not define the quality assurance testing and procedures necessary to ensure that fuel in the distribution system continues to comply with this specification after batch certification. Such procedures are defined elsewhere, for example in ICAO 9977, EI/JIG Standard 1530, JIG 1, JIG 2, API 1543, API 1595, and ATA-103.

1.5 This specification does not include all fuels satisfactory for aviation turbine engines. Certain equipment or conditions of use may permit a wider, or require a narrower, range of characteristics than is shown by this specification.

1.6 While aviation turbine fuels defined by Table 1 of this specification can be used in applications other than aviation turbine engines, requirements for such other applications have not been considered in the development of this specification.

1.7 Synthetic blending components, synthetic fuels, and blends of synthetic fuels with conventional petroleum-derived fuels in this specification have been evaluated and approved in accordance with the principles established in Practice D4054.

1.8 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.9 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>  
D56 Test Method for Flash Point by Tag Closed Cup Tester

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.J0.06 on Emerging Turbine Fuels.

Current edition approved Nov. 1, 2015. Published December 2015. Originally approved in 2009. Last previous edition approved in 2015 as D7566 – 15b. DOI: 10.1520/D7566-15C.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

\*A Summary of Changes section appears at the end of this standard

- D86** Test Method for Distillation of Petroleum Products at Atmospheric Pressure
- D93** Test Methods for Flash Point by Pensky-Martens Closed Cup Tester
- D129** Test Method for Sulfur in Petroleum Products (General High Pressure Decomposition Device Method)
- D130** Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D156** Test Method for Saybolt Color of Petroleum Products (Saybolt Chromometer Method)
- D240** Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter
- D323** Test Method for Vapor Pressure of Petroleum Products (Reid Method)
- D381** Test Method for Gum Content in Fuels by Jet Evaporation
- D445** Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)
- D1266** Test Method for Sulfur in Petroleum Products (Lamp Method)
- D1298** Test Method for Density, Relative Density, or API Gravity of Crude Petroleum and Liquid Petroleum Products by Hydrometer Method
- D1319** Test Method for Hydrocarbon Types in Liquid Petroleum Products by Fluorescent Indicator Adsorption
- D1322** Test Method for Smoke Point of Kerosine and Aviation Turbine Fuel
- D1405** Test Method for Estimation of Net Heat of Combustion of Aviation Fuels
- D1655** Specification for Aviation Turbine Fuels
- D1840** Test Method for Naphthalene Hydrocarbons in Aviation Turbine Fuels by Ultraviolet Spectrophotometry
- D2276** Test Method for Particulate Contaminant in Aviation Fuel by Line Sampling
- D2386** Test Method for Freezing Point of Aviation Fuels
- D2425** Test Method for Hydrocarbon Types in Middle Distillates by Mass Spectrometry
- D2622** Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry
- D2624** Test Methods for Electrical Conductivity of Aviation and Distillate Fuels
- D2710** Test Method for Bromine Index of Petroleum Hydrocarbons by Electrometric Titration
- D2887** Test Method for Boiling Range Distribution of Petroleum Fractions by Gas Chromatography
- D2892** Test Method for Distillation of Crude Petroleum (15-Theoretical Plate Column)
- D3227** Test Method for (Thiol Mercaptan) Sulfur in Gasoline, Kerosine, Aviation Turbine, and Distillate Fuels (Potentiometric Method)
- D3240** Test Method for Undissolved Water In Aviation Turbine Fuels
- D3241** Test Method for Thermal Oxidation Stability of Aviation Turbine Fuels
- D3242** Test Method for Acidity in Aviation Turbine Fuel
- D3338** Test Method for Estimation of Net Heat of Combustion of Aviation Fuels
- D3343** Test Method for Estimation of Hydrogen Content of Aviation Fuels
- D3701** Test Method for Hydrogen Content of Aviation Turbine Fuels by Low Resolution Nuclear Magnetic Resonance Spectrometry
- D3828** Test Methods for Flash Point by Small Scale Closed Cup Tester
- D3948** Test Method for Determining Water Separation Characteristics of Aviation Turbine Fuels by Portable Separator
- D4052** Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- D4054** Practice for Qualification and Approval of New Aviation Turbine Fuels and Fuel Additives
- D4057** Practice for Manual Sampling of Petroleum and Petroleum Products
- D4171** Specification for Fuel System Icing Inhibitors
- D4176** Test Method for Free Water and Particulate Contamination in Distillate Fuels (Visual Inspection Procedures)
- D4294** Test Method for Sulfur in Petroleum and Petroleum Products by Energy Dispersive X-ray Fluorescence Spectrometry
- D4306** Practice for Aviation Fuel Sample Containers for Tests Affected by Trace Contamination
- D4529** Test Method for Estimation of Net Heat of Combustion of Aviation Fuels
- D4629** Test Method for Trace Nitrogen in Liquid Petroleum Hydrocarbons by Syringe/Inlet Oxidative Combustion and Chemiluminescence Detection
- D4809** Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter (Precision Method)
- D4865** Guide for Generation and Dissipation of Static Electricity in Petroleum Fuel Systems
- D4952** Test Method for Qualitative Analysis for Active Sulfur Species in Fuels and Solvents (Doctor Test)
- D4953** Test Method for Vapor Pressure of Gasoline and Gasoline-Oxygenate Blends (Dry Method)
- D5001** Test Method for Measurement of Lubricity of Aviation Turbine Fuels by the Ball-on-Cylinder Lubricity Evaluator (BOCLE)
- D5006** Test Method for Measurement of Fuel System Icing Inhibitors (Ether Type) in Aviation Fuels
- D5190** Test Method for Vapor Pressure of Petroleum Products (Automatic Method) (Withdrawn 2012)<sup>3</sup>
- D5191** Test Method for Vapor Pressure of Petroleum Products (Mini Method)
- D5291** Test Methods for Instrumental Determination of Carbon, Hydrogen, and Nitrogen in Petroleum Products and Lubricants
- D5452** Test Method for Particulate Contamination in Aviation Fuels by Laboratory Filtration
- D5453** Test Method for Determination of Total Sulfur in Light Hydrocarbons, Spark Ignition Engine Fuel, Diesel Engine Fuel, and Engine Oil by Ultraviolet Fluorescence

<sup>3</sup> The last approved version of this historical standard is referenced on [www.astm.org](http://www.astm.org).

- D5972** Test Method for Freezing Point of Aviation Fuels (Automatic Phase Transition Method)
- D6045** Test Method for Color of Petroleum Products by the Automatic Tristimulus Method
- D6304** Test Method for Determination of Water in Petroleum Products, Lubricating Oils, and Additives by Coulometric Karl Fischer Titration
- D6379** Test Method for Determination of Aromatic Hydrocarbon Types in Aviation Fuels and Petroleum Distillates—High Performance Liquid Chromatography Method with Refractive Index Detection
- D6469** Guide for Microbial Contamination in Fuels and Fuel Systems
- D6866** Test Methods for Determining the Biobased Content of Solid, Liquid, and Gaseous Samples Using Radiocarbon Analysis
- D7042** Test Method for Dynamic Viscosity and Density of Liquids by Stabinger Viscometer (and the Calculation of Kinematic Viscosity)
- D7111** Test Method for Determination of Trace Elements in Middle Distillate Fuels by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES)
- D7153** Test Method for Freezing Point of Aviation Fuels (Automatic Laser Method)
- D7154** Test Method for Freezing Point of Aviation Fuels (Automatic Fiber Optical Method)
- D7359** Test Method for Total Fluorine, Chlorine and Sulfur in Aromatic Hydrocarbons and Their Mixtures by Oxidative Pyrohydrolytic Combustion followed by Ion Chromatography Detection (Combustion Ion Chromatography-CIC)
- D7974** Test Method for Determination of Farnesane, Saturated Hydrocarbons, and Hexahydrofarnesol Content of Synthesized Iso-Paraffins (SIP) Fuel for Blending with Jet Fuel by Gas Chromatography
- E29** Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- 2.2 *Energy Institute Standards*:<sup>4</sup>
- EI/JIG 1530** Quality Assurance Requirements for the Manufacture, Storage and Distribution of Aviation Fuels to Airports
- IP 12** Determination of Specific Energy
- IP 16** Determination of the Freezing Point of Aviation Fuels—Manual Method
- IP 30** Detection of Mercaptans, Hydrogen Sulfide, Elemental Sulfur and Peroxides—Doctor Test Method
- IP 34** Determination of Flash Point—Pensky-Martens Closed Cup Method
- IP 69** Vapour Pressure-Reid Method (St-B-9)
- IP 71, Section 1** Petroleum Products—Transparent and Opaque Liquids—Determination of Kinematic Viscosity and Calculation of Dynamic Viscosity
- IP 123** Petroleum Products—Determination of Distillation Characteristics at Atmospheric Pressure
- IP 154** Petroleum Products—Corrosiveness to Copper—Copper Strip Test
- IP 156** Petroleum Products and Related Materials—Determination of Hydrocarbon Types—Fluorescent Indicator Adsorption Method
- IP 160** Crude Petroleum and Liquid Petroleum Products—Laboratory Determination of Density—Hydrometer Method
- IP 170** Determination of Flash Point—Abel Closed-Cup Method
- IP 216** Particulate Contaminant in Aviation Fuel
- IP 225** Determination of Copper in Light Petroleum Distillates—Spectrophotometric Method
- IP 227** Corrosiveness to Silver of Aviation Turbine Fuels—Silver Strip Method
- IP 274** Determination of Electrical Conductivity of Aviation and Distillate Fuels
- IP 299** Determination of Bromine Index—Electrometric Titration Method
- IP 323** Determination of Thermal Oxidation Stability of Gas Turbine Fuels
- IP 336** Petroleum Products—Determination of Sulfur Content—Energy-Dispersive X-ray Fluorescence Spectrometry
- IP 342** Petroleum Products—Determination of Thiol (Mercaptan) Sulfur in Light and Middle Distillate Fuels—Potentiometric Method
- IP 354** Determination of the Acid Number of Aviation Fuels—Colour-Indicator Titration Method
- IP 365** Crude Petroleum and Petroleum Products—Determination of Density—Oscillating U-tube Method
- IP 379** Determination of Organically Bound Trace Nitrogen—Oxidative Combustion and Chemiluminescence Method
- IP 394** Liquid Petroleum Products—Vapour Pressure—Part 1: Determination of Air Saturated Vapour Pressure (ASVP) and Calculated Dry Vapour Pressure Equivalent (DVPE)
- IP 406** Petroleum Products—Determination of Boiling Range Distribution by Gas Chromatography
- IP 423** Determination of Particulate Contaminant in Aviation Turbine Fuels by Laboratory Filtration
- IP 435** Determination of the Freezing Point of Aviation Turbine Fuels by the Automatic Phase Transition Method
- IP 436** Determination of Aromatic Hydrocarbon Types in Aviation Fuels and Petroleum Distillates—High Performance Liquid Chromatography Method with Refractive Index Detection
- IP 438** Determination of Water—Coulometric Karl Fischer Titration Method
- IP 475** Petroleum Liquids—Manual Sampling
- IP 523** Determination of Flash Point—Rapid Equilibrium Closed Cup Method
- IP 524** Determination of Flash/No Flash—Rapid Equilibrium Closed Cup Method
- IP 528** Determination for the Freezing Point of Aviation Turbine Fuels—Automatic Fibre Optic Method
- IP 529** Determination of the Freezing Point of Aviation Fuels—Automatic Laser Method

<sup>4</sup> Available from Energy Institute, 61 New Cavendish St., London, WIG 7AR, U.K., <http://www.energyinst.org.uk>.

**IP 540** Determination of the Existent Gum Content of Aviation Turbine Fuel—Jet Evaporation Method

**IP 585** Determination of Fatty Acid Methyl Esters (FAME), Derived from Bio-diesel Fuel, in Aviation Turbine Fuel—GC-MS with Selective Ion Monitoring/Scan Detection Method

**IP 590** Determination of Fatty Acid Methyl Esters (FAME) in Aviation Turbine Fuel—HPLC Evaporative Light Scattering Detector Method

**IP 598** Petroleum Products—Determination of the Smoke Point of Kerosine, Manual and Automated Method

2.3 *ANSI Standard*.<sup>5</sup>

**ANSI 863** Report of Test Results

2.4 *API Standards*.<sup>6</sup>

**API 1543** Documentation, Monitoring and Laboratory Testing of Aviation Fuel During Shipment from Refinery to Airport

**API 1595** Design, Construction, Operation, Maintenance, and Inspection of Aviation Pre-Airfield Storage Terminals<sup>6</sup>

2.5 *Joint Inspection Group Standards*.<sup>7</sup>

**JIG 1** Aviation Fuel Quality Control & Operating Standards for Into-Plane Fuelling Services

**JIG 2** Aviation Fuel Quality Control & Operating Standards for Airport Depots & Hydrants<sup>7</sup>

2.6 *IATA Guidance*.<sup>8</sup>

**9680-04** IATA Guidance Material on Microbiological Contamination in Aircraft Fuel Tanks

2.7 *UOP Test Methods*.<sup>9</sup>

**UOP 389** Trace Metals in Oils by Wet Ash/ICP-AES

2.8 *U.S. Department of Defense Specifications*.<sup>10</sup>

**MIL-PRF-25017** Inhibitor, Corrosion/Lubricity Improver, Fuel Soluble

**QDS-25017** Qualified Data Set for MIL-PRF-25017 (Inhibitor, Corrosion/Lubricity Improver, Fuel Soluble)

2.9 *Other Standards*:

**ATA-103** Standard for Jet Fuel Quality Control at Airports<sup>11</sup>  
**Defence Standard 91-91** Turbine Fuel, Aviation Kerosine Type, Jet A-1<sup>12</sup>

**ICAO 9977** Manual on Civil Aviation Jet Fuel Supply<sup>13</sup>

**AFRL-RQ-WP-TR-2013-0271** Determination of the Minimum Use Level of Fuel System Icing Inhibitor (FSII) in JP-8 that will Provide Adequate Icing Inhibition and Biostatic Protection for Air Force Aircraft<sup>14</sup>

### 3. General

3.1 This specification, unless otherwise provided, prescribes the required properties of aviation turbine fuel at the time and place of batch origination.

### 4. Terminology

#### 4.1 Definitions:

4.1.1 *conventional hydrocarbons, n*—hydrocarbons derived from the following conventional sources: crude oil, natural gas liquid condensates, heavy oil, shale oil, and oil sands.

#### 4.2 Definitions of Terms Specific to This Standard:

4.2.1 *batch origination, n*—location at which fuel is certified as D7566.

4.2.2 *conventional blending component, n*—blending streams derived from conventional hydrocarbons.

4.2.3 *hydroprocessed, adj*—conventional chemical processing in which hydrogen is reacted with organic compounds in the presence of a catalyst to remove impurities such as oxygen, sulfur, nitrogen; to saturate unsaturated hydrocarbons; or to alter the molecular structure of the hydrocarbon molecules.

4.2.4 *identified incidental materials, n*—chemicals and compositions that have defined upper content limits in an aviation fuel specification but are not approved additives.

4.2.5 *synthesized hydrocarbons, n*—hydrocarbons derived from alternative sources such as coal, natural gas, biomass, and hydrogenated fats and oils by processes such as gasification, Fischer-Tropsch synthesis, and hydroprocessing.

4.2.6 *synthetic blending component, n*—synthesized hydrocarbons that meet the requirements of **Annex A1**, **Annex A2**, or **Annex A3**.

4.2.7 *synthesized iso-paraffins (SIP), n*—synthetic blending component that is comprised essentially of iso-paraffins.

4.2.8 *synthesized paraffinic kerosine (SPK), n*—synthetic blending component that is comprised essentially of iso-paraffins, normal paraffins, and cycloparaffins.

4.2.8.1 *Discussion*—Trace materials are permitted provided they are components that normally occur in hydroprocessed jet fuel including, but not limited to, trace organics, nitrogen compounds, water, dissolved air, etc.

4.2.9 *synthesized paraffinic kerosine plus aromatics (SPK/A), n*—synthetic blending component that is comprised of synthesized paraffinic kerosine (SPK) to which synthesized aromatics have been added.

### 5. Classification

5.1 Two grades of aviation turbine fuels are provided, as follows:

<sup>14</sup> Available from Defense Technical Information Center (DTIC), 8725 John J. Kingman Rd., Ft. Belvoir, VA 22060-6218, <http://www.dtic.mil/dtic>, accession number ADA595127.

<sup>5</sup> Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, <http://www.ansi.org>.

<sup>6</sup> Available from American Petroleum Institute (API), 1220 L. St., NW, Washington, DC 20005-4070, <http://www.api.org>.

<sup>7</sup> Available from Joint Inspection Group (JIG), <http://www.jigonline.com>.

<sup>8</sup> Available from International Air Transport Association (IATA). Head Office: 800 Place Victoria, PO Box 113, Montreal, H4Z 1M1, Quebec, Canada. Executive Office: 33, Route de l'Aéroport, PO Box 416, 1215 Geneva, 15 Airport, Switzerland. [www.iata.org](http://www.iata.org).

<sup>9</sup> Available from ASTM International, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org).

<sup>10</sup> Available from the Standardization Document Order Desk, 700 Robbins, Avenue, Building 4D, Philadelphia PA 19111-5094 (<http://assist.daps.dla.mil>).

<sup>11</sup> Available from Air Transport Association of America, Inc. (ATA) d/b/a Airlines for America, 1301 Pennsylvania Ave. NW, Suite 1100, Washington, D.C. 20004, <http://www.airlines.org>.

<sup>12</sup> Available from Defence Equipment and Support, UK Defence Standardization, Kentigern House, 65 Brown Street, Glasgow, G2 8EX (<http://www.dstan.mod.uk>).

<sup>13</sup> Available from International Civil Aviation Organization (ICAO), 999 University St., Montreal, Quebec H3C 5H7, Canada, <http://www.icao.int>.

5.1.1 *Jet A and Jet A-1*—Relatively high flash point distillates of the kerosine type.

5.2 Jet A and Jet A-1 represent two grades of kerosine fuel that differ in freezing point. Other grades would be suitably identified.

## 6. Materials and Manufacture

6.1 Aviation turbine fuel, except as otherwise defined in this specification, shall consist of the following blends of components or fuels:

6.1.1 Conventional blending components or Jet A or Jet A-1 fuel certified to Specification **D1655**; with up to 50 % by volume of the synthetic blending component defined in **Annex A1**.

6.1.2 Conventional blending components or Jet A or Jet A-1 fuel certified to Specification **D1655**; with up to 50 % by volume of the synthetic blending component defined in **Annex A2**.

NOTE 1—The ability to add 50 % of **Annex A1** or **Annex A2** blending components (SPK) to Jet A or Jet A-1 is also limited by the physical properties of the fuel with which it is being blended. Practice has shown that density, or aromatic content, or both, of the refined fuel often limit the amount of SPK that can be added to the final blend to less than 50 %.

6.1.3 Conventional blending components or Jet A or Jet A-1 fuel certified to Specification **D1655**; with up to 10 % by volume of the synthetic blending component defined in **Annex A3**.

NOTE 2—The ability to add 10 % of **Annex A3** blending components (SIP) to Jet A or Jet A-1 may also be limited by the physical properties of the fuel with which it is being blended. It is possible in extreme cases that viscosity of the refined fuel may limit the amount of SIP that can be added to the final blend to less than 10 %.

6.1.4 Conventional blending components or Jet A or Jet A-1 fuel certified to Specification **D1655**; with up to 50 % by volume of the synthetic blending component defined in **Annex A4**.

NOTE 3—The ability to add 50 % of **Annex A4** blending components (SPK/A) to Jet A or Jet A-1 may also be limited by the physical properties of the fuel with which it is being blended. The density, or aromatic content, or both, of the refined fuel may limit the amount of SPK/A that can be added to the final blend to less than 50 %.

6.2 Fuels used in certified engines and aircraft are ultimately approved by the certifying authority subsequent to formal submission of evidence to the authority as part of the type certification program for that aircraft and engine model. Additives to be used as supplements to an approved fuel must also be similarly approved on an individual basis (see **X1.2.4**).

6.3 *Additives*—Only additives approved by the aviation industry (including the aircraft certifying authority) are permitted in the fuel on which an aircraft is operated. The additives approved for use in D7566 jet fuel are shown in **Table 1** and **Table 2** and may be used within the concentration limits shown in the tables subject to any restrictions described in the table footnotes.<sup>15</sup>

<sup>15</sup> Supporting data (Guidelines for Approval or Disapproval of Additives) have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D02-1125.

6.4 Guidance material is presented in **Appendix X3** concerning the need to control processing additives in jet fuel production.

6.5 From the point of manufacture to the point of blending to meet this specification, the synthetic blending component shall be handled and transported in the same manner as finished jet fuel in order to maintain product integrity. Appropriate management of change measures shall be used at manufacturing locations, distribution, and storage to maintain product integrity (see **Appendix X3**).

## 7. Detailed Requirements

7.1 The aviation turbine fuel shall conform to the requirements prescribed in **Table 1** Part 1 and **Table 1** Part 2 unless otherwise noted in **7.2**, **Annex A1**, **Annex A2**, **Annex A3**, or **Annex A4**, whichever is applicable.

7.2 The fluidity requirement of Part 2 of **Table 1** only applies to each batch of fuel containing the synthesized iso-paraffins (SIP) blending component as defined in **Annex A3** and blended in accordance with **6.1.3**. This requirement does not apply to fuel containing **Annex A1**, **Annex A2**, or **Annex A4** synthesized components and blended in accordance with **6.1.1**, **6.1.2**, or **6.1.4**.

7.3 The additional requirements of Part 2 of **Table 1** apply only for each batch of fuel intentionally containing a synthetic blending component. The additional requirements of Part 2 of **Table 1** are not mandated if conventionally-derived jet fuel is mixed with the residue of a D7566 semi-synthetic aviation turbine fuel in refinery equipment from a previous batch of certified final blended product, for example in a tank heel.

7.4 Test results shall not exceed the maximum or be less than the minimum values specified in **Table 1**, **Tables A1.1** and **A1.2**, **Tables A2.1** and **A2.2**, **Tables A3.1** and **A3.2**, and **Tables A4.1** and **A4.2**. No allowance shall be made for the precision of the test methods. To determine conformance to the specification requirement, a test result may be rounded to the same number of significant figures as in **Table 1**, **Tables A1.1** and **A1.2**, **Tables A2.1** and **A2.2**, **Tables A3.1** and **A3.2**, and **Tables A4.1** and **A4.2** using Practice **E29**. Where multiple determinations are made, the average result, rounded in accordance with Practice **E29**, shall be used.

## 8. Workmanship, Finish, and Appearance

8.1 The aviation turbine fuel specified in this specification shall be visually free of undissolved water, sediment, and suspended matter. The odor of the fuel shall not be nauseating or irritating. If the fuel has an odor similar to that of “rotten egg,” please refer to **X1.12.5** for further discussion. No substance of known dangerous toxicity under usual conditions of handling and use shall be present, except as permitted in this specification.

## 9. Sampling

9.1 Because of the importance of proper sampling procedures in establishing fuel quality, use the appropriate procedures in Practice **D4057** or IP 475 to obtain a representative sample from the batch of fuel for specification compliance

**TABLE 1 Detailed Requirements of Aviation Turbine Fuels Containing Synthesized Hydrocarbons<sup>A</sup>**

## Part 1—Basic Requirements

Property		Jet A or Jet A-1	Test Method <sup>B</sup>
<b>COMPOSITION</b>			
Acidity, total mg KOH/g	Max	0.10	D3242/IP 354
Aromatics: One of the following requirements shall be met:			
1. Aromatics, volume percent	Max	25	D1319 or IP 156
2. Aromatics, volume percent	Max	26.5	D6379/IP 436
Sulfur, mercaptan, <sup>C</sup> mass percent	Max	0.003	D3227/IP 342
Sulfur, total mass percent	Max	0.30	D1266, D2622, D4294, D5453, or IP 336
<b>VOLATILITY</b>			
Distillation			
Distillation temperature, °C:			
10 % recovered, temperature (T10)	Max	205	D2887/IP 406 <sup>D</sup> or D86 <sup>E</sup> or IP 123 <sup>F</sup>
50 % recovered, temperature (T50)		report	
90 % recovered, temperature (T90)		report	
Final boiling point, temperature	Max	300	
Distillation residue, percent	Max	1.5	
Distillation loss, percent	Max	1.5	
Flash point, °C	Min	38 <sup>F</sup>	D56 or D3828 <sup>G</sup> , IP 170 <sup>G</sup> or IP 523 <sup>G</sup>
Density at 15 °C, kg/m <sup>3</sup>		775 to 840	D1298/IP 160 or D4052 or IP 365
<b>FLUIDITY</b>			
Freezing point, °C	Max	−40 Jet A <sup>H</sup>	D5972/IP 435, D7153/IP 529, D7154/IP 528, or D2386/IP 16
		−47 Jet A-1 <sup>H</sup>	
Viscosity −20 °C, mm <sup>2</sup> /s <sup>I</sup>	Max	8.0	D445/IP 71, Section 1, D7042 <sup>J</sup>
<b>COMBUSTION</b>			
Net heat of combustion, MJ/kg	Min	42.8 <sup>K</sup>	D4529, D3338, D4809 or IP 12
One of the following requirements shall be met:			
(1) Smoke point, mm, or	Min	25.0	D1322/IP 598
(2) Smoke point, mm, and	Min	18.0	D1322/IP 598
Naphthalenes, volume, percent	Max	3.0	D1840
<b>CORROSION</b>			
Copper strip, 2 h at 100 °C	Max	No. 1	D130/IP 154
<b>THERMAL STABILITY</b>			
2.5 h at control temperature of 260 °C, min			
Filter pressure drop, mm Hg	Max	25	D3241 <sup>L</sup> /IP 323 <sup>L</sup>
Tube rating: One of the following requirements shall be met: <sup>M</sup>			
(1) Annex A1 VTR, VTR Color Code	Less than	3	
		No peacock or abnormal color deposits	
(2) Annex A2 ITR or Annex A3 ETR, nm avg over area of 2.5 mm <sup>2</sup>	Max	85	
<b>CONTAMINANTS</b>			
Existent gum, mg/100 mL	Max	7	D381, IP 540
Microseparator, <sup>N</sup> Rating			D3948
Without electrical conductivity additive	Min	85	
With electrical conductivity additive	Min	70	
<b>ADDITIVES</b>			
Electrical conductivity, pS/m		See 6.3 <sup>O</sup>	D2624/IP 274

## Part 2—Extended Requirements

Property		Jet A or Jet A-1	Test Method <sup>B</sup>
<b>COMPOSITION</b>			
Aromatics: One of the following requirements shall be met:			
1. Aromatics, volume percent	Min <sup>P,Q</sup>	8	D1319 or IP 156
2. Aromatics, volume percent	Min <sup>P,Q</sup>	8.4	D6379/IP 436
<b>VOLATILITY</b>			
Distillation			
T50-T10, °C	Min <sup>Q,R</sup>	15	D2887/IP 406 <sup>D</sup> , D86 <sup>E</sup> or IP 123 <sup>F</sup>
T90-T10, °C	Min <sup>Q,R</sup>	40	
<b>LUBRICITY</b>			
Lubricity, <sup>O,N</sup> mm	Max	0.85	D5001
<b>FLUIDITY<sup>S</sup></b>			
Viscosity −40 °C, mm <sup>2</sup> /s	Max	12	D445 <sup>T</sup> /, Section 1 <sup>T</sup>

<sup>A</sup> For compliance of test results against the requirements of [Table 1](#), see [7.3](#).

<sup>B</sup> The test methods indicated in this table are referred to in [Section 11](#).

<sup>C</sup> The mercaptan sulfur determination may be waived if the fuel is considered sweet by the doctor test described in Test Method [D4952](#) or IP 30.

<sup>D</sup> Distillation property criteria are specified in [D86](#) or IP 123 scale units. [D2887](#)/IP 406 results shall be converted to estimated [D86](#) or IP 123 results by application of the correlation in Appendix X5 of [D2887](#) or Annex G of IP 406 for comparison with the specified property criteria. Distillation residue and loss limits provide control of the distillation process during the [D86](#) and IP 123 test methods and do not apply to [D2887](#)/IP 406. Distillation residue and loss shall be reported as “not applicable” (N/A) when reporting [D2887](#)/IP 406 results.

<sup>E</sup> [D86](#) or IP 123 distillation of jet fuel is run at Group 4 conditions, except Group 3 condenser temperature is used.

<sup>F</sup> A higher minimum flash point specification may be agreed upon between purchaser and supplier.

<sup>G</sup> Results obtained by other test methods can be up to 2 °C lower than those obtained by Test Method [D56](#), which is the preferred method. In case of dispute, Test Method [D56](#) will apply.

<sup>H</sup> Other freezing points may be agreed upon between supplier and purchaser.

<sup>I</sup> 1 mm<sup>2</sup>/s = 1 cSt.

<sup>J</sup> Test Method [D7042](#) results shall be converted to bias-corrected kinematic viscosity results by the application of the correction described in Test Method [D7042](#), section 15.4.4.

<sup>K</sup> For all grades use either Eq 1 or Table 1 in Test Method [D4529](#) or Eq 2 in Test Method [D3338](#) or IP 12. Test Method [D4809](#) may be used as an alternative. In case of dispute, Test Method [D4809](#) shall be used.

<sup>L</sup> [D3241](#)/IP 323 Thermal Stability is a critical aviation fuel test, the results of which are used to assess the suitability of jet fuel for aviation operational safety and regulatory compliance. The integrity of [D3241](#)/IP 323 testing requires that heater tubes (test coupons) meet the requirements of [D3241](#) Table 2 and give equivalent [D3241](#) results to the heater tubes supplied by the original equipment manufacturer (OEM). A test protocol to demonstrate equivalence of heater tubes from other suppliers is on file at ASTM International Headquarters and can be obtained by requesting Research Report RR:D02-1550. Heater tubes and filter kits, manufactured by the OEM (PAC, 8824 Fallbrook Drive, Houston, TX 77064) were used in the development of the [D3241](#)/IP 323 test method. Heater tube and filter kits, manufactured by Falex (Falex Corporation, 1020 Airpark Dr., Sugar Grove, IL, 60554-9585) were demonstrated to give equivalent results (see [D3241](#) for research report references). These historical facts should not be construed as an endorsement or certification by ASTM International.

<sup>M</sup> Tube deposit ratings shall be measured by [D3241](#) Annex A2 ITR or Annex A3 ETR, when available. If the Annex A2 ITR device reports “N/A” for a tube’s volume measurement, the test shall be a failure and the value reported as >85 nm. Visual rating of the heater tube by the method in [D3241](#) Annex A1 is not required when Annex A2 ITR or Annex A3 ETR deposit thickness measurements are reported. In case of dispute between results from visual and metrological methods, the referee shall be considered the Annex A3 ETR method if available, otherwise Annex A2 ITR.

<sup>N</sup> At point of manufacture.

<sup>O</sup> If electrical conductivity additive is used, the conductivity shall not exceed 600 pS/m at the point of use of the fuel. When electrical conductivity additive is specified by the purchaser, the conductivity shall be 50 pS/m to 600 pS/m under the conditions at point of delivery. (1 pS/m = 1 × 10<sup>-12</sup> Ω<sup>-1</sup>m<sup>-1</sup>)

<sup>P</sup> Minimum aromatics contents are based on current experience with the approved synthetic fuels and those levels were established from what is typical for refined jet fuel. Research is ongoing on the actual need for aromatics.

<sup>Q</sup> The minimum aromatics and distillation slope criteria only apply to aviation turbine fuels containing synthesized hydrocarbons produced to this specification and are not applicable to conventional aviation turbine fuels produced to Specification [D1655](#). Some batches of aviation turbine fuels produced to Specification [D1655](#) may not meet the minimum aromatics and distillation slope criteria specified in [Table 1](#) of this specification.

<sup>R</sup> These distillation slope limits are based on current experience with the approved synthetic fuels and these values were established from what is typical for refined jet fuel. Research is ongoing on the actual requirements for distillation slope.

<sup>S</sup> The fluidity requirement applies only to jet fuel containing synthesized iso-paraffins specified in [Annex A3](#) and blended in accordance with [6.1.3](#). It does not apply to jet fuel containing [Annex A1](#), [Annex A2](#), or [Annex A4](#) synthesized components blended in accordance with [6.1.1](#), [6.1.2](#), or [6.1.4](#).

<sup>T</sup> [D445](#) or IP 71, Section 1 allows measuring the viscosity at –40 °C, however the precision values were determined down to –20 °C. Data correlating test results at –40 °C for [D445](#) and other related ASTM test methods is provided in Research Report RR:D02-1776, Evaluation of Synthesized Iso-Paraffins produced from Hydroprocessed Fermented Sugars (SIP Fuels), prepared by TOTAL New Energies, Amyris, Inc. and the United States Air Force Research Laboratory (AFRL), Final Version, February 2014. A revision to Test Method [D445](#) to specify measurement precision at –40 °C is in process.

## ASTM D7566-15c

<https://standards.iteh.ai/catalog/standards/sist/d3494b68-c3d2-4887-8f6f-a7f2ca505f14/astm-d7566-15c>

testing. This requirement is met by producing fuel as a discrete batch then testing it for specification compliance. This requirement is not satisfied by averaging online analysis results.

9.2 A number of jet fuel properties, including thermal stability, water separation, electrical conductivity, and others, are very sensitive to trace contamination, which can originate from sample containers. For recommended sample containers, refer to Practice [D4306](#).

## 10. Report

10.1 The type and number of reports to ensure conformance with the requirements of this specification shall be mutually agreed upon by the seller and the purchaser of the aviation turbine fuel.

10.2 A suggested form for reporting inspection data on aviation turbine fuels is given in [Appendix X4](#).

## 11. Test Methods

NOTE 4—Where IP test methods are referenced in this standard as alternatives to ASTM test methods, the following nomenclature is used. Where test methods are officially jointed, this is denoted as Dxxxx/IP xxx. Where test methods are technically equivalent or related but not officially jointed, this is denoted as Dxxxx or IP xxx.

11.1 Determine the requirements enumerated in this specification in accordance with the following test methods.

11.1.1 *Density*—Test Method [D1298](#)/IP 160 or [D4052](#) or IP 365.

11.1.2 *Distillation*—Test Method [D86](#) or IP 123. For Jet A and Jet A-1, Test Method [D2887](#)/IP 406 may be used as an alternate. Results from Test Method [D2887](#)/IP 406 shall be reported as estimated [D86](#) or IP 123 results by application of the correlation in Appendix X5 of [D2887](#) or Annex G of IP 406. In case of dispute, Test Method [D86](#) shall be the referee method (see [X1.6.1.1](#)).

11.1.3 *Flash Point*—Test Method [D56](#), [D3828](#), IP 170 or IP 523.

11.1.4 *Freezing Point*—Test Method [D5972](#)/IP 435, [D7153](#)/IP 529, [D7154](#)/IP 528, or [D2386](#)/IP 16. Any of these test methods may be used to certify and recertify jet fuel. However, Test Method [D2386](#)/IP 16 is the referee method. An interlaboratory study (RR:D02-1572<sup>16</sup>) that evaluated the ability of freezing point methods to detect jet fuel contamination

<sup>16</sup> Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D02-1572. Contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org).

**TABLE 2 Detailed Requirements for Additives in Aviation Turbine Fuels**

Additive	Dosage
Fuel Performance Enhancing Additives	
Antioxidants <sup>A,B</sup> One of the following: 2,6 ditertiary-butyl phenol 2,6 ditertiary-butyl-4-methyl phenol 2,4 dimethyl-6-tertiary-butyl-phenol 75 % minimum, 2,6 ditertiary-butyl phenol plus 25 % maximum mixed tertiary and tritertiary butyl-phenols 55 % minimum 2,4 dimethyl-6-tertiary-butyl phenol plus 15 % minimum 2,6 ditertiary-butyl-4-methyl phenol, remainder as monomethyl and dimethyl tertiary-butyl phenols 72 % minimum 2,4 dimethyl-6-tertiary-butyl phenol plus 28 % maximum monomethyl and dimethyl-tertiary-butyl-phenols	24.0 mg/L max <sup>C</sup>
Metal Deactivator <sup>A</sup> N,N-disalicylidene-1,2-propane diamine On initial blending After field reblending cumulative concentration	2.0 mg/L max <sup>C,D</sup> 5.7 mg/L max
Fuel System Icing Inhibitor <sup>E,F</sup> Diethylene Glycol Monomethyl Ether (see Specification D4171 Type III)	0.07 % by volume min <sup>G</sup> 0.15 % by volume max
Fuel Handling and Maintenance Additives	
Electrical Conductivity Improver <sup>H</sup> Stadis 450 <sup>I</sup> On initial blending After field reblending, cumulative concentration If the additive concentration is unknown at time of retreatment, additional concentration is restricted to 2 mg/L max	3 mg/L max 5 mg/L max
Leak Detection Additive Tracer A (LDTA-A) <sup>J</sup>	1 mg/kg max
Biocidal Additives <sup>E,K,L</sup> Biobor JF <sup>M</sup> Kathon FP1.5 <sup>N</sup> Corrosion Inhibitor/Lubricity Improvers <sup>O</sup> One of the following: HITEC 580 Innospec DCI-4A Nalco 5403	23 mg/L max 23 mg/L max 23 mg/L max

<sup>A</sup> The active ingredient of the additive must meet the composition specified.

<sup>B</sup> Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D02-1125.

<sup>C</sup> Active ingredient (not including weight of solvent).

<sup>D</sup> If copper contamination is suspected, initial treatment may exceed 2.0 mg/L but cumulative total must be below 5.7 mg/L.

<sup>E</sup> Quantity must be declared by the fuel supplier and agreed to by the purchaser.

<sup>F</sup> DIEGME content can be analyzed by Test Method D5006.

<sup>G</sup> The lower FSII concentration limit allowable in Jet Fuel is based on research by the US Air Force as documented in report AFRL-RQ-WP-TR-2013-0271. Some engines and aircraft as certificated require higher minimum concentrations of icing inhibitor than the lower limit in this Jet Fuel specification. When fueling an aircraft, the fuel should be added to the concentration levels specified in the appropriate engine and aircraft manual.

<sup>H</sup> If electrical conductivity improver is used, the conductivity shall not exceed 600 pS/m at the point of use of the fuel. When electrical conductivity additive is specified by the purchaser, the conductivity shall be 50 pS/m to 600 pS/m under the conditions at point of delivery. (1 pS/m =  $1 \times 10^{-12} \Omega^{-1} \text{m}^{-1}$ )

<sup>I</sup> Stadis 450 is a registered trademark marketed by Innospec Inc., Innospec Manufacturing Park, Oil Sites Road, Ellesmere Port, Cheshire, CH65 4EY, UK.

<sup>J</sup> Tracer A (LDTA-A) is a registered trademark of Tracer Research Corp., 3755 N. Business Center Dr., Tucson, AZ 85705.

<sup>K</sup> Biocidal additives are available for controlled usage. Where such an additive is used in the fuel, the approval status of the additive and associated conditions must be checked for the specific aircraft and engines to be operated.

<sup>L</sup> Refer to the Aircraft Maintenance Manual (AMM) to determine if either biocide is approved for use and for their appropriate use and dosage.

<sup>M</sup> Biobor JF is a registered trademark of Hammonds Technical Services, Inc., 910 Rankin Rd., Houston, TX 77073.

<sup>N</sup> KATHON is a trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow, 2030 Dow Center, Midland, MI 48674. HITEC 580 is a trademark of Afton Chemical Corp., 500 Spring St., Richmond, VA 23219. Innospec DCI-4A is available from Innospec Inc., Innospec Manufacturing Park, Oil Sites Road, Ellesmere Port, Cheshire, CH65 4EY, UK.

<sup>O</sup> More information concerning minimum treat rates of corrosion inhibitor/lubricity improver additives is contained in X1.10.2.

by diesel fuel determined that Test Methods D5972/IP 435 and D7153/IP 529 provided significantly more consistent detection of freeze point changes caused by contamination than Test Methods D2386/IP 16 and D7154/IP 528. It is recommended to certify and recertify jet fuel using either Test Method D5972/IP 435 or Test Method D7153/IP 529, or both, on the basis of the reproducibility and cross-contamination detection reported in RR:D02-1572.<sup>16</sup> The cause of freezing point results outside

specification limits by automated methods should be investigated, but such results do not disqualify the fuel from aviation use if the results from the referee method (Test Method D2386/IP 16) are within the specification limit.

11.1.5 *Viscosity*—Test Method D445/IP 71, Section 1 or Test Method D7042. Results from Test Method D7042 shall be reported as bias-corrected kinematic viscosity results by application of the correction in Test Method D7042, subsection



15.4.4, Relative Bias for jet fuel. In case of dispute, Test Method **D445** shall be the referee method.

11.1.6 *Net Heat of Combustion*—Test Method **D4529**, **D3338**, **D4809**, or IP 12.

11.1.7 *Corrosion (Copper Strip)*—Test Method **D130/IP 154**.

11.1.8 *Total Acidity*—Test Method **D3242/IP 354**.

11.1.9 *Sulfur*—Test Method **D1266**, **D2622**, **D4294**, **D5453**, or IP 336.

11.1.10 *Mercaptan Sulfur*—Test Method **D3227/IP 342**.

11.1.11 *Microseparometer*—Test Method **D3948**.

11.1.12 *Existent Gum*—Test Method **D381** or IP 540. Test Method **D381**, using steam jet operating conditions, shall be the referee test method.

11.1.13 *Thermal Stability*—Test Method **D3241/IP 323**.

11.1.14 *Aromatics*—Test Method **D1319**, IP 156 or **D6379/IP 436**. Test Method **D1319** shall be the referee test method.

11.1.15 *Smoke Point*—Test Method **D1322/IP 598**.

11.1.16 *Naphthalene Content*—Test Method **D1840**.

11.1.17 *Electrical Conductivity*—Test Method **D2624 / IP 274**.

## 12. Keywords

12.1 aviation turbine fuel; avtur; Jet A; Jet A-1; jet fuel; synthesized aromatics; synthesized hydrocarbons; synthesized iso-paraffins; synthesized paraffinic kerosine; synthesized paraffinic kerosine plus aromatics; synthetic blending component; turbine fuel

## ANNEXES

### (Mandatory Information)

#### A1. FISCHER-TROPSCH HYDROPROCESSED SYNTHESIZED PARAFFINIC KEROSENE

##### A1.1 Scope

A1.1.1 This annex defines hydroprocessed synthesized paraffinic kerosine (SPK) for use as a synthetic blending component in aviation turbine fuels for use in civil aircraft and engines. The specifications in this annex can be used for contractual exchange of synthetic blending components.

A1.1.2 The synthetic blending components defined in this annex are not satisfactory for aviation turbine engines unless blended with conventional fuel or conventional blending components in accordance with the limitations described in **6.1.1**.

A1.1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

##### A1.2 General

A1.2.1 All requirements of the main body of this specification apply except as detailed in this annex.

##### A1.3 Terminology

A1.3.1 *Definitions of Terms Specific to This Annex:*

A1.3.1.1 *Fischer-Tropsch hydroprocessed synthesized paraffinic kerosine (FT-SPK), n*—SPK produced from one or more precursors synthesized by Fischer-Tropsch processing.

##### A1.4 Materials and Manufacture

A1.4.1 FT-SPK synthetic blending components shall be comprised of hydroprocessed synthesized paraffinic kerosine wholly derived from:

A1.4.1.1 Paraffins and olefins derived from synthesis gas via the Fischer-Tropsch (FT) process using Iron or Cobalt catalyst.

A1.4.1.2 Subsequent processing of the product shall include hydrotreating, hydrocracking, or hydroisomerization and is

expected to include, but not be limited to, a combination of other conventional refinery processes such as polymerization, isomerization, and fractionation.<sup>17</sup>

##### A1.5 Detailed Batch Requirements

A1.5.1 Each batch of synthetic blending component shall conform to the requirements prescribed in **Table A1.1**.

A1.5.2 *Test Methods*—Determine the requirements enumerated in this annex in accordance with the following test methods.

A1.5.2.1 *Density*—Test Method **D1298/IP 160**, **D4052** or IP 365.

A1.5.2.2 *Distillation*—Test Methods **D86** or IP 123, and **D2887/IP 406**.

A1.5.2.3 *Flash Point*—Test Method **D56**, **D3828**, IP 170 or IP 523.

A1.5.2.4 *Freezing Point*—Test Method **D5972/IP 435**, **D7153/IP 529**, **D7154/IP 528**, or **D2386/IP 16**. Any of these test methods may be used to certify and recertify jet fuel. However, Test Method **D2386/IP 16** is the referee method. An interlaboratory study (RR:D02-1572<sup>16</sup>) that evaluated the ability of freezing point methods to detect jet fuel contamination by diesel fuel determined that Test Methods **D5972/IP 435** and **D7153/IP 529** provided significantly more consistent detection of freeze point changes caused by contamination than Test Methods **D2386/IP 16** and **D7154/IP 528**. It is recommended to certify and recertify jet fuel using either Test Method **D5972/IP 435** or Test Method **D7153/IP 529**, or both, on the basis of the reproducibility and cross-contamination detection reported in

<sup>17</sup> Coordinating Research Council (CRC) Report, "Comparative Evaluation of Semi-Synthetic Jet Fuels," September 2008, provides a more detailed description of the composition and performance of FT-SPK blending components that evolved from the evaluation of representative samples of these blending components.

RR:D02-1572.<sup>16</sup> The cause of freezing point results outside specification limits by automated methods should be investigated, but such results do not disqualify the fuel from aviation use if the results from the referee method (Test Method **D2386**/IP 16) are within the specification limit.

A1.5.2.5 *Total Acidity*—Test Method **D3242**/IP 354.

A1.5.2.6 *Thermal Stability*—Test Method **D3241**/IP 323.

#### **A1.6 Other Detailed Requirements**

A1.6.1 The hydroprocessed SPK blend component shall meet the requirements of **Table A1.2**. It is not necessary to analyze each batch of hydroprocessed SPK for compliance with **Table A1.2** once it is demonstrated that the process scheme is adequately controlled to support the expectation that these requirements are always met. At a minimum, significant changes in production operations shall be cause for recertifying that these limits continue to be met.

A1.6.2 *Test Methods*—Determine the requirements enumerated in this annex in accordance with the following test methods.

A1.6.2.1 *Cycloparaffins*—Test Method **D2425**.

A1.6.2.2 *Aromatics*—Test Method **D2425**.

A1.6.2.3 *Paraffins*—Test Method **D2425**.

A1.6.2.4 *Carbon and Hydrogen*—Test Method **D5291**.

A1.6.2.5 *Nitrogen*—Test Method **D4629**/IP 379.

A1.6.2.6 *Water*—Test Method **D6304** or IP 438.

A1.6.2.7 *Sulfur*—Test Methods **D5453** or **D2622**. Either of these test methods can be used to certify and recertify jet fuel. However, Test Method **D5453** is the referee method.

A1.6.2.8 *Metals*—Test Method **D7111** or UOP 389.

A1.6.2.9 *Halogens*—Test Method **D7359**.

iTeh Standards  
(<https://standards.itih.ai>)  
Document Preview

[ASTM D7566-15c](#)

<https://standards.itih.ai/catalog/standards/sist/d3494b68-c3d2-4887-8f6f-a7f2ca505f14/astm-d7566-15c>

**TABLE A1.1 Detailed Batch Requirements; Fischer–Tropsch Hydroprocessed SPK<sup>A</sup>**

Property		FT–SPK	Test Method <sup>B</sup>
<b>COMPOSITION</b>			
Acidity, total mg KOH/g	Max	0.015	D3242/IP 354
<b>VOLATILITY</b>			
Distillation—both of the following requirements shall be met:			
1. Physical Distillation			
Distillation temperature, °C:			
10 % recovered, temperature (T10)	Max	205	D86 <sup>C</sup> or IP 123 <sup>C</sup>
50 % recovered, temperature (T50)		report	
90 % recovered, temperature (T90)		report	
Final boiling point, temperature T90-T10, °C	Max	300	
	Min	22	
Distillation residue, percent	Max	1.5	
Distillation loss, percent	Max	1.5	
2. Simulated Distillation			
Distillation temperature, °C:			
10 % recovered, temperature (T10)		report	D2887/IP 406
50 % recovered, temperature (T50)		report	
90 % recovered, temperature (T90)		report	
Final boiling point, temperature		report	
Flash point, °C	Min	38 <sup>D</sup>	D56, D3828 <sup>E</sup> , IP 170 <sup>E</sup> or IP 523 <sup>E</sup>
Density at 15 °C, kg/m <sup>3</sup>		730 to 770	D1298 / IP 160, D4052 or IP 365
Freezing point, °C	Max	−40	D5972 / IP 435, D7153/IP 529, D7154/IP 528, or D2386/IP 16
<b>Thermal Stability (2.5 h at control temperature)</b>			
Temperature, °C	Min	325 <sup>F</sup>	D3241 <sup>G</sup> /IP 323 <sup>G</sup>
Filter pressure drop, mm Hg	Max	25	
Tube rating: One of the following requirements shall be met: <sup>H</sup>			
(1) Annex A1 VTR, VTR Color Code	Less than	3	No peacock or abnormal color deposits
(2) Annex A2 ITR or Annex A3 ETR, nm avg over area of 2.5 mm <sup>2</sup>	Max	85	
<b>ADDITIVES</b>			
Antioxidants, mg/L <sup>I</sup>	Min	17	
	Max	24	

<sup>A</sup> For compliance of test results against the requirements of Table A1.1, see 7.4.

<sup>B</sup> The test methods indicated in this table are referred to in A1.5.2.

<sup>C</sup> D86 or IP 123 distillation of jet fuel is run at Group 4 conditions, except Group 3 condenser temperature is used.

<sup>D</sup> A higher or lower minimum flash point specification may be agreed upon between purchaser and supplier. When the agreed flash point is less than 38 °C then the product shall not be known as SPK or as kerosine, but may be used as an Annex A1 blending component.

<sup>E</sup> Results obtained by other test methods can be up to 2 °C lower than those obtained by Test Method D56, which is the preferred method. In case of dispute, Test Method D56 will apply.

<sup>F</sup> Control temperature of 325 °C is specified to provide a recurring, batch-by-batch verification of process stability and compositional consistency.

<sup>G</sup> D3241/IP 323 Thermal Stability is a critical aviation fuel test, the results of which are used to assess the suitability of jet fuel for aviation operational safety and regulatory compliance. The integrity of D3241/IP 323 testing requires that heater tubes (test coupons) meet the requirements of D3241 Table 2 and give equivalent D3241 results to the heater tubes supplied by the original equipment manufacturer (OEM). A test protocol to demonstrate equivalence of heater tubes from other suppliers is on file at ASTM International Headquarters and can be obtained by requesting Research Report RR:D02-1550. Heater tubes and filter kits, manufactured by the OEM (PAC, 8824 Fallbrook Drive, Houston, TX 77064) were used in the development of the D3241/IP 323 test method. Heater tube and filter kits, manufactured by Falex (Falex Corporation, 1020 Airpark Dr., Sugar Grove, IL, 60554-9585) were demonstrated to give equivalent results (see D3241 for research report references). These historical facts should not be construed as an endorsement or certification by ASTM International.

<sup>H</sup> Tube deposit ratings shall be measured by D3241 Annex A2 ITR or Annex A3 ETR, when available. If the Annex A2 ITR device reports “N/A” for a tube’s volume measurement, the test shall be a failure and the value reported as >85 nm. Visual rating of the heater tube by the method in D3241 Annex A1 is not required when Annex A2 ITR or Annex A3 ETR deposit thickness measurements are reported. In case of dispute between results from visual and metrological methods, the referee shall be considered the Annex A3 ETR method if available, otherwise Annex A2 ITR.

<sup>I</sup> Antioxidant shall be added to the bulk product prior to movements or operations that will significantly expose the product to air and in such a way as to ensure adequate mixing. This shall be done as soon as practicable after hydroprocessing or fractionation to prevent peroxidation and gum formation after manufacture. In-line injection and tank blenders are considered acceptable methods for ensuring adequate mixing.