

**SLOVENSKI STANDARD**  
**SIST EN 301 384 V1.1.2:2003**

**01-november-2003**

---

**Telekomunikacijsko upravljavno omrežje (TMN) - Nadzorovanje zmogljivosti  
vmesnikov pleziohrone digitalne hierarhije (PDH) - Informacijski model, gledano s  
strani omrežnega elementa (NE)**

Telecommunications Management Network (TMN); Performance monitoring for  
Plesiochronous Digital Hierarchy (PDH) interfaces; Information model for the Network  
Element (NE) view

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN 301 384 V1.1.2:2003](#)

[https://standards.iteh.ai/catalog/standards/sist/c9f6033f-5c22-48c7-8549-  
05a6b0e05c97/sist-en-301-384-v1-1-2-2003](https://standards.iteh.ai/catalog/standards/sist/c9f6033f-5c22-48c7-8549-05a6b0e05c97/sist-en-301-384-v1-1-2-2003)

**Ta slovenski standard je istoveten z: EN 301 384 Version 1.1.2**

---

**ICS:**

33.040.35      Telefonska omrežja      Telephone networks

**SIST EN 301 384 V1.1.2:2003**      en

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 384 V1.1.2:2003

<https://standards.iteh.ai/catalog/standards/sist/e9f6033f-5c22-48c7-8549-05a6b0e05c97/sist-en-301-384-v1-1-2-2003>

# ETSI EN 301 384 V1.1.2 (2001-02)

European Standard (Telecommunications series)

## Telecommunications Management Network (TMN); Performance monitoring for Plesiochronous Digital Hierarchy (PDH) interfaces; Information model for the Network Element (NE) view

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

SIST EN 301 384 V1.1.2:2003  
<https://standards.iteh.ai/catalog/standards/sist/e9f6033f-5c22-48c7-8549-05a6b0e05c97/sist-en-301-384-v1-1-2-2003>



---

Reference

REN/TMN-00050

---

KeywordsNE, PDH, performance, Q3 interface,  
transmission***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse 06 N° 7303/88**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

---

[SIST EN 301 384 V1.1.2:2003](#)  
<https://standards.iteh.ai/catalog/standards/sist/e9f6033f-5c22-48c7-8549-05a6b0e05c97/sist-en-301-384-v1-1-2-2003>

---

***Important notice***

Individual copies of the present document can be downloaded from:  
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:  
[editor@etsi.fr](mailto:editor@etsi.fr)

---

***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.  
All rights reserved.

---

## Contents

Intellectual Property Rights .....	4
Foreword .....	4
1 Scope.....	5
2 References .....	6
3 Abbreviations .....	7
4 Performance Monitoring Management Model .....	7
5 Managed object class definitions.....	7
6 Packages.....	13
7 Attributes.....	13
8 Actions .....	13
9 Notifications .....	13
10 Name bindings.....	13
11 ASN.1 definitions .....	15
History .....	17

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

SIST EN 301 384 V1.1.2:2003  
<https://standards.iteh.ai/catalog/standards/sist/e9f6033f-5c22-48c7-8549-05a6b0e05c97/sist-en-301-384-v1-1-2-2003>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Telecommunications Management Network (TMN).

<b>National transposition dates</b>	
Date of adoption of this EN:	23 February 2001
Date of latest announcement of this EN (doa):	31 May 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2001
Date of withdrawal of any conflicting National Standard (dow):	30 November 2001

SIST EN 301 384 V1.1.2:2003  
<https://standards.iteh.ai/catalog/standards/sist/e9f6033f-5c22-48c7-8549-05a6b0e05c97/sist-en-301-384-v1-1-2-2003>

---

## 1 Scope

The present document provides an information model for the performance monitoring of Synchronous Digital Hierarchy (SDH) network. This model describes the managed object classes and their properties for the performance monitoring function, as defined in ITU-T Recommendation G.784 [1] and EN 301 167 [2] and as related to SDH Network Elements (NEs). These objects are useful to describe information exchanged across interfaces defined in ITU-T Recommendation M.3010 [3] Telecommunications Management Network (TMN) architecture for the management of the performance monitoring function.

PDH performance monitoring functions are used to monitor specified performance events of specified termination points managed objects as defined in EN 300 371 [4] and to report these performance data, as well as quality of service alarms to its managing system according to a given schedule.

ITU-T Recommendation M.2120 [5] defines maintenance of transport network, ITU-T Recommendation G.784 [1] defines the management of SDH based NE. The present document defines the object model based on ITU-T Recommendation Q.822 [6] according to the requirements described in ITU-T Recommendation G.784 [1], EN 301 167 [2] and ITU-T Recommendation M.2120 [5]. This model uses generic mechanism defined in ITU-T Recommendation Q.822 [6].

The present document defines:

- an information model, as related to the performance monitoring function for the Plesiochronous Digital Hierarchy (PDH).

The present document does not define:

- iTeh STANDARD PREVIEW  
(standards.iteh.ai)
- the protocol stack to be used for message communication;
  - the network level management processes;
  - the application contexts;
  - the conformance requirements to be met by an implementation of this information model;  
SIST EN 301 384 V1.1.2:2003  
05a6b0e05c97/sist-en-301-384-v1-1-2-2003
  - information models for other systems or equipment.

The information model defined here (and the corresponding message set) is concerned with the management of NEs, the equipment by which they are implemented and the functions contained within them. More precisely, it applies to an equipment domain visible at the element manager to element interface and is only concerned with information available within that domain. Information proper to the domain of a network level management process is not included within this model.

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, subsequent revisions do apply.

- [1] ITU-T Recommendation G.784 (1994): "Synchronous Digital Hierarchy (SDH) management".
- [2] ETSI EN 301 167: "Transmission and Multiplexing (TM); Management of Synchronous Digital Hierarchy (SDH) transmission equipment; Fault management and performance monitoring; Functional description".
- [3] ITU-T Recommendation M.3010 (1996): "Principles for a telecommunications management network".
- [4] ETSI EN 300 371: "Telecommunications Management Network (TMN); Plesiochronous Digital Hierarchy (PDH) information model for the Network Element (NE) view".
- [5] ITU-T Recommendation M.2120 (1997): "PDH path, section and transmission system and SDH path and multiplex section fault detection and localization procedures".
- [6] ITU-T Recommendation Q.822 (1994): "Stage 1, stage 2 and stage 3 description for the Q3 interface - Performance management".
- [7] ITU-T Recommendation G.774-01 (1996): "Synchronous Digital Hierarchy (SDH) bidirectional performance monitoring for the network element view".
- [8] ITU-T Recommendation G.774-06 (1997): "Synchronous Digital Hierarchy (SDH) unidirectional performance monitoring for the network element view".
- [9] ETSI EN 300 417-1-1: "Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 1-1: Generic processes and performance".
- [10] ETSI EN 300 417-5-1: "Transmission and Multiplexing (TM); Generic requirements of transport functionality of equipment; Part 5-1: Plesiochronous Digital Hierarchy (PDH) path layer functions".
- [11] ITU-T Recommendation G.826 (1996): "Error performance parameters and objectives for international, constant bit rate digital paths at or above the primary rate".
- [12] ITU-T Recommendation X.739 (1993): "Information technology - Open Systems Interconnection - Systems management: Metric objects and attributes".
- [13] ITU-T Recommendation M.3100 (1995): "Generic network information model".

### 3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BBE	Background Block Error
CSES	Consecutive Severely Errored Seconds
CTP	Connection Termination Point
ES	Errored Second
FEBBE	Far End Background Block Error
FEES	Far End Errored Second
FESES	Far End Severely Errored Seconds
NE	Network Element
PDH	Plesiochronous Digital Hierarchy
SDH	Synchronous Digital Hierarchy
SEMF	Synchronous Equipment Management Function
SES	Severely Errored Second
TMN	Telecommunications Management Network
TR	Threshold Reset
TPP	Trail Termination Point
UAS	Unavailable Seconds

### 4 Performance Monitoring Management Model

The performance monitoring requirements to be met by the SDH Equipment Management Function (SEMF) are described in ITU-T Recommendation G.784 [1], clause 5.3 and in EN 301 167 [2], clauses 5.1 to 5.2.

The functional model given in the SEMF for performance monitoring of SDH signals is basically applicable for PDH signals as well.

### 5 Managed object class definitions

In the context of the present document, the IMPORTS clause specifies the object classes which can be instantiated in the Scope of the present document. The IMPORTS clause does not include uninstantiated superclasses.

```
BEGIN
IMPORTS
currentData,
historyData
FROM Q822-PM-ASN1Module { itu(0) recommendation(0) q(17) q822(822) informationModel(0)
managedObjectClass(3)}
;
END
```

#### PDH Current Data Unidirectional

```
pdhCurrentDataUnidirectional      MANAGED OBJECT CLASS
DERIVED FROM                      "Recommendation Q.822 [6] : 1993": currentData;
CHARACTERIZED BY
"Recommendation Q.822 [6] : 1993": zeroSuppressionPkg,
"Recommendation Q.822 [6] : 1993": thresholdPkg,
pdhCurrentDataUnidirectionalPackage PACKAGE
    BEHAVIOUR pdhCurrentDataUnidirectionalBehaviour;
    ATTRIBUTES
"Recommendation M.3100 [13] : 1995": currentProblemList      GET,
"Recommendation X.739 [12] : 1993": granularityPeriod        PERMITTED VALUES
                                                PDHPMASN1.UniDGranularityPeriod;;
CONDITIONAL PACKAGES
"Recommendation G.774-01 [7] : 1994": historyPackage PRESENT IF
    "an instance does not support flexible assignment of the history length",
"Recommendation G.774-01 [7] : 1994": unavailableTimeAlarmPackage PRESENT IF
    "starting and ending of unavailable period has to be reported and the granularity period
is 24 hours";
REGISTERED AS {en1384ObjectClass 1};
```