



## Designation: ~~D5855 – 95~~ (Reapproved 2013) D5855/D5855M – 15

# Standard Test Method for (Analytical Procedure) for Determining Transmissivity and Storage Coefficient of Confined Nonleaky or Leaky Aquifer by Constant Drawdown Method in Flowing Well<sup>1</sup>

This standard is issued under the fixed designation ~~D5855~~; D5855/D5855M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope\*

1.1 This test method covers an analytical solution for determining transmissivity and storage coefficient of a leaky or nonleaky confined aquifer. It is used to analyze data on the flow rate from a control well while a constant head is maintained in the well.

1.2 This analytical procedure is used in conjunction with the field procedure in Practice [D5786](#).

1.3 *Limitations*—The limitations of this technique for the determination of hydraulic properties of aquifers are primarily related to the correspondence between field situation and the simplifying assumption of the solution.

1.4 *Units*—~~Units~~~~The~~—The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values in each system may not be exact equivalents; therefore each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard. Reporting of test results in units other than SI shall not be regarded as nonconformance with this test method.

1.5 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice [D6026](#).

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

## 2. Referenced Documents

2.1 *ASTM Standards*:<sup>2</sup>

[D653 Terminology Relating to Soil, Rock, and Contained Fluids](#)

[D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction](#)

[D4043 Guide for Selection of Aquifer Test Method in Determining Hydraulic Properties by Well Techniques](#)

[D5786 Practice for \(Field Procedure\) for Constant Drawdown Tests in Flowing Wells for Determining Hydraulic Properties of Aquifer Systems](#)

[D6026 Practice for Using Significant Digits in Geotechnical Data](#)

## 3. Terminology

3.1 *Definitions*:

3.1.1 For definitions of terms used in this test method, see Terminology [D653](#).

3.1 *Derfinitions*:

3.1.1 For definitions of terms used in this test method, see Terminology [D653](#).

3.2 *Symbols and Dimensions*:

3.2.1  $T$ —transmissivity [ $L^2T^{-1}$ ].

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee [D18](#) on Soil and Rock and is the direct responsibility of Subcommittee [D18.21](#) on Groundwater and Vadose Zone Investigations.

Current edition approved ~~March 15, 2013~~Nov. 1, 2015, Published ~~April 2013~~December 2015. Originally approved in 1995. Last previous edition approved in ~~2006~~2013 as ~~D5855 – 95 (2006)~~(2013). DOI: ~~10.1520/D5855-95R13~~-10.1520/D5855\_D5855M-15.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

\*A Summary of Changes section appears at the end of this standard

- 3.2.2  $K_1$ — modified Bessel function of the second kind, first order [nd].
- 3.2.3  $K_2$ — modified Bessel function of the second kind, zero order [nd].
- 3.2.4  $J_0$ — Bessel function of the first kind, zero order [nd].
- 3.2.5  $Y_0$ — Bessel function of the second kind, zero order [nd].
- 3.2.6  $W(u)$ —w (well) function of  $u$  [nd].
- 3.2.7  $u$ —variable of integration [nd].
- 3.2.8  $t$ —elapsed time test [  $T$ ].
- 3.2.9  $Q$ —discharge rate [ $L^3T^{-1}$ ].
- 3.2.10  $s_w$ —constant drawdown in control well [ $L$ ].
- 3.2.11  $S$ —storage coefficient [nd].
- 3.2.12  $r_w$ —radius of control well.

#### 4. Summary of Test Method

4.1 This test method describes the analytical procedure for analyzing data collected during a constant drawdown aquifer test. This test method is usually performed on a flowing well. After the well has been shut-in for a period of time, the well is opened and the discharge rate is measured over a period of time after allowing the well to flow. The water level in the control well while the well is flowing is the elevation of the opening of the control well through which the water is allowed to flow. Data are analyzed by plotting the discharge rate versus time.

NOTE 1—This test method involves the withdrawal of water from a control well that is fully screened through the confined aquifer. The withdrawal rate is varied to cause the water level within the well to remain constant. The field procedure involved in conducting a constant drawdown test is given in Practice D5786. Methods used to develop a conceptual model of the site and for initially selecting an analytical procedure are described in Guide D4043.

4.2 *Leaky Aquifer Solution*—The solution is given by Hantush.<sup>3</sup> Transmissivity is calculated as follows:

NOTE 2—These are Eq (93) through (97) of Lohman.<sup>4</sup>

$$T = \frac{Q}{2\pi s_w G(\alpha, r_w/B)} [L^2T^{-1}] \quad (1)$$

where:

$$\alpha = \frac{Tt}{Sr_w^2} [nd] \quad (2)$$

$$r_w/B = r_w [T/(K/b')]^{-0.5} [L^2] \quad (3)$$

and:

$$G \left[ \frac{r_w}{B} \right] = \left[ \frac{r_w}{B} \right] \left[ \frac{K_1(r_w/b)}{K_0(r_w/b)} \right] + \frac{r}{\pi^2} \exp \left[ -\alpha \left( \frac{r_w}{B} \right)^2 \right]. \quad (4)$$

$$\int_0^\infty \frac{u \exp(-\alpha u^2)}{J_0^2(u) + Y_0^2(u)} \cdot \frac{du}{u^2 + (r_w/B)^2} [nd]$$

4.2.1 Storage coefficient is given by:

$$S = \frac{Tt}{r_w^2 \alpha} [nd] \quad (5)$$

4.3 *Non-Leaky Aquifer:*

4.3.1 *Log-Log*—The solution is given by Lohman.<sup>4</sup>

NOTE 3—These equations are Eq (66) through (69) of Lohman.<sup>4</sup>

4.3.1.1 Transmissivity is calculated as follows:

$$T = \frac{Q}{2\pi G(\alpha)_s} [L^2T^{-1}] \quad (6)$$

where:

<sup>3</sup> Hantush, M. S., "Nonsteady Flow to Flowing Wells in Leaky Aquifer," *Journal of Geophysical Research*, Vol 64, No. 8, 1959, pp. 1043–1052.

<sup>4</sup> Lohman, S. W., "Ground-Water Hydraulics," *Professional Paper 708*, U.S. Geological Survey, 1972.

$$\alpha = \frac{Tt}{Sr_w^2} [nd] \quad (7)$$

and:

$$G(a) = \frac{4\alpha}{\pi} \int_0^\infty x e^{-\alpha x^2} \left[ \frac{\pi}{2} + \tan^{-1} \left( \frac{Y_o(x)}{J_o(x)} \right) \right] dx [nd] \quad (8)$$

4.3.1.2 Storage coefficient is given by:

$$S = \frac{Tt}{\alpha r_w^2} [nd] \quad (9)$$

4.3.2 *Semi-Log*—The solution is given by Jacob and Lohman.<sup>5</sup>

NOTE 4—Jacob and Lohman<sup>5</sup> showed that for all but extremely small values of  $t$ , the function of  $G(a)$  shown above can be approximated very closely by  $2/W(u)$ . For sufficiently small values of  $u$ ,  $W(u)$  are further approximated by  $2.30 \log_{10} 2.25Tt/r_w^2 S$ . The use of this semi-logarithmic method will produce values of transmissivity that are slightly elevated. Examples of this error are shown below:

| $u$      | $W(u)$   | Estimated Error, % |
|----------|----------|--------------------|
| 0.25000  | 1.044283 | 25                 |
| 0.00625  | 4.504198 | 10                 |
| 0.000833 | 6.513694 | 5                  |
| 1.25E-05 | 10.71258 | 2                  |

4.3.2.1 Transmissivity is calculated as follows:

NOTE 5—These equations are Eqs (71) and (73) of Lohman.<sup>4</sup>

$$T = \frac{2.30}{4\pi\Delta(s_w/Q)/\Delta\log_{10}(t/r_w^2)} [L^2 T^{-1}] \quad (10)$$

by extrapolating the straight line to  $s_w/Q = 0$  (the point of zero drawdown), storage coefficient is given by:

$$S = 2.25 T \frac{t}{r_w^2} [nd] \quad (11)$$

NOTE 6—In (Eq 10) and (Eq 11),  $Q$  is in cubic feet per day,  $t$  is in days.

## 5. Significance and Use

NOTE 7—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D3740 are generally considered capable of competent and objective testing/sampling/inspection/etc. Users of this standard are cautioned that compliance with Practice D3740 does not in itself assure reliable results. Reliable results depend on many factors; Practice D3740 provides a means of evaluating some of those factors. <https://standards.iteh.ai/>

### 5.1 Assumptions—Leaky Aquifer:

- 5.1.1 Drawdown ( $s_w$ ) in the control well is constant,
- 5.1.2 Well is infinitesimal diameter and fully penetrates aquifer,
- 5.1.3 The aquifer is homogeneous, isotropic, and areally extensive, and
- 5.1.4 The control well is 100 % efficient.

### 5.2 Assumptions—Nonleaky Aquifer:

- 5.2.1 Drawdown ( $s_w$ ) in the control well is constant,
- 5.2.2 Well is infinitesimal diameter and fully penetrates aquifer,
- 5.2.3 The aquifer is homogeneous, isotropic, and areally extensive,
- 5.2.4 Discharge from the well is derived exclusively from storage in the nonleaky aquifer, and
- 5.2.5 The control well is 100 % efficient.

### 5.3 Implications of Assumptions:

5.3.1 The assumptions are applicable to confined aquifers and fully penetrating control wells. However, this test method may be applied to partially penetrating wells where the method may provide an estimate of hydraulic conductivity for the aquifer adjacent to the open interval of the well if the horizontal hydraulic conductivity is significantly greater than the vertical hydraulic conductivity.

5.3.2 Values obtained for storage coefficient are less reliable than the values calculated for transmissivity. Storage coefficient values calculated from control well data are not reliable.

<sup>5</sup> Jacob, C. E., and Lohman, S. W., "Nonsteady Flow to a Well of Constant Drawdown in an Extensive Aquifer," *American Geophysical Union Transactions*, Vol 33, No. 4, 1952, pp. 552–569.