



SLOVENSKI STANDARD
SIST EN 301 277 V1.2.1:2003
01-december-2003

:]_gb]fUX]g_]g]ghYa]ÈCdfYa U]hdU]c _U]c _UÈJ]gc_c`na c[`]j]X][]H]b]
fUX]g_]g]ghYa]ž_]cXXU]c`GHA!(`U](`I`GHA!%j `fUX]cZY_j Yb bYa `UbUi `(\$
A<n]b`i dcfUV`Uc`Xj c`bc`dc`Uf]nUW]c`dfY_`gcgYXb^Y[U`UbUUf7 8 DŁ

Fixed Radio Systems; Point-to-point equipment; High capacity digital radio systems transmitting STM-4 or 4 x STM-1 in a 40 MHz radio frequency channel using Co-Channel Dual Polarized (CCDP) operation

iteh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003>

Ta slovenski standard je istoveten z: EN 301 277 Version 1.2.1

ICS:

33.060.30 Radiorelejni in fiksni satelitski komunikacijski sistemi Radio relay and fixed satellite communications systems

SIST EN 301 277 V1.2.1:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 277 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003>

ETSI EN 301 277 V1.2.1 (2001-02)

European Standard (Telecommunications series)

**Fixed Radio Systems;
Point-to-point equipment;
High capacity digital radio systems transmitting STM-4
or 4 x STM-1 in a 40 MHz radio frequency channel using
Co-Channel Dual Polarized (CCDP) operation**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 301 277 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003>



Reference

REN/TM-04111-01

Keywordsdigital, DRRS, radio, SDH, STM, transmission,
point-to-point**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 301 277 V1.2.1:2003<https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
1 Scope.....	6
2 References.....	6
3 Symbols and abbreviations.....	8
3.1 Symbols.....	8
3.2 Abbreviations.....	9
4 General characteristics	9
4.1 Frequency bands and channel arrangements.....	9
4.2 Modes of operation.....	10
4.3 Compatibility requirements.....	10
4.4 Performance and availability requirements.....	10
4.5 Environmental conditions	10
4.5.1 Equipment within weather protected locations (indoor locations).....	10
4.5.2 Equipment for non-weather protected locations (outdoor locations).....	10
4.6 Mechanical dimensions	10
4.7 Power supply.....	11
4.8 Electromagnetic Compatibility (EMC).....	11
4.9 TMN interfaces	11
4.10 Block diagram.....	11
4.11 Branching / feeder / antenna requirements.....	12
4.11.1 Antenna radiation pattern	12
4.11.2 Antenna cross-polar discrimination	12
5 SDH baseband characteristics	12
6 Transmitter characteristics	12
6.1 Output power	12
6.2 Automatic Transmit Power control (ATPC).....	13
6.3 Remote Transmit Power Control (RTPC).....	13
6.4 RF spectrum masks	14
6.5 Discrete CW lines exceeding the spectrum mask limit.....	16
6.5.1 Spectral lines at the symbol rate	16
6.5.2 Other spectral lines	16
6.6 Spurious emissions.....	17
6.6.1 Spurious emissions-External	17
6.6.2 Spurious emissions-Internal.....	17
6.7 Radio frequency tolerance	17
6.8 Return loss	18
6.9 Intermodulation products.....	18
7 Receiver characteristics.....	18
7.1 Local oscillator frequency tolerance.....	18
7.2 Receiver image rejection	18
7.3 Spurious emissions.....	18
7.3.1 Spurious emissions-External	18
7.3.2 Spurious emissions-Internal.....	18
7.4 Input level range.....	18
7.5 Return loss	19
8 System performance without diversity	19
8.1 Equipment background BER.....	19
8.2 BER as a function of receive input level (dBm).....	19
8.3 Interference sensitivity	20
8.3.1 Co-channel "external" interference sensitivity.....	20

8.3.2	Adjacent channel interference sensitivity	21
8.4	Distortion sensitivity	21
8.5	Sensitivity to dynamic fading.....	21
9	System characteristics with diversity	22
9.1	Differential delay compensation	22
9.2	BER performance.....	22
9.3	Interference sensitivity	22
9.4	Distortion sensitivity	22
10	Cross polar interference sensitivity.....	23
10.1	Co-channel "internal" interference sensitivity in flat fading conditions	23
10.2	Co-channel "internal" interference sensitivity in dispersive fading conditions	23
Annex A (informative): Additional information		24
A.1	ATPC	24
A.2	Branching, feeder and antenna	24
A.2.1	Antenna radiation pattern envelopes	24
A.2.2	Cross-polar discrimination (XPD).....	24
A.2.3	Interport isolation	24
A.2.4	Feeder / antenna return loss	24
A.3	Compatibility.....	25
A.4	Mechanical requirements	25
Annex B (informative): Bibliography.....		26
History		27

ITeH STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 277 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Transmission and Multiplexing (TM).

The former title of the present document was: "Transmission and Multiplexing (TM); Digital Radio Relay Systems (DRRS); High capacity DRRS transmitting STM-4 or 4 x STM-1 in a 40 MHz radio frequency channel using Co-Channel Dual Polarized (CCDP) operation".

National transposition dates	
Date of adoption of this EN:	9 February 2001
Date of latest announcement of this EN (doa):	31 May 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2001
Date of withdrawal of any conflicting National Standard (dow):	30 November 2001

1 Scope

The present document defines technical parameters for a high capacity Digital Radio Relay System (DRRS) operating in frequency bands with 40 MHz channel spacing e.g. the 4 GHz, 5 GHz, U 6 GHz and 11 GHz bands. The capacity should be STM-4 or $4 \times$ STM-1 per 40 MHz RF-channel by using both polarizations in the co-channel dual polarized (CCDP) mode of operation.

The area of application of these DRRS is foreseen to be in regional and trunk networks forming part of a SDH-network including STM-4 rings.

Systems considered in the present document should be able to respect ITU-R high grade performance objectives.

The systems considered should operate in these networks having regard for existing hop length, which are considered to be normally up to about 30 km to 40 km for regional and about 60 km for trunk networks, respectively. Hop lengths greater than this latter length are used in special applications.

For information about compatibility with other systems see clause A.3.

The parameters specified fall into two categories:

- a) Those that are required to provide compatibility between channels from different sources of equipment on the same route connected to separate antennas.

NOTE: Equipment supplied by different manufacturers on the same path or existing radio-relay systems operate on different frequencies.

- b) Parameters defining the transmission quality of the proposed system.

The standardization deals with baseband and RF characteristics relevant to SDH. Antenna/feeder system requirements are also considered.

Baseband interfaces have to be considered for STM-1 signals and STM-4 signals in accordance with ITU-T Recommendations G.707 [6] and G.957 [21] respectively.

2 References

The following documents contain provisions, which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, subsequent revisions do apply.

- [1] ITU-R Recommendation F.384-6 (1995): "Radio-frequency channel arrangements for medium and high capacity analogue or digital radio-relay systems operating in the upper 6 GHz band".
- [2] ITU-R Recommendation F.387-7 (1995): "Radio-frequency channel arrangements for radio-relay systems operating in the 11 GHz band".
- [3] ITU-R Recommendation F.635-4 (1997): "Radio-frequency channel arrangements based on a homogeneous pattern for radio-relay systems operating in the 4 GHz band".
- [4] ITU-R Recommendation F.750-3 (1997): "Architectures and functional aspects of radio-relay systems for SDH-based networks".
- [5] ITU-R Recommendation F.1099-2 (1997): "Radio-frequency channel arrangements for high-capacity digital radio-relay systems in the 5 GHz (4 400 MHz to 5 000 MHz) band".

- [6] ITU-T Recommendation G.707 (1996): "Network node interface for the synchronous digital hierarchy (SDH)".
- [7] ITU-R Recommendation SM.329-7 (1997): "Spurious Emissions".
- [8] ITU-T Recommendation G.773 (1993): "Protocol suites for Q-interfaces for management of transmission systems".
- [9] ITU-T Recommendation G.784 (1999): "Synchronous digital hierarchy (SDH) management".
- [10] ETSI ETS 300 019 (all parts): "Equipment engineering (EE); Environmental conditions and environmental tests for telecommunications equipment".
- [11] ETSI ETS 300 119 (all parts): "Equipment engineering (EE); European telecommunication standard for equipment practice".
- [12] ETSI EN 300 385: "Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for fixed radio links and ancillary equipment".
- [13] ETSI ETS 300 132 (all parts): "Equipment Engineering (EE); Power supply interface at the input to telecommunications equipment".
- [14] ETSI ETS 300 635: "Transmission and Multiplexing (TM); Synchronous Digital Hierarchy (SDH); Radio specific functional blocks for transmission of M x STM-N".
- [15] ETSI EN 300 833: "Fixed Radio Systems; Point to Point Antennas; Antennas for point-to-point fixed radio systems operating in the frequency band 3 GHz to 60 GHz".
- [16] ITU-T Recommendation G.703 (1991): "Physical/electrical characteristics of hierarchical digital interfaces".
- [17] ITU-R Recommendation F.91-1 (1997): "Bandwidths and unwanted emissions of digital radio-relay systems".
- [18] ITU-T Recommendation O.151 (1992): "Error performance measuring equipment operating at the primary rate and above".
- [19] ITU-T Recommendation O.181 (1996): "Equipment to assess error performance on STM-N interfaces".
- [20] ITU-T Recommendation G.783 (1997): "Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks".
- [21] ITU-T Recommendation G.957 (1995): "Optical interfaces for equipments and systems relating to the synchronous digital hierarchy".
- [22] ETSI TR 101 035: "Transmission and Multiplexing (TM); Synchronous Digital Hierarchy (SDH) aspects regarding Digital Radio Relay Systems (DRRS)".
- [23] ITU-R Recommendation F.695 (1990): "Availability objectives for real digital radio-relay links forming part of a high-grade circuit within an integrated services digital network".
- [24] ITU-R Recommendation F.1092-1 (1997): "Error performance objectives for constant bit rate digital path at or above the primary rate carried by digital radio-relay systems which may form part of the international portion of a 27 500 km hypothetical reference path".
- [25] ITU-R Recommendation F.1189-1 (1997): "Error performance objectives for constant bit rate digital paths at or above the primary rate carried by digital radio-relay systems which may form part or all of the national portion of a 27 500 km hypothetical reference path".
- [26] ITU-R Recommendation F.557-4 (1997): "Availability objective for radio-relay systems over a hypothetical reference circuit and a hypothetical reference digital path".
- [27] ITU-T Recommendation G.826 (1996): "Error performance parameters and objectives for international, constant bit rate digital paths at or above the primary rate".

- [28] ITU-T Recommendation G.827 (1996): "Availability parameters and objectives for path elements of international constant bit-rate digital paths at or above the primary rate".
- [29] ITU-R Recommendation F.752-1 (1994): "Diversity techniques for radio-relay systems".
- [30] ITU-R Recommendation F.1093-1 (1997): "Effects of multipath propagation on the design and operation of line-of-sight digital radio-relay systems".
- [31] ITU-R Recommendation F.1101 (1994): "Characteristics of digital radio-relay systems below about 17 GHz".
- [32] ETSI EN 301 127: "Fixed Radio Systems; Point-to-point equipment; High capacity digital radio systems carrying SDH signals (2 x STM-1) in frequency bands with about 30 MHz channel spacing and using Co-Channel Dual Polarized (CCDP) operation".
- [33] CEPT/ERC Recommendation 12-08: "Harmonized radio frequency channel arrangements and block allocations for low, medium and high capacity systems in the band 3 600 MHz to 4 200 MHz".
- [34] CEPT/ERC Recommendation 14-02: "Radio-frequency channel arrangements for medium and high capacity analogue or high capacity digital radio-relay systems operating in the band 6 425 MHz to 7 125 MHz".
- [35] CEPT/ERC Recommendation 12-06: "Harmonized radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 10,7 GHz to 11,7 GHz".
- [36] ETSI ETR 019: "Transmission and Multiplexing (TM); Specification of new generation high-capacity digital radio systems carrying 2 x STM-1 Synchronous Digital Hierarchy (SDH) signals in frequency bands with 40 MHz channel spacing".
- [37] ETSI TR 101 127: "Transmission and Multiplexing (TM); Digital Radio Relay Systems (DRRS); Synchronous Digital Hierarchy (SDH); High capacity DRRS carrying SDH signals (1 x STM-1) in frequency bands with about 30 MHz channel spacing and using Co-Channel Dual Polarized (CCDP) operation". [SIST EN 301 277 V1.2.1:2003](https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-0200ad30d338/sist-en-301-277-v1-2-1-2003)
<https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-0200ad30d338/sist-en-301-277-v1-2-1-2003>
- [38] CEPT/ERC Recommendation 74-01: "Spurious emissions".

3 Symbols and abbreviations

3.1 Symbols

For the purposes of the present document, the following symbols apply:

dB	decibel
dBm	decibel relative to 1 mW
GHz	GigaHertz
km	kilometre
Mbit/s	Mega-bit per second
MHz	MegaHertz
m/s	metres per second
ppm	parts per million
ns	nanosecond
W/m ²	Watts per square metre

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATPC	Automatic Transmit Power Control
BER	Bit Error Rate
C/I	Carrier to Interference ratio
CCDP	Co-Channel Dual Polarized
CSmin	minimum practical Channel Separation (for a given radio-frequency channel arrangement)
IF	Intermediate Frequency
NFD	Net Filter Discrimination
PDH	Plesiochronous Digital Hierarchy
QAM	Quadrature Amplitude Modulation
RCSOH	Radio Complementary Sectra OverHeat
RF	Radio Frequency
RFCOH	Radio Frame Complementary OverHeat
RX	Receiver
SDH	Synchronous Digital Hierarchy
SOH	Section OverHead
STM-1	Synchronous Transport Module Level 1 (155,52 Mbit/s)
STM-4	Synchronous Transport Module Level 4 (622 Mbit/s)
TMN	Telecommunication Management Network
TX	Transmitter
U6	Upper 6 (GHz frequency band)
XIF	Cross polarization improvement factor due to XPIC operation
XPD	Cross Polar Discrimination
XPI	Cross Polar Interference
XPIC	Cross Polar Interference Canceller

STANDARD PREVIEW
(standards.iteh.ai)

4 General characteristics

<https://standards.iteh.ai/catalog/standards/sist/02d776c5-2eea-48b5-a12a-cfce9ad43e1d/sist-en-301-277-v1-2-1-2003>

4.1 Frequency bands and channel arrangements

The system shall be required to operate in the following frequency bands, according to the specified CEPT and ITU-R Recommendations on the quoted channel spacings.

4 GHz

CEPT/ERC Recommendation 12-08 [33], annex A, Part 1 with 40 MHz channel spacing ITU-T Recommendation G.826 [27] and ITU-R Recommendation F.635-4 [3] with 40 MHz channel spacing. The centre gap between transmitters and receivers in ITU-R Recommendation F.635-4 [3] is 80 MHz.

5 GHz

ITU-R Recommendation F.1099-2 [5] with 40 MHz channel spacing. The centre gap between transmitters and receivers in ITU-R Recommendation F.1099-2 [5] is 60 MHz.

U 6 GHz

CEPT/ERC Recommendation 14-02 [34] and ITU-R Recommendation F.384-6 [1] with 40 MHz channel spacing. The centre gap between transmitters and receivers in ITU-R Recommendation F.384-6 [1] is 60 MHz.

11 GHz

CEPT/ERC Recommendation 12-06 [35] and ITU-R Recommendation F.387-7 [2] with 40 MHz channel spacing. The centre gap between transmitters and receivers in ITU-R Recommendation F.387-7 [2] is 130 MHz.