



Designation: F3173/F3173M – 15

Standard Specification for Handling Characteristics of Aeroplanes¹

This standard is issued under the fixed designation F3173/F3173M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification establishes the airworthiness design standards associated with general airplane-handling characteristics in flight and on ground and water.

1.2 This specification is applicable to aeroplanes.

1.3 The applicant for a design approval shall seek the individual guidance of their respective civil aviation authority (CAA) body concerning the use of this specification as part of a certification plan. For information on which CAA regulatory bodies have accepted this specification (in whole or in part) as a means of compliance to their small aircraft airworthiness regulations (hereinafter referred to as “the Rules”), refer to the ASTM Committee F44 webpage (www.ASTM.org/COMITTEE/F44.htm) which includes CAA website links.

1.4 *Units*—The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in nonconformance with the standard.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

[F3060 Terminology for Aircraft](#)

[F3061/F3061M Specification for Systems and Equipment in Small Aircraft](#)

[F3174/F3174M Specification for Establishing Operating Limitations and Information for Aeroplanes](#)

¹ This specification is under the jurisdiction of ASTM Committee F44 on General Aviation Aircraft and is the direct responsibility of Subcommittee F44.20 on Flight. Current edition approved Dec. 1, 2015. Published February 2016. DOI: 10.1520/F3173_F3173M-15.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

2.2 *Federal Standard:*³

[14 CFR Part 23 \(Amendment 62\) Airworthiness Standards: Normal, Utility, Aerobatic, and Commuter Category Aircraft](#)

3. Terminology

3.1 Refer to Terminology [F3060](#) referenced in Section 2.

4. General Requirements

4.1 *General*—Unless otherwise specified in a specific requirement, the airplane shall meet the requirements of [4.2 – 4.9](#), Sections [5 – 8](#), [9.1](#), and [9.2](#) at all practical loading conditions and operating altitudes for which certification has been requested, not exceeding the maximum operating altitude established in Specification [F3174/F3174M](#), subsection 4.11, and without requiring exceptional piloting skill, alertness, or strength.

4.2 *Control Forces (General):*

4.2.1 The airplane shall be safely controllable and maneuverable during all flight phases including:

4.2.1.1 Takeoff,

4.2.1.2 Climb,

4.2.1.3 Level flight,

4.2.1.4 Descent,

4.2.1.5 Go-around, and

4.2.1.6 Landing (power on and power off) with the wing flaps extended and retracted.

4.2.2 It shall be possible to make a smooth transition from one flight condition to another (including turns and slips) without danger of exceeding the limit load factor under any probable operating condition (including, for multiengine airplanes, those conditions normally encountered in the sudden failure of any engine).

4.2.3 If marginal conditions exist with regard to required pilot strength, the control forces necessary shall be determined by quantitative tests. In no case may the control forces under the conditions specified in [4.2.1](#) and [4.2.2](#) exceed those prescribed in [Table 1](#).

4.3 *Longitudinal Control:*

³ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401.

TABLE 1 Control Forces

| Control | Longitudinal | Lateral | Directional |
|--------------------------------|------------------|----------------|-----------------|
| (a) For temporary application: | | | |
| Stick | 267 N [60 lbf] | 133 N [30 lbf] | |
| Wheel (two hands on rim) | 334 N [75 lbf] | 222 N [50 lbf] | |
| Wheel (one hand on rim) | 222 N [50 lbf] | 111 N [25 lbf] | |
| Rudder pedal | — | — | 667 N [150 lbf] |
| (b) For prolonged application: | | | |
| | 44 N kg [10 lbf] | 22 N [5 lbf] | 89 N [20 lbf] |

4.3.1 *Longitudinal Control*—With the airplane as nearly as possible in trim at $1.3 V_{S1}$, it shall be possible, at speeds below the trim speed, to pitch the nose downward so that the rate of increase in airspeed allows prompt acceleration to the trim speed with:

- 4.3.1.1 Maximum continuous power on each engine;
- 4.3.1.2 Power off; and
- 4.3.1.3 Wing flap and landing gear:

- (1) Retracted and
- (2) Extended.

4.3.2 Unless otherwise required, it shall be possible to carry out the following maneuvers without requiring the application of single-handed control forces exceeding those specified in **Table 1**. The trimming controls shall not be adjusted during the maneuvers.

4.3.2.1 With the landing gear extended, the flaps retracted, and the airplane as nearly as possible in trim at $1.4 V_{S1}$, extend the flaps as rapidly as possible and allow the airspeed to transition from $1.4 V_{S1}$ to $1.4 V_{S0}$:

- (1) With power off and
- (2) With the power necessary to maintain level flight in the initial condition.

4.3.2.2 With landing gear and flaps extended, power off, and the airplane as nearly as possible in trim at $1.3 V_{S0}$, quickly apply takeoff power and retract the flaps as rapidly as possible to the recommended go around setting and allow the airspeed to transition from $1.3 V_{S0}$ to $1.3 V_{S1}$. Retract the gear when a positive rate of climb is established.

4.3.2.3 With landing gear and flaps extended, in level flight, power necessary to attain level flight at $1.1 V_{S0}$, and the airplane as nearly as possible in trim, it shall be possible to maintain approximately level flight while retracting the flaps as rapidly as possible with simultaneous application of not more than maximum continuous power. If gated flap positions are provided, the flap retraction may be demonstrated in stages with power and trim reset for level flight at $1.1 V_{S1}$, in the initial configuration for each stage:

- (1) From the fully extended position to the most extended gated position;
- (2) Between intermediate gated positions, if applicable; and
- (3) From the least extended gated position to the fully retracted position.

4.3.2.4 With power off, flaps and landing gear retracted and the airplane as nearly as possible in trim at $1.4 V_{S1}$, apply takeoff power rapidly while maintaining the same airspeed.

4.3.2.5 With power off, landing gear and flaps extended, and the airplane as nearly as possible in trim at V_{REF} , obtain and maintain airspeeds between $1.1 V_{S0}$ and either $1.7 V_{S0}$ or V_{FE} ,

whichever is lower without requiring the application of two-handed control forces exceeding those specified in **Table 1**.

4.3.2.6 With maximum takeoff power, landing gear retracted, flaps in the takeoff position, and the airplane as nearly as possible in trim at VFE appropriate to the takeoff flap position, retract the flaps as rapidly as possible while maintaining constant speed.

4.3.3 At speeds above V_{MO}/M_{MO} , and up to the maximum speed shown under **8.1**, a maneuvering capability of 1.5 g shall be demonstrated to provide a margin to recover from upset or inadvertent speed increase.

4.3.4 It shall be possible, with a pilot control force of not more than 45 N [10 lbf], to maintain a speed of not more than V_{REF} during a power-off glide with landing gear and wing flaps extended, for any weight of the airplane, up to and including the maximum weight.

4.3.5 By using normal flight and power controls, except as otherwise noted in **4.3.5.1** and **4.3.5.2**, it shall be possible to establish a zero rate of descent at an attitude suitable for a controlled landing without exceeding the operational and structural limitations of the airplane, as follows:

4.3.5.1 For single-engine airplanes with a stall speed in the landing configuration of more than 45 knots and multiengine airplanes, without the use of the primary longitudinal control system; and

4.3.5.2 For multiengine airplanes:

- (1) Without the use of the primary directional control and
- (2) If a single failure of any one connecting or transmitting link would affect both the longitudinal and directional primary control system, without the primary longitudinal and directional control system.

4.4 *Directional and Lateral Control:*

4.4.1 For each multiengine airplane, it shall be possible, while holding the wings level within 5° , to make sudden changes in heading safely in both directions. This ability shall be shown at $1.4 V_{S1}$ with heading changes up to 15° , except that the heading change at which the rudder force corresponds to the limits specified in **Table 1** need not be exceeded, with the:

- 4.4.1.1 Critical engine inoperative and its propeller in the minimum drag position;
- 4.4.1.2 Remaining engines at maximum continuous power;
- 4.4.1.3 Landing gear:
 - (1) Retracted,
 - (2) Extended, and
- 4.4.1.4 Flaps retracted.

4.4.2 For each multiengine airplane, it shall be possible to regain full control of the airplane without exceeding a bank angle of 45° , reaching a dangerous attitude, or encountering dangerous characteristics in the event of a sudden and complete failure of the critical engine, making allowance for a delay of 2 s in the initiation of recovery action appropriate to the situation, with the airplane initially in trim, in the following condition:

- 4.4.2.1 Maximum continuous power on each engine,
- 4.4.2.2 The wing flaps retracted,
- 4.4.2.3 The landing gear retracted,

4.4.2.4 A speed equal to that at which compliance with 23.69(a) has been shown, and

4.4.2.5 All propeller controls in the position at which compliance with 23.69(a) has been shown.

4.4.3 For airplanes with a stall speed in the landing configuration of more than 45 knots, it shall be shown that the airplane is safely controllable without the use of the primary lateral control system in any all-engine configuration(s) and at any speed or altitude within the approved operating envelope. It shall also be shown that the airplane's flight characteristics are not impaired below a level needed to permit continued safe flight and the ability to maintain attitudes suitable for a controlled landing without exceeding the operational and structural limitations of the airplane. If a single failure of any one connecting or transmitting link in the lateral control system would also cause the loss of additional control system(s), compliance with the above requirement shall be shown with those additional systems also assumed to be inoperative.

4.5 *Minimum Control Speed:*

4.5.1 V_{MC} is the calibrated airspeed at which, when the critical engine is suddenly made inoperative, it is possible to maintain control of the airplane with that engine still inoperative and, thereafter, maintain straight flight at the same speed with an angle of bank of not more than 5° . The method used to simulate critical engine failure shall represent the most critical mode of powerplant failure expected in service with respect to controllability.

4.5.2 V_{MC} for takeoff shall not exceed:

4.5.2.1 For multi-engine airplanes with a $V_{S0} \leq 65$ kt and that during the climb demonstration in 23.67(a)(2) cannot climb after a critical loss of thrust, V_{S1} , where V_{S1} is determined for all practical weights and takeoff configurations.

4.5.2.2 For all other multi-engine airplanes, $1.2 V_{S1}$, where V_{S1} is determined at the maximum takeoff weight.

4.5.3 V_{MC} shall be determined with the most unfavorable weight and center-of-gravity position and the airplane airborne and the ground effect negligible, for the takeoff configuration(s) with:

4.5.3.1 Maximum available takeoff power initially on each engine,

4.5.3.2 The airplane trimmed for takeoff,

4.5.3.3 Flaps in the takeoff position(s),

4.5.3.4 Landing gear retracted, and

4.5.3.5 All propeller controls in the recommended takeoff position throughout.

4.5.4 For all airplanes except low-speed Level 1 and 2 airplanes, the conditions of 4.5.1 shall also be met for the landing configuration with:

4.5.4.1 Maximum available takeoff power initially on each engine;

4.5.4.2 The airplane trimmed for an approach, with all engines operating, at V_{REF} , at an approach gradient equal to the steepest used in the landing distance demonstration of 23.75;

4.5.4.3 Flaps in the landing position;

4.5.4.4 Landing gear extended; and

4.5.4.5 All propeller controls in the position recommended for approach with all engines operating.

4.5.5 A minimum speed to render the critical engine inoperative intentionally shall be established and designated as the safe, intentional, one-engine-inoperative speed (V_{SSE}).

4.5.6 At V_{MC} , the rudder pedal force required to maintain control shall not exceed 667 N [150 lbf] and it shall not be necessary to reduce power of the operative engine(s). During the maneuver, the airplane shall not assume any dangerous attitude and it shall be possible to prevent a heading change of more than 20° .

4.5.7 At the option of the applicant, to comply with the requirements of 23.51(c)(1), V_{MCG} may be determined. V_{MCG} is the minimum control speed on the ground and is the calibrated airspeed during the takeoff run at which, when the critical engine is suddenly made inoperative, it is possible to maintain control of the airplane using the rudder control alone (without the use of nose wheel steering) as limited by 667 N [150 lbf] of force and using the lateral control to the extent of keeping the wings level to enable the takeoff to be safely continued. In the determination of V_{MCG} , assuming that the path of the airplane accelerating with all engines operating is along the centerline of the runway, its path from the point at which the critical engine is made inoperative to the point at which recovery to a direction parallel to the centerline is completed may not deviate more than 9.1 m [30 ft] laterally from the centerline at any point. V_{MCG} shall be established with:

4.5.7.1 The airplane in each takeoff configuration or, at the option of the applicant, in the most critical takeoff configuration;

4.5.7.2 Maximum available takeoff power on the operating engines;

4.5.7.3 The most unfavorable center of gravity position;

4.5.7.4 The airplane trimmed for takeoff; and

4.5.7.5 The most unfavorable weight in the range of takeoff weights.

4.6 *Aerobic Maneuvers*—Each aerobatic airplane shall be able to perform safely the aerobatic maneuvers for which certification is requested. Safe entry speeds for these maneuvers shall be determined.

4.7 *Control during Landings*—It shall be possible, while in the landing configuration, to complete a landing safely without exceeding the one-hand control force limits specified in **Table 1** following an approach to land:

4.7.1 At a speed of V_{REF} minus 5 knots;

4.7.2 With the airplane in trim, or as nearly as possible in trim and without the trimming control being moved throughout the maneuver;

4.7.3 At an approach gradient equal to the steepest used in the landing distance demonstration of; and

4.7.4 With only those power changes, if any, that would be made when landing normally from an approach at V_{REF} .

4.8 *Elevator Control Force in Maneuvers:*

4.8.1 The elevator control force needed to achieve the positive limit maneuvering load factor shall not be less than:

4.8.1.1 For wheel controls, $W/10$ N (where W is the maximum mass in kg) [$W/100$ lbf (where W = maximum weight in

lbf] or 89 N [20 lbf], whichever is greater, except that it need not be greater than 222 N [50 lbf] or

4.8.1.2 For stick controls, $W/14$ N (where W is the maximum mass in kg) [$W/140$ lbf (where W = maximum weight in lbf)] or 67 N [15 lbf], whichever is greater, except that it need not be greater than 156 N [35 lbf].

4.8.2 The requirement of 4.8.1 shall be met at maximum cruise power and with the wing flaps and landing gear retracted:

4.8.2.1 In a turn, with the trim setting used for wings level flight at V_O , and

4.8.2.2 In a turn, with the trim setting used for the maximum wings level flight speed, except that the speed may not exceed V_{NE} or V_{MO}/M_{MO} , whichever is appropriate.

4.8.3 There shall be no excessive decrease in the gradient of the curve of stick force versus maneuvering load factor with increasing load factor.

4.9 Rate of Roll:

4.9.1 *Takeoff*—It shall be possible, using a favorable combination of controls, to roll the airplane from a steady 30° banked turn through an angle of 60°, so as to reverse the direction of the turn within:

4.9.1.1 For a Level 1 or 2 airplane, 5 s from initiation of roll and

4.9.1.2 For a Level 3 or 4 airplane, $(W + 200)/590$ but not more than 10 s, where W is the weight in kg [$(W + 500)/1300$, but not more than 10 s, where W = weight in lbs].

4.9.2 The requirement of 4.9.1 shall be met when rolling the airplane in each direction with:

4.9.2.1 Flaps in the takeoff position;

4.9.2.2 Landing gear retracted;

4.9.2.3 For a single-engine airplane, at maximum takeoff power, and a multiengine airplane with the critical engine inoperative and the propeller in the minimum drag position and the other engines at maximum takeoff power; and

4.9.2.4 The airplane trimmed at a speed equal to the greater of 1.2 V_{S1} or 1.1 V_{MC} or as nearly as possible in trim for straight flight.

4.9.3 *Approach*—It shall be possible, using a favorable combination of controls, to roll the airplane from a steady 30° banked turn through an angle of 60°, so as to reverse the direction of the turn within:

4.9.3.1 For a Level 1 or 2 airplane, 4 s from initiation of roll and

4.9.3.2 For a Level 3 or 4 airplane, $(W + 1300)/1000$, but not more than 7 s, where W is weight in kg [$(W + 2800)/2200$, but not more than 7 s, where W = weight in pounds].

4.9.4 The requirement of 4.9.3 shall be met when rolling the airplane in each direction in the following conditions:

4.9.4.1 Flaps in the landing position(s),

4.9.4.2 Landing gear extended,

4.9.4.3 All engines operating at the power for a 3° approach, and

4.9.4.4 The airplane trimmed at V_{REF} .

5. Trim Requirements

5.1 *General*—Each airplane shall meet the trim requirements of this section after being trimmed and without further

pressure upon, or movement of, the primary controls or their corresponding trim controls by the pilot or the automatic pilot. In addition, it shall be possible in other conditions of loading, configuration, speed, and power to ensure that the pilot will not be unduly fatigued or distracted by the need to apply residual control forces exceeding those for prolonged application of Table 1. This applies in normal operation of the airplane and, if applicable, to those conditions associated with the failure of one engine for which performance characteristics are established.

5.2 *Lateral and Directional Trim*—The airplane shall maintain lateral and directional trim in level flight with the landing gear and wing flaps retracted as follows:

5.2.1 For Level 1, 2, and 3 airplanes, at a speed of 0.9 V_H , V_C , or V_{MO}/M_{MO} , whichever is lowest and

5.2.2 For Level 4 airplanes, at all speeds from 1.4 V_{S1} to the lesser of V_H or V_{MO}/M_{MO} .

5.3 *Longitudinal Trim*—The airplane shall maintain longitudinal trim under each of the following conditions:

5.3.1 For Level 1 airplanes with $V_{S0} \leq 45$ KCAS:

5.3.1.1 In level flight at any speed from 1.4 V_{S1} to 0.9 V_H or V_C (whichever is lower), and

5.3.1.2 In a climb with maximum continuous power at a speed V_Y with landing gear and wing flaps retracted, and

5.3.1.3 In a descent with idle power at a speed of 1.3 V_{S1} with landing gear extended and wing flaps in the landing position.

5.3.2 For Level 1 airplanes with $V_{S0} > 45$ KCAS and all other airplanes, a climb with:

5.3.2.1 Takeoff power, landing gear retracted, wing flaps in the takeoff position(s), at the speeds used in determining the climb performance required by 23.65 and

5.3.2.2 Maximum continuous power at the speeds and in the configuration used in determining the climb performance required by 23.69(a).

5.3.3 Level flight at all speeds from the lesser of V_H and either V_{NO} or V_{MO}/M_{MO} (as appropriate), to 1.4 V_{S1} , with the landing gear and flaps retracted;

5.3.4 A descent at V_{NO} or V_{MO}/M_{MO} , whichever is applicable, with power off and with the landing gear and flaps retracted; and

5.3.5 Approach with landing gear extended and with:

5.3.5.1 A 3° angle of descent with flaps retracted and at a speed of 1.4 V_{S1} ;

5.3.5.2 A 3° angle of descent with flaps in the landing position(s) at V_{REF} , and

5.3.5.3 An approach gradient equal to the steepest used in the landing distance demonstrations of 23.75 with flaps in the landing position(s) at V_{REF} .

5.4 In addition, each multiengine airplane shall maintain longitudinal and directional trim, and the lateral control force shall not exceed 22 N [5 lbf] at the speed used in complying with 23.67(a), (b)(2), or (c)(3), as appropriate, with:

5.4.1 The critical engine inoperative and, if applicable, its propeller in the minimum drag position;

5.4.2 The remaining engines at maximum continuous power;