

Designation: D4077 - 16

Standard Specification for Cumene (Isopropylbenzene)¹

This standard is issued under the fixed designation D4077; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

- 1.1 This specification covers cumene (isopropylbenzene).
- 1.2 The following applies to all specified limits in this specification: for purposes of determining conformance with this specification, an observed value or a calculated value shall be rounded off "to the nearest unit" in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.
- 1.3 Units—The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.
- 1.4 Consult current OSHA Regulations and Supplier's Safety Data Sheets, and local regulations for all materials used in this specification.

2. Referenced Documents

- 2.1 ASTM Standards:²
- D1492 Test Method for Bromine Index of Aromatic Hydrocarbons by Coulometric Titration
- D2710 Test Method for Bromine Index of Petroleum Hydrocarbons by Electrometric Titration
- D3160 Test Method for Phenol Content of Cumene (Isopropylbenzene) or AMS (α–Methylstyrene)
- D3437 Practice for Sampling and Handling Liquid Cyclic **Products**
- D3760 Test Method for Analysis of Isopropylbenzene (Cumene) by Gas Chromatography
- D5386 Test Method for Color of Liquids Using Tristimulus
- D7057 Test Method for Analysis of Isopropylbenzene (Cumene) by Gas Chromatography (External Standard) D7183 Test Method for Determination of Total Sulfur in

- D7359 Test Method for Total Fluorine, Chlorine and Sulfur in Aromatic Hydrocarbons and Their Mixtures by Oxidative Pyrohydrolytic Combustion followed by Ion Chromatography Detection (Combustion Ion Chromatography-
- D8005 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)
- E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- E298 Test Methods for Assay of Organic Peroxides
- E299 Test Method for Trace Amounts of Peroxides In **Organic Solvents**
- 2.2 Other Documents:
- OSHA Regulations, 29 CFR paragraphs 1910.1000 and 1910.1200^{-3}

3. Properties

3.1 Cumene (isopropylbenzene) shall conform to the following requirements:

Property	Specifications	ASTM Test Method ^A
Purity, weight %, min 0 481086767696 Alpha-Methylstrene, weight %, max Benzene, weight %, max Butylbenzenes, weight %, max Diisopropylbenzenes, weight %, max Ethylbenzene, weight %, max Phenols, mg/kg, max	99.92 40 0.01 0.001 0.02 0.002 0.002 0.01 5	D3760 or D7057 D3760 or D7057 D3760 or D7057 D3760 or D7057 D3760 or D7057 D3760 or D7057 D3160, D3760 or
n-Propylbenzene, weight %, max Sulfur, mg/kg, max Bromine index, max Appearance Color, Pt/Co, max Cumene hydroperoxide, at loading, mg/kg, max	0.03 1 100 <i>B</i> 15 100	D7057 D3760 or D7057 D7183 or D7359 D1492 or D2710 visual D5386 or D8005 E298 or E299

¹ This specification is under the jurisdiction of ASTM Committee D16 on Aromatic Hydrocarbons and Related Chemicals and is the direct responsibility of Subcommittee D16.07 on Styrene, Ethylbenzene and C9 and C10 Aromatic Hydrocarbons.

4. Sampling

4.1 Sampe the material in accordance with Practice D3437.

Aromatic Hydrocarbons and Related Chemicals by Ultraviolet Fluorescence

Current edition approved June 1, 2016. Published June 2016. Originally approved in 1981. Last previous edition approved in 2011 as D4077 - 11. DOI: 10.1520/D4077-16.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

^A If more than one method is listed for a property, the producer and the user should agree on the referee test method. $^{\it B}$ Clear liquid, free of sediment and haze from 18.3 to 25.6 $^{\rm o}$ C.

³ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, http:// www.access.gpo.gov.