



SLOVENSKI STANDARD
PSIST ETS 300 125:1996

01-oktober-1996

**Digitalno omrežje z integriranimi storitvami (ISDN) - Specifikacija podatkovne
povezovalne plasti vmesnika uporabnik-omrežje - Aplikacija priporočil CCIT
Q.920/I.440 in Q.921/I.441**

Integrated Services Digital Network (ISDN); User-network interface data link layer
specification; Application of CCITT Recommendations Q.920/I.440 and Q.921/I.441

Ta slovenski standard je istoveten z: ETS 300 125 Edition 1

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
35.100.20	Podatkovni povezovalni sloj	Data link layer

PSIST ETS 300 125:1996

en



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 125

September 1991

Source: ETSI TC-SPS

Reference: T/S 46-20 [CC]

ICS: 33.080

Key words: ISDN, data link layer, Q.920, Q.921

**Integrated Services Digital Network (ISDN);
User-network interface data link layer specification;
Application of CCITT Recommendations Q.920/I.440
and Q.921/I.441**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1991. All rights reserved.

Contents

Foreword	9
Scope	9
PART 1: Application of CCITT Recommendation Q.920(I.440)	11
ISDN user-network interface data link layer - General aspects.....	11
1 General.....	11
2 Concepts and terminology.....	11
3 Overview description of LAPD functions and procedures	15
3.1 General	15
3.2 Unacknowledged operation	17
3.3 Acknowledged operation.....	17
3.4 Establishment of information transfer modes	17
3.4.1 Data link connection identification	17
3.4.2 Data link states.....	18
3.4.3 TEI administration	19
3.4.4 Establishment of multiple frame operation	20
4 Service characteristics	20
4.1 General	20
4.2 Services provided to layer 3.....	20
4.2.1 Unacknowledged information transfer service	20
4.2.2 Acknowledged information transfer service	20
4.3 Services provided to layer management.....	21
4.4 Administrative services	22
4.5 Model of the data link service:	22
4.5.1 General.....	22
4.5.2 Data link layer representation as seen by layer 3.....	23
4.5.2.1 Data Link Connection Endpoint States.....	23
4.5.2.2 Broadcast data link layer connection services.....	23
4.5.2.3 Point-to-point data link connection endpoint services	23
4.5.2.4 Sequences of primitives at one point-to-point data link connection endpoint.....	23
4.6 Services required from the physical layer	24
5 Data link layer - Management structure	24
5.1 Data link procedure.....	26
5.2 Multiplex procedure.....	26
5.3 Structure of the data link procedure.....	26
5.4 Additions for European networks	27
5.4.1 General.....	27
5.4.2 Enhanced functional block diagram and block interaction diagram	27
References (used in Q.920)	31
PART 2: Application of CCITT Recommendation Q.921(I.441)	32
ISDN user-network interface - Data link layer specification	32
1 General.....	32
2 Frame structure for peer-to-peer communication	32

2.1	General.....	32
2.2	Flag sequence.....	32
2.3	Address field.....	32
2.4	Control field.....	33
2.5	Information field.....	33
2.6	Transparency.....	33
2.7	FCS field.....	33
2.8	Format convention.....	34
	2.8.1 Numbering Convention.....	34
	2.8.2 Order of bit transmission.....	34
	2.8.3 Field mapping convention.....	34
2.9	Invalid frames.....	35
2.10	Frame abort.....	35
3	Elements of procedures and formats of fields for data link layer peer-to-peer communication.....	35
3.1	General.....	35
3.2	Address field format.....	35
3.3	Address field variables.....	36
	3.3.1 Address field extension bit (EA).....	36
	3.3.2 Command/Response field bit (C/R).....	36
	3.3.3 Service Access Point Identifier (SAPI).....	36
	3.3.4 Terminal Endpoint Identifier (TEI).....	37
	3.3.4.1 TEI for broadcast data link connection.....	37
	3.3.4.2 TEI for point-to-point data link connection.....	37
3.4	Control field formats.....	37
	3.4.1 Information transfer (I) format.....	38
	3.4.2 Supervisory (S) format.....	38
	3.4.3 Unnumbered (U) format.....	38
3.5	Control field parameters and associated state variables.....	38
	3.5.1 Poll/Final bit.....	38
	3.5.2 Multiple frame operation - variables and sequence numbers.....	39
	3.5.2.1 Modulus.....	39
	3.5.2.2 Send state variable V(S).....	39
	3.5.2.3 Acknowledge state variable V(A).....	39
	3.5.2.4 Send sequence number N(S).....	39
	3.5.2.5 Receive state variable V(R).....	39
	3.5.2.6 Receive sequence number N(R).....	39
	3.5.3 Unacknowledged operation - variables and parameters.....	39
3.6	Frame types.....	39
	3.6.1 Commands and responses.....	39
	3.6.2 Information (I) command.....	40
	3.6.3 Set asynchronous balanced mode extended (SABME) command.....	40
	3.6.4 DISConnect (DISC) command.....	41
	3.6.5 Unnumbered Information (UI) command.....	41
	3.6.6 Receive Ready (RR) command/response.....	41
	3.6.7 REject (REJ) command/response.....	41
	3.6.8 Receive Not Ready (RNR) command/response.....	41
	3.6.9 Unnumbered Acknowledgement (UA) response.....	42
	3.6.10 Disconnected Mode (DM) response.....	42
	3.6.11 Frame reject (FRMR) response.....	42
	3.6.12 Exchange identification (XID) command/response.....	43
4	Elements for layer-to-layer communication.....	44
4.1	General.....	44
	4.1.1 Generic names.....	44
	4.1.1.1 DL-ESTABLISH.....	44
	4.1.1.2 DL-RELEASE.....	44
	4.1.1.3 DL-DATA.....	44
	4.1.1.4 DL-UNIT DATA.....	44
	4.1.1.5 MDL-ASSIGN.....	44
	4.1.1.6 MDL-REMOVE.....	45
	4.1.1.7 MDL-ERROR.....	45
	4.1.1.8 MDL-UNIT DATA.....	45

	4.1.1.9	MDL-XID	45
	4.1.1.10	PH-DATA	45
	4.1.1.11	PH-ACTIVATE	45
	4.1.1.12	PH-DEACTIVATE	45
	4.1.1.13	MPH-ACTIVATE (See Appendix III)	45
	4.1.1.14	MPH-DEACTIVATE (See Appendix III)	45
	4.1.1.15	MPH-INFORMATION	45
	4.1.2	Primitive types	45
	4.1.2.1	REQUEST	46
	4.1.2.2	INDICATION	46
	4.1.2.3	RESPONSE	46
	4.1.2.4	CONFIRM	46
	4.1.3	Parameter definition	46
	4.1.3.1	Priority indicator	46
	4.1.3.2	Message unit	46
4.2		Primitive procedures	47
	4.2.1	General	47
	4.2.2	Layer 3 - data link layer interactions	47
5		Definition of the peer-to-peer procedures of the data link layer	49
5.1		Procedure for the use of the P/F bit	50
	5.1.1	Unacknowledged information transfer	50
	5.1.2	Acknowledged multiple frame information transfer	50
5.2		Procedures for unacknowledged information transfer	50
	5.2.1	General	50
	5.2.2	Transmission of unacknowledged information	51
	5.2.3	Receipt of unacknowledged information	51
5.3		Terminal Endpoint Identifier (TEI) management procedures	51
	5.3.1	General	51
	5.3.2	TEI assignment procedure	52
	5.3.2.1	Expiry of timer T202	54
	5.3.3	TEI check procedure	54
	5.3.3.1	Use of the TEI check procedure	54
	5.3.3.2	Operation of the TEI check procedure	55
	5.3.4	TEI removal procedure	56
	5.3.4.1	Action taken by the data link layer entity receiving the MDL-REMOVE-REQUEST primitive	56
	5.3.4.2	Conditions for TEI removal	56
	5.3.5	TEI identity verify procedure	57
	5.3.5.1	General	57
	5.3.5.2	Operation of the TEI identity verify procedure	57
	5.3.5.3	Expiry of timer T202	58
	5.3.6	Formats and codes	58
	5.3.6.1	General	58
	5.3.6.2	Layer management entity identifier	59
	5.3.6.3	Reference number (Ri)	59
	5.3.6.4	Message type	59
	5.3.6.5	Action indicator (Ai)	59
5.4		Automatic negotiation of data link layer parameters	60
5.5		Procedures for establishment and release of multiple frame operation	60
	5.5.1	Establishment of multiple frame operation	60
	5.5.1.1	General	60
	5.5.1.2	Establishment procedures	60
	5.5.1.3	Procedure on expiry of timer T200	61
	5.5.2	Information transfer	61
	5.5.3	Termination of multiple frame operation	61
	5.5.3.1	General	61
	5.5.3.2	Release procedure	61
	5.5.3.3	Procedure on expiry of timer T200	62
	5.5.4	TEI-assigned state	62
	5.5.5	Collision of unnumbered commands and responses	62
	5.5.5.1	Identical transmitted and received commands	62
	5.5.5.2	Different transmitted and received commands	63

5.5.6	Unsolicited DM response and SABME or DISC command	63
5.6	Procedures for information transfer in multiple frame operation	63
5.6.1	Transmitting I frames	63
5.6.2	Receiving I frames	63
5.6.2.1	P bit set to 1	63
5.6.2.2	P bit set to 0	64
5.6.3	Sending and receiving acknowledgements	64
5.6.3.1	Sending acknowledgements	64
5.6.3.2	Receiving acknowledgements	64
5.6.4	Receiving REJ frames	64
5.6.5	Receiving RNR frames	65
5.6.6	Data link layer own receiver busy condition	67
5.6.7	Waiting acknowledgement	67
5.7	Re-establishment of multiple frame operation	68
5.7.1	Criteria for re-establishment	68
5.7.2	Procedures	68
5.8	Exception condition reporting and recovery	69
5.8.1	N(S) sequence error	69
5.8.2	N(R) sequence error	69
5.8.3	Timer recovery condition	69
5.8.4	Invalid frame condition	70
5.8.5	Frame rejection condition	70
5.8.6	Receipt of an FRMR response frame	70
5.8.7	Unsolicited response frames	70
5.8.8	Multiple-assignment of TEI value	71
5.9	List of system parameters	71
5.9.1	Timer T200	71
5.9.2	Maximum number of retransmissions (N200)	71
5.9.3	Maximum number of octets in an information field (N201)	72
5.9.4	Maximum number of transmission of the TEI identity request message (N202)	72
5.9.5	Maximum number of outstanding I frames (k)	72
5.9.6	Timer T201	72
5.9.7	Timer T202	72
5.9.8	Timer T203	72
5.10	Data link layer monitor function	73
5.10.1	General	73
5.10.2	Data link layer supervision in the multiple-frame-established state	73
5.10.3	Connection verification procedures	73
5.10.3.1	Start timer T203	73
5.10.3.2	Stop Timer T203	74
5.10.3.3	Expiry of timer T203	74
	Annex A (to Recommendation Q.921) Provision of point-to-point signalling connections	75
	Annex B (to Recommendation Q.921) SDL for point-to-point procedures	76
B.1	General	76
B.2	An overview of the states of the point-to-point data link layer entity	76
B.3	Cover notes	79
B.4	The use of queues	80
B.5	SDL representation	81
	Annex C (to Recommendation Q.921) An SDL representation of the broadcast procedures of the data link layer	109
	Annex D (to Recommendation Q.921) State transition table of the point-to-point procedures of the data link layer	110