



## Designation: D7802 – 12 (Reapproved 2016)

# Standard Terminology for Paint Roller Application Tools<sup>1</sup>

This standard is issued under the fixed designation D7802; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This standard establishes the definitions or terminology used in the manufacturing and testing of paint rollers.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>2</sup>

D5069 Practice for Preparation of Paint-Roller Covers for Evaluation of Architectural Coatings

D6337 Practice for Physical Characterization of Woven Paint Applicator Fabrics

D7073 Guide for Application and Evaluation of Brush and Roller Applied Paint Films

<sup>1</sup> This terminology is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.61 on Paint Application Tools.

Current edition approved Dec. 1, 2016. Published December 2016. Originally approved in 2012. Last previous edition approved in 2012 as D7802 – 12. DOI: 10.1520/D7802-12R16.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or [service@astm.org](mailto:service@astm.org) (e-mail); or through the ASTM website ([www.astm.org](http://www.astm.org)). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; <http://www.copyright.com/>*

## 3. Terminology

### 3.1 Definitions:

**fabric**, *n*—*for paint applicators*, a paint carrying medium made by knitting or weaving; fabrics may consist of synthetic or natural materials, or a combination of both.

**formulation**, *n*—a specification that gives ingredients and amounts, or process.

**matting**, *n*—*for fabric fibers*, a condition where they tend to lie flat during application.

**nap**, *n*—*for fabric fibers*, the length of fibers essentially perpendicular to the surface.

**pick-up**, *n*—*for paint applicators*, after break-in, the amount of paint, or other coating material, an applicator can hold.

**release**, *n*—*for paint applicators*, after break-in, the amount of paint, or other coating materials, that the applicator can dispense after pick up.

**sliver knitting**, *n*—a process for producing an array of fibers locked essentially perpendicular to a knit backing.

**wet edge time**, *n*—the length of time a wet, coated region can stand before showing lap marks when an overlapped region is coated; this is also known as wet edge retention.

## 4. Keywords

4.1 definitions; fabric; terminology