



Designation: F2931 – 16^{ε1}

Standard Guide for Analytical Testing of Substances of Very High Concern in Materials and Products¹

This standard is issued under the fixed designation F2931; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

^{ε1} NOTE—Keywords were added editorially in March 2017.

1. Scope

1.1 This guide contains a list of potential test methods for the analysis of Substances of Very High Concern (SVHC) as designated by ECHA, the European Chemicals Agency. Information on the test methods cited is publicly available and is drawn from a variety of sources. The guide is intended to assist in the selection of test methods that are applicable for the SVHCs identified.

1.2 The specific SVHCs covered within this guide are compiled from the ECHA Candidate List of Substances of Very High Concern. This list is also referred to as the REACH Candidate List.

1.3 This guide specifically addresses methods for the analysis of SVHCs in products. It is not intended to cover the many and varied analysis challenges associated in the manufacturing environment.

1.4 Limitations:

1.4.1 This guide is intended to provide a compilation of available test methods for the SVHCs listed on the ECHA Candidate list and is not intended to be exhaustive. The test methods within this guide are not the only ones available for any specific substances and this guide does not recommend any specific test method.

1.4.2 Test methods for specific substances at the detection limits required for REACH reporting are not always available. In some cases, it is necessary to deduce the quantity of substance present through the analysis and quantification of its elements. Although this approach is routinely used some degree of uncertainty exists in the final result due to the reduced specificity of the test method.

1.4.3 Although this guide is intended to be updated on a periodic basis to capture new developments in the field, there is no assurance that the information provided is the most current.

1.5 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.6 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

D1257 Specification for High-Gravity Glycerin

D1385 Test Method for Hydrazine in Water

D1971 Practices for Digestion of Water Samples for Determination of Metals by Flame Atomic Absorption, Graphite Furnace Atomic Absorption, Plasma Emission Spectroscopy, or Plasma Mass Spectrometry

D3335 Test Method for Low Concentrations of Lead, Cadmium, and Cobalt in Paint by Atomic Absorption Spectroscopy

D3545 Test Method for Alcohol Content and Purity of Acetate Esters by Gas Chromatography

D4309 Practice for Sample Digestion Using Closed Vessel Microwave Heating Technique for the Determination of Total Metals in Water

D5831 Test Method for Screening Fuels in Soils

D7065 Test Method for Determination of Nonylphenol, Bisphenol A, *p*-*tert*-Octylphenol, Nonylphenol Monoethoxylate and Nonylphenol Diethoxylate in Environmental Waters by Gas Chromatography Mass Spectrometry

D7485 Test Method for Determination of Nonylphenol, *p*-*tert*-Octylphenol, Nonylphenol Monoethoxylate and Nonylphenol Diethoxylate in Environmental Waters by Liquid Chromatography/Tandem Mass Spectrometry

D7823 Test Method for Determination of Low Level, Regulated Phthalates in Poly (Vinyl Chloride) Plastics by

¹ This guide is under the jurisdiction of ASTM Committee F40 on Declarable Substances in Materials and is the direct responsibility of Subcommittee F40.02 on Management Practices and Guides.

Current edition approved July 1, 2016. Published August 2016. Originally approved in 2011. Last previous edition approved in 2015 as F2931 – 15. DOI: 10.1520/F2931-16E01.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

Thermal Desorption—Gas Chromatography/Mass Spectrometry

D7968 Test Method for Determination of Perfluorinated Compounds in Soil by Liquid Chromatography Tandem Mass Spectrometry (LC/MS/MS)

E1621 Guide for Elemental Analysis by Wavelength Dispersive X-Ray Fluorescence Spectrometry

F2576 Terminology Relating to Declarable Substances in Materials

2.2 *European Commission.*³

Article 57 of the European Union Regulation #1907/2006

2.3 *International Electrotechnical Commission TC111:*⁴

IEC 62321 Electrotechnical Products – Determination of Levels of Six Regulated Substances (Lead, Mercury, Cadmium, Hexavalent Chromium, Polybrominated Biphenyls, Polybrominated Diphenyl Ethers)

2.4 *Joint Industry Guide (JIG):*⁵

JIG-101 Material Composition Declaration for Electrotechnical Products. Ed 4.0, 2011

3. Terminology

3.1 Definitions:

3.1.1 Terms and definitions related to declarable substances in materials may be found in Terminology F2576.

3.1.2 Terms and definitions in the guide not found in Terminology F2576 are found in a common dictionary or other reference documents such as the ASTM Dictionary of Engineering Science & Technology.⁶

3.2 Definitions of Terms Specific to This Standard:

3.2.1 *article*—“an object which during production is given a special shape, surface or design which determines its function to a greater degree than its chemical composition” as defined in Article 3(3) of the REACH Regulation.

3.2.2 *brominated flame retardant*—a group of brominated organic compounds that are used to inhibit initiation of a fire.

3.2.3 *Joint Industry Guide*—An industry standard of the Electric Industries Alliance that “establishes the relevant substances as well as reporting thresholds that the industry agrees should govern material content disclosures.”⁵

3.2.4 *phthalates*—also known as *phthalate esters*, are esters of phthalic acid primarily used as a plasticizer for polyvinyl chloride or as solvents for many different types of consumer products.

3.2.5 *plasticizer*—any of a group of substances used in plastics and other materials to control viscosity, flexibility or softness of the finished product.

3.2.6 *Substances of Very High Concern (SVHC)*—substances that have hazards of serious consequences and meet

the criteria for carcinogenic, mutagenic and reproductive toxic substances of category 1 and 2.

3.2.6.1 *Discussion*—SVHC can be persistent, bioaccumulative and toxic (PBT) substances or very persistent and very bioaccumulative (VPvB) substances. Other substances giving rise to an equivalent level of concern as potential SVHC include endocrine disruptors.

3.3 Acronyms:

3.3.1 *AAS*—Atomic Absorption Spectrometry

3.3.2 *AED*—Atomic Emission Detection

3.3.3 *AES*—Atomic Emission Spectrometry

3.3.4 *AFS*—Atomic Fluorescence Spectrometry

3.3.5 *BFR*—Brominated Flame Retardant

3.3.6 *CAS*—Chemical Abstract Services

3.3.7 *CMR*—Carcinogenic, Mutagenic and Toxic to Reproduction

3.3.8 *CPSC*—United States Consumer Product Safety Commission

3.3.9 *DMF*—Dimethylformamide

3.3.10 *ECD*—Electron Capture Detection

3.3.11 *ECHA*—European Chemicals Agency

3.3.12 *ECNI*—Electron Capture Negative Ion

3.3.13 *EEE*—Electrical and Electronic Equipment

3.3.14 *EIA*—Electronic Industries Alliance

3.3.15 *EPA*—United States Environmental Protection Agency

3.3.16 *EU*—European Union

3.3.17 *FID*—Flame Ionization Detection

3.3.18 *FPD*—Flame Photometric Detection

3.3.19 *GC-MS*—Gas Chromatography-Mass Spectrometry

3.3.20 *GFAA*—Graphite Furnace Atomic Absorption Spectrometry

3.3.21 *HAFID*—Hydrogen Atmosphere Flame Ionization Detection

3.3.22 *HFAA*—Heptafluoroxylic acid anhydride

3.3.23 *HIPS*—High Impact Polystyrene

3.3.24 *HPLC*—High Performance (or Pressure) Liquid Chromatography

3.3.25 *ICP-MS*—Inductively Coupled Plasma – Mass Spectrometry

3.3.26 *ICP-OES*—Inductively Coupled Plasma – Optical Emission Spectrometry

3.3.27 *IR*—Infrared Spectrometry

3.3.28 *LC-MS-MS*—Liquid Chromatography-Tandem

3.3.29 *MSP*—Microspectrophotometer

3.3.30 *NIOSH*—United States National Institute for Occupational Health and Safety

3.3.31 *PAH*—Polycyclic Aromatic Hydrocarbon

3.3.32 *PTFE*—Polytetrafluoroethylene (Teflon)

3.3.33 *PVC*—Polyvinyl Chloride

³ Europese Commissie, B-1049, Brussels, Belgium, http://ec.europa.eu/index_en.htm.

⁴ Available from International Electrotechnical Commission (IEC), 3, rue de Varembé, P.O. Box 131, CH-1211 Geneva 20, Switzerland, <http://www.iec.ch>.

⁵ Available from the Consumer Electronics Association, 1919 S. Eads St. Arlington, VA 22202, <http://www.ce.org>

⁶ ASTM Dictionary of Engineering Science & Technology, 10th Edition. Available from www.astm.org.

3.3.34 *REACH*—Registration, Evaluation and Authorization of Chemicals

3.3.35 *RoHS*—Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment

3.3.36 *UV-VIS*—UltraViolet-Visible Spectrometry

3.3.37 *XRF*—X-ray Fluorescence Spectrometry

4. Summary of Guide

4.1 This guide provides a list of test methods for the determination of the Substances of Very High Concern as identified in the REACH Candidate list. Screening methods are discussed in [Appendix X2](#).

4.2 This guide provides identifiers for each substance such as chemical name, synonyms, chemical formulas, CAS and EU numbers.

4.3 Common uses for each of the substances are identified.

5. Significance and Use

5.1 The REACH Candidate list classifies substances as SVHCs thus making them subject to possible authorization. Compliance to the REACH regulation requires that any identified SVHC be present at a concentration of less than 0.1 % (w/w) of the total article weight to avoid triggering a reporting obligation. This guide is intended to assist in the identification of available test methods for quantitative analysis of the substance(s) of interest.

5.2 When possible, industry accepted standard test methods are cited. However, industry vetted test methods are not available for all of the substances contained in the REACH Candidate List. Thus, some caution and due diligence must be exercised when applying some of the methods listed in this guide.

5.3 In some cases, test methods for the identification and quantification of a specific substance are not available. An example would include CoCl₂. Methods currently in practice involve the individual determination of Co and Cl concentrations and use other sources of information or chemical judgment to assign the expected CoCl₂ concentration. This approach obviously has its limitations and pitfalls and must be used judiciously.

5.4 Under the REACH regulation, EU manufacturers, importers or distributors of articles containing more than 0.1 % (w/w) of a substance that the Agency has listed as being an SVHC shall provide their customers with the name of the substance and information allowing the safe use of the article. Producers and distributors of articles containing SVHC shall also supply the same information to consumers, upon request. In situations where this information is not readily available from the supply chain it is incumbent upon the supplier to collect this information through actual chemical analysis or other means. This guide is intended to assist in the selection of appropriate test methods in the event that chemical analysis is required.

6. Substance List and Uses

6.1 The substances listed in [Table 1](#) were derived from the ECHA SVHC Candidate List published in October 2008. Any

substances that have been subsequently added after October 2008 are not included.

6.2 The CAS or EU numbers are unique identifiers for the substance. It is possible for a particular substance to have one or more commonly used names.

6.3 Common uses of the substance help to identify in which products or materials these substance is likely to be found. Note that the list of common uses is not exhaustive.

7. SVHC Test Methods

7.1 This guide is not intended to be exhaustive in the identification of available test methods. The intent is to provide guidance and some examples of available test methods relevant to the required analysis. Some of the SVHCs do not have industry standard test methods associated with them. Literature citations of these non-standard methods are meant to be for information only.

7.2 Standard test methods do not exist for all of the SVHCs listed. Therefore, the test methods cited for those substances must be validated for analytical accuracy before use in regulatory compliance demonstration. Moreover, when a method is applied outside of its intended scope, validation of the altered method is required. Considerations such as sample matrix, analytical requirements, etc. for the intended analysis will determine its applicability. All deviations from the published method must be clearly noted.

NOTE 1—If a standardized method is used beyond the stated scope, that addition must be validated. All deviations from published methods must be documented.

7.3 In many cases, test methods that are specific for a particular substance have not been developed. Therefore, the approach to quantitative analysis is not straightforward. A combination of test methods and the use of logical assumptions are required. These assumptions shall be clearly articulated because they will determine the limitations of the approach.

7.4 Screening methods can be utilized to determine whether a detectable amount of a substance is present. In many situations the application of a screening process can obviate the need to perform full quantitative analysis. See [Appendix X2](#) for more information on screening methodologies.

7.5 In some cases, sample preparation methods are dependent upon the physical state of the sample to be analyzed. For many of the test methods, several sample preparation references are cited when applicable.

7.6 In some cases, limitations in the sample preparation method cited in [Appendix X1.2](#) can produce a sample for analysis that is non-optimal. Incomplete extraction, incomplete digestion, loss of analyte, etc. often require adjustments to the sample preparation methods to obtain the desired analytical result. At a minimum the limitations in the sample preparation method shall be accounted for, when possible, in the calculation of the analytical result. Additionally, if these adjustments to the method do not produce a satisfactory sample for analysis, it may be necessary to develop an alternative method. Validation of the sample preparation method will thus be required.

TABLE 1 SVHC Substances and Their Common Uses

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
4,4'-Diaminodiphenylmethane	4,4'-Methylene-dianiline, MDA	101-77-9	202-974-4	C ₁₃ H ₁₄ N ₂	Converted to methylenediphenyl diisocyanate (MDI). MDI used for polyurethane production. Other uses include: (1) hardener for epoxy resins and adhesives, (2) basic ingredient of colorant, and (3) intermediate for high-performance polymer. Used as a fragrant particularly for consumer cosmetic products.
5-tert-Butyl-2,4,6-Trinitro-m-Xylene	Musk Xylene (2,4,6-Trinitro-1,3-dimethyl-5-t-butylbenzene), Short Chain Chlorinated Paraffins (SCCP)	81-15-2	201-329-4	C ₁₂ H ₁₅ N ₃ O ₆	
Alkanes, C10-13, chloro	85535-84-8	287-476-5		C _x H _(2x-y+2) Cl _y where x=10 ¹³ and y=1 ⁻¹³	May act as a secondary plasticizer or flame retardant in PVC. Other uses include: (1) metal working lubricant, (2) rubber parts, (3) paints, (4) sealant, (5) leather work, and (6) fiber.
Anthracene	Paranaphthalene	120-12-7	204-371-1	C ₁₄ H ₁₀	An intermediate in the production of dyes; used in the manufacture of pyrotechnic products.
Benzyl butyl phthalate	Phthalic acid, benzyl butyl ester	85-68-7	201-622-7	C ₁₉ H ₂₀ O ₄	Plasticizer in flooring material such as PVC foam. Other uses are as a plasticizer in traffic cones, food conveyor belts, artificial leather, etc.
Bis(2-ethylhexyl)phthalate	Diethylphthalate	117-81-7	204-211-0	C ₂₄ H ₃₈ O ₄	Commonly used as a plasticizer in manufacturing of articles made of PVC, resins, rubbers, packaging materials, some paper products, and various medical devices, including the blood bags. It can also be found in some hydraulic fluids or dielectric fluids in capacitors. It is often found in coatings, pigments, textiles, or used as a solvent in light sticks.
Bis (tributyltin) oxide		56-35-9	200-268-0	C ₂₄ H ₅₄ OSn ₂	Primarily used as a biocide for boats, mildew proofing for leather work.
Cobalt dichloride	Distannoxane, hexabutyl-Cobaltous Chloride	7646-79-9	231-569-4	CoCl ₂	
↓ Diarsenic pentoxide	Diarsenic Pentoxide	1303-28-2	215-116-9	As ₂ O ₅	This substance can be used for (1) humidity indicator, (2) absorbent of ammonia gas, (3) gas mask, (4) production for vitamin B ₁ , (5) trace amount of nutrient factor for food, (6) trace amount of element for nitric-acid pesticides, (7) solvent in purifying magnesium. Additionally, it may be used for packaging.
Diarsenic trioxide	Arsenic Trioxide	1327-53-3	215-481-4	As ₂ O ₃	This substance can be used for (1) colorants, (2) metal refining, (3) special glass production, and (4) antiseptic agent for wood.
Dibutyl phthalate	1,2-Benzenedicarboxylic acid di-n-butyl ester	84-74-2	201-557-4	C ₁₆ H ₂₂ O ₄	This substance can be used for (1) decorants for glasses and enamel, (2) purifying and oxidizing agent in production of special glasses and lead crystal, (3) antiseptic agent for wood, and (4) medicine for leukemia.
Hexabromocyclooctadecane	Cyclododecane, hexabromo-isomers Lead Acid Arsenate Sodium Bichromate	25637-99-4	247-148-4	C ₁₂ H ₁₈ Br ₆	Common plasticizer used in various polymers to keep crystals from forming. It is also used in paints, pigments, or printing inks as an adhesive agent. It is soluble in various organic solvents. This property allows it to be used as fixatives in perfumes or as an ectoparasiticide.
Lead hydrogen arsenate	7784-40-9	232-064-2		(AsO ₄ H)Pb	Used as a brominated flame retardant for polystyrene materials, for example, HIPS case material and packaging.
Sodium dichromate dihydrate	7789-12-0	234-190-3		Na ₂ Cr ₂ O ₇ ·2H ₂ O	Insecticide or pesticide
Triethyl arsenate	Arsenic acid Triethyl Ester	15606-95-8	427-700-2	(C ₂ H ₅ O) ₃ AsO	Used for integrated circuit manufacturing as an intermediate for n-type doping of semiconductors.
2,4-Dinitrotoluene	1-methyl-2,4-dinitrotoluene	121-14-2	204-450-0	C ₇ H ₆ N ₂ O ₄	2,4-dinitrotoluene is used in the production of toluene diisocyanate, which is used for the manufacture of flexible polyurethane foams. The substance is also used as gelatinizing-plasticizing agent for the manufacture of explosive mixtures (for example, for airbags in cars).
VITREOUS		142844-00-6			Refractory ceramic fibres are used for high-temperature insulation, almost exclusively in industrial applications (insulation of industrial furnaces and equipment, equipment for the automotive and aircraft/aerospace industry) and in fire protection (buildings and industrial process equipment).
Aluminosilicate Refractory Ceramic Fibres					The substances are mainly used in the manufacture of other substances such as anthraene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.
Anthracene oil	Anthracene Phenanthrene Carbazole	90640-80-5	292-602-7	C ₁₄ H ₁₀ C ₁₂ H ₉ N	

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
Anthracene oil, anthracene paste	Anthracene Phenanthrene Carbazole	90640-81-6	292-603-2	$C_{14}H_{10}$ $C_{12}H_9N$	The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.
Anthracene oil, anthracene paste, anthracene fraction	Anthracene Phenanthrene Carbazole	91995-15-2	295-275-9	$C_{14}H_{10}$ $C_{12}H_9N$	The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.
Anthracene oil, anthracene paste,distr. lights	Anthracene Phenanthrene Carbazole	91995-17-4	295-278-5	$C_{14}H_{10}$ $C_{12}H_9N$	The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.
Anthracene oil, anthracene-low	Anthracene Phenanthrene Carbazole	90640-82-7	292-604-8	$C_{14}H_{10}$ $C_{12}H_9N$	The substances are mainly used in the manufacture of other substances such as anthracene and carbon black. They may also be used as reducing agents in blast furnaces, as components in bunker fuel, for impregnating, sealing and corrosion protection.
Diisobutyl phthalate	Bis(2-methylpropyl) benzene-1,2-dicarboxylate	84-69-5	201-553-2	$C_{16}H_{22}O_4$	Diisobutyl phthalate is used as plasticiser for nitrocellulose, cellulose ether, polyacrylate and polyacetate dispersions, and as a gelling aid in combination with other plasticisers, which are widely used for plastics, lacquers, adhesives, explosive material and nail polish.
Lead chromate	Lead(2+) chromate	7758-97-6	231-846-0	$CrH_2O_4 \cdot Pb$	Lead chromate is used for manufacturing pigments and dyes, as a pigment or coating agent in industrial and maritime paint products or for embalming/ restoring of art products. Further potential uses include as detergents and bleaches, photosensitive materials and for the manufacture of pyrotechnic powder.
Lead chromate molybdate	Lead(2+) chromate lead(2+) sulfate lead(2+) molybdate	12656-85-8	235-759-9	$CrH_2O_4 \cdot Pb$ $H_2O_4S \cdot Pb$ $PbMoO_4$	Lead chromate molybdate sulphate red (C.I. Pigment Red 104) is used as a colouring, painting and coating agent in sectors such as the rubber, plastic and paints, coatings and varnishes industries. Applications comprise the production of agricultural equipment, vehicles and aircraft as well as road and airstrip painting.
Lead sulfochromate yellow	Lead(2+) chromate lead(2+) sulfate	1344-37-2	215-693-7	$CrH_2O_4 \cdot Pb$ $H_2O_4S \cdot Pb$	Lead sulfochromate yellow (C.I. Pigment Yellow 34) is used as a colouring, painting and coating agent in sectors such as the rubber, plastic and paints, coatings and varnishes industries. Applications comprise the production of agricultural equipment, vehicles and aircraft as well as road and airstrip painting. The substance is further used for camouflage or ammunition marking in the defence area.
Pitch, coal tar, high temperature	anode pitch, binder pitch, clay pigeon binder, electrode pitch, hard pitch, impregnating pitch, soft pitch, vacuum pitch	65996-93-2	266-028-2	not applicable	Pitch, coal tar, high temperature is mainly used in the production of electrodes for industrial applications. Smaller volumes are dedicated to specific uses such as heavy duty corrosion protection, special purpose paving, manufacture of other substances and the production of clay targets. Tris(2-chloroethyl)phosphate is mainly used as an additive plasticiser and viscosity regulator with flame-retarding properties for acrylic resins, polyurethane, polyvinyl chloride and other polymers. Other fields of application are adhesives, coatings, flame-resistant paints and varnishes. The main industrial branches to use TCEP are the furniture, the textile and the building industry.
Zirconia Aluminosilicate Refractory Ceramic Fibres					Refractory ceramic fibres are used for high-temperature insulation, almost exclusively in industrial applications (insulation of industrial furnaces and equipment, equipment for the automotive and aerospace industry) and in fire protection (buildings and industrial process equipment).
Acrylamide	Prop-2-enamide	79-06-1	201-173-7	C_3H_5NO	Acrylamide is almost exclusively used for the synthesis of polyacrylamides, which are used in various applications, in particular in waste water treatment and paper processing. Minor uses of acrylamide comprise the preparation of polyacrylamide gels for research purposes and as grouting agents in civil engineering.

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
Ammonium dichromate	Diammonium dichromate, Ammonium bichromate, ammonium chromate, chromic acid ($H_2Cr_2O_7$) diammonium salt, diammonium dichromate, dichromic acid diammonium salt	7789-09-5 10043-35-3 11113-50-1	232-143-1 234-343-4	$Cr_2H_2O_7 \cdot 2H_3N$	Ammonium dichromate is mainly used as an oxidising agent. Other known uses are in the manufacture of photosensitive screens and as mordant in the manufacture of textiles. Minor uses seem to comprise metal treatment and laboratory analytical agent.
Boric acid		233-139-2 234-343-4		BH_3O_3	Boric acid is widely used on account of its consistency-influencing, flame-retarding, antiseptic and preservative properties. It is a component of detergents and cleaners, adhesives, toys, industrial fluids, brake fluids, glass, ceramics, flame retardants, paints, disinfectants, cosmetics, food additives, fertilisers, insecticides and other products.
Dissodium tetraborate, anhydrous	Disodium tetraborate decahydrate, Disodium tetraborate anhydrous. Disodium tetraborate pentahydrate, borax decahydrate, boric acid, disodium salt, borax pentahydrate	1303-96-4 1330-43-4 12179-04-3	215-540-4	$Na_2B_4O_7 \cdot 10H_2O$ $Na_2B_4O_7$ $Na_2B_4O_7 \cdot 5H_2O$	Disodium tetraborate and tetraboron disodium heptaoxide form the same compounds in aqueous solutions. Uses include a multitude of applications, for example, in detergents and cleaners, in glass and glass fibres, ceramics, industrial fluids, metallurgy, adhesives, flame retardants, personal care products, biocides, fertilisers.
Potassium chromate	Dipotassium chromate, Bipotassium chromate, Dipotassium monochromate, Bipotassium monochromate, Neutral potassium chromate, Potassium chromate (VI), Chromate of potash (potass), Chromic acid dipotassium salt Chromic acid ($H_2Cr_2O_7$) dipotassium salt, dichromic acid dipotassium salt, dipotassium bichromate, dipotassium dichromate, Lopezite, potassium bichromate, potassium dichromate(VI), dipotassium dichromium hepta-oxide	7789-00-6	232-140-5	K_2CrO_4	Potassium chromate is used as a corrosion inhibitor for treatment and as coating of metals, for manufacture of reagents, chemicals and textiles, as a colouring agent in ceramics, in the manufacture of pigments/inks and in the laboratory as analytical agent.
	Disodium chromate	7778-50-9	231-906-6	$K_2Cr_2O_7$	Potassium dichromate is used for chrome metal manufacturing and as corrosion inhibitor for treatment and coating of metals. It is further used as textile mordant, as laboratory analytical agent for cleaning of laboratory glassware, in the manufacture of other reagents and as oxidising agent in photolithography.
	Sodium chromate	7775-11-3	231-889-5	Na_2CrO_4	Sodium chromate is mainly used as an intermediate in the manufacture of other chromium compounds as well as a laboratory analytical agent, but this use is limited. Other potential uses are mentioned in the literature but whether they occur in the EU is not clear.
	Tetraboron disodium heptaoxide, hydrate	12267-73-1	235-541-3	$B_4Na_2O_7 \cdot xH_2O$	Disodium tetraborate and tetraboron disodium heptaoxide form the same compounds in aqueous solutions. Uses include a multitude of applications, for example, in detergents and cleaners, in glass and glass fibres, ceramics, industrial fluids, metallurgy, adhesives, flame retardants, personal care products, biocides, fertilisers.
	Trichloroethylene	79-01-6	201-167-4	C_2HCl_3	Trichloroethylene is mainly used as intermediate in the manufacture of chlorinated and fluorinated organic compounds. Other uses are for cleaning and degreasing of metal parts or as solvent in adhesives.
Chromium trioxide	Acetylene trichloride, Ethynyl trichloride, Trichloroethene, TRI, TRIC, 1-Chloro-2,2-dichloroethylene, 1,1,2-Trichloroethylene, Trilene, Triklone®, Trimar. Industrial abbreviations include trichloroethylene, trichlor, Trike, Tricky and trichloroethylene. Trioxochromium	1333-82-0	215-607-8	CrO_3	Formulation of mixtures containing chromium trioxide, which are mainly used for example, metal finishing/surface treatment or in much smaller amounts as catalysts containing chromium trioxide.

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
Acids generated from chromium trioxide and their oligomers	Dichromic acid ($H_2Cr_2O_7$), hydroxy-(hydroxy)dioxo(chromio)oxy-dioxochromium, Chromic acid (H_2CrO_4), dihydroxy(dioxo)chromium	13630-68-2 7738-94-5	236-881-5 231-801-5	$Cr_2H_2O_7$ CrH_2O_4	Chromic acid, dichromic acid and oligomers of chromic and dichromic acid are spontaneously generated products of the reaction of chromic trioxide with water. Refer to the uses for chromium trioxide.
Cobalt (II) sulphate	Sulfuric acid, cobalt(2+) salt (1:1).	10124-43-3	233-334-2	CoH_2O_4S	Mainly used in the production of other chemicals. Further applications may include manufacture of catalysts and driers, surface treatments (such as electroplating), corrosion prevention, production of pigments, decolorising (in glass, pottery), batteries, animal food supplement, soil fertilizer, and others.
Cobalt (II) dinitrate		10141-05-6	233-402-1	CoN_2O_6	Mainly used in the production of other chemicals and the manufacture of catalysts. Further applications may include surface treatment and batteries, additive, production of other chemicals, production of pigments, and adhesion (in ground coat frit).
Cobalt (II) carbonate		513-79-1	208-169-4	$CoCO_3$	Mainly used in the manufacture of catalysts. Minor uses may include feed
Cobalt (II) diacetate	Cobalt di(acetate)	71-48-7	200-755-8	$C_4H_6CoO_4$	Mainly used in the manufacture of catalysts. Minor uses may include production of other chemicals, surface treatment, alloys, production of pigments, dyes, rubber adhesion, and feed additive.
2-Methoxyethanol	ethylene glycol monomethyl ether; EGME, Ethanol, 2-methoxy-ethylene glycol monoethyl ether;	109-86-4	203-713-7	$C_3H_8O_2$	Mainly used as solvent, chemical intermediate and additive for fuels.
2-Ethoxyethanol	EGEE, Ethanol, 2-ethoxy-Ethanol, 2-ethoxy-acetate; ethylene glycol mono ethyl ether acetate;	110-80-5	203-804-1	$C_4H_{10}O_2$	Mainly used as solvent and chemical intermediate.
2-ethoxyethyl acetate	Ethylglycoo acetate; ethylene glycol mono ethyl ether acetate; 2-EEA; acetic acid, 2-ethoxyethyl ester; ethoxyethanol acetate	111-15-9	203-839-2	$C_6H_{12}O_3$	As solvent in coatings and in the chemical industry, intermediate in the manufacture of cyanoacrylate adhesives.
Strontium chromate	Chromic acid (H_2CrO_4), strontium salt (1:1), Chromium diolatodioxo-strontium salt (1:1), C.I. Pigment Yellow 32, Deep Lemon Yellow, Strontium chromate (V), Strontium Yellow Di-C ₇ -11 (linear and branched)-alkyl phthalate, Dialkyl phthalate (C ₇ -11) branched and linear phthalate ester; 711P; D711P; Di-711-phthalate; Dialkyl(C ₇ -11-branched and linear) phthalate (DHNUP); Di(heptyl, nonyl, undecyl) phthalate (mixed isomers); Phthalic acid, dialkyl (C ₇ -C ₁₁) ester; Sanitizer 711 H ₂ O; H ₂ O (fuel); Levoxine; Nitrogen hydride(N ₂ H ₄); Oxytreat 35	7789-06-2	232-142-6	$SrCrO_4$	As corrosion inhibitor in coating mixtures used in the aeronautic / aerospace sector, in the coil coating sector of steel and aluminium and in the vehicle coating sector.
			271-084-6	$C_{22}H_{34}O_4-$ $C_{30}H_{50}O_4$	As plasticiser in PVC, foam, adhesives and coatings.
Hydrazine			206-114-9	H_4N_2	As intermediate in the manufacture of hydrazine derivatives, as a monomer in polymerisations, as a corrosion inhibitor in water treatment and for metal reduction and refining of chemicals. It is also used as a propellant for aerospace vehicles and as fuel in military (emergency) power units.

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
1-methyl-2-pyrrolidone N 0131	2-Pyrrolidone, 1-methyl-, 1-Methylpyrrolidin-2-one, 1-Methyl-2-pyrrolidone N-Methyl- α -pyrrolidone N-Methyl- γ -butyrolactam N-Methyl-2-ketopyrrolidine N-Methyl-2-pyrrolidone N-Methylbutyrolactam N-Methylpyrrolidone NSC 4594	872-50-4 212-828-1		C ₅ H ₉ NO	As solvent in coatings, cleaning products, for electronic equipment manufacture, as well as in semiconductor industry, petrochemical processing, pharmaceuticals and agrochemicals.
Pyrol M SL 1332	Propane, 1,2,3-trichloro-, Allyl trichloride; Glycerol trichlorohydrin; Glyceryl trichlorohydrin; NSC 35403; Trichlorohydrin;	96-18-4	202-486-1	C ₃ H ₅ Cl ₃	Intermediate in the manufacture of chlorinated solvents and agricultural products. It is also used as monomer. In the past, it was used as solvent, paint and varnish remover and as degreasing agent.
1,2,3-trichloropropane C7-rich	C ₆ -8-(branched)-Alkyl benzene-1,2-dicarboxylate, C ₆ -8-(branched)-Alkyl phthalate, Diisobutyl phthalate, DiHP Chromic acid (H ₂ CrO ₄), chromium(3+) salt (3:2), Dichromium(3+) trichromate, Chromic chromate, Chromium (III) chromate, Dichromium Trischromate, Accomet C; other trade names are confidential	71888-89-6 24613-89-6	276-158-1 246-356-2	Cr ₅ O ₁₂ CrH ₂ O ₄ .2/3Cr	As plasticiser in PVC and in sealants, coatings and potentially printing inks.
Dichromium tris(chromate)	Zinc chromate hydroxide (Zn ₅ (CrO ₄) ₃ (OH) ₈), Zinc tetraoxychromate, Zinc tetroxy chromate, Zinc chromate, Zinc hydroxide, Basic zinc chromate, Zinc chromate, Trizinc, dioxydo(dioxo)chromium dihydroxide	49663-84-5	234-329-8	(C ₆ H ₇ NCH ₂ O) _x	Aeronautic/ aerospace coating, steel and aluminium coil coating, and vehicle coating.
Potassium hydroxyoctaoxodizincated-chromate Peniazinc chromate octahydroxide	Formaldehyde, polymer with benzamine, polymeric MDA3, crude MDA, technical grade, 1,2-Benzenedicarboxylic acid, 1,2-bis(2(methoxyethyl))ester, Di(methoxethyl) phthalate, Bis(methylglycol) phthalate	11103-86-9 256-418-0	500-036-1 204-212-6	C ₁₄ H ₁₈ O ₆	Vehicle coating and aeronautic / aerospace coating Manufacture of other substances. Minor uses are as ion exchange resins in nuclear power plants, as hardener for epoxy resins. Plasticiser in polymeric materials and paints, lacquers and varnishes, including printing inks.
Formaldehyde, oligomeric reaction products with aniline (technical MDA)					
Bis(2-methoxyethyl) phthalate					

iTeh Standards
(https://standards.iteh.ai)
Document Preview

ASTM F2931-16e1

<https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1>

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
2-Methoxyaniline; o-Anisidine	Benzanamine, 2-methoxy-, 2-methoxybenzeneamine, 4-(2,4,4-trimethylpentan-2-yl)phenol, 4-(1,1,3,3-tetramethylbutyl)-	90-04-0	201-963-1	C ₇ H ₉ NO	Manufacture of dyes for tattooing and coloration of paper, polymers and aluminium foil.
4-(1,1,3,3-Tetramethylbutyl)phenol, (4-tert-Octylphenol)	Ethane, 1,2-dichloro-, Ethylene dichloride, dichloroethylene, 1,2-DCE,, 1,2-EDC	140-66-9	205-426-2	C ₁₄ H ₂₂ O	Manufacture of polymer preparations and of ethoxylate surfactants. Also used as a component in adhesives, coatings, inks and rubber articles.
1,2-Dichloroethane	Ethane, 1,1'-oxybis[2-methoxy-, 1-methoxy-2-(2-methoxyethoxy)ethane, Diglyme, DEGDME,	107-06-2	203-458-1	C ₂ H ₄ Cl ₂	Manufacture of other substances. Minor uses as solvent in chemical and pharmaceutical industries.
Bis(2-methoxyethyl) ether	Ethane, 1,1'-oxybis[2-methoxy-, 1-methoxy-2-(2-methoxyethoxy)ethane, Diglyme, Diethylenglycoldimethylether, Dimethylglycol, 2-(2-Methoxyethoxy)-1-methoxyethane, 2,5,8-Trioxanone, Di(2, Methoxyethyl) ether, Dimethyl carbitol, Ether, bis(2-methoxyethyl), 1,1'-Oxybis[2-methoxyethane], Methylidiglyme, (CAS registry numbers still in use: 70-992-86-8, 54631-70-8, 142939-39-7 although deleted in CAS, registry)	111-96-6	203-924-4	C ₆ H ₁₄ O ₃	Used primarily as a reaction solvent or process chemical in a wide variety of applications. Also used as solvent for battery electrolytes, and possibly in sealants, adhesives, fuels and automotive care products.
Arsenic acid	Arsenic acid (H ₃ AsO ₄), arsenic acid, trihydroxidoarsenic (IUPAC 2005), Orthoarsenic acid	7778-39-4	231-901-9	AsH ₃ O ₄	Mainly used to remove gas bubbles from ceramic glass melt (fining agent) and in production of laminated printed circuit boards. Also used in the manufacture of semiconductors and as laboratory agent.
	Arsenic acid (H ₃ AsO ₄), calcium salt (2:3), Tricalcium(2+) diarsenate, Arsenic acid calcium salt; calcium orthoarsenate; tricalcium arsenate	7778-44-1	231-904-5	As ₂ Ca ₃ O ₈	Present in complex raw materials that are used mainly for copper and lead refining. Also used to precipitate nickel from the molten metal and to manufacture darsenic trioxide.
Calcium arsenate	Arsenic acid (H ₃ AsO ₄), lead salt (2:3), Trilead (2+) diarsenate, Lead (II) arsenate, lead arsenate Acetamide, N,N-dimethyl-, Acetdimethylamide, DMA, DMAA, DMAC, Dimethylamide acetate, N,N-Dimethylethanamide	3687-31-8	222-979-5	As ₂ O ₈ Pb ₃	Present in complex raw materials for manufacture of copper, lead and a range of precious metals.
	2,2'-Dichloro-4,4'-methylenedianiline (MOCA)	127-19-5	204-826-4	C ₄ H ₉ N O	Used as solvent, mainly in the manufacture of various substances and in the production of fibres for clothing. Also used as reagent, and in products such as industrial coatings, insulation paper, polyimide films, paint strippers and ink removers.
Phenolphthalein	2,2'-Dichloro-4,4'-methylenedianiline (MOCA)	101-14-4	202-918-9	C ₁₃ H ₁₂ Cl ₂ N ₂	Mainly used as curing agent in resins and in the production of polymer articles and also for manufacture of other substances.
	1(3H)-Isobenzofuranone, 3,3-bis(4-hydroxyphenyl)-; 3,3-Bis(4-hydroxyphenyl)-2-benzofuran-1(3H)-one; 3,3-Bis(p-chlorophenyl)methane	77-09-8	201-004-7	C ₂₀ H ₁₄ O ₄	Mainly used as laboratory agent (pH indicator solutions). Minor uses are in pharmaceutical preparations and in some special applications.
Lead azide	Lead diazide	13424-46-9	236-542-1	N ₆ Pb	Mainly used as initiator or booster in detonators for both civilian and military uses and as initiator in pyrotechnic devices.

iTeh Standards
(https://standards.iteh.ai)

ASTM F2931-16e1

<https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1>

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
Lead styphnate	lead 2,4,6-trinitro-m-phenylene dioxide; 1,3-Benzenediol, 2,4,6-trinitro-, lead(2+)- salt (1:1); Lead(2+) 2,4,6-trinitrobenzene-1,3-diolate; 2,4-Dioxa-3-plumbabicyclo[3.3.1]nona-1(9),5,7-triene; 3,3dihydro-6,8,9-trinitro-; Lead, [styphnato(2-)]-; Resorcinol, 2,4,6-trinitro-, lead(2+)- salt (1:1); Lead styphnate; Lead tricinate; Lead trinitroresorinate; Tricinat Phenol, 2,4,6-trinitro-, lead(2+) salt (2:1); Lead(2+) bis(2,4,6-trinitrophenolate); Lead, bis(picryloxy)-; Phenol, 2,4,6-trinitro-, lead(2+)- salt; Picric acid, lead(2+)- salt; Lead(II) picrate 2,5,8,11-tetraoxadodecane; Triglyme; TEGDME; Triethylene glycol dimethyl ether; Ansil Ether 161; DMTG; Ethane, 1,2-bis(2-methoxyethoxy)-; Glyme 4; Hisolve MTM; Methyltriglyme; NSC 66400	15245-44-0	239-290-0	C ₆ H ₄ N ₆ O ₈ Pb	Mainly used as a primer for small calibre and rifle ammunition. Other common uses are in ammunition pyrotechnics, powder actuated devices and detonators for civilian use.
Lead dipicrate		6477-64-1	229-335-2	C ₁₂ H ₄ N ₆ O ₁₄ Pb	The substance is an explosive like lead diazide and lead styphnate.
1,2-bis(2-Methoxyethoxy)ethane (TEGDME; triglyme)		11-49-2	203-977-3	C ₈ H ₁₈ O ₄	Triglyme is used as an inert solvent for grignard-, reduction- and alkylation-reactions. Reactions involving alkali metals can be carried out in triglyme and alkali metal dispersions in triglyme are used for etching of Teflon and Fluoropolymers. Triglyme is also used as an inert solvent for reduction reactions using Sodium borohydride and used as a solvent to carry out methylation reactions using dimethyl carbonato (and other dialkyl carbonates). Triglyme is also used as part of absorbing liquids in the industrial cleaning of gases. Triglyme has been reported to be used in Brake fluids.
Ethane, 1,2-dimethoxy-; ethylene glycol dimethyl ether (EGDME)		110-71-4	203-794-9	C ₄ H ₁₀ O ₂	EGDM _E is used as a solvent or processing aid in the manufacture or formulation of industrial chemicals. The large majority of the EGDME sold by the producer is used as a site limited processing aid for industrial chemical manufacture.
Ammoniumpentadecafluoro octanoate (APFO)		3825-26-1	223-320-4	C ₈ H ₄ NF ₁₅ NO ₂	PF _O A is used as a group name for PF _O A and its salts, and PF _O A is mainly produced and used as its ammonium salt, ammoniumpentadecafluoro octanoate (APFO, CAS Number: 3825-26-1). However, the perfluoroctanoate anion is the molecule of primary interest. APFO and PF _O A are sometimes used interchangeably as both PF _O -anion and PF _O A (neutral species) exist in solution.

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
C.I. Basic Blue 26 [4-[4-anilino-1-naphthyl][4-(dimethylamino)phenyl]methylenecyclohexa-2,5-dien-1-ylidene]dimethylammonium chloride)	Méthanaminium, N-4-[4-(dimethylamino)phenyl][4-(phenylamino)-1-naphthalenyl]methylene]-2,5-cyclohexadien-1-ylidene]-N-methyl-, chloride (1:1); 4-[4-(Dimethylamino)phenyl][4-(phenylamino)naphthalen-1-ylmethylene]-N,N-dimethylcyclohexa-2,5-dien-1-iminium Chloride; C.I. Basic Blue 26; Methanaminium, N-4-[4-(dimethylamino)phenyl][4-(phenylamino)-1-naphthalenyl]methylene]-2,5-cyclohexadien-1-ylidene]-N-methyl-, chloride; Victoria Blue B; ADC Victoria Blue B; Aizen Victoria Blue BH; BTK Victoria Blue; Basazol C Blue 57; Basic Blue; 26; Basic Blue B; Basic Victoria Blue B; Basonyl Blue 640; Basonyl Blue 644; Basovict Victoria Blue; C-WR Blue 8; C.I. 44045; Calcozine Blue B; Conbasic Blue AK; Dycosbasic Victoria Blue B; Flexo Blue 630; Flexo Blue 640; Hecto Blue B; Hidaco Victoria Blue B; Libbase Victoria Blue LB; Lowacyt Blue 26; Mitsui Victoria Blue B; Ravi Victoria Blue; Tetraphene Blue; Victoria Blue; Victoria Blue 2B; Victoria Blue B 353; Victoria Blue B chloride; Victoria Blue BA; Victoria Blue BH; Victoria Blue BN; Victoria Blue BN Cl 44045; Victoria Blue BP; Victoria Blue BS; Victoria Blue BSA; Victoria Blue BX; Victoria Blue FB; Victoria Pure Blue B; Victoria Pure Blue BC	2380-56-5	219-943-6	C ₃₃ H ₃₂ CIN ₃	Basic Blue 26 is used in inks, dyes, paints, and pigments. Among potential uses registered by companies in the Colour Index (2012), for products (dyestuff) containing Basic Blue 26, are in printing inks (according to Gessner and Mayer, 2000, melted in oleic or stearic acid), spirit inks, and pigments. According to Denmal et al. (2010), blue and black ball point pen inks may contain Basic Blue 26; with around 80% of blue and black ball point pen inks containing "Basic Violet 3 and its homologues".

iTeh Standards (<https://standards.iteh.ai>)

Document Preview

[ASTM F2931-16e1](https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1)
<https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1>

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
C.I. Basic Violet 3	[4-[4-(bis(dimethylamino)benzylidene)cyclohexa-2,5-dien-1-ylidene]]; dimethylammonium chloride; Methanaminium, N-[4-[bis[4-(dimethylamino)phenyl]methylene]-2,5-cyclohexadien-1-ylidene]-N-methylchloride(1:1); 4-[Bis[4-(dimethylamino)phenyl]methylene]-N,N-dimethylcyclohexa-2,5-dien-1-iminium; Chloride; Basic Violet 3; Crystal Violet Technical; Crystal Violet USP; General; Gentian violet; Gentian Violet B; Gentieverm; Genitcid; Gentioletten; Hecto Violet R; Hexograph Violet SR; Hexamethyl violet; Hexamethyl-p-rosaniline chloride; Hexamethylpararosaniline chloride	548-62-9	208-953-6	C ₂₅ H ₃₀ ClN ₃	The main uses of C.I. Basic Violet 3 are as a dye in ink applied in cartridges for printers and in ball pens and as dyestuff for paper colouring. Minor dyestuff uses include carbon papers (where dyestuff is suspended in wax and applied to a thin impregnated paper), staining of dried flowers/plants (dried plants dyed by immersion in a hot water solution of the dyestuff) and as a marker (i.e. where dyestuff is used to improve the visibility of a liquid). Furthermore, C.I. Basic Violet 3 is used in microbial and clinical laboratories (for example, as stain to distinguish gram negative from gram positive bacteria) in presumably thousands of laboratories and teaching institutions around Europe.
C.I. Solvent Blue 4:([α,α -bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1-methanol);		6786-83-0	2299-851-8	C ₃₃ H ₃₃ N ₃ O	The main use of the substance is in the production of inks.
C.I. Solvent Violet 8:([4,4'-(dimethylamino)phenyl]-4-(dimethylamino)phenyl)-4-(methylamino)- Bis[4-(dimethylamino)phenyl]-4-(methylamino)- Bis[4-(dimethylamino)phenyl]-4-(methylamino)phenyl)methanol;		561-41-1	209-218-2	C ₂₄ H ₂₉ N ₃ O	Uses of 4,4'-bis(dimethylamino)-4''-(methylamino)trityl alcohol are as formulation and production of writing inks.
Di-n-pentyl phthalate			205-017-9		Undetermined
Diboron trioxide, boric oxide	Boron oxide (B ₂ O ₃); diboron trioxide	1303-86-2	215-125-8	B ₂ O ₃	Undetermined
Diisopentylphthalate			210-088-4		Undetermined
Distillates (coal tar), heavy oils		605-50-5	292-607-4		Undetermined
Distillates (coal tar), heavy oils,		90640-86-1	295-304-5		Undetermined
pyrene fraction		91995-42-5			
Distillates (coal tar), pitch,		91995-52-7	295-313-4		
pyrene fraction		75-12-7	200-842-0	CH ₃ NO	Although formamide is not registered for consumer use it was measured in toys like wooden toys (Danish EPA, 2005) and foam puzzle mats as well as in fitness and exercise mats which are made of ethylene vinyl acetate (EVA).
Formamide					Undetermined
Further Arsenic compounds					

[ASTM F2931-16e1](https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1)
<https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1>

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
Lead(II) bis(methanesulfonate)	Methanesulfonic acid, lead(2+) salt (2:1); Methanesulfonic acid, lead(2+) salt; Lead methane sulphonate; Lead salt FP (trade name); Methanesulfonicacid,lead(2+)salt; Lead Methane Sulfate; Methanesulfonic acid, lead(II) salt; Lead methyl sulfonate Benzanamine, 4,4'- methylenebis[N,N-dimethyl-]; 4,4'- methylenebis[N,N- dimethylaniline]; Aniline, 4,4'- methylenebis[N,N-dimethyl-] (6Cl,7Cl,8Cl); Aniline, p,p'- methylenedi- (4Cl); 4,4'- (Dimethylamino)diphenylmethane; 4,4'- Bis(dimethylamino)diphenylmethane;	17570-76-2	401-750-5	C ₂ H ₆ O ₆ PbS ₂	Methanesulphonic acid-based plating technology is the dominant electrolytic plating process for high-speed reel-to-reel processing of electronic components.
Michler's Base;(N,N,N',N'- tetramethyl-4,4'- methylenedianiline)	101-61-1	202-989-2	C ₁₇ H ₂₂ N ₂		Used as chemical intermediate in the manufacture of dyes and pigments, also used as chemical intermediate in the manufacture of its hydrochloric salt. The latter is used as an analytical reagent for the determination of lead.

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[ASTM F2931-16e1](https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1)

<https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1>

iTeh Standards
<https://standards.iteh.ai>)
Document Preview

ASTM F2931-16e1

[https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49/astm-f2931-16e1](https://standards.iteh.ai/catalog/standards/sist/28894c65-ae3e-4a9d-beb0-1b75a0749d49 ASTM F2931-16e1)

TABLE 1 *Continued*

Substance Name	Synonym	CAS Number	EU Number	Chemical Formula	Common Uses
Michler's Ketone;(4,4'-bis(dimethylamino)benzophenone)	Methanone, bis[4-(dimethylaminophenyl); bis[4-(dimethylaminophenyl)methane; Benzophenone, 4,4'-bis(dimethylamino)- (6C1,8C1); 4,4'-Bis(N,N-dimethylamino)benzophenone; 4,4'-Bis(dimethylamino)benzophenone; 4,4'-Tetramethyldiaminobenzophenone; Bis(4-dimethylaminophenyl)ketone; Bis[4-(dimethylamino)phenyl]methane; Bis[(N,N-dimethylamino)phenyl]methane; ketone; DABP; Di(4-dimethylamino)benzophenone; Michler's ketone; N,N,N',N'-Tetramethyl-4,4'-diaminobenzophenone; NSC 9602; Nissos Cure MABP; S 112; S 112 (ketone); p,p'-Bis(dimethylamino)benzophenone; p,p'-Tetramethyldiaminobenzophenone	90-94-8	202-027-5	C ₁₇ H ₂₀ N ₂ O	Michler's ketone is an important intermediate in the manufacture of triphenylmethane dyes.
Perfluorooctanoic acid (PFOA)	Pentadecafluoroctanoic acid	335-67-1	206-397-9	C ₈ HF ₁₅ O ₂ (PFOA)	PFOA is used in a variety of commercial applications as refrigerants, surfactants and polymers, and as components of pharmaceuticals, fire retardants, lubricants, adhesives, paints, cosmetics, paper coatings, and insecticides.
Residues (coal tar), pitch distn.		92061-94-4	295-507-9		Undetermined